

InterLab®

## FCC Measurement/Technical Report on

### WLAN transceiver

incorporated in

Mobile Handheld Computer

Datalogic Joya X2 BASIC

Wifi with DE2011 reader

FCC ID: U4GJX2W

IC: 3862E-JX2W

and

### WLAN transceiver

incorporated in

Datalogic Joya X2 PLUS

Wifi + BT with SE4500 reader

FCC ID: U4GJX2WB

IC: 3862E-JX2WB

**Report Reference:** MDE\_DATA\_1408\_FCCe

**Test Laboratory:**

Borsigstrasse 11  
Germany  
7Layers AG  
40880 Ratingen



**Note:**

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7 layers AG  
Borsigstrasse 11  
40880 Ratingen, Germany  
Phone: +49 (0) 2102 749 0  
Fax: +49 (0) 2102 749 350  
www.7Layers.com

Aufsichtsratsvorsitzender •  
Chairman of the Supervisory Board:  
Peter Mertel  
Vorstand • Board:  
Dr. H.-J. Meckelburg  
Dr. H. Ansorge

Registergericht • registered in:  
Düsseldorf, HRB 44096  
USt-IdNr • VAT No.:  
DE 203159652  
TAX No. 147/5869/0385

## Table of Contents

<b>0</b>	<b>Applied Standards and Test Summary</b>	<b>3</b>
0.1	Technical Report Summary	3
0.2	FCC and IC Correlation Table	4
0.3	Measurement Summary	5
0.4	Revision History	6
<b>1</b>	<b>Administrative Data</b>	<b>7</b>
1.1	Testing Laboratory	7
1.2	Project Data	7
1.3	Applicant Data	7
1.4	Manufacturer Data	7
<b>2</b>	<b>Test object Data</b>	<b>8</b>
2.1	General EUT Description	8
2.2	EUT Main components	9
2.3	Ancillary Equipment	9
2.4	Auxiliary Equipment	9
2.5	EUT Setups	9
2.6	Operating Modes	10
2.7	Special software used for testing	11
2.8	Product labelling	11
<b>3</b>	<b>Test Results</b>	<b>12</b>
3.1	Spurious radiated emissions	12
3.2	Band edge compliance	20
<b>4</b>	<b>Test Equipment</b>	<b>23</b>
<b>5</b>	<b>Photo Report</b>	<b>31</b>
<b>6</b>	<b>Setup Drawings</b>	<b>31</b>

## 0 Applied Standards and Test Summary

### 0.1 Technical Report Summary

#### Type of Authorization

Certification for an Intentional Radiator (Digital Device / Spread Spectrum).

#### Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 and 15 (10-1-13 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz

#### Note:

The tests were selected and performed with reference to the FCC Public Notice "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247, 558074 D01 DTS Meas Guidance v03r02, 2014-06-05".

Instead of applying ANSI C63.4–1992 which is referenced in the FCC Public Note, the newer ANSI C63.4–2009 is applied.

#### Summary Test Results:

**The EUT complied with all performed tests as listed in chapter 0.3 Measurement Summary.**

## 0.2 FCC and IC Correlation Table

### Correlation of measurement requirements for DTS devices (e.g. WLAN 2.4/5 GHz) equipment

The following tables show the correlation of measurement requirements for DTS (e.g. WLAN) equipment and Information Technology Equipment (ITE) from FCC and IC standards.

#### DTS equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.207	RSS-Gen Issue 3: 7.2.4
Occupied bandwidth	§ 15.247 (a) (2)	RSS-210 Issue 8: A8.2 (a)
Peak power output	§ 15.247 (b) (3), (4)	RSS-210 Issue 8: A8.4 (4)
Spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen Issue 3: 6; RSS-210 Issue 8: A8.5
Spurious radiated emissions	§ 15.247 (d); § 15.209 (a)	RSS-Gen Issue 3: 6; RSS-210 Issue 8: A8.5
Band edge compliance	§ 15.247 (d)	RSS-210 Issue 8: A8.5
Power density	§ 15.247 (e)	RSS-210 Issue 8: A8.2 (b)
Antenna requirement	§ 15.203 / 15.204	RSS-Gen Issue 3: 7.1.2
Receiver spurious emissions	–	RSS-210 Issue 8: 2.3 RSS Gen Issue 3: 6 *)

\*) Receivers which are part of Transceivers are exempted with respect to Notice 2012-DRS0126.

#### Information Technology Equipment (ITE)

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.107	ICES-003 Issue 5: 6.1
Spurious Radiated Emissions	§ 15.109	ICES-003 Issue 5: 6.2

### 0.3 Measurement Summary

<b>FCC Part 15, Subpart C</b>		<b>§ 15.207</b>	
Conducted emissions (AC power line)			
The measurement was performed according to ANSI C63.4			
<b>Setup</b>	<b>Port</b>	<b>2009</b>	<b>Final Result</b>
-	AC port		N/A
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (a) (1)</b>	
Occupied bandwidth			
The measurement was performed according to FCC § 15.31			
<b>Setup</b>	<b>Port</b>	<b>10-1-13 Edition</b>	<b>Final Result</b>
Setup_01	Temp.ant.connector		Not performed
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (b) (1)</b>	
Peak power output			
The measurement was performed according to FCC § 15.31			
<b>Setup</b>	<b>Port</b>	<b>10-1-13 Edition</b>	<b>Final Result</b>
-	Temp.ant.connector		Not performed
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (d), § 15.35 (b), § 15.207</b>	
Spurious conducted emissions			
The measurement was performed according to ANSI C63.4			
<b>Setup</b>	<b>Port</b>	<b>2009</b>	<b>Final Result</b>
-	Temp.ant.connector		Not performed
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (d), § 15.35 (b), § 15.209</b>	
Spurious radiated emissions			
The measurement was performed according to ANSI C63.4			
<b>Setup</b>	<b>Port</b>	<b>2009</b>	<b>Final Result</b>
Setup_01	Enclosure		passed
Setup_02	Enclosure		passed
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (d)</b>	
Band edge compliance			
The measurement was performed according to FCC § 15.31 / ANSI C63.4			
<b>Setup</b>	<b>Port</b>	<b>10-1-13 Edition / 2009</b>	<b>Final Result</b>
Setup_01	Enclosure		passed
Setup_02	Enclosure		passed
<b>FCC Part 15, Subpart C</b>		<b>§ 15.247 (e)</b>	
Power density			
The measurement was performed according to FCC § 15.31			
<b>Setup</b>	<b>Port</b>	<b>10-1-13 Edition</b>	<b>Final Result</b>
-	Temp.ant.connector		Not performed

N/A not applicable (the EUT is powered by DC)

Responsible for  
Accreditation Scope:

B. P. H.

Responsible  
for Test Report:

D. Gall

This report contains only the applicable radiated tests.  
The applicable conducted tests were tested and reported by another laboratory.

#### 0.4 Revision History

Report version control			
Version	Release date	Change Description	Version validity
Initial	2014-10-10	--	Not valid
Rev01	2014-10-22	test results for Bluetooth removed; editorial corrections	valid

## 1 Administrative Data

### 1.1 Testing Laboratory

Company Name: 7 Layers AG  
Address Borsigstr. 11  
40880 Ratingen  
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716 .

The test facility is also accredited by the following accreditation organisation:  
Laboratory accreditation no.: DAkKS D-PL-12140-01-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka  
Dipl.-Ing. Robert Machulec  
Dipl.-Ing. Thomas Hoell  
Dipl.-Ing. Andreas Petz  
Dipl.-Ing. Marco Kullik

Report Template Version: 2014-08-26

### 1.2 Project Data

Responsible for testing and report: Dipl.-Ing. Daniel Gall  
Date of Test(s): 2014-05-27 to 2014-07-25  
Date of Report: 2014-10-22

### 1.3 Applicant Data

Company Name: Datalogic ADC s.r.l.  
Address: Via S. Vitalino, 13  
40012 Lippo di Calderara di Reno, Bologna  
Italy  
Contact Person: Mr. Eucarpio Guarisco

### 1.4 Manufacturer Data

Company Name: Please see applicant data  
Address:  
Contact Person:

## 2 Test object Data

### 2.1 General EUT Description

<b>Equipment under Test:</b>	IEEE 802.11b/g/n WLAN transceiver
<b>Type Designation:</b>	Datalogic Joya X2 and Joya X2 PLUS
<b>Kind of Device:</b>	Mobile Handheld Computer
<b>(optional)</b>	
<b>Voltage Type:</b>	DC
<b>Voltage Level:</b>	3.7 V
<b>Tested Modulation Type:</b>	WLAN: DBPSK; OFDM: BPSK

#### General product description:

The WLAN transceiver is incorporated in a mobile handheld computer, which runs with Windows Mobile 6 CE.

#### Specific product description for the EUT:

The focus of this test report is the WLAN transceiver of the Datalogic Joya X2 family, consequently switched on the IEEE 802.11 b/g/n modes, working in the 2.4 GHz band. The tested representative variants are "PLUS" including WLAN and Bluetooth and "BASIC" containing WLAN radio only.

#### The EUT provides the following ports:

##### Ports

Enclosure  
System-port

The main components of the EUT are listed and described in Chapter 2.2



## 2.2 EUT Main components

### Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
EUT A (Code: DE1006006ba01)	WLAN (& BT) transceiver	Datalogic Joya X2 PLUS Wifi + BT with SE4500 reader	Z14P00157	P/N: 911300127	1.80.024.04-SS000
Remark: EUT A is equipped with two integral antennas. For Bluetooth an integrated chip antenna with a gain of about 2dB is used. For Wifi a single band antenna with a gain of 3.7dB is used.					
EUT B (Code: DE1006006da01)	WLAN transceiver	Datalogic Joya X2 BASIC Wifi with DE2011 reader	Z14P00100	P/N: 911300120	1.80.024.04-SS000
Remark: EUT B is equipped with one integral. A single band antenna with a gain of 3.7dB is used.					

NOTE: The short description used to simplify the identification of the EUT in this test report.

## 2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment, which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
-	-	-	-	-	-

## 2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment, which is used temporarily to enable operational and control features especially used for the tests of the EUT, which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
-	-	-	-	-	-

## 2.5 EUT Setups

This chapter describes the combination of EUTs and equipment used for testing. The rationale for selecting the EUTs, ancillary and auxiliary equipment and interconnecting cables, is to test a representative configuration meeting the requirements of the referenced standards.

Setup	Combination of EUTs	Description and Rationale
Setup_01	EUT A	Setup for radiated radio measurements variant "PLUS"
Setup_02	EUT B	Setup for radiated radio measurements variant "BASIC"

## 2.6 Operating Modes

This chapter describes the operating modes of the EUTs used for testing.

### 2.6.1 Test Channels

<b>Band:</b>		
<b>WLAN 2.4 GHz ISM</b>		
<b>2400 - 2483.5 MHz</b>		
<b>Bottom</b>	<b>Middle</b>	<b>Top</b>
1	6	11
2412	2437	2462

### 2.6.2 Datarates

**SISO:**

WLAN b-mode; 20 MHz; 1 Mbit/s; DSSS Modulation
WLAN g-mode; 20 MHz; 6 Mbit/s; OFDM Modulation
WLAN n-mode; 20 MHz; 6.5 Mbit/s; OFDM Modulation

The g-mode was selected as “worst case” for OFDM Modulation. Consequently the testing was performed in b-mode and in g-Mode (and not in n-mode).

## **2.7 Special software used for testing**

The Windows program "SRU" is used to control the WLAN module which was provided by the applicant.

## **2.8 Product labelling**

### **2.8.1 FCC ID label**

Please refer to the documentation of the applicant.

### **2.8.2 Location of the label on the EUT**

Please refer to the documentation of the applicant.

## 3 Test Results

### 3.1 Spurious radiated emissions

**Standard** FCC Part 15, Subpart C

**The test was performed according to:** ANSI C63.4

#### 3.1.1 Test Description

The test set-up was made in accordance to the general provisions of ANSI C63.4 in a typical installation configuration. The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m<sup>2</sup> in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.

The measurement procedure is implemented into the EMI test software ES-K1 from R&S. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is performed at 2 axes. A pre-check is performed while the EUT is powered from a DC power source.

#### 1. Measurement up to 30 MHz

The Loop antenna HFH2-Z2 is used.

**Step 1:** pre measurement

- Anechoic chamber
- Antenna distance: 10 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 MHz and 0.15 – 30 MHz
- Frequency steps: 0.1 kHz and 5 kHz
- IF-Bandwidth: 0.2 kHz and 10 kHz
- Measuring time / Frequency step: 100 ms

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

**Step 2:** final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 – 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 0.2 - 10 kHz
- Measuring time / Frequency step: 100 ms

## 2. Measurement above 30 MHz and up to 1 GHz

### Step 1: Preliminary scan

This is a preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Antenna distance: 3 m
- Detector: Peak-Maxhold
- Frequency range: 30 – 1000 MHz
- Frequency steps: 60 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100  $\mu$ s
- Turntable angle range:  $-180^{\circ}$  to  $180^{\circ}$
- Turntable step size:  $90^{\circ}$
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

### Step 2: second measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range:  $-180^{\circ}$  to  $180^{\circ}$
- Turntable step size:  $45^{\circ}$
- Height variation range: 1 – 4 m
- Height variation step size: 0.5 m
- Polarisation: horizontal + vertical

After this step, the EMI test system has determined the following values for each frequency (of step 1):

- Frequency
- Azimuth value (of turntable)
- Antenna height

The last two values have now the following accuracy:

- Azimuth value (of turntable):  $45^{\circ}$
- Antenna height: 0.5 m

### Step 3: final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved.

This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will slowly vary by  $\pm 22.5^{\circ}$  around this value. During this action, the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position, the antenna height will also slowly vary by  $\pm 25$  cm around the antenna height determined. During this action, the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range:  $\pm 22.5^{\circ}$  around the determined value
- Height variation range:  $\pm 25$  cm around the determined value

**Step 4:** final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:

- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

**3. Measurement above 1 GHz**

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

The Equipment Under Test (EUT) was set up on a non-conductive support at 1.4 m height in the fully-anechoic chamber. The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse linear-distance squared for the power reference level measurements). Due to the fact, that in this frequency range a double-ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18–25 GHz) are used, the steps 2-4 are omitted. Step 1 was performed with one height of the receiving antenna only.

EMI receiver settings:

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

For the data rate in mode n the test is performed as worst-case-check in order to verify that emissions have a comparable level as found at modes b and g. Typically, the measurement is performed in the frequency range 1 to 8 GHz but it depends on the emissions found during the test for the modes b and g. Please refer to the results for the used frequency range.

**3.1.2 Test Requirements / Limits**

FCC Part 15, Subpart C, §15.247 (e)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

...

The same method of determining the conducted output power shall be used to determine the power spectral density.

### 3.1.3 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit ( $\mu\text{V}/\text{m}$ )	Measurement distance (m)	Calculated Limits( $\text{dB}\mu\text{V}/\text{m}$ @10m)	Limits( $\text{dB}\mu\text{V}/\text{m}$ @10m)
0.009 – 0.49	2400/F(kHz)	300 59.1 dB	(48.5 – 13.8) + 30 dB	78.5 – 43.8
0.49 – 1.705	24000/F(kHz)	30 19.1 dB	(48.9 – 23.0) + 10 dB	58.9 – 33.0
1.705 – 30	30	30 19.1 dB	29.5 + 10 dB	39.5

Frequency in MHz	Limit ( $\mu\text{V}/\text{m}$ )	Measurement distance (m)	Limit ( $\text{dB}\mu\text{V}/\text{m}$ )
30 – 88	100	3	40.0
88 – 216	150	3	43.5
216 – 960	200	3	46.0
above 960	500	3	54.0

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor:  $\text{Limit (dB}\mu\text{V}/\text{m)} = 20 \log (\text{Limit } (\mu\text{V}/\text{m})/1\mu\text{V}/\text{m})$

### 3.1.4 Test Protocol

Temperature: 23–27 °C  
 Air Pressure: 997-1011 hPa  
 Humidity: 33–50 %

WLAN b-Mode; 20 MHz; 1 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dBµV/m]	Margin to Limit [dB]
Joya X2 Variant "PLUS"							
1/78	2412/2480	2333.0	50.4	PK	1000	74.0	23.6
1/78	2412/2480	2333.0	41.2	AV	1000	54.0	12.8
1/78	2412/2480	2491.0	56.0	PK	1000	74.0	18.0
1/78	2412/2480	2491.0	48.6	AV	1000	54.0	5.4
1/78	2412/2480	4824.0	41.35	PK	1000	74.0	32.65
1/78	2412/2480	4824.0	34.85	AV	1000	54.0	19.15
6/39	2437/2441	2358.0	52.2	PK	1000	74.0	21.8
6/39	2437/2441	2358.0	42.0	AV	1000	54.0	12.0
6/39	2437/2441	7312.0	44.33	PK	1000	74.0	29.67
6/39	2437/2441	7312.0	36.36	AV	1000	54.0	17.64
11/0	2462/2402	1602.0	47.5	PK	1000	74.0	26.5
11/0	2462/2402	1602.0	37.8	AV	1000	54.0	16.2
11/0	2462/2402	2383.0	52.8	PK	1000	74.0	21.2
11/0	2462/2402	2383.0	43.8	AV	1000	54.0	10.2
11/0	2462/2402	2483.0	50.5	PK	1000	74.0	23.5
11/0	2462/2402	2483.0	39.3	AV	1000	54.0	14.7
11/0	2462/2402	7385.0	45.6	PK	1000	74.0	28.4
11/0	2462/2402	7385.0	38.2	AV	1000	54.0	15.8

Note: No (further) spurious emissions in the range 20 dB below the limit found.  
 During testing also the Bluetooth Transceiver was switched on (BT FSK modulation, 1-DH1).



WLAN b-Mode; 20 MHz; 1 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dBµV/m]	Margin to Limit [dB]
Joya X2 Variant "BASIC"							
1	2412	1235.0	45.3	PEAK	1000	74.0	28.7
1	2412	2333.0	35.7	AV	1000	54.0	18.4
1	2412	2333.0	52.1	PEAK	1000	74.0	21.9
1	2412	2333.0	43.7	AV	1000	54.0	10.3
1	2412	2387.0	51.5	PEAK	1000	74.0	22.6
1	2412	2387.0	42.1	AV	1000	54.0	11.9
1	2412	2491.0	58.1	PEAK	1000	74.0	15.9
1	2412	2491.0	51.7	AV	1000	54.0	2.3
1	2412	4824.0	41.8	PEAK	1000	74.0	32.2
1	2412	4824.0	37.4	AV	1000	54.0	16.6
6	2437	1235.0	45.5	PEAK	1000	74.0	28.5
6	2437	1235.0	35.7	AV	1000	54.0	18.3
6	2437	2356.0	53.7	PEAK	1000	74.0	20.3
6	2437	2356.0	44.9	AV	1000	54.0	9.1
6	2437	4874.0	41.3	PEAK	1000	74.0	32.7
6	2437	4874.0	36.5	AV	1000	54.0	17.5
6	2437	7310.0	44.6	PEAK	1000	74.0	29.5
6	2437	7310.0	35.3	AV	1000	54.0	18.7
11	2462	1235.0	46.1	PEAK	1000	74.0	27.9
11	2462	1235.0	35.7	AV	1000	54.0	18.4
11	2462	2383.0	53.1	PEAK	1000	74.0	20.9
11	2462	2383.0	44.7	AV	1000	54.0	9.3
11	2462	2487.0	51.2	PEAK	1000	74.0	22.9
11	2462	2487.0	40.0	AV	1000	54.0	14.0
11	2462	7387.0	44.1	PEAK	1000	74.0	29.9
11	2462	7387.0	36.0	AV	1000	54.0	18.0

Note: No (further) spurious emissions in the range 20 dB below the limit found.  
The measurement was performed from 9 kHz up to 8 GHz because at pre-measurements no significant spurious emissions have been found outside this frequency range.

WLAN g-Mode; 20 MHz; 6 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dB $\mu$ V/m]	Margin to Limit [dB]
Joya X2 Variant "PLUS"							
1/78	2412/2480	2338.0	50.9	PEAK	1000	74.0	23.1
1/78	2412/2480	2338.0	39.2	AV	1000	54.0	14.8
1/78	2412/2480	2390.0	60.6	PEAK	1000	74.0	13.4
1/78	2412/2480	2390.0	46.0	AV	1000	54.0	8.0
1/78	2412/2480	2488.0	58.3	PEAK	1000	74.0	15.7
1/78	2412/2480	2488.0	47.6	AV	1000	54.0	6.4
6/39	2437/2441	2360.0	52.7	PEAK	1000	74.0	21.3
6/39	2437/2441	2360.0	41.1	AV	1000	54.0	12.9
6/39	2437/2441	2483.5	51.7	PEAK	1000	74.0	22.3
6/39	2437/2441	2483.5	39.3	AV	1000	54.0	14.7
6/39	2437/2441	7312.0	51.1	PEAK	1000	74.0	22.9
6/39	2437/2441	7312.0	36.0	AV	1000	54.0	18.0
11/0	2462/2402	1602.0	47.3	PEAK	1000	74.0	26.7
11/0	2462/2402	1602.0	37.8	AV	1000	54.0	16.2
11/0	2462/2402	2383.0	51.1	PEAK	1000	74.0	22.9
11/0	2462/2402	2383.0	39.9	AV	1000	54.0	14.1
11/0	2462/2402	2483.0	60.8	PEAK	1000	74.0	13.2
11/0	2462/2402	2483.0	44.8	AV	1000	54.0	9.2

Note: No (further) spurious emissions in the range 20 dB below the limit found.  
 The measurements were performed from 1 GHz up to 8 GHz because at pre-measurements no significant spurious emissions have been found outside this frequency range.  
 During testing also the Bluetooth Transceiver was switched on (BT PSK modulation, 2-DH1).

WLAN g-Mode; 20 MHz; 6 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dBuV/m]	Margin to Limit [dB]
Joya X2 Variant "BASIC"							
1	2412	1235.0	45.1	PEAK	1000	74.0	28.9
1	2412	1235.0	35.4	AV	1000	54.0	18.6
1	2412	2333.0	51.2	PEAK	1000	74.0	22.9
1	2412	2333.0	40.0	AV	1000	54.0	14.0
1	2412	2390.0	62.5	PEAK	1000	74.0	11.5
1	2412	2390.0	47.0	AV	1000	54.0	7.0
1	2412	2493.0	57.7	PEAK	1000	74.0	16.3
1	2412	2493.0	46.9	AV	1000	54.0	7.1
6	2437	1235.0	45.6	PEAK	1000	74.0	28.4
6	2437	1235.0	35.7	AV	1000	54.0	18.4
6	2437	2356.0	54.9	PEAK	1000	74.0	19.2
6	2437	2356.0	44.2	AV	1000	54.0	9.8
6	2437	2483.5	52.6	PEAK	1000	74.0	21.4
6	2437	2483.5	40.9	AV	1000	54.0	13.2
11	2462	1235.0	45.0	PEAK	1000	74.0	29.0
11	2462	1235.0	35.5	AV	1000	54.0	18.5
11	2462	2383.0	53.3	PEAK	1000	74.0	20.7
11	2462	2383.0	41.8	AV	1000	54.0	12.2
11	2462	2483.5	64.5	PEAK	1000	74.0	9.5
11	2462	2483.5	47.9	AV	1000	54.0	6.1

Note: No (further) spurious emissions in the range 20 dB below the limit found.  
The measurements were performed from 1 GHz up to 8 GHz because at pre-measurements no significant spurious emissions have been found outside this frequency range.

## 3.2 Band edge compliance

**Standard** FCC Part 15, Subpart C

**The test was performed according to:** ANSI C63.4–2009, FCC §15.31

### 3.2.1 Test Description

The procedure to show compliance with the band edge requirement is divided into two measurements:

1. Show compliance of the lower and higher band edge by a conducted measurement. For the conducted measurement, the Equipment Under Test (EUT) is placed in a shielded room.

For the lower band edge the EUT is set to transmit as follows:

For a WLAN transmitter working in the 2.4 GHz band on lowest channel:

CH1 = 2412 MHz / CH3 = 2422 MHz for a channel bandwidth of 20 / 40 MHz.

The lower band edge is 2400 MHz for 2.4 GHz band transmitter.

For the higher band edge the EUT is set to transmit as follows:

For a WLAN transmitter working in the 2.4 GHz band on highest channel:

CH11 = 2462 MHz or CH13 = 2472 MHz / CH11 = 2462 MHz for a channel bandwidth of 20 / 40 MHz.

The higher band edge is 2483.5 MHz for a 2.4 GHz band transmitter.

Analyzer settings for conducted measurement:

- Detector: Peak
- RBW / VBW = 100 / 300 kHz

2. Showing compliance of the higher band edge falls in to restricted bands by a radiated measurement.

The radiated emissions measurements are performed in a typical installation configuration inside the fully anechoic chamber using a horn antenna at 1 m distance.

EMI receiver settings for radiated measurement:

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

### 3.2.2 Test Requirements / Limits

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. ...

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the conducted measurement the RF power at the band edge shall be “at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power...”

For the radiated measurement of the higher band edge connected to a restricted band the limit is “specified in Section 15.209(a)”.

### 3.2.3 Test Protocol


#### 3.2.3.1 Radiated measurement, higher band edge

Temperature: 23–27 °C  
 Air Pressure: 997-1011 hPa  
 Humidity: 33–50 %

WLAN b-Mode; 20 MHz; 1 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dBµV/m]	Margin to Limit [dB]
Joya X2 Variant “BASIC”							
11	2462	2483.5	50.7	PEAK	1000	74.0	23.3
11	2462	2483.5	39.8	AV	1000	54.0	14.2
Joya X2 Variant “PLUS”							
11	2462	2483.5	50.5	PEAK	1000	74.0	23.5
11	2462	2483.5	39.3	AV	1000	54.0	14.7

WLAN g-Mode; 20 MHz; 6 Mbit/s							
Ch. No.	Channel Center Frequency [MHz]	Frequency [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Limit [dBµV/m]	Margin to Limit [dB]
Joya X2 Variant “BASIC”							
11	2462	2483.5	64.5	PEAK	1000	74.0	9.5
11	2462	2483.5	47.9	AV	1000	54.0	6.1
Joya X2 Variant “PLUS”							
11	2462	2483.5	60.8	PEAK	1000	74.0	13.2
11	2462	2483.5	44.8	AV	1000	54.0	9.2

### 3.2.3.2 Measurement Plot (showing the highest value, "worst case")



WLAN mode g variant "BASIC"

## 4 Test Equipment

### List of Used Test Equipment

The calibration, hardware and software states are shown for the testing period.

#### Test Equipment Anechoic Chamber

<b>Lab ID:</b>	<b>Lab 2</b>		
<b>Manufacturer:</b>	Frankonia		
<b>Description:</b>	Anechoic Chamber for radiated testing		
<b>Type:</b>	10.58x6.38x6.00 m <sup>3</sup>		
	<i>Calibration Details</i>	<i>Last Execution</i>	<i>Next Exec.</i>
	NSA (FCC)	2014/01/09	2017/01/09

#### Single Devices for Anechoic Chamber

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6.00 m <sup>3</sup>	none	Frankonia
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	FCC listing 96716 3m Part15/18		2014/01/09 2017/01/08
Controller Maturo	MCU	961208	Maturo GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

#### Test Equipment Auxiliary Equipment for Conducted emissions

<b>Lab ID:</b>	<b>Lab 1</b>
<b>Manufacturer:</b>	Rohde & Schwarz GmbH & Co.KG
<b>Description:</b>	EMI Conducted Auxiliary Equipment

#### Single Devices for Auxiliary Equipment for Conducted emissions

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>
AC Power Source	Chroma 6404	64040001304	Chroma ATE INC.
Cable "LISN to ESI"	RG214	W18.03+W48.03	Huber&Suhner
Impedance Stabilization Network	ISN T800	36159	Teseq GmbH
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2014/02/06 2016/02/28
Impedance Stabilization Network, Coupling Decoupling Network	ISN/CDN ENY41	100002	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2013/03/01 2015/03/31
Impedance Stabilization Network, Coupling Decoupling Network	ISN/CDN ST08	36292	Teseq GmbH
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2014/01/10 2016/01/31

**Single Devices for Auxiliary Equipment for Conducted emissions (continued)**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>	
Impedance Stabilization Network, Coupling Decoupling Network	ISN/CDN T8-Cat6	32187	Teseq GmbH	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2014/01/08	2016/01/31
One-Line V-Network	ESH 3-Z6	100489	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	standard calibration		2014/06/18	2017/11/30
One-Line V-Network	ESH 3-Z6	100570	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2013/11/25	2016/11/24
Two-Line V-Network	ESH 3-Z5	828304/029	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standart Calibration		2013/03/01	2015/02/28
Two-Line V-Network	ESH 3-Z5	829996/002	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2013/03/01	2015/02/28



### Test Equipment Auxiliary Equipment for Radiated emissions

**Lab ID:** Lab 2  
**Description:** Equipment for emission measurements  
**Serial Number:** see single devices

#### Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Type	Serial Number	Manufacturer		
Antenna mast	AM 4.0	AM4.0/180/119205 13	Maturo GmbH		
Biconical dipole	VUBA 9117 <i>Calibration Details</i>	9117-108	Schwarzbeck	<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration			2012/01/18	2015/01/17
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P	849785	Miteq		
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4	-	Miteq		
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P	896037	Miteq		
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01-2+W38.01- 2	Kabel Kusch		
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02-2+W38.02- 2	Rosenberger Micro-Coax		
Double-ridged horn	HF 906 <i>Calibration Details</i>	357357/001	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration			2012/05/18	2015/05/17
Double-ridged horn	HF 906 <i>Calibration Details</i>	357357/002	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration			2012/06/26	2015/06/25
High Pass Filter	4HC1600/12750-1.5-KK	9942011	Trilithic		
High Pass Filter	5HC2700/12750-1.5-KK	9942012	Trilithic		
High Pass Filter	5HC3500/12750-1.2-KK	200035008	Trilithic		
High Pass Filter	WHKX 7.0/18G-8SS	09	Wainwright		
Horn Antenna Schwarzbeck 15-26 GHz BBHA 9170	BBHA 9170				
Log.-per. Antenna	HL 562 Ultralog <i>Calibration Details</i>	100609	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration			2012/12/18	2015/12/17
Log.-per. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG		
Loop Antenna	HFH2-Z2 <i>Calibration Details</i>	829324/006	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i>	<i>Next Exec.</i>
	Standard calibration			2011/10/27	2014/10/26
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH		
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH		

### Single Devices for Auxiliary Equipment for Radiated emissions (continued)

Single Device Name	Type	Serial Number	Manufacturer
Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	TD1.5-10kg/024/3790709	Maturo GmbH

### Test Equipment Auxiliary Test Equipment

<b>Lab ID:</b>	<b>Lab 2, Lab 3</b>
<b>Manufacturer:</b>	see single devices
<b>Description:</b>	Single Devices for various Test Equipment
<b>Type:</b>	various
<b>Serial Number:</b>	none

### Single Devices for Auxiliary Test Equipment

Single Device Name	Type	Serial Number	Manufacturer
AC Power Source	Chroma 6404	64040001304	Chroma ATE INC.
Broadband Power Divider N (Aux)	1506A / 93459	LM390	Weinschel Associates
Broadband Power Divider SMA	WA1515	A855	Weinschel Associates
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Customized calibration		2013/12/04   2015/12/03
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorwerke GmbH
Notch Filter Ultra Stable (Aux)	WRCA800/960-6EEK	24	Wainwright
Signal Analyzer	FSV30	103005	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard		2014/02/10   2016/02/09
Spectrum Analyser	FSP3	836722/011	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard		2012/06/13   2015/06/12
Spectrum Analyser	FSU26	200418	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2013/07/29   2014/07/28
Vector Signal Generator	SMIQ 03B	832492/061	Rohde & Schwarz GmbH & Co.KG

## Test Equipment Digital Signalling Devices

**Lab ID:** Lab 1, Lab 2, Lab 3  
**Description:** Signalling equipment for various wireless technologies.

### Single Devices for Digital Signalling Devices

Single Device Name	Type	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT CBT		100589	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/11/24    2014/11/23
CMW500	CMW500	107500	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2014/01/27    2016/01/26
Digital Radio Communication Tester	CMD 55	831050/020	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/11/28    2014/11/27
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	Hardware: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B56V14, B68 3v04, PCMCIA, U65V04 Software: K21 4v21, K22 4v21, K23 4v21, K24 4v21, K42 4v21, K43 4v21, K53 4v21, K56 4v22, K57 4v22, K58 4v22, K59 4v22, K61 4v22, K62 4v22, K63 4v22, K64 4v22, K65 4v22, K66 4v22, K67 4v22, K68 4v22, K69 4v22 Firmware: µP1 8v50 02.05.06 ---		2007/07/16
Universal Radio Communication Tester	CMU 200	837983/052	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/12/07    2014/12/06
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B54V14, B56V14, B68 3v04, B95, PCMCIA, U65V02 SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K27 4v10, K28 4v10, K42 4v11, K43 4v11, K53 4v10, K65 4v10, K66 4v10, K68 4v10, Firmware: µP1 8v40 01.12.05 ---		2007/01/02
	SW: K62, K69		2008/11/03
Vector Signal Generator	SMU200A	100912	Rohde & Schwarz GmbH & Co. KG

### Test Equipment Emission measurement devices

**Lab ID:** Lab 1, Lab 2  
**Description:** Equipment for emission measurements  
**Serial Number:** see single devices

#### Single Devices for Emission measurement devices

Single Device Name	Type	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Power Meter	NRVD	828110/016	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2014/05/13   2015/05/12
Sensor Head A	NRV-Z1	827753/005	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2014/05/13   2015/05/12
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2014/01/07   2016/01/31
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	Firmware-Update 4.34.4 from 3.45 during calibration		2009/12/03

### Test Equipment Multimeter 12

**Lab ID:** Lab 4, Lab 5  
**Description:** Ex-Tech 520  
**Serial Number:** 05157876

#### Single Devices for Multimeter 12

Single Device Name	Type	Serial Number	Manufacturer
Digital Multimeter 12 (Multimeter)	EX520	05157876	Extech Instruments Corp.
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Customized calibration		2013/12/04   2015/12/03

### Test Equipment T/A Logger 13

**Lab ID:** Lab 1, Lab 2, Lab 3  
**Description:** Lufft Opus10 TPR  
**Type:** Opus10 TPR  
**Serial Number:** 13936

#### Single Devices for T/A Logger 13

Single Device Name	Type	Serial Number	Manufacturer
ThermoAirpressure Datalogger 13 (Environ)	Opus10 TPR (8253.00)	13936	Lufft Mess- und Regeltechnik GmbH
<i>Calibration Details</i>			<i>Last Execution</i> <i>Next Exec.</i>
Customized calibration			2013/02/07   2015/02/06

### Test Equipment T/H Logger 02

**Lab ID:** Lab 1  
**Description:** Lufft Opus10  
**Serial Number:** 7489

#### Single Devices for T/H Logger 02

Single Device Name	Type	Serial Number	Manufacturer
ThermoHygro DataloggerOpus10 THI (8152.00) 02 (Environ)	Opus10 THI (8152.00)	7489	Lufft Mess- und Regeltechnik GmbH
<i>Calibration Details</i>			<i>Last Execution</i> <i>Next Exec.</i>
Customized calibration			2013/02/07   2015/02/06

### Test Equipment T/H Logger 03

**Lab ID:** Lab 3  
**Description:** Lufft Opus10  
**Serial Number:** 7482

#### Single Devices for T/H Logger 03

Single Device Name	Type	Serial Number	Manufacturer
ThermoHygro DataloggerOpus10 THI (8152.00) 03 (Environ)	Opus10 THI (8152.00)	7482	Lufft Mess- und Regeltechnik GmbH
<i>Calibration Details</i>			<i>Last Execution</i> <i>Next Exec.</i>
Customized calibration			2013/02/07   2015/02/06

### Test Equipment T/H Logger 12

**Lab ID:** Lab 2  
**Description:** Lufft Opus10  
**Serial Number:** 12482

#### Single Devices for T/H Logger 12

Single Device Name	Type	Serial Number	Manufacturer
ThermoHygro DataloggerOpus10 THI (8152.00) 12 (Environ)	Opus10 THI (8152.00)	12482	Lufft Mess- und Regeltechnik GmbH
<i>Calibration Details</i>			<i>Last Execution</i> <i>Next Exec.</i>
Customized calibration			2013/01/07   2015/01/06

**Test Equipment T/H Logger 15**

**Lab ID:** Lab 4, Lab 5  
**Description:** Lufft Opus10  
**Serial Number:** 13985


**Single Devices for T/H Logger 15**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>	
ThermoHygro DataloggerOpus10 THI (8152.00) 15 (Environ)		13985	Lufft Mess- und Regeltechnik GmbH	
<i>Calibration Details</i>			<i>Last Execution</i>	<i>Next Exec.</i>
Customized calibration			2013/01/07	2015/01/06

## 5 Photo Report

Please refer to external report.

## 6 Setup Drawings



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

**Drawing 1:** Setup in the Anechoic chamber. For measurements below 1 GHz the ground was replaced by a conducting groundplane.