



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	Hitron Technologies
Applicant Address	No.1-8, Lising 1st Rd. Hsinchu Science Park, Hsinchu 300, Taiwan
FCC ID	U4P-CGNVM
Manufacturer's company	Hitron Technologies
Manufacturer Address	No.1-8, Lising 1st Rd. Hsinchu Science Park, Hsinchu 300, Taiwan

Product Name	Wireless Cable Gateway
Brand Name	hitron
Model No.	CGNVM-XXXX
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	May 19, 2015
Final Test Date	Jul. 22, 2015
Submission Type	Original Equipment

### Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r03 and KDB 662911 D01 v02r01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. VERIFICATION OF COMPLIANCE</b> .....	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT</b> .....	<b>2</b>
<b>3. GENERAL INFORMATION</b> .....	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes .....	7
3.6. Table for Testing Locations.....	8
3.7. Table for Multiple List.....	8
3.8. Table for Supporting Units .....	8
3.9. Table for Parameters of Test Software Setting .....	9
3.10. EUT Operation during Test .....	9
3.11. Duty Cycle.....	9
3.12. Test Configurations .....	10
<b>4. TEST RESULT</b> .....	<b>12</b>
4.1. AC Power Line Conducted Emissions Measurement.....	12
4.2. Maximum Conducted Output Power Measurement.....	16
4.3. Power Spectral Density Measurement .....	18
4.4. 6dB Spectrum Bandwidth Measurement .....	27
4.5. Radiated Emissions Measurement .....	34
4.6. Emissions Measurement .....	53
4.7. Antenna Requirements .....	71
<b>5. LIST OF MEASURING EQUIPMENTS</b> .....	<b>72</b>
<b>6. MEASUREMENT UNCERTAINTY</b> .....	<b>74</b>
<b>APPENDIX A. TEST PHOTOS</b> .....	<b>A1 ~ A5</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE</b> .....	<b>B1 ~ B3</b>
<b>APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT</b> .....	<b>C1 ~ C3</b>



## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR562321AA	Rev. 01	Initial issue of report	Sep. 01, 2015



## 1. VERIFICATION OF COMPLIANCE

Product Name : Wireless Cable Gateway  
Brand Name : hitron  
Model No. : CGNVM-XXXX  
Applicant : Hitron Technologies  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May 19, 2015 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in black ink that reads 'Sam Chen'.

Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.40 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	1.68 dB
4.3	15.247(e)	Power Spectral Density	Complies	1.81 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.02 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.17 dB
4.7	15.203	Antenna Requirements	Complies	-

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From AC Power
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	IEEE 802.11b: 14.59 MHz IEEE 802.11g: 19.45 MHz IEEE 802.11n MCS0 (HT20): 18.06 MHz IEEE 802.11n MCS0 (HT40): 39.80 MHz
Maximum Conducted Output Power	IEEE 802.11b: 27.73 dBm IEEE 802.11g: 28.32 dBm IEEE 802.11n MCS0 (HT20): 27.89 dBm IEEE 802.11n MCS0 (HT40): 24.69 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Beamforming Function	<input type="checkbox"/> With beamforming <input checked="" type="checkbox"/> Without beamforming

**Antenna and Band width**

Antenna	Three (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

**IEEE 11n Spec.**

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS 0-23
802.11n (HT40)	3	MCS 0-23

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).  
Then EUT supports HT20 and HT40.

Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n

**3.2. Accessories**

Power Cable\*1: Non-Shielded, 1.8m

### 3.3. Table for Filed Antenna

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)		
					2.4GHz	5GHz	
						Band 1	Band 4
1	Airgian	M2445J-T6-G100U	PIFA Ant.	I-PEX	3.1	-	-
2	Airgian	M2445J-T6-G100U	PIFA Ant.	I-PEX	3.4	-	-
3	Airgian	M2445J-T6-G100U	PIFA Ant.	I-PEX	2.9	-	-
4	Airgian	M5X10CM-T6-G100U	PIFA Ant.	I-PEX	-	2.4	4.5
5	Airgian	M5X10CM-T6-G100U	PIFA Ant.	I-PEX	-	3.8	3.7
6	Airgian	M5X10CM-T6-G100U	PIFA Ant.	I-PEX	-	4.1	5.8

Note: The EUT has six antennas.

**<For 2.4GHz>**

For IEEE 802.11b/g/n mode (3TX/3RX)

Chain 1, Chain 2 and Chain 3 can be used as transmitting/receiving antenna.



Chain 1, Chain 2 and Chain 3 could transmit/receive simultaneously.

**<For 5GHz>**

For IEEE 802.11a/n/ac mode (3TX/3RX)

Chain 4, Chain 5 and Chain 6 can be used as transmitting/receiving antenna.

Chain 4, Chain 5 and Chain 6 could transmit/receive simultaneously.





### 3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3

Note: The EUT can only be used at Y axis.

The following test modes were performed for all tests:

**For Conducted Emission test:**

Mode 1. Place EUT in Y axis

**For Radiated Emission test<Below 1GHz>:**

Mode 1. Place EUT in Y axis (2.4GHz)

Mode 2. Place EUT in Y axis (5GHz)

Mode 1 is the worst case, so it was selected to record in this test report.

**For Radiated Emission test<Above 1GHz>:**

Mode 1. Place EUT in Y axis

### For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Multiple List

The model number detail information for the following table:

Model No.	Description
CGNVM-XXXX	Where XXXX=any alpha character "a"-“z”, “A”-“Z”, or numeric character “0”-“9”, or combination of alpha and numeric characters.

### 3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
NB	DELL	E4300	DoC

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	ART2-GUI 2.3					
Mode	Test Frequency (MHz)					
	NCB: 20MHz			NCB: 40MHz		
	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
802.11b	22	23	22	-	-	-
802.11g	18	23	17.5	-	-	-
802.11n MCS0 HT20	17	23	17	-	-	-
802.11n MCS0 HT40	-	-	-	16	19.5	18.5

### 3.10. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

### 3.11. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1.000	1.000	100.00%	0.00	0.01
802.11g	1.346	1.402	95.99%	0.18	0.74
802.11n MCS0 HT20	1.270	1.310	96.95%	0.13	0.79
802.11n MCS0 HT40	0.624	0.672	92.86%	0.32	1.60


### 3.12. Test Configurations

#### 3.12.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m

### 3.12.2. Radiation Emissions Test Configuration



Item	Connection	Shielded	Length(m)
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.






4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	21°C	Humidity	57%
Test Engineer	Ryo Fan	Phase	Line
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISM Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1508	41.74	-14.22	55.96	31.79	9.93	0.02	LINE	Average
2	0.1508	53.50	-12.46	65.96	43.55	9.93	0.02	LINE	QP
3	0.1532	28.95	-26.87	55.82	19.00	9.93	0.02	LINE	Average
4	0.1532	47.30	-18.52	65.82	37.35	9.93	0.02	LINE	QP
5	0.1607	22.72	-32.71	55.43	12.77	9.93	0.02	LINE	Average
6	0.1607	45.34	-20.09	65.43	35.39	9.93	0.02	LINE	QP
7	0.1712	31.92	-22.98	54.90	21.97	9.93	0.02	LINE	Average
8	0.1712	48.44	-16.46	64.90	38.49	9.93	0.02	LINE	QP
9	0.4612	34.59	-12.08	46.67	24.62	9.93	0.04	LINE	Average
10	0.4612	39.95	-16.72	56.67	29.98	9.93	0.04	LINE	QP
11	14.5942	30.97	-19.03	50.00	20.39	10.32	0.26	LINE	Average
12	14.5942	35.82	-24.18	60.00	25.24	10.32	0.26	LINE	QP

Temperature	21°C	Humidity	57%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1508	48.56	-7.40	55.96	38.76	9.78	0.02	NEUTRAL	Average
2	0.1508	54.09	-11.87	65.96	44.29	9.78	0.02	NEUTRAL	QP
3	0.1590	30.04	-25.48	55.52	20.24	9.78	0.02	NEUTRAL	Average
4	0.1590	45.07	-20.45	65.52	35.27	9.78	0.02	NEUTRAL	QP
5	0.1624	26.97	-28.37	55.34	17.17	9.78	0.02	NEUTRAL	Average
6	0.1624	43.65	-21.69	65.34	33.85	9.78	0.02	NEUTRAL	QP
7	0.1677	21.86	-33.22	55.08	12.06	9.78	0.02	NEUTRAL	Average
8	0.1677	46.10	-18.98	65.08	36.30	9.78	0.02	NEUTRAL	QP
9	0.1777	26.89	-27.70	54.59	17.08	9.79	0.02	NEUTRAL	Average
10	0.1777	44.93	-19.66	64.59	35.12	9.79	0.02	NEUTRAL	QP
11	0.4588	32.91	-13.80	46.71	23.08	9.79	0.04	NEUTRAL	Average
12	0.4588	42.33	-14.38	56.71	32.50	9.79	0.04	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

The limit for output power is 30dBm.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r03 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	45%
Test Engineer	Lucas Huang	Test Date	Jun. 03, 2015

Mode	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Total		
802.11b	2412 MHz	22.70	22.13	22.40	27.19	30.00	Complies
	2437 MHz	23.22	22.80	22.84	27.73	30.00	Complies
	2462 MHz	22.64	22.40	22.50	27.29	30.00	Complies
802.11g	2412 MHz	19.28	18.66	18.24	23.52	30.00	Complies
	2437 MHz	24.22	23.11	23.23	28.32	30.00	Complies
	2462 MHz	18.98	18.47	18.08	23.30	30.00	Complies
802.11n MCS0 HT20	2412 MHz	18.42	17.93	17.44	22.72	30.00	Complies
	2437 MHz	23.24	23.25	22.84	27.89	30.00	Complies
	2462 MHz	18.38	17.86	17.63	22.74	30.00	Complies
802.11n MCS0 HT40	2422 MHz	18.23	16.72	17.64	22.34	30.00	Complies
	2437 MHz	19.72	19.63	20.37	24.69	30.00	Complies
	2452 MHz	18.17	18.03	18.83	23.13	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	45%
Test Engineer	Lucas Huang		


Mode	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Total		
802.11b	2412 MHz	-1.21	-2.16	-1.95	3.02	6.09	Complies
	2437 MHz	-0.01	-0.92	-0.58	4.28	6.09	Complies
	2462 MHz	-0.94	-0.78	-1.43	3.73	6.09	Complies
802.11g	2412 MHz	-5.80	-6.17	-6.13	-1.26	6.09	Complies
	2437 MHz	-1.27	-3.33	-3.06	2.32	6.09	Complies
	2462 MHz	-6.71	-6.62	-7.24	-2.08	6.09	Complies
802.11n MCS0 HT20	2412 MHz	-7.95	-8.19	-7.28	-3.02	6.09	Complies
	2437 MHz	-1.87	-1.69	-1.96	2.93	6.09	Complies
	2462 MHz	-6.80	-7.71	-8.43	-2.82	6.09	Complies
802.11n MCS0 HT40	2422 MHz	-7.64	-12.25	-10.59	-4.96	6.09	Complies
	2437 MHz	-8.50	-8.93	-5.71	-2.69	6.09	Complies
	2452 MHz	-8.54	-10.15	-9.32	-4.52	6.09	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{IS}} \left( \sum_{k=1}^{N_{ANT}} S_{j,k} \right)^2}{N_{ANT}} \right] = 7.91 \text{ dBi}$ , So Limit =  $8 - (7.91 - 6) = 6.09 \text{ dBm/3kHz}$ .

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1



Date: 3 JUN 2015 15:37:44


Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 2




Date: 3 JUN 2015 15:35:34




**Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 3**



**Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1**




**Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 2**




Date: 3 JUN .2015 15:40:01

**Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 3**




Date: 3 JUN .2015 15:40:30


**Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1**



**Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 2**




**Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 3**




Date: 3 JUN 2015 15:42:04

**Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1**




Date: 3 JUN 2015 16:01:19

**Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 2**



**Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 3**



## 4.4. 6dB Spectrum Bandwidth Measurement

### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

### 4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth = > 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

### 4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	25°C	<b>Humidity</b>	45%
<b>Test Engineer</b>	Lucas Huang		


Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11b	2412 MHz	11.59	13.37	500	Complies
	2437 MHz	11.01	14.59	500	Complies
	2462 MHz	10.09	14.59	500	Complies
802.11g	2412 MHz	15.71	16.58	500	Complies
	2437 MHz	15.30	19.45	500	Complies
	2462 MHz	14.20	16.67	500	Complies
802.11n MCS0 HT20	2412 MHz	15.71	17.97	500	Complies
	2437 MHz	15.19	18.06	500	Complies
	2462 MHz	14.84	17.71	500	Complies
802.11n MCS0 HT40	2422 MHz	36.41	39.80	500	Complies
	2437 MHz	31.42	35.89	500	Complies
	2452 MHz	35.83	38.35	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.




6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 1 + Chain 2 + Chain 3




99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1 + Chain 2 + Chain 3




6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Chain 1 + Chain 2 + Chain 3




99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1 + Chain 2 + Chain 3




**6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Chain 1 + Chain 2 + Chain 3**



**99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3**




**6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1 + Chain 2 + Chain 3**



Date: 3 JUN. 2015 15:11:23

**99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2422 MHz / Chain 1 + Chain 2 + Chain 3**



Date: 3 JUN. 2015 15:01:56

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	21°C	Humidity	65%
Test Engineer	Lucke Hsieh	Configurations	CTX
Test Date	Jun. 13, 2015	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

## 4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	21°C	Humidity	65%
Test Engineer	Lucke Hsieh	Configurations	CTX
Test Mode	Mode 1		

## Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	148.34	38.97	43.50	-4.53	58.66	1.10	11.36	32.15	200	265	QP	HORIZONTAL
2	158.04	38.95	43.50	-4.55	59.07	1.17	10.88	32.17	200	101	Peak	HORIZONTAL
3	375.32	41.57	46.00	-4.43	56.07	1.68	15.91	32.09	100	325	Peak	HORIZONTAL
4	521.79	42.69	46.00	-3.31	54.75	1.94	18.19	32.19	150	241	QP	HORIZONTAL
5	531.49	41.87	46.00	-4.13	53.72	1.95	18.36	32.16	150	241	Peak	HORIZONTAL
6	625.01	45.95	46.00	-0.05	56.77	2.08	19.35	32.25	125	224	QP	HORIZONTAL

**Vertical**



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	375.01	45.82	46.00	-0.18	60.31	1.68	15.92	32.09	151	102	QP	VERTICAL
2	383.08	42.70	46.00	-3.30	56.94	1.69	16.11	32.04	150	108	QP	VERTICAL
3	393.75	42.41	46.00	-3.59	56.36	1.72	16.36	32.03	125	92	QP	VERTICAL
4	403.45	42.19	46.00	-3.81	55.98	1.74	16.54	32.07	125	264	QP	VERTICAL
5	429.64	42.45	46.00	-3.55	55.98	1.78	16.86	32.17	100	288	QP	VERTICAL
6	434.49	42.25	46.00	-3.75	55.66	1.79	16.92	32.12	125	120	QP	VERTICAL
7	439.34	45.11	46.00	-0.89	58.41	1.80	16.98	32.08	125	34	QP	VERTICAL
8	445.16	42.58	46.00	-3.42	55.83	1.81	17.04	32.10	125	107	QP	VERTICAL
9	450.01	44.77	46.00	-1.23	57.98	1.82	17.10	32.13	100	115	QP	VERTICAL
10	459.71	44.19	46.00	-1.81	57.13	1.84	17.24	32.02	125	112	QP	VERTICAL
11	470.38	44.07	46.00	-1.93	56.80	1.85	17.39	31.97	125	264	QP	VERTICAL
12	481.05	43.61	46.00	-2.39	56.22	1.87	17.54	32.02	100	43	QP	VERTICAL
13	490.75	45.13	46.00	-0.87	57.63	1.89	17.68	32.07	100	280	QP	VERTICAL
14	501.42	45.11	46.00	-0.89	57.53	1.90	17.83	32.15	100	275	QP	VERTICAL
15	511.39	44.57	46.00	-1.43	56.82	1.92	18.01	32.18	100	268	QP	VERTICAL
16	521.79	44.86	46.00	-1.14	56.91	1.94	18.20	32.19	100	62	QP	VERTICAL
17	531.49	43.23	46.00	-2.77	55.06	1.95	18.38	32.16	100	261	QP	VERTICAL
18	542.16	42.40	46.00	-3.60	54.00	1.97	18.56	32.13	100	122	QP	VERTICAL
19	551.86	42.30	46.00	-3.70	53.71	1.99	18.72	32.12	100	261	QP	VERTICAL
20	562.53	41.37	46.00	-4.63	52.69	2.00	18.80	32.12	100	256	QP	VERTICAL
21	625.02	45.98	46.00	-0.02	56.79	2.08	19.36	32.25	100	61	QP	VERTICAL

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 19, 2015		

##### *Horizontal*

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.36	47.71	74.00	-26.29	41.12	6.11	33.56	33.08	265	125	Peak	HORIZONTAL
2	4824.16	34.02	54.00	-19.98	27.43	6.11	33.56	33.08	265	125	Average	HORIZONTAL
3	12060.80	48.52	54.00	-5.48	31.40	10.97	39.64	33.49	219	127	Average	HORIZONTAL
4	12061.28	59.05	74.00	-14.95	41.93	10.97	39.64	33.49	219	127	Peak	HORIZONTAL

##### *Vertical*

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.96	34.23	54.00	-19.77	27.64	6.11	33.56	33.08	331	150	Average	VERTICAL
2	4824.32	46.96	74.00	-27.04	40.37	6.11	33.56	33.08	331	150	Peak	VERTICAL
3	12060.88	48.66	54.00	-5.34	31.54	10.97	39.64	33.49	360	151	Average	VERTICAL
4	12061.04	58.74	74.00	-15.26	41.62	10.97	39.64	33.49	360	137	Peak	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7310.04	55.20	74.00	-18.80	43.75	8.28	36.64	33.47	59	136	Peak	HORIZONTAL
2	7310.22	49.88	54.00	-4.12	38.43	8.28	36.64	33.47	59	136	Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Limit	Level	Loss	Factor	Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7311.84	49.94	54.00	-4.06	38.47	8.30	36.64	33.47	147	123	Average	VERTICAL
2	7311.90	55.97	74.00	-18.03	44.50	8.30	36.64	33.47	147	123	Peak	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7383.72	53.42	74.00	-20.58	41.72	8.34	36.85	33.49	292	126	Peak	HORIZONTAL
2	7386.78	44.01	54.00	-9.99	32.31	8.34	36.85	33.49	292	126	Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7386.42	55.41	74.00	-18.59	43.71	8.34	36.85	33.49	127	133	Peak	VERTICAL
2	7386.78	48.48	54.00	-5.52	36.78	8.34	36.85	33.49	127	133	Average	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 27, 2015		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4820.70	47.00	74.00	-27.00	40.41	6.11	33.56	33.08	115	160	Peak	HORIZONTAL
2	4821.77	34.22	54.00	-19.78	27.63	6.11	33.56	33.08	115	160	Average	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4821.60	47.43	74.00	-26.57	40.84	6.11	33.56	33.08	124	214	Peak	VERTICAL
2	4822.64	34.87	54.00	-19.13	28.28	6.11	33.56	33.08	124	214	Average	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 27, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7313.81	67.68	74.00	-6.32	56.21	8.30	36.64	33.47	311	145	Peak	HORIZONTAL
2	7314.37	52.57	54.00	-1.43	41.10	8.30	36.64	33.47	311	145	Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7309.48	53.95	54.00	-0.05	42.50	8.28	36.64	33.47	3	183	Average	VERTICAL
2	7318.45	68.95	74.00	-5.05	57.43	8.30	36.69	33.47	3	183	Peak	VERTICAL



<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 27, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4922.81	34.11	54.00	-19.89	27.36	6.05	33.76	33.06	59	164	Average	HORIZONTAL
2	4923.21	48.01	74.00	-25.99	41.26	6.05	33.76	33.06	59	164	Peak	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4921.50	34.18	54.00	-19.82	27.43	6.05	33.76	33.06	207	198	Average	VERTICAL
2	4926.26	47.57	74.00	-26.43	40.82	6.05	33.76	33.06	207	198	Peak	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT20 CH 1 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4821.90	34.82	54.00	-19.18	28.23	6.11	33.56	33.08	278	150	Average	HORIZONTAL
2	4824.58	48.17	74.00	-25.83	41.58	6.11	33.56	33.08	278	150	Peak	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.02	47.81	74.00	-26.19	41.22	6.11	33.56	33.08	226	114	Peak	VERTICAL
2	4825.46	34.75	54.00	-19.25	28.16	6.11	33.56	33.08	226	114	Average	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT20 CH 6 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7307.80	66.01	74.00	-7.99	54.56	8.28	36.64	33.47	62	166	Peak	HORIZONTAL
2	7308.80	50.97	54.00	-3.03	39.52	8.28	36.64	33.47	62	166	Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7308.60	53.18	54.00	-0.82	41.73	8.28	36.64	33.47	7	167	Average	VERTICAL
2	7309.00	69.13	74.00	-4.87	57.68	8.28	36.64	33.47	7	167	Peak	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT20 CH 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7385.72	53.15	74.00	-20.85	41.45	8.34	36.85	33.49	297	152	Peak	HORIZONTAL
2	7385.93	39.14	54.00	-14.86	27.44	8.34	36.85	33.49	297	152	Average	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	7385.75	39.30	54.00	-14.70	27.60	8.34	36.85	33.49	253	143	Average	VERTICAL
2	7388.24	52.84	74.00	-21.16	41.11	8.37	36.85	33.49	253	143	Peak	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT40 CH 3 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	Jun. 03, 2015		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4839.57	32.73	54.00	-21.27	28.24	7.07	33.70	31.12	HORIZONTAL	33	175	Average
2	4845.90	45.41	74.00	-28.59	40.90	7.07	33.69	31.13	HORIZONTAL	33	175	Peak

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4839.72	32.68	54.00	-21.32	28.18	7.07	33.70	31.13	VERTICAL	26	175	Average
2	4847.36	45.32	74.00	-28.68	40.81	7.07	33.69	31.13	VERTICAL	26	175	Peak

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT40 CH 6 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	Jun. 03, 2015		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4859.30	33.09	54.00	-20.91	28.54	7.08	33.69	31.16	HORIZONTAL	44	175	Average
2	4888.59	45.80	74.00	-28.20	41.17	7.10	33.68	31.21	HORIZONTAL	44	175	Peak
3	7301.68	40.51	54.00	-13.49	29.62	8.85	33.99	36.03	HORIZONTAL	165	175	Average
4	7304.29	53.01	74.00	-20.99	42.10	8.86	33.99	36.04	HORIZONTAL	165	175	Peak

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4878.75	45.10	74.00	-28.90	40.51	7.09	33.68	31.18	VERTICAL	229	225	Peak
2	4883.32	32.96	54.00	-21.04	28.33	7.10	33.68	31.21	VERTICAL	229	225	Average
3	7298.09	40.46	54.00	-13.54	29.55	8.85	33.99	36.05	VERTICAL	112	225	Average
4	7304.11	53.52	74.00	-20.48	42.60	8.86	33.99	36.05	VERTICAL	112	225	Peak

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT40 CH 9 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	Jun. 03, 2015		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4896.56	33.32	54.00	-20.68	28.67	7.11	33.68	31.22	HORIZONTAL	27	175	Average
2	4908.63	46.52	74.00	-27.48	41.83	7.12	33.67	31.24	HORIZONTAL	27	175	Peak
3	7349.03	40.94	54.00	-13.06	29.94	8.89	34.04	36.15	HORIZONTAL	201	175	Average
4	7361.41	54.54	74.00	-19.46	43.51	8.90	34.05	36.18	HORIZONTAL	201	175	Peak

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4894.59	33.21	54.00	-20.79	28.57	7.11	33.68	31.21	VERTICAL	219	225	Average
2	4902.78	46.08	74.00	-27.92	41.41	7.11	33.67	31.23	VERTICAL	219	225	Peak
3	7347.06	53.54	74.00	-20.46	42.53	8.89	34.03	36.15	VERTICAL	307	225	Peak
4	7362.86	40.84	54.00	-13.16	29.79	8.90	34.05	36.20	VERTICAL	307	225	Average

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.



#### **4.6.4. Test Setup Layout**

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.

#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11b CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 19, 2015 ~ May 21, 2015		

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2385.40	63.49	74.00	-10.51	30.66	4.37	28.46	0.00	241	127	Peak	HORIZONTAL
2	2387.20	51.92	54.00	-2.08	19.06	4.37	28.49	0.00	241	127	Average	HORIZONTAL
3	2411.00	120.06			87.12	4.41	28.53	0.00	241	127	Peak	HORIZONTAL
4	2411.20	116.02			83.08	4.41	28.53	0.00	241	127	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2355.00	50.72	54.00	-3.28	17.97	4.33	28.42	0.00	240	127	Average	HORIZONTAL
2	2358.60	61.18	74.00	-12.82	28.43	4.33	28.42	0.00	240	127	Peak	HORIZONTAL
3	2434.20	112.96			79.96	4.44	28.56	0.00	240	127	Average	HORIZONTAL
4	2434.60	117.06			84.06	4.44	28.56	0.00	240	127	Peak	HORIZONTAL
5	2483.50	47.44	54.00	-6.56	14.26	4.51	28.67	0.00	240	127	Average	HORIZONTAL
6	2485.10	59.85	74.00	-14.15	26.67	4.51	28.67	0.00	240	127	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2463.80	112.41			79.30	4.48	28.63	0.00	232	127	Average	HORIZONTAL
2	2465.00	116.35			83.24	4.48	28.63	0.00	232	127	Peak	HORIZONTAL
3	2483.50	52.30	54.00	-1.70	19.12	4.51	28.67	0.00	232	127	Average	HORIZONTAL
4	2483.50	61.77	74.00	-12.23	28.59	4.51	28.67	0.00	232	127	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 27, 2015		

**Channel 1**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	2388.92	53.80	54.00	-0.20	20.94	4.37	28.49	0.00	229	162 Average	HORIZONTAL
2	2389.40	72.23	74.00	-1.77	39.37	4.37	28.49	0.00	229	162 Peak	HORIZONTAL
3	2412.96	107.58			74.64	4.41	28.53	0.00	229	162 Average	HORIZONTAL
4	2413.28	116.46			83.52	4.41	28.53	0.00	229	162 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	2387.00	53.29	54.00	-0.71	20.43	4.37	28.49	0.00	233	124 Average	HORIZONTAL
2	2387.64	63.73			30.87	4.37	28.49	0.00	233	124 Peak	HORIZONTAL
3	2434.76	117.93			84.93	4.44	28.56	0.00	233	124 Peak	HORIZONTAL
4	2486.04	50.74	54.00	-3.26	17.56	4.51	28.67	0.00	233	124 Average	HORIZONTAL
5	2486.68	65.08	74.00	-8.92	31.90	4.51	28.67	0.00	233	124 Peak	HORIZONTAL

Item 2, 3 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	2455.91	105.82			72.71	4.48	28.63	0.00	231	176 Average	HORIZONTAL
2	2456.23	114.83			81.72	4.48	28.63	0.00	231	176 Peak	HORIZONTAL
3	2483.50	53.45	54.00	-0.55	20.27	4.51	28.67	0.00	231	176 Average	HORIZONTAL
4	2483.50	68.69	74.00	-5.31	35.51	4.51	28.67	0.00	231	176 Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	May 21, 2015		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2389.60	52.40	54.00	-1.60	19.54	4.37	28.49	0.00	61	148	Average	HORIZONTAL
2	2389.60	69.11	74.00	-4.89	36.25	4.37	28.49	0.00	61	148	Peak	HORIZONTAL
3	2418.40	103.04			70.07	4.44	28.53	0.00	61	148	Average	HORIZONTAL
4	2418.80	112.25			79.28	4.44	28.53	0.00	61	148	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2387.00	66.94	74.00	-7.06	34.08	4.37	28.49	0.00	242	126	Peak	HORIZONTAL
2	2390.00	52.61	54.00	-1.39	19.71	4.41	28.49	0.00	242	126	Average	HORIZONTAL
3	2439.40	119.28			86.24	4.44	28.60	0.00	242	126	Peak	HORIZONTAL
4	2440.20	110.13			77.09	4.44	28.60	0.00	242	126	Average	HORIZONTAL
5	2484.20	49.85	54.00	-4.15	16.67	4.51	28.67	0.00	242	126	Average	HORIZONTAL
6	2485.40	65.96	74.00	-8.04	32.78	4.51	28.67	0.00	242	126	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2466.80	105.25			72.11	4.51	28.63	0.00	239	143	Average	HORIZONTAL
2	2467.60	114.30			81.16	4.51	28.63	0.00	239	143	Peak	HORIZONTAL
3	2483.50	53.83	54.00	-0.17	20.65	4.51	28.67	0.00	239	143	Average	HORIZONTAL
4	2484.00	70.48	74.00	-3.52	37.30	4.51	28.67	0.00	239	143	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	21°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3
<b>Test Date</b>	Jun. 03, 2015		

**Channel 3**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	2384.21	53.62	54.00	-0.38	21.69	4.91	0.00	27.02	HORIZONTAL	248	184	Average
2	2390.00	71.63	74.00	-2.37	39.67	4.92	0.00	27.04	HORIZONTAL	248	184	Peak
3	2439.66	100.75			68.62	4.97	0.00	27.16	HORIZONTAL	248	184	Average
4	2439.66	110.67			78.54	4.97	0.00	27.16	HORIZONTAL	248	184	Peak

Item 3, 4 are the fundamental frequency at 2422 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	2388.84	73.29	74.00	-0.71	41.34	4.91	0.00	27.04	HORIZONTAL	246	175	Peak
2	2390.00	53.94	54.00	-0.06	21.98	4.92	0.00	27.04	HORIZONTAL	246	175	Average
3	2425.13	113.64			81.57	4.95	0.00	27.12	HORIZONTAL	246	175	Peak
4	2426.58	102.98			70.90	4.95	0.00	27.13	HORIZONTAL	246	175	Average
5	2483.50	49.45	54.00	-4.55	17.18	5.01	0.00	27.26	HORIZONTAL	246	175	Average
6	2484.95	68.07	74.00	-5.93	35.80	5.01	0.00	27.26	HORIZONTAL	246	175	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 9**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	2435.79	101.66			69.55	4.96	0.00	27.15	HORIZONTAL	247	178	Average
2	2435.79	111.69			79.58	4.96	0.00	27.15	HORIZONTAL	247	178	Peak
3	2483.50	52.23	54.00	-1.77	19.96	5.01	0.00	27.26	HORIZONTAL	247	178	Average
4	2483.50	69.21	74.00	-4.79	36.94	5.01	0.00	27.26	HORIZONTAL	247	178	Peak

Item 1, 2 are the fundamental frequency at 2452 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**For Emission not in Restricted Band**


**Plot on Configuration IEEE 802.11b / Reference Level**




**Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)**




Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)



Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 2 JUN 2015 14:43:43




Plot on Configuration IEEE 802.11g / Reference Level




Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)



Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 2 JUN 2015 14:55:09


Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)



Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 2 JUN 2015 15:05:09


Plot on Configuration IEEE 802.11n MCS0 HT40 / Reference Level



Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)



Date: 2 JUN 2015 15:11:12


Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 2 JUN 2015 15:12:29



Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 2 JUN 2015 15:12:57

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 22, 2015	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 02, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 02, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 03, 2014	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 06, 2015	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 12, 2015	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Feb. 24, 2015	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 12, 2015	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Nov. 06, 2014	Radiation (03CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 21, 2015	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 12, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 03, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

## 6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%