

Specifications

Mini-Nanoblade

Internal Antenna – Embedded


Specifications:

- Covers 2.4 to 2.5 GHz for 802.11b, and 4.9 to 6 GHz for 802.11a and all US, European, and Japanese WLAN applications
- Coaxial cable pigtail with various connector choices
- Omni-directional patterns at all frequencies with increased gain in upper bands for optimal coverage
- Conformance to European RoHs Directive 2002/95/EC



Frequency	2.4 – 2.5 GHz 4.9 – 6.0 GHz
Gain	2.0 – 2.5 dBi (2.4 – 2.5 GHz) 2.5 – 4.8 dBi (4.9 – 5.875 GHz)
Polarization	Vertical, Omni- directional
Norminal Impedance	50 ohms
VSWR	< 2 :1
Size	1.42" x 0.475"

Azimuth Patterns



Specifications subject to change without notice

CONFIDENTIAL and PROPRIETARY

The Information contained in this document is Confidential and Proprietary to **Laird Technologies (M) Sdn. Bhd.** and is subject to Non-Disclosure Agreements. It may not be reproduced without express written permission of **Laird Technologies (M) Sdn. Bhd.** Plot No. 522, Lorong Perusahaan Baru 3, Perai Industrial Estate, 13600 Prai Penang, West Malaysia.