

FCC Statement:

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device and its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.

IMPORTANT NOTE:

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator & your body.

INTEGRATION INFORMATION:

This module is intended for OEM integrator. The OEM integrator is still responsible for the FCC compliance requirement of the end product, which integrates this module.

20 cm minimum distance has to be able to be maintained between the antenna and the users for the host this module is grates into. Under such configuration, the FCC radiation exposure limits set forth for an population/uncontrolled environment can be satisfied.

Approved antennas:

#1: Puck antenna; Brand: TE connectivity; Part No. 1513164-1, Peak gain: +4 dBi

Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate this equipment.

USERS MANUAL OF THE END PRODUCT:

In the users manual of the end product, the end user has to be informed to keep at least 20 cm separation with the antenna while this end product is installed and operated. The end user has to be informed that the FCC radio-frequency exposure guidelines for an uncontrolled environment can be satisfied. The end user has to also be informed that any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate this equipment. If the size of the end product is smaller than 8x10cm, then additional FCC part 15.19 statement is required to be available in the users manual: This device complies with Part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

LABEL OF THE END PRODUCT:

The final end product must be labeled in a visible area with the following
"Contains FCC ID: U4Y-ESLREVC2".

In addition, the following FCC part 15.19 statement also has to be printed on the label:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

ISED Canada Statement:

This device complies with ISED Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'ISED Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This device and its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.

Cet appareil et son antenne (s) ne doit pas être co-localisés ou fonctionnement en association avec une autre antenne ou transmetteur.

IMPORTANT NOTE:**Canada Radiation Exposure Statement:**

This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator & your body.

NOTE IMPORTANTE:

Cet équipement est conforme aux IC RSS-102 limites d'exposition aux radiations définies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec distance minimum de 20 cm entre le radiateur et votre corps.

INTEGRATION INFORMATION:

This module is intended for OEM integrator. The OEM integrator is still responsible for the IC compliance requirement of the end product, which grates this module.

20 cm minimum distance has to be able to be maintained between the antenna and the users for the host this module is grated into. Under such configuration, the IC RSS-102 radiation exposure limits set forth for an population/uncontrolled environment can be satisfied.

Approved antennas:

#1: Puck antenna; Brand: TE connectivity; Part No. 1513164-1, Peak gain: +4 dBi

Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate this equipment.

RENSEIGNEMENTS D'INTÉGRATION:

L'intégrateur OEM est toujours responsable de la IC exigence de conformité du produit final, qui intègre ce module. 20cm distance minimale doit être capable d'être manue entre l'antenne et le utilisateurs pour l'hôte de ce module est intégré. Sous une telle configuration, le circuit intégré limites RSS-102 exposition aux radiations définies pour / un environnement non contrôlé de la population peut être satisfaite.

Antennas approuvées:

#1: Puck antenna; Brand: TE connectivity; Part No. 1513164-1, Peak gain: +4 dBi

Tout changement ou modification non expressément approuvés par le fabricant pourrait annuler la l'autorité de l'utilisateur à utiliser cet équipement.

USERS MANUAL OF THE END PRODUCT:

In the user's manual of the end product, the end user has to be informed to keep at least 20 cm separation with the antenna while this end product is installed and operated. The end user has to be informed that the IC radio-frequency exposure guidelines for an uncontrolled environment can be satisfied. The end user has to also be informed that any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate this equipment. The following IC statement is required to be available in the users manual:

This Class B digital apparatus complies with Canadian ICES-003.

Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

This device and its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.

This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator & your body.

DANS LE MANUEL D'UTILISATION DU PRODUIT FINAL:

L'utilisateur final doit être informé de garder au moins 20 cm de séparation avec l'antenne alors que ce produit final est installé et utilisé. Le utilisateur final doit être informé que les fréquences radioélectriques directives d'exposition IC pour un environnement non contrôlé peut être satisfaite. L'utilisateur final doit également être informé que toute changements ou modifications non expressément approuvés par le fabricant pourrait annuler la l'autorité de l'utilisateur à utiliser cet équipement. La déclaration suivant IC doit être disponible dans le manuel d'utilisation:

Cet appareil numérique de classe B est conforme à la norme ICES-003 du Canada.

Le fonctionnement est soumis aux deux conditions suivantes: (1) ce dispositif ne peut pas causer nuisibles interference et (2) cet appareil doit accepter toutes les interference reçues, y compris interference qui peuvent causer un mauvais fonctionnement.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Cet appareil et son antenne (s) ne doit pas être co-localisés ou fonctionnement en association avec une autre antenne ou transmetteur.

Cet équipement est conforme aux IC RSS-102 limites d'exposition aux radiations définies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec distance minimum de 20 cm entre le radiateur et votre corps.

LABEL OF THE END PRODUCT:

The final end product must be labeled in a visible area with the following "Contains IC: 7049A-ESLREVC2".

Le produit final doit être étiqueté dans une zone visible avec ce qui suit "Contient IC: 7049A-ESLREVC2".