

7th-8th FL, MiraeAsset Venture Tower, 20, Pangyoyeok-ro 241beongil, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea Tel No: +82-31-218-5582 Fax No: +82-31-218-5589

MODULAR APPROVAL LETTER

September 6, 2016

Applicant: BIXOLON Co., Ltd.

FCC ID: U5MBPM500

We would like to answer for limited Single Modular Approval in accordance with the requirement of rule part 15.212 as described below

No.	Requirements	Comment	Comply (Y/N)
1	The radio element of the modular transmitter has its own shielding	Refer to the external photo	Υ
2	The modular transmitter must have buffered modulation data/inputs (if such inputs are provided)	All input to the modules are buffered through microprocessor inputs.	Υ
3	The modular transmitter must have its own power supply regulation.	The module has power supply regulation, it is integrated in chip CSR8811A12	Υ
4	The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c).	Refer to the internal photo	Υ
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing.	The EUT was tested in a standalone configuration via a External UART cable. Refer to the test setup photo	Υ
6	The modular transmitter must be labeled with its own FCC ID. If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module	Refer to the user manual	Υ
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements	Refer to the user manual	Y
8	The modular transmitter must comply with any applicable RF exposure requirements	Refer to the RF exposure evaluation in the Test report.	Y

Sincerely,

Jisung Shin / Assistant Manager BIXOLON Co., Ltd.