

RR051-14-106166-2-A Ed. 0

## Certification test report

According to the standard:  
CFR 47 FCC PART 15

Equipment under test:  
REMOTE CONTROL  
REMOTE TRAINER

Model: RT350

FCC ID:  
U50-CDS35001

Company:  
Num'axes

DISTRIBUTION: Mrs Tonneau

(Company: ADEUNIS RF)

Number of pages: 27 with 6 appendixes

Ed.	Date	Modified pages	Written by		Technical Verification and Quality Approval	
			Name	Visa	Name	Visa
0	22/05/2015	Creation	S. LOUIS	SL		

Duplication of this test report is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.  
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.



**DESIGNATION OF PRODUCT:** REMOTE CONTROL REMOTE TRAINER

**Serial number (S/N):** —

**Reference / model (P/N):** RT 350

**Software version:** —

**MANUFACTURER:** Num'axes

**COMPANY SUBMITTING THE PRODUCT:**

**Company:** ADEUNIS RF

**Address:** 283, rue Louis Néel  
PARC TECHNOLOGIQUE PRE ROUX  
38920 CROLLES  
FRANCE

**Responsible:** Mrs Tonneau

**DATE(S) OF TEST:** From 10-FEB-2015 to 25-FEB-2015 and 18-MAY-2015

**TESTING LOCATION:** EMITECH ANGERS laboratory at JUIGNE SUR LOIRE (49) FRANCE  
EMITECH ANGERS open area test site in JUIGNE SUR LOIRE (49)  
FRANCE  
21 rue de la Fuye  
49610 Juigne sur Loire  
France  
FCC 2.948 Listed Site Registration Number: 90469  
FCC Accredited under US-EU MRA Designation Number: FR0009  
Test Firm Registration Number: 873677

**TESTED BY:** S. LOUIS

## CONTENTS

<i>TITLE</i>	<i>PAGE</i>
<b>1. INTRODUCTION</b> _____	<b>4</b>
<b>2. PRODUCT DESCRIPTION</b> _____	<b>4</b>
<b>3. NORMATIVE REFERENCE</b> _____	<b>4</b>
<b>4. TEST METHODOLOGY</b> _____	<b>5</b>
<b>5. TEST EQUIPMENT CALIBRATION DATES</b> _____	<b>6</b>
<b>6. TESTS AND CONCLUSIONS</b> _____	<b>7</b>
<b>7. RADIATED EMISSION LIMITS</b> _____	<b>11</b>
<b>8. ADDITIONAL PROVISIONS TO THE GENERAL RADIATED EMISSION LIMITATIONS</b> _____	<b>13</b>
<b>9. FUNDAMENTAL AND HARMONICS FIELD STRENGTH</b> _____	<b>15</b>
<b>10. OUT-OF-BAND EMISSIONS</b> _____	<b>17</b>

APPENDIX 1: Photos of the equipment under test

APPENDIX 2: Test set up

APPENDIX 3: Test equipment list

APPENDIX 4: Band edge

APPENDIX 5: 6 dB bandwidth

APPENDIX 6: 20 dB bandwidth

## **1. INTRODUCTION**

This document presents the result of RADIO test carried out on the following equipment: **REMOTE CONTROL REMOTE TRAINER RT350** in accordance with normative reference.

This equipment integrates the same radio part than the equipment REMOTE CONTROL REMOTE TRAINER with another antenna.

## **2. PRODUCT DESCRIPTION**

Class:	B (residential)
Antenna type and gain:	Internal antenna: unknown gain
Operating frequency range:	from 902 MHz to 928 MHz
Number of channels:	1
Channel spacing:	Not concerned
Modulation:	OOK
Power source:	Lithium battery 3Vdc type CR2430

Power level, frequency range and channels characteristics are not user adjustable.  
The details pictures of the product and the circuit boards are joined with this file.

## **3. NORMATIVE REFERENCE**

The standards and testing methods related throughout this report are those listed below.  
They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

CFR 47 FCC Part 15 (2014)	Radio Frequency Devices
ANSI C63.4	2009 Methods of measurement of Radio-Noise Emissions from low-voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
ANSI C63.10	2013 Testing Unlicensed Wireless Devices.

#### **4. TEST METHODOLOGY**

Radio performance tests procedures given in CFR 47 part 15:

##### Subpart A –General

- Paragraph 19: labelling requirements
- Paragraph 21: information to user

##### Subpart B –Unintentional Radiators

- Paragraph 105: information to the user
- Paragraph 107: Conducted limits
- Paragraph 109: Radiated emission limits
- Paragraph 111: Antenna power conduction limits for receivers

##### Subpart C – Intentional Radiators

- Paragraph 203: Antenna requirement
- Paragraph 205: Restricted bands of operation
- Paragraph 207: Conducted limits
- Paragraph 209: Radiated emission limits; general requirements
- Paragraph 212: Modular transmitter
- Paragraph 215: Additional provisions to the general radiated emission limitations
- Paragraph 249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0-24.25 GHz.

**5. TEST EQUIPMENT CALIBRATION DATES**

Equipment	Model	Type	Last verification	Next verification	Validity
0000	BAT-EMC V3.6.0.32	Software	/	/	/
1406	EMCO 6502	Loop antenna	27/01/2015	27/01/2017	27/03/2017
1922	Microwave DB C020180F-4B1	Low-noise amplifier	20/08/2014	20/08/2015	20/10/2015
4088	R&S FSP40	Spectrum Analyzer	22/08/2013	22/08/2015	22/10/2015
6609	Hewlett Packard HPM11630	High Pass Filter	24/02/2014	24/02/2016	24/04/2016
8511	HP 8447D	Low noise preamplifier	20/08/2014	20/08/2015	20/10/2015
8526	Schwarzbeck VHBB 9124	Biconical antenna	12/06/2012	12/06/2016	12/08/2016
8530	CHASE CBL6112A	Bi-log antenna	05/03/2013	05/03/2017	05/05/2017
8535	EMCO 3115	Antenna	29/10/2012	29/10/2016	29/12/2016
8543	Schwarzbeck UHALP 9108A	Log periodic antenna	12/06/2012	12/06/2016	12/08/2016
8593	SIDT Cage 2	Anechoic chamber	/	/	/
8675	AOIP MN5102B	Multimeter	23/02/2015	23/02/2017	23/04/2017
8707	R&S ESI7	Test receiver	11/12/2014	11/12/2016	11/02/2017
8732	Emitech	OATS	23/08/2013	23/08/2016	23/10/2016
8749	La Crosse Technology WS-9232	Meteo station	03/09/2014	03/09/2016	03/11/2016
8750	La Crosse Technology WS-9232	Meteo station	03/09/2014	03/09/2016	03/11/2016
8896	ACQUISYS GPS8	Satellite synchronized frequency standard	/	/	/

**6. TESTS AND CONCLUSIONS**

**6.1 general**

Test procedure	Description of test	Respected criteria?				Comment
		Yes	No	NAP	NAs	
FCC Part 15.19	LABELLING REQUIREMENTS				X	See certification documents
FCC Part 15.21	INFORMATION TO USER				X	See certification documents

NAP: Not Applicable

NAs: Not Asked

**LABEL SHALL CONTAIN**

The label shall be located in a conspicuous location on the device

The label shall not be a stick-on, paper label. The label on these products shall be permanently affixed to the product and shall be readily visible to the purchaser at the time of purchase

**§15.19:**

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

**USER NOTICE SHALL CONTAIN**

The user notice, not provided during tests, shall include the following informations:

**§15.21:**

*Any changes or modifications to this equipment not expressly approved by Num'axes may cause, harmful interference and void the FCC authorization to operate this equipment*

**6.2 unintentional radiator (subpart B)**

Test procedure	Description of test	Respected criteria?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.105	INFORMATION TO THE USER				X	See certification documents
FCC Part 15.107	CONDUCTED LIMITS			X		
FCC Part 15.109	RADIATED EMISSION LIMITS	X				B
FCC Part 15.111	ANTENNA POWER CONDUCTED LIMITS FOR RECEIVER			X		

NAp: Not Applicable

NAs: Not Asked

**USER NOTICE SHALL CONTAIN**

The user notice, not provided during tests, shall include the following informations:

**§ 15.105:**

*NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference's by one or more of the following measures:*

- Reorient or relocate the receiving antenna.*
- Increase the separation between the equipment and the receiver.*
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.*
- Consult the dealer or an experienced radio/TV technician for help.*



**6.2 intentional radiator (subpart C)**

Test procedure	Description of test	Respected criteria?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.203	ANTENNA REQUIREMENT	X				Note 1
FCC Part 15.205	RESTRICTED BANDS OF OPERATION	X				
FCC Part 15.207	CONDUCTED LIMITS			X		
FCC Part 15.209	RADIATED EMISSION LIMITS; general requirements	X				Note 2
FCC Part 15.212	MODULAR TRANSMITTERS			X		
FCC part 15.215	ADDITIONAL PROVISIONS TO THE GENERAL RADIATED EMISSION LIMITATIONS					
	(a) Alternative to general radiated emission limits	X				
	(b) Unwanted emissions outside of §15.249 frequency bands	X				Note 3
	(c) 20 dB bandwidth and band-edge compliance	X				
FCC Part 15.249	OPERATION WITHIN THE BANDS 902-928 MHZ, 2400-2483.5 MHz, 5725-5850 MHz AND 24.0-24.25 GHz					
	(a) Fundamental and harmonics field strength	X				
	(b) Fixed point-to-point operation		X			
	(c) Measurement distance	X				
	(d) Out-of-band emissions	X				
	(e) Field strength limits above 1 GHz	X				

NAp: Not Applicable

NAs: Not Asked

Note 1: Integral / dedicated antenna. Professionally installed equipment.

Note 2: See FCC part 15.249 (d).

Note 3: See FCC part 15.209. Unwanted emissions levels are all below the fundamental emission field strength level.

**RF EXPOSURE:**

Maximum measured power = 92.6 dB $\mu$ V/m = 0.546 mW

*In accordance with KDB 447498 D01 General RF Exposure Guidance v05r02, Paragraph 4.3.1.*

*The product must respect the exclusion limit for 10-g extremity SAR:*

*$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 7.5$*

*min. test separation distance, mm  $\geq [(\text{max. power of channel, including tune-up tolerance, mW}) * [\sqrt{f(\text{GHz})} / 7.5]$*

*min. test separation distance, mm  $\geq 0.546(\text{mW}) * [\sqrt{(0.915)/7.5}]$*

*min. test separation distance, mm  $\geq$  **0.069 mm***

*The minimum distance between the user and the antenna is more than 0.09 mm (see photos in appendix 1).*

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.

## **7. RADIATED EMISSION LIMITS**

**Standard:** FCC Part 15

**Test procedure:** Paragraph 109

**Limit class:** Class B

### **Test set up:**

First an exploratory radiated measurement was performed. During this phase the product is oriented in three orthogonal planes.

Then the final measurement is realized with the product on the most critical orientation.

The final measure is realized on open area test site under 1 GHz and in anechoic chamber above 1 GHz.

When the system is tested in an open area test site (OATS), the EUT is placed on a rotating table, 0.8m from a ground plane.

When the system is tested in anechoic chamber, the EUT is placed on a rotating table, 1.5m from a ground plane.

Zero degree azimuths correspond to the front of the device under test.

See photos in appendix 2.

**Frequency range:** From 30 MHz to 5GHz (5<sup>th</sup> harmonic of the highest frequency used '915 MHz').

**Detection mode:** Quasi-peak (F < 1 GHz)                      Average (F > 1 GHz)

**Bandwidth:** 120 kHz (F < 1 GHz)                              1 MHz (F > 1 GHz)

**Distance of antenna:** 10 meters (in open area test site) / 3 meters (in anechoic room)

**Antenna height:** 1 to 4 meters (in open area test site) / 1.5 meter (in anechoic room)

**Antenna polarization:** vertical and horizontal (only the highest level is recorded)

**Equipment under test operating condition:**

The equipment is blocked in reception mode.

**Results:**

Ambient temperature (°C): 21.4  
Relative humidity (%): 29

Power source:

We used for power source the internal battery of the equipment and we noted:

Voltage at the beginning of test (V): 3.09  
Voltage at the end of test (V): 3.03  
Percentage of voltage drop during the test (%): 1.94

**Sample N° 1:**

Not any spurious has been detected.

Applicable limits:	for $30 \text{ MHz} \leq F \leq 88 \text{ MHz}$ :	40 dB $\mu$ V/m at 3 meters
	for $88 \text{ MHz} < F \leq 216 \text{ MHz}$ :	43.5 dB $\mu$ V/m at 3 meters
	for $216 \text{ MHz} < F \leq 960 \text{ MHz}$ :	46 dB $\mu$ V/m at 3 meters
	Above 960 MHz :	54 dB $\mu$ V/m at 3 meters

Note: any spurious which has more than 20 dB of margin compared to the applicable limit is not necessarily reported.

**Test conclusion:**

RESPECTED STANDARD

**8. ADDITIONAL PROVISIONS TO THE GENERAL RADIATED EMISSION LIMITATIONS**

**Standard:** FCC Part 15

**Test procedure:** Paragraph 15.215

**Test set up:**

Test realized in near field. All field strength measurements are correlated with the radiated maximum peak output power

**Test operating condition of the equipment:**

The equipment under test is blocked in continuous transmission mode, modulated by internal data signal, at the highest output power level which the transmitter is intended to operate.

**Results:**

Ambient temperature (°C): 21.2  
 Relative humidity (%): 36

Power source:

We used for power source the internal battery of the equipment and we noted:

Voltage at the beginning of test (V): 3.09  
 Voltage at the end of test (V): 3.03  
 Percentage of voltage drop during the test (%): 1.94

Lower Band Edge: band from 900 MHz to 902 MHz  
 Upper Band Edge: band from 928 MHz to 930 MHz

Sample N° 1:

FUNDAMENTAL FREQUENCY (MHZ)	FIELD STRENGTH LEVEL OF FUNDAMENTAL (DBµV/M)	DETECTOR (PEAK OR AVERAGE)	FREQUENCY OF MAXIMUM BAND-EDGES EMISSION (MHZ)	DELTA MARKER (DB)*	CALCULATED MAX OUT-OF-BAND EMISSION LEVEL (DBµV/M)	LIMIT (DBµV/M)	MARGIN (DB)
915	92.6	PEAK	901.952	56.46	36.14	46	9.86
915	92.6	PEAK	928.208	57.93	34.67	46	11.33

\* Marker-Delta method

The 20 dB bandwidth curves are given in appendix 6; band-edge curves are given in appendix 4.

**Test conclusion:**

RESPECTED STANDARD

## **9. FUNDAMENTAL AND HARMONICS FIELD STRENGTH**

**Standard:** FCC Part 15

**Test procedure:** paragraph 15.249 (a)

### **Test set up:**

First an exploratory radiated measurement was performed. During this phase the product is oriented in three orthogonal planes.

Then the final measurement is realized with the product on the most critical orientation.

The final measure is realized on open area test site under 1 GHz and in anechoic chamber above 1 GHz.

When the system is tested in an open area test site (OATS), the EUT is placed on a rotating table, 0.8m from a ground plane.

When the system is tested in anechoic chamber, the EUT is placed on a rotating table, 1.5m from a ground plane.

Zero degree azimuths correspond to the front of the device under test.

See photos in appendix 2.

**Frequency range:** From 9 kHz to 10GHz (10<sup>th</sup> harmonic of the highest fundamental frequency '915 MHz').

**Detection mode:** Quasi-peak (F < 1 GHz)                      Peak / Average (F > 1 GHz)

**Bandwidth:** 120 kHz (30 MHz < F < 1 GHz)  
1 MHz (F > 1 GHz)

**Distance of antenna:** 10 meters (in open area test site) / 3 meters (in anechoic room)

**Antenna height:** 1 to 4 meters (in open area test site) / 1.5 meter (in anechoic room)

**Antenna polarization:** vertical and horizontal (only the highest level is recorded)

### **Equipment under test operating condition:**

The equipment under test is blocked in continuous transmission mode, modulated by internal data signal, at the highest output power level which the transmitter is intended to operate.

**Results:**

Ambient temperature (°C): 21.4  
 Relative humidity (%): 29

Power source:

We used for power source the internal battery of the equipment and we noted:

Voltage at the beginning of test (V): 3.09  
 Voltage at the end of test (V): 3.03  
 Percentage of voltage drop during the test (%): 1.94

Sample N° 1

FREQUENCIES (MHz)	Detector <i>P: Peak Av: Average QP: Quasi-Peak</i>	Antenna height (cm)	Azimuth (degree)	resolution bandwidth (kHz)	Polarization H: Horizontal V: Vertical	Field strength (dBμV/m)	Limits (dBμV/m)	Margin (dB)
915	QP	219	246	120	V	91.91*	94	2.09
1830.1	P	150	—	1000	V	48.3**	74	25.7
2745.4	P	150	—	1000	V	48.6**	74	25.4

\* Fundamental emission

\*\*The peak level is lower than the average limit (54 dBμV/m).

Note: any spurious which has more than 20 dB of margin compared to the limit is not necessarily reported.

**Test conclusion:**

RESPECTED STANDARD



## **10. OUT-OF-BAND EMISSIONS**

**Standard:** FCC Part 15

**Test procedure:** paragraph 15.205  
paragraph 15.209  
paragraph 15.249 (d)

### **Test set up:**

First an exploratory radiated measurement was performed. During this phase the product is oriented in three orthogonal planes.

Then the final measurement is realized with the product on the most critical orientation.

The final measure is realized on open area test site under 1 GHz and in anechoic chamber above 1 GHz.

When the system is tested in an open area test site (OATS), the EUT is placed on a rotating table, 0.8m from a ground plane.

When the system is tested in anechoic chamber, the EUT is placed on a rotating table, 1.5m from a ground plane.

Zero degree azimuths correspond to the front of the device under test.

See photos in appendix 2.

**Frequency range:** From 9 kHz to 10<sup>th</sup> harmonic of the highest fundamental frequency (915 MHz).

**Detection mode:** Quasi-peak (F < 1 GHz)                      Peak / Average (F > 1 GHz)

**Bandwidth:** 200Hz (9 kHz < F < 150 kHz)  
9 kHz (150 kHz < F < 30MHz)  
120 kHz (30 MHz < F < 1 GHz)  
1 MHz (F > 1 GHz)

**Distance of antenna:** 10 meters (in open area test site) / 3 meters (in anechoic room)

**Antenna height:** 1 to 4 meters (in open area test site) / 1.5 meter (in anechoic room)

**Antenna polarization:** vertical and horizontal (only the highest level is recorded)

### **Equipment under test operating condition:**

The equipment under test is blocked in continuous transmission mode, modulated by internal data signal, at the highest output power level which the transmitter is intended to operate.

**Results:**

Ambient temperature (°C): 21.4  
Relative humidity (%): 29

Power source:

We used for power source the internal battery of the equipment and we noted:

Voltage at the beginning of test (V): 3.09  
Voltage at the end of test (V): 3.03  
Percentage of voltage drop during the test (%): 1.94

Sample N° 1

Not any spurious has been detected.

Applicable limits: see 15.209


Note: any spurious which has more than 20 dB of margin compared to the applicable limit is not necessarily reported.

**Test conclusion:**

RESPECTED STANDARD



**□□□ End of report, 6 appendixes to be forwarded □□□**

## APPENDIX 1: Photos of the equipment under test




## APPENDIX 2: Test set up

In anechoic room test site



In open area test site



## APPENDIX 3: Test equipment list

### Radiated emission limits

TYPE	MANUFACTURER	EMITECH NUMBER
Anechoic Chamber	EMITECH	8593
Satellite synchronized frequency standard GPS8	ACQUISYS	8896
Spectrum Analyzer FSP40	Rohde & Schwarz	4088
Biconical antenna VHBB 9124	Schwarzbeck	8526
Log periodic antenna UHALP 9108A	Schwarzbeck	8543
Antenna 3115	Electrometrics	8535
Low-noise amplifier 8447D	Hewlett Packard	8511
Low-noise amplifier C020180F-4B1	Microwave DB	1922
Multimeter MN5102B	AOIP	8675
Meteo station WS-9232	La Crosse Technology	8750
Software	BAT-EMC V3.6.0.32	0000

### Additional provisions to the general radiated emission limitations

TYPE	MANUFACTURER	EMITECH NUMBER
Test receiver ESI7	Rohde & Schwarz	8707
Log periodic antenna UHALP 9108A	Schwarzbeck	8543
Multimeter MN5102B	AOIP	8675
Meteo station WS-9232	La Crosse Technology	8750
Software	GPIBShot V2.4	-

**Fundamental and harmonics field strength**

TYPE	MANUFACTURER	EMITECH NUMBER
Open test site	EMITECH	8732
Anechoic Chamber	EMITECH	8593
Satellite synchronized frequency standard GPS8	ACQUISYS	8896
Test receiver ESI7	Rohde & Schwarz	8707
Spectrum Analyzer FSP40	Rohde & Schwarz	4088
Biconical antenna VHBB 9124	Schwarzbeck	8526
Log periodic antenna UHALP 9108A	Schwarzbeck	8543
Bi-log antenna CBL6112A	Chase	8530
Antenna 3115	Electrometrics	8535
Low-noise amplifier 8447D	Hewlett Packard	8511
Low-noise amplifier C020180F-4B1	Microwave DB	1922
High pass filter HPM11630	Hewlett Packard	6609
Multimeter MN5102B	AOIP	8675
Meteo station WS-9232	La Crosse Technology	8749
Meteo station WS-9232	La Crosse Technology	8750
Software	BAT-EMC V3.6.0.32	0000

**Out of band emissions**


TYPE	MANUFACTURER	EMITECH NUMBER
Anechoic Chamber	EMITECH	8593
Satellite synchronized frequency standard GPS8	ACQUISYS	8896
Spectrum Analyzer FSP40	Rohde & Schwarz	4088
Loop antenna 6502	EMCO	1406
Biconical antenna VHBB 9124	Schwarzbeck	8526
Log periodic antenna UHALP 9108A	Schwarzbeck	8543
Antenna 3115	Electrometrics	8535
Low-noise amplifier 8447D	Hewlett Packard	8511
Low-noise amplifier C020180F-4B1	Microwave DB	1922
High pass filter HPM11630	Hewlett Packard	6609
Multimeter MN5102B	AOIP	8675
Meteo station WS-9232	La Crosse Technology	8750
Software	BAT-EMC V3.6.0.32	0000







## APPENDIX 5: 6 dB bandwidth



## APPENDIX 6: 20 dB bandwidth

