

**Resolution Products, Inc.**

**Wireless Driveway Transmitter**  
**FCC ID: U5X-RE104**

**Certification Test Report**

**June 9, 2010**

# Contents

1. Introduction.....	3
2. Statement of Compliance.....	3
2.1. FCC Part 2 §2.907.....	3
2.2. FCC Part 2 §2.911.....	3
2.3. FCC Part 2 §2.913.....	3
2.4. FCC Part 2 §2.915.....	3
2.5. FCC Part 2 §2.925.....	3
2.6. FCC Part 2 §2.943, 2.945.....	3
2.7. FCC Part 2 §2.947.....	4
2.8. FCC Part 2 §2.948.....	4
2.9. FCC Part 2 §2.1033.....	5
3. Discussion of Laboratory Measurements and Rules Compliance.....	6
3.1. FCC Part 15 §15.231(a)(1).....	6
3.2. FCC Part 15 §15.231(a)(3).....	6
3.3. FCC Part 15 §15.231(a)(4).....	7
3.4. FCC Part 15 §15.231(a)(5).....	7
3.5. FCC Part 15 §15.231(b).....	7
3.5.1. Raw Field Strength Limits.....	7
3.5.2. Duty Cycle Correction Factor and Resulting Limits.....	8
3.5.3. Measured Radiated Field Strength Data.....	9
3.6. FCC Part 15 §15.231(c).....	9

## **1. Introduction**

This device is a wireless driveway transmitter for use in a wireless security system. The unit is powered by two C-size alkaline batteries. The transmitter is centered at 319.5MHz and is controlled by a SAW resonator. The device measures 5.1 x 3.8”.

This transmitter is activated by an internal magnetometer that detects the change in the earth's magnetic field caused by a nearby vehicle. Transmission packets are sent by the device upon valid activation. These packets are 20ms in length and are sent with a random spacing of 170ms to 800ms. Upon completion of these packets, the device goes into sleep mode and will not transmit again until another activation. If no activation is received for one hour, three supervisory packets are sent with the same spacing given above.

Certification is requested under FCC Rules, Part 15, Subpart C, Paragraph 15.231.

## **2. Statement of Compliance**

Specific sections of FCC Rules Part 2 that require information or listing are given below.

### **2.1. FCC Part 2 §2.907**

This is an application for certification of original equipment

### **2.2. FCC Part 2 §2.911**

- a) This application has been filed electronically using form 731.
- b) All required information has been supplied in this application and its attachments.
- c) This application has been electronically signed by an officer of Resolution Products, Inc.
- d) The technical test data has been signed by the agency performing the testing.
- e) Signature supplied in appropriate block on form 731.
- f) Processing fee has been paid by credit card.
- g) Signatures have been supplied electronically.

### **2.3. FCC Part 2 §2.913**

- a) This application has been filed electronically.
- b) Appropriate fees have been filed electronically.
- c) Equipment samples shall be supplied as requested.

### **2.4. FCC Part 2 §2.915**

We are requesting a grant of certification. This application shows compliance with the technical standards.

### **2.5. FCC Part 2 §2.925**

A label shall be affixed to each piece of equipment, showing the FCC identifier. The label shall read “FCC ID: U5X-RE104”. See Exhibit A for a photograph showing the label and location on the device.

### **2.6. FCC Part 2 §2.943, 2.945**

Sample production equipment shall be submitted to the FCC upon request.

### **2.7. FCC Part 2 §2.947**

- a) Measurement procedure follows ANSI C63.4: 2003.
- b) A description of utilized test equipment is contained in the report.

### **2.8. FCC Part 2 §2.948**

Radiated measurements were taken at the following FCC-approved facility:

**Rhein Tech Laboratories, Inc.**


**360 Herndon Parkway, Suite 1400**

**Herndon, VA 20170 USA**

**Contact: Rick McMurray**

**703-689-0368**

A photograph of the test site is shown below:



## **2.9. FCC Part 2 §2.1033**

- a) Form 731 has been filed electronically.
- b) The technical report, along with its exhibits, contains the information as follows:
  - (1) full name and mailing address of the manufacturer of the device and the applicant for certification:  
Resolution Products, Inc.  
226 Locust Street, Suite 4  
Hudson, WI 54016
  - (2) FCC Identifier is U5X-RE104
  - (3) Copy of the installation/user instructions is furnished as Exhibit E.
  - (4) A brief description of the device and operation is furnished in Exhibit F. Schematic is furnished in Exhibit G.
  - (5) Block diagram furnished in Exhibit H.
  - (6) This document constitutes a technical test report.
  - (7) Internal and external photographs have been furnished in Exhibits A - C.
  - (8) Not applicable. There are no peripheral or accessory devices used with this device. It is a standalone device.
  - (9) This application not pursuant to the transition rules of section 15.37
  - (10) Not applicable. This device does not include a scanning receiver.
  - (11) Not applicable.
  - (12) Not applicable.
- c) Not applicable. This device shall operate under Part 15 of the rules.
- d) Not applicable.
- e) Not applicable. This is not a composite system.


### 3. Discussion of Laboratory Measurements and Rules Compliance

#### 3.1. FCC Part 15 §15.231(a)(1)

This transmitter is activated by an internal magnetometer that detects the change in the earth's magnetic field caused by a nearby vehicle. Transmission packets are sent by the device upon valid activation. These packets are 20ms in length and are sent with a random spacing of 170ms to 800ms. Upon completion of these packets, the device goes into sleep mode and will not transmit again until another activation. If no activation is received for one hour, three supervisory packets are sent with the same spacing given above.

A plot of the transmissions is shown below. This plot shows the transmissions occurring in a 5 second window as a result of one activation. The packets are shown to conclude within the 5-second window.

This plot made using Hewlett Packard Model 8591E Spectrum Analyzer (calibration due date 12/2/2010).



#### 3.2. FCC Part 15 §15.231(a)(3)

If no switch activations have been received for a period of one hour, three supervision packets are transmitted. These supervision packets are then transmitted every hour in the absence of activations. The total transmission time resulting from these supervision transmissions is well under the allowed 2 seconds per hour. They conclude within the 5-second window.

### **3.3. FCC Part 15 §15.231(a)(4)**

While this device is used in a security application, it does not continue transmitting beyond the packets resulting from each activation.

### **3.4. FCC Part 15 §15.231(a)(5)**

While this device is used in a security application, there is no setup information transmitted with this device.

### **3.5. FCC Part 15 §15.231(b)**

#### **3.5.1. Raw Field Strength Limits**

Interpolation performed on the data in the §15.231(b) table yields raw field strength limits as follows:

Fundamental: 75.9dBuV/m

Spurious: : 55.9dBuV/m

Certain harmonics of the transmitted signal fall in the restricted bands of §15.205. These harmonics are all above 960MHz and have the following limit as given in §15.209:


**Restricted band limit = 500uV/m = 54dBuV/m.**



### 3.5.2. Duty Cycle Correction Factor and Resulting Limits

This transmitter uses ASK modulation. 63 bits are transmitted in each packet, and the "on" time for each bit is 122usec, except for one bit which has an "on" time of 366usec. The resulting "on" time per packet is 7.93ms. The transmitted packets are limited to one packet in a 125ms period. The transmitter duty cycle over a 100ms time period is therefore  $7.93/100 = 7.93\%$ .

The packet width measurement below was made using Hewlett Packard Model 8591E Spectrum Analyzer (calibration due date 12/2/2010).



Calculating the allowed duty cycle correction factor as given in §15.35(c):

$$20\log(7.93/100) = -22.01\text{dB}$$

This transmitter therefore qualifies for the maximum duty cycle correction factor allowed in §15.35(c). The maximum duty cycle correction factor allowed is 20dB. Resulting radiated field strength limits are as follows:

<b>Fundamental:</b>	<b>95.9dBuV/m</b>
<b>Spurious: :</b>	<b>75.9dBuV/m</b>
<b>Restricted Band:</b>	<b>74dBuV/m</b>



### 3.5.3. Measured Radiated Field Strength Data

Measured radiated field strength data is shown in Exhibit L. Emissions data was taken at 3 meters in all three orthogonal planes in order to measure the highest emissions. Emissions from 0.009 MHz to the tenth harmonic were measured as per §15.33(a). Appropriate correction factors were applied to account for cable and other site-specific losses. The highest measurements are shown in the table for each frequency showing measurable signal.

The fundamental signal, at 95.1dBuV/m, passed by 0.8dB

The highest spurious signal was the ninth harmonic, which passed by 5.2dB.

### 3.6. FCC Part 15 §15.231(c)


Allowed 20dB bandwidth of the transmitted signal is 0.25% of the carrier frequency.

BW Limit =  $0.0025 \times 319.5 \text{ MHz}$


**BW Limit = 0.799 MHz**

Bandwidth measurements were made using Hewlett Packard Model 8591E Spectrum Analyzer (calibration due date 12/2/2010).

The following plot shows the unmodulated carrier signal



The following plot shows the modulated signal. Bandwidth of the modulated signal is 166.5kHz or .1665MHz.



These measurements show compliance with the bandwidth requirements.