



Model: RE113 GE-Compatible Smoke
FCC ID: UXX-RE113
IC: 8310A-RE113
ResolutorProducts.com
442841810 or 442841810 (Canada) Date: 11/2013



Test Weekly	
Alarm Maintenance Cycle	
Chime	90-240 minutes
Chime	10-60 minutes
Chime	4-15 minutes

LED indicator 5 min. warm-up after battery is installed. Orange LED will flash once every 15s, and the photo will sound once every minute. Normal operation is indicated by the green LED flashing once a minute.

For Repair, Return unit to: EVERDAY Technology Co., Ltd
No. 95, Sec. 2, Ligong 1st Rd., Linyu Industrial Park, Yilan County 26541, Taiwan

WARNING: Carbon Monoxide can not be seen or smelled but can kill you. It is a silent killer. If you have a carbon monoxide alarm, test it every month. If you have a carbon monoxide alarm, test it every month. If you have a carbon monoxide alarm, test it every month.

CAUTION: Push the test button gently to test the operating function. Use a maximum pressure to clean the air vents periodically to keep them free of dust.

SIGNALING
UL LISTED
Single-Station Carbon Monoxide Alarm
SLS HC 06-6 9 9 8 8
522651


International Carbon Monoxide Alarm Standard No. IEC623 Type A Rating: ICC-1 (ULFA's Standard No. IEC 62301) Date of Approval: 2013, July 20. Alarm maintenance time: 400 years within 0.1% tolerance.

WARNING: Use Only Batteries Specified in Manual. Use Of A Different Battery May Cause A Short-Circuit When The Alarm Operates.

Troubleshooting:
Batteries - Push on gently, one after per minute.
Low Battery - Battery will flash once per minute, and beep per minute.
Low Sensitivity - Battery will flash twice per minute, one chirp per minute.
Malfunction Alarm - Battery will flash three times per minute, one chirp per minute.
Dead of Use - Battery will flash four times per minute, one chirp per minute.
Considered appropriate to high or low temperature or high humidity may reduce battery life. For replacements, please refer to user's manual.
General: For further details, please refer to user's manual.

Model: RE113 GE-Compatible Carbon Monoxide Sensor
FCC ID: UXX-RE113
IC: 8310A-RE113
ResolutorProducts.com
442841810 or 442841810 (Canada) Date: 11/2013

reset/silence button. 2) Call your emergency services (fire department or 911). 3) Immediately move to fresh air - outdoors or by an open door/windows



Model No. M330, Type A Rating: DC 4.5V/AA*3
Series No MF26031 Date of MFG : 2013 . Jun 20
Alarm response time: 400 ppm within 4-15minutes

CAUTION: Push the test button weekly to test its operating function. Use a vacuum cleaner to clean the air vents occasionally to keep them free of dust.

WARNING: Use Only Batteries Specified In Marking. Use Of A Different Battery May Have A Detrimental Effect On Alarm Operation.

SIGNALING

LISTED
Single-Station
Carbon Monoxide Alarm
ISSUE NO. BN- **6 9 9 8 8**
E326257

Troubles:

- Tamper - Yellow on Steady, one chirp per minute.
- Low Battery - Yellow will flash once per minute, one beep per minute.
- Low Sensitivity - Yellow will flash twice per minute, one chirp per minute.
- Malfunction Error - Yellow will flash three times per minute, one chirp per minute.
- End of Life - Yellow will flash four times per minute, one chirp per minute.

Constant exposures to high or low temperatures or high humidity may reduce battery life. For replace batteries, please refer to user's manual.

Remark: For further details, please refer to user's manual.

Model: RE113 GE-Compatible Carbon Monoxide Sensor
FCC ID: U5X-RE113
IC: 8310A-RE113
ResolutionProducts.com
ASSEMBLED IN US OF US/IMPORTED COMPONENTS Date: 13263

