



Engineering Solutions & Electromagnetic Compatibility Services

**FCC 15.231 Test Data**

**for**

**Model: 345 MHz Door Window Sensor**

**Board Number: 56-0010-02 Rev A02**

(RTL barcode: 20539)

**for**

**Resolution Engineering**

**RTL Project Number 2012055**

**Test Engineer: Jon Wilson**

This report may not be reproduced, except in full, without the full written approval of Rhein Tech Laboratories, Inc. and Resolution Engineering. Test results relate only to the item tested.

These tests are accredited and meet the requirements of ISO/IEC 17025 as verified by ANSI-ASQ National Accreditation Board/ACLASS. Refer to certificate and scope of accreditation AT-1445.

**Description of testing presented in this test report**

The data and limits presented in this report are for peak emissions limiting per 15.231(b)(2) which references 15.35(b), and peak limiting for restricted bands per 15.209(e) which again references 15.35(b)(2), as procured by Resolution Engineering. No average data is presented in this report.

**Radiated Emissions Test Data – FCC Limits / 3m Distance**

Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pass/Fail
345.017	Peak	V	64.0	27.4	91.4	97.3	-5.9	Pass
690.002	Peak	H	72.8	-5.9	66.9	77.3	-10.4	Pass
1035.012	Peak	H	52.7	-0.7	52.0	74.0	-22.0	Pass
1380.012	Peak	V	61.0	4.2	65.2	74.0	-8.8	Pass
1725.012	Peak	V	39.9	8.0	47.9	77.3	-29.4	Pass
2070.012	Peak	V	58.5	-9.1	49.4	77.3	-27.9	Pass
2415.012	Peak	V	54.7	-8.3	46.4	77.3	-30.9	Pass
2760.012	Peak	V	56.2	-8.1	48.1	74.0	-25.9	Pass
3105.012	Peak	V	47.6	-7.6	40.0	77.3	-37.3	Pass
3450.012	Peak	V	56.7	-7.1	49.6	77.3	-27.7	Pass

**Test Procedure**

Radiated emissions of the harmonics were tested at three meters. The EUT was tested in the three orthogonal planes with the receive antenna in both polarities. The emissions were maximized per ANSI C63.4:2003 8.3.1.2; that is, the measurement antenna height was varied between 1 and 4 m, and the EUT was rotated through 360° on a rotating turntable until the maximum emissions were found. Both horizontal and vertical measurement antenna polarizations were used. A resolution bandwidth of 100 kHz was used for frequencies less than 1000 MHz, and a resolution bandwidth of 1 MHz was used for frequencies greater than or equal to 1000 MHz. The video bandwidth was set to a value at least three times greater than the resolution bandwidth.


**EUT Disposition**

The EUT was adapted to continuously transmit for testing purposes.

**Radiated Emissions Test Equipment**


Part	Manufacturer	Model	Serial Number	RTL Bar Code	Calibration Due Date
Amplifier (20 MHz-2 GHz)	Rhein Tech Laboratories, Inc.	PR-1040	900905	900905	4/10/12
Bilog Periodic Antenna (25 MHz-2 GHz)	Schaffner Chase	CBL6112	2099	900791	12/12/12
EMI Receiver RF Section (9 KHz-6.5 GHz)	Hewlett Packard	85462A	3325A00159	900913	6/8/12
RF Filter Section (100 KHz-6.5 GHz)	Hewlett Packard	85460A	3330A00107	900914	6/8/12
Amplifier (1 GHz-26.0 GHz)	Rhein Tech Laboratories, Inc.	PR-1042	N/A	901364	7/14/12
Horn Antenna (2.0-4.0 GHz)	EMCO	3161-02	9804-1044	900772	6/13/12
Emissions Testing Software	Rhein Tech Laboratories, Inc.	Automated Emission Tester	Rev. 14.0.2	N/A	N/A

**Test Personnel:**


Jon Wilson		February 3, 2012
Test Engineer	Signature	Date of Test

### Test Configuration Photographs

**X-Axis**




**Y-Axis**





**Z-Axis**



Rhein Tech Laboratories, Inc.  
360 Herndon Parkway  
Suite 1400  
Herndon, VA 20170  
<http://www.rheintech.com>

Client: Resolution Engineering  
Model: 345 MHz Door Window Sensor  
FCC ID: N/A  
Standards: FCC Part 2, 15  
Report #: 2012055

**EUT Photograph**

