



Engineering Solutions & Electromagnetic Compatibility Services

FCC Part 15.231 Test Data

345 MHz 360PIR

Model: 56-0092-02 RevB00

for

**Resolution Engineering, Inc.
1402 Heggen Street
Hudson, WI 54016
Contact: Josh Gathje**

Testing Conducted By:

**Rhein Tech Laboratories, Inc.
360 Herndon Parkway, Suite 1400
Herndon, VA 20170
RTL Test Engineer: Dan Baltzell**

RTL Project/Report Number: 2017246

January 3, 2018

This report may not be reproduced, except in full, without the full written approval of Rhein Tech Laboratories, Inc. and Resolution Engineering. Test results relate only to the item tested.

These tests are accredited and meet the requirements of ISO/IEC 17025 as verified by ANAB. Refer to certificate and scope of accreditation AT-1445.

Testing Represented in Report

The data and limits presented in this report are for radiated emissions per 15.231(b)(2) which references 15.35(b), and peak limiting for restricted bands per 15.209(e), which again references 15.35(b)(2), as procured by Resolution Engineering. No average data is presented in this report. Data is also presented for spurious, non-harmonic radiated emissions per 15.209. The Equipment Under Test (EUT) was the **345 MHz Sensor (RTL Bar Code 22676)**.

Test Procedure

Radiated fundamental and spurious emissions were tested at three meters. The EUT was tested in the three orthogonal planes with the receive antenna in both polarities. The emissions were maximized; that is, the measurement antenna height was varied between 1 and 4 m, and the EUT was rotated through 360° on a rotating turntable until the maximum emissions were found. Both horizontal and vertical measurement antenna polarizations were used. A resolution bandwidth of 120 kHz was used for frequencies less than 1000 MHz, and a resolution bandwidth of 1 MHz was used for frequencies greater than or equal to 1000 MHz. The video bandwidth was set to a value at least three times greater than the resolution bandwidth.

EUT Disposition

The EUT was adapted to continuously transmit for testing purposes.

15.231 Radiated Spurious Harmonics Emissions Test Data – Peak

| Emission Frequency (MHz) | Test Detector | Antenna Polarity (H/V) | Analyzer Reading (dBuV) | Site Correction Factor (dB/m) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Pass/Fail |
|--------------------------|---------------|------------------------|-------------------------|-------------------------------|-------------------------|----------------|-------------|-----------|
| 345.0 | Peak | H | 67.4 | 29.4 | 96.8 | 97.3 | -0.5 | Pass |
| 690.0 | Peak | V | 73.9 | 0.4 | 74.3 | 77.3 | -3.0 | Pass |
| 1035.0 | Peak | H | 41.1 | 7.5 | 48.6 | 74.0 | -25.4 | Pass |
| 1380.0 | Peak | H | 39.3 | 14.5 | 53.8 | 74.0 | -20.2 | Pass |
| 1725.0 | Peak | H | 34.6 | 21.9 | 56.5 | 77.3 | -20.8 | Pass |
| 2070.0 | Peak | V | 10.2 | 24.8 | 35.0 | 77.3 | -42.3 | Pass |
| 2415.0 | Peak | H | 21.2 | 25.4 | 46.6 | 77.3 | -30.7 | Pass |
| 2760.0 | Peak | V | 13.3 | 25.9 | 39.2 | 74.0 | -34.8 | Pass |
| 3105.0 | Peak | V | 19.1 | 26.6 | 45.7 | 77.3 | -31.6 | Pass |
| 3450.0 | Peak | H | 9.0 | 27.2 | 36.2 | 77.3 | -41.1 | Pass |

All spurious emissions in the applicable frequency range were investigated; only harmonic emissions were present as noted above.

Radiated Emissions Test Equipment

| RTL Bar Code | Manufacturer | Model | Part Type | Serial Number | Calibration Due Date |
|--------------|-------------------------------|-------------------|---|---------------|----------------------|
| 900913 | Hewlett Packard | 85462A | EMI Receiver RF Section (9 KHz – 6.5 GHz) | 3325A00159 | 4/4/19 |
| 900914 | Hewlett Packard | 85460A | RF Filter Section, 100 kHz to 6.5 GHz | 3330A00107 | 4/4/19 |
| 900905 | Rhein Tech Laboratories, Inc. | PR-1040 | Amplifier (20 MHz – 2 GHz) | 900905 | 8/18/18 |
| 901592 | Insulated Wire Inc. | KPS-1503-3600-KPR | SMK RF Cables 20' | NA | 8/18/18 |
| 900791 | Chase | CBL6112 | Antenna (30 MHz – 2 GHz) | 2099 | 10/4/20 |
| 900772 | EMCO | 3161-02 | Horn Antenna 2 - 4 GHz | 9804-1044 | 4/9/18 |
| 901581 | Rohde & Schwarz | FSU | Spectrum Analyzer | 1166.1660.50 | 3/22/18 |

Test Personnel:

| | | |
|---------------|--|-------------------|
| Dan Baltzell |  | November 16, 2017 |
| Test Engineer | Signature | Date of Test |

FCC/IC Cross Reference


| | |
|------------------|----------------------|
| FCC 15.231(a) | RSS-210 Issue 9 A1.1 |
| FCC 15.231(b)(2) | RSS-210 Issue 9 A1.2 |
| FCC 15.35(b) | RSS-Gen Issue 4 6.10 |
| FCC 15.205 | RSS-Gen Issue 4 8.10 |
| FCC 15.209 | RSS-Gen Issue 4 8.9 |
| FCC 15.231(c) | RSS-210 Issue 9 A1.3 |

Occupied Bandwidth

15.231(c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz

$$345 \text{ MHz} * 0.25\% = 863 \text{ kHz} = \text{Limit}$$


99% Bandwidth is 94.3 kHz
 20 dB Bandwidth is 25.7 kHz



Occupied Bandwidth Test Equipment

| RTL Bar Code | Manufacturer | Model | Part Type | Serial Number | Calibration Due Date |
|--------------|----------------------|--------|--------------------------------------|---------------|----------------------|
| 901583 | Agilent Technologies | N9010A | EXA Signal Analyzer (10 Hz-26.5 GHz) | MY51250846 | 4/21/18 |

Test Personnel:

| | | |
|---------------|---|-------------------|
| Khue Do |  | November 16, 2017 |
| Test Engineer | Signature | Date of Test |


Transmitter Deactivation

15.231(a)

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.


Test Equipment

| RTL Bar Code | Manufacturer | Model | Part Type | Serial Number | Calibration Due Date |
|--------------|-----------------|-------|-------------------|---------------|----------------------|
| 901581 | Rohde & Schwarz | FSU | Spectrum Analyzer | 1166.1660.50 | 3/22/18 |



Date: 14.DEC.2017 10:34:29

Test Personnel:

| | | |
|---------------|---|-------------------|
| Dan Baltzell |  | December 14, 2017 |
| Test Engineer | Signature | Date of Test |