

Resolution Products, Inc. 1402 Heggen St. Hudson, WI 54016 715-808-0164

August 30, 2013

RE: U5X-RE927 Request for Limited Modular Approval

To Whom It May Concern:

We hereby request Limited Modular Approval for U5X-RE927 as described under 47 CFR 15.212(b). This device is usable on only one host device, and that fact has been stated in the manual. The following pages describe the compliance with this device with the requirements.

Sincerely,

All

Paul Saldin Vice President

Resolution Products, Inc.

	nt/Grantee Resolution Products, Inc						
FCC ID	FCC ID: U5X-RE927						
Section 15.212 Modular Transmitters							
Request		lest for Limited Modular Approval					
	Requirements	EUT Conditions	Comply (Y/N)				
		Approval Requirements	1				
1	The radio elements of the modular	Not required for LMA	Y				
	transmitter must have their own						
	shielding. The physical crystal and						
	tuning capacitors may be located						
2	external to the shielded radio elements.		N7				
2	The modular transmitter must have	N/A - These inputs are not provided	Y				
	buffered modulation/data inputs (if such						
	inputs are provided) to ensure that the module will comply with Part 15						
	requirements under conditions of						
	excessive data rates or over-modulation.						
3	The modular transmitter must have its	Not required for LMA	Y				
5	own power supply regulation.						
4	The modular transmitter must comply	The antenna is permanently attached to	Y				
	with the antenna and transmission	the board and is not removable.					
	system requirements of Sections 15.203,						
	15.204(b) and 15.204(c). The antenna						
	must either be permanently attached or						
	employ a "unique" antenna coupler (at						
	all connections between the module and						
	the antenna, including the cable). The						
	"professional installation" provision of						
	Section 15.203 is not applicable to						
	modules but can apply to limited						
	modular approvals under paragraph (b)						
5	of this section. The modular transmitter must be tested	Not required for IMA As greating in	Y				
5	in a stand-alone configuration, <i>i.e.</i> , the	Not required for LMA. As specified in 15.212(b), the manufacturer must only	I				
	module must not be inside another	"demonstrate by alternative					
	device during testing for compliance	means in the application for					
	with Part 15 requirements. Unless the	equipment authorization that the					
	transmitter module will be battery	modular transmitter meets all the					
	powered, it must comply with the AC	applicable Part 15 requirements					
	line conducted requirements found in	under the operating conditions in					
	Section 15.207. AC or DC power lines	which the transmitter will be used."					
	and data input/output lines connected to						
	the module must not contain ferrites,	We have done this by testing the device					
	unless they will be marketed with the	in the host with which it will be used.					
	module (see Section 15.27(a)). The	This is the ONLY host that may be used					
	length of these lines shall be the length	with this device.					
	typical of actual use or, if that length is						
	unknown, at least 10 centimeters to						
	insure that there is no coupling between						
	the case of the module and supporting						
	equipment. Any accessories, peripherals,						

	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	FCC label shall be affixed to the top of	Y
	equipped with either a permanently	the device so that it is visible when the	
	affixed label or must be capable of	module is installed in the host. Please	
	electronically displaying its FCC	see Internal Photos and ID Label Photos	
	identification number.	which show this.	
	(A) If using a permanently affixed label, the	which show this.	
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment authorization, or, must provide adequate		
	instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording		
	such as the following:		
	"Contains FCC certified transmitter module(s)." Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	We have provided instructions in the	Y
	with any specific rules or operating	user manual.	
	requirements that		
	ordinarily apply to a complete		
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		
8	The modular transmitter must comply	N/A - this device is not meant to be used	Y
	······································		4

	with any applicable RF exposure	near the body			
	requirements in its final configuration.				
A <b>limited modular approval</b> may be granted for single or split modular transmitters that do not comply with all					
of the above requirements, e.g., shielding, minimum signaling amplitude, buffered modulation/data inputs, or					
power supply regulation, if the manufacturer can demonstrate by alternative means in the application for					
equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the					
operating	operating conditions in which the transmitter will be used. Limited modular approval also may be granted in				
those instances where compliance with RF exposure rules is demonstrated only for particular product					
configura	configurations. The applicant for certification must state how control of the end product into which the module				
will be in	will be installed will be maintained such that full compliance of the end product is always ensured.				