

Wireless Security Solutions

Resolution Products, Inc. 1402 Heggen St. Hudson, WI 54016 715-808-0164

December 11, 2014

RE: U5X-RE312 Request for Limited Modular Approval

To Whom It May Concern:

We hereby request Limited Modular Approval for U5X-RE312 as described under 47 CFR 15.212(b). This device is usable on only one host device. Installation of module into completed device is under full control and done before shipping to the customer. The following pages describe the compliance of this device with the requirements.

Sincerely,

Paul Saldin Vice President

Resolution Products, Inc.

	nt/Grantee Resolution Products, Inc					
FCC ID: U5X-RE312						
Section 15.212 Modular Transmitters						
Reques	·	est for Limited Modular Approval				
Requirements EUT Conditions Comply (Y/N)						
1		Approval Requirements	X 7			
1	The radio elements of the modular transmitter must have their own	Not required for LMA	Y			
	shielding. The physical crystal and tuning capacitors may be located					
	external to the shielded radio elements.					
2	The modular transmitter must have	N/A - These inputs are not provided	Y			
_	buffered modulation/data inputs (if such	Twite inputs are not provided	•			
	inputs are provided) to ensure that the					
	module will comply with Part 15					
	requirements under conditions of					
	excessive data rates or over-modulation.					
3	The modular transmitter must have its	Not required for LMA	Y			
	own power supply regulation.					
4	The modular transmitter must comply	The antenna is permanently attached to	Y			
	with the antenna and transmission	the board and is not removable.				
	system requirements of Sections 15.203,					
	15.204(b) and 15.204(c). The antenna must either be permanently attached or					
	employ a "unique" antenna coupler (at					
	all connections between the module and					
	the antenna, including the cable). The					
	"professional installation" provision of					
	Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
	of this section.					
5	The modular transmitter must be tested	Not required for LMA. As specified in	Y			
	in a stand-alone configuration, <i>i.e.</i> , the	15.212(b), the manufacturer must only				
	module must not be inside another	"demonstrate by alternative				
	device during testing for compliance with Part 15 requirements. Unless the	means in the application for equipment authorization that the				
	transmitter module will be battery	modular transmitter meets all the				
	powered, it must comply with the AC	applicable Part 15 requirements				
	line conducted requirements found in	under the operating conditions in				
	Section 15.207. AC or DC power lines	which the transmitter will be used."				
	and data input/output lines connected to					
	the module must not contain ferrites,	We have done this by testing the device				
	unless they will be marketed with the	in the host with which it will be used.				
	module (see Section 15.27(a)). The	This is the ONLY host that may be used				
	length of these lines shall be the length	with this device.				
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to insure that there is no coupling between					
	the case of the module and supporting					
	equipment. Any accessories, peripherals,					
	equipment. Any accessories, peripherals,	<u> </u>				

	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	FCC label shall be affixed to the device	Y
	equipped with either a permanently	so that it is visible when the module is	
		installed in the host. Please see Internal	
	affixed label or must be capable of		
	electronically displaying its FCC	Photos and ID Label Photos which show	
	identification number.	this.	
	(A) If using a permanently affixed label, the		
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain		
	this requirement. In the latter case, a copy of these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording		
	such as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	We have provided instructions in the	Y
	with any specific rules or operating	user manual.	
	requirements that		
	ordinarily apply to a complete		
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		
8	The modular transmitter must comply	N/A - this device is not meant to be used	Y

with any applicable RF exposure	near the body	
requirements in its final configuration.		

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.