



FCC 47 CFR PART 15 SUBPART E

TEST REPORT

For

Wireless LAN Access Point

Model: H3C WA2110-AG

Trade Name: H3C

Prepared for

Hangzhou H3C Technologies Co., Ltd
310 Liuhe Road, Zhijiang Science Park,
Hangzhou 310053, P.R.China

Prepared by

COMPLIANCE CERTIFICATION SERVICES (KUNSHAN) INC.

10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300) CHINA

TEL: 86-512-57355888

FAX: 86-512-57370818



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

| | |
|---|-----------|
| 1. TEST RESULT CERTIFICATION..... | 3 |
| 2. EUT DESCRIPTION | 4 |
| 3. TEST METHODOLOGY | 5 |
| EUT CONFIGURATION..... | 5 |
| EUT EXERCISE | 5 |
| GENERAL TEST PROCEDURES..... | 5 |
| FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS..... | 6 |
| DESCRIPTION OF TEST MODES..... | 7 |
| 4. INSTRUMENT CALIBRATION..... | 8 |
| 5. FACILITIES AND ACCREDITATIONS | 9 |
| FACILITIES | 9 |
| EQUIPMENT | 9 |
| LABORATORY ACCREDITATIONS AND LISTING..... | 9 |
| TABLE OF ACCREDITATIONS AND LISTINGS | 10 |
| 6. SETUP OF EQUIPMENT UNDER TEST | 11 |
| SETUP CONFIGURATION OF EUT | 11 |
| 7. FCC PART 15.407 REQUIREMENTS..... | 12 |
| RADIO FREQUENCY EXPOSURE (15.407)..... | 12 |
| PEAK POWER (15.407) | 13 |
| RADIATED UNDESIRABLE EMISSION (15.407)..... | 17 |
| PEAK POWER SPECTRAL DENSITY (15.407)..... | 28 |
| CONDUCTED UNDESIRABLE EMISSION (15.407)..... | 32 |
| FREQUENCY STABILITY (15.407)..... | 38 |
| 26 DB EMISSION BANDWITH (15.407) | 39 |
| PEAK EXCURSION (15.407) | 43 |
| POWERLINE CONDUCTED EMISSION (15.407) | 47 |



1. TEST RESULT CERTIFICATION

Applicant: Hangzhou H3C Technologies Co., Ltd
310 Liuhe Road, Zhijiang Science Park, Hangzhou 310053,
P.R.China

Equipment Under Test: Wireless LAN Access Point

Trade Name: H3C

Model: H3C WA2110-AG

Date of Test: From January 20, 2007 to November 29, 2007

| APPLICABLE STANDARDS | |
|-----------------------|-------------------------|
| STANDARD | TEST RESULT |
| FCC Part 15 Subpart E | No non-compliance noted |

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4(2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.407.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Miro Chueh
EMC Manager
Compliance Certification Service Inc.

Tested by:

Ruth Wu
EMC engineer
Compliance Certification Service Inc.



2. EUT DESCRIPTION

| | |
|---|---|
| Product | Wireless LAN Access Point |
| Trade Name | H3C |
| Model Number | H3C WA2110-AG |
| Model Discrepancy | All the above models are identical except the model designation for different market. |
| Serial Number | N/A |
| Power Adapter Power Rating | Powered from an AC/DC power adapter Model Number: FSP025-1AD207A Input: AC 100-240V, 50-60Hz, 0.7A Output: DC 48V, 0.52A |
| DC Power Cable Type | Unshielded, 1.5m (Non-Detachable) at Power Adapter with a core |
| Frequency Range | 5150 ~ 5250 MHz |
| Transmit Power | IEEE 802.11a: 5150 ~ 5250 MHz : 15.69dBm |
| Modulation Technique | IEEE 802.11a: OFDM (QPSK, BPSK, 16-QAM, 64-QAM) |
| Antenna Specification | PIFA antenna with 3.5dBi gain (Max) |

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: U6IH3CEWTO235A22W filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4. Radiated testing was performed at an antenna to EUT distance 3 meters.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT is operated in the engineering mode to fix the Tx frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E. The composite system (Digital device) is in compliance with Subpart B authorized under the DoC procedure.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4



FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|----------------------------|---------------------|-----------------|------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.52525 | 2655 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 156.7 - 156.9 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 162.0125 - 167.17 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 167.72 - 173.2 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 240 - 285 | 3600 - 4400 | (²) |
| 13.36 - 13.41 | 322 - 335.4 | | |

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



DESCRIPTION OF TEST MODES

The following test mode was scanned during the preliminary test:

Mode 1: Wall, ceiling mounting, set the EUT vertically on the table top.

Mode 2: Table top mounting, set the EUT horizontally on the table top.

After the preliminary scan, the following test mode was found to produce the highest emission level.

Mode 2: Table top mounting, set the EUT horizontally on the table top.

Then, the EUT configuration and cable configuration of the above highest emission mode was recorded for all final test items.

IEEE802.11a: 5150~5250MHz Channel low(5180MHz), Channel middle(5200MHz) and Channel high(5240MHz) with preliminary test 54/48/36/24/18/12/9/6, After the preliminary scan , the following test mode 6Mbps data rate (the worst case) are chosen for the final testing. Below 1G: After the preliminary scan, the following test mode :normal link(the worst case) are chosen for the final testing



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



5. FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#, Weiye Rd, Innovation Park Eco. & Tec. Development Zone Kunshan city JiangSu, (215300)CHINA.

The measurement facilities are constructed in conformance with the requirements of CISPR 16-1, ANSI C63.4 and other equivalent standards.

EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by A2LA for the specific scope of accreditation under testing cert#2541.01 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission.



TABLE OF ACCREDITATIONS AND LISTINGS

| Country | Agency | Scope of Accreditation | Logo |
|---------|--------|---|--|
| USA | A2LA | 47 CFR FCC Part 15/18 (using ANSI C63.4:2003); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997+A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998+A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24 |  ACCREDITED TESTING CERT #2541.01 |
| USA | FCC | 3/10 meter Sites to perform FCC Part 15/18 measurements |  93105, 90471 |
| Japan | VCCI | 3/10 meter Sites and conducted test sites to perform radiated/conducted measurements |  R-1600 C-1707 |
| Norway | NEMKO | EN61000-6-1/2/3/4, EN 50082-1/2, IEC 61000-6-1/2/3/4, EN 50091-2, EN 55011, EN 55022, EN 55024, EN 61000-3-2/3, EN 61000-11, IEC 61000-4-2/3/4/5/6/8/11, CISPR16-1/2/3/4 |  ELA 105 |

* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

SUPPORT EQUIPMENT

| No | Equipment | Model | Serial No. | FCC ID | Trade Name | Data Cable | Power Cord |
|----|------------------------|--------|----------------------|--------|------------|---------------------------------|----------------------|
| 1 | NB | HP6130 | 3106010149 | DoC | HP | Shielded 1.2m with a Core | Un-Shielded, 1.5m |
| 2 | Wireless Controller | WX5002 | 02A23S006B0000 07 | DoC | WX | Un-Shielded, 1.2m | Un-Shielded, 1.5m |

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



7. FCC PART 15.407 REQUIREMENTS RADIO FREQUENCY EXPOSURE (15.407)

In adopt with the Human Exposure IEEE C95.1, and according to the FCC 1.1310. The *Maximum Permissible Exposure (MPE)* is obligated to measure in order to prove the safety of radiation harmfulness to the human body.

The *Gain* of the antenna used is measured in an *anechoic chamber*. The *maximum total power to the antenna* is to be recorded. By adopting the ***Friis Transmission Formula*** and the *power gain of the antenna*, we can find the distance right away from the product, where the limit of the MPE is.

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Filed Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) |
|--|-------------------------------|-----------------------------------|---|---|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | 100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | 900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | -- | -- | f/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | 100 | 30 |
| 1.34-30 | 824/f | 2.19/f | 180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | -- | -- | f/1500 | 30 |
| 1500-100,000 | -- | -- | 1.0 | 30 |

According to **OET BULLETIN 56 Fourth Edition/August 1999, Equation for Predicting RF Fields:**

$$\text{Power density at the specific separation (portable): } S = \frac{PG}{4\pi R^2} = \frac{37.07 \times 2.24}{4\pi(20)^2} = 0.0165 \text{ mW/cm}^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

The *Numeric gain G* of antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain}/10)$$

$$G = \text{Log}^{-1} (3.50 / 10) = 2.24$$

PEAK POWER (15.407)

LIMIT

- For the band 5.15-5.25 GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 50mW (17dBm) or 4dBm + 10log B, where B is the 26dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4dBm in any 1 MHz band.
- For the band 5.25-5.35 GHz and 5.47-5.725GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 250mW (24dBm) or 11dBm + 10logB, where B is the 26dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 11dBm in any 1 MHz band.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. The peak power shall not exceed the limit as follows:

Specified Limit of the Peak Power


| Frequency (MHz) | 10 Log B (dB) | 4 + 10 Log B | Power Limit (dBm) |
|-----------------|---------------|--------------|-------------------|
| 5200 | 15.6 | 19.6 | 19.6 |

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|----------------|--------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Low-Loss RF Cable | Huber + Suhner | Sucoflex 104 | N/A | N/A |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The test is performed in accordance with <FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices> – Part 15, Subpart E, August 2002.

**TEST RESULTS**

No non-compliance noted

Tested by: Ruth

Base Mode

5150~5250MHz


| Channel | Frequency (MHz) | Peak Power (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------------|------------------|-------------|-------------|
| Low | 5180 | 15.69 | 17 | -2.31 |
| Middle | 5200 | 13.96 | 17 | -3.04 |
| High | 5240 | 14.52 | 17 | -2.48 |

Test Data Plots

5150 - 5250MHz Band

CH Low

* Agilent 14:54:55 Apr 1, 2007




| BW/Avg | |
|--------------|-------------|
| Res BW | 1.0 MHz |
| Auto | Man |
| Video BW | 3.0 MHz |
| Auto | Man |
| VBW/RBW | 1.00000 |
| Auto | Man |
| Average | 100 |
| On | Off |
| Avg/VBW Type | Pwr (RMS) ▶ |
| Auto | Man |
| Span/RBW | 106 |
| Auto | Man |

Unable to save file

CH Mid

* Agilent 12:37:08 Apr 1, 2007




| BW/Avg | |
|--------------|-------------|
| Res BW | 1.0 MHz |
| Auto | Man |
| Video BW | 3.0 MHz |
| Auto | Man |
| VBW/RBW | 1.00000 |
| Auto | Man |
| Average | 100 |
| On | Off |
| Avg/VBW Type | Pwr (RMS) ▶ |
| Auto | Man |
| Span/RBW | 106 |
| Auto | Man |

Unable to save file

CH High

* Agilent 12:39:42 Apr 1, 2007



**RADIATED UNDESIRABLE EMISSION (15.407)****LIMIT**

For transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27dBm / MHz (68.2dBuV/m). But Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

The provisions of §15.205 apply to intentional radiators operating under this section. The EUT is set to transmit in a continuous mode.



MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Pre-Amplifier | Miteq | NSP4000-NF | 870731 | 01/21/2008 |
| Horn Antenna | AustriaH | BBHA9120D | D267 | 09/20/2007 |
| Turn Table | CT | CT123 | 4162 | N.C.R |
| Antenna Tower | CT | CTERG23 | 3253 | N.C.R |
| Controller | CT | CT100 | 95635 | N.C.R |
| Coax Switch | Anitsu | MP 598 | M 80094 | N/A |
| Site NSA | CCS Lab. | N/A | N/A | 12/11/2007 |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

Radiated Emission Test Setup (for frequency below 1000MHz)



Radiated Emission Test Setup (for frequency over 1 GHz)

TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable is rotated for 360 degrees to determine the orientation for generating the maximum emission level.
3. The EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure is performed on the six highest emissions to ensure EUT compliance.
5. Then, each emission is to be maximized by changing the polarization of receiving antenna both horizontal and vertical.



6. Repeat the above procedure until all channels are recorded.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 100kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.

Factor Calculation

The Factor is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$F = AF + CL - AG$$

Where F = Factor

E = Field Strength in Volts / meter

AF = Antenna factor

CL = Cable attenuation factor (cable loss)

AG = Amplifier gain

EIRP Calculation

Given $E = \frac{\sqrt{(30 \times P \times G)}}{d}$

Where E = Field strength (Volts/Meter)

P = Power (Watts)

G = Numeric antenna gain

d = Distance (Meter)

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields

$$P \times G = \frac{(d \times E)^2}{30}$$

Re-arranging the terms yields

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = 100 * d (m)$$

Converting to the logarithmic form and changing to units of mW and μ V/m, using

$$P (mW) = P (W) / 1000 \text{ and } E (\mu V/m) = E (V/m) / 1000000$$

Yields

$$10 \log(P \times G) = 10 \log d^2 + 10 \log E^2 - 10 \log 30 - 10 \log 10^9 = 20 \log d + 20 \log E - 104.77$$

Where $10 \log (P \times G)$ is PG in dBm and $20 \log (E)$ is E in dBuV/m

Since

$$EIRP = P * G$$

Then, at a specification distance of 3 meters, the EIRP, in terms of field strength, is

$$EIRP (dBm) = P * G (dBm) = E (dBuV/m) - 95.2$$

Band-edge Radiated Emissions

TEST RESULTS


No non-compliance noted

Tested by: Ruth

Band Edges (802.11a/ CH 5180MHz)


Detector mode: Peak



Polarity: Vertical



Detector mode: Average

Polarity: Vertical




Detector mode: Peak
Polarity: Horizontal

Detector mode: Average
Polarity: Horizontal


Band Edges (802.11a/ CH 5240MHz)


Detector mode: Peak



Polarity: Vertical



Detector mode: Average

Polarity: Vertical



Detector mode: Peak
Polarity: Horizontal

Detector mode: Average
Polarity: Horizontal




Harmonic and Spurious Radiated Emission

Below 1 GHz

Operation Mode: Normal Link

Test Date: March 28, 2007

Temperature: 20°C

Tested by: ruth

Humidity: 60 % RH

Polarity: Ver. / Hor.

| Freq. (MHz) | Ant.Pol. | Detector | Reading (dBuV) | Factor (dB) | Actual FS (dBuV/m) | Limit 3m (dBuV/m) | Safe Margin (dB) |
|----------------|----------|-----------------|-------------------|----------------|-----------------------|----------------------|------------------------|
| <hr/> | | | | | | | |
| | H/V | Mode (PK/QP) | | | | | |
| 76.5331 | V | QP | 51.82 | -14.41 | 37.41 | 40 | -2.59 |
| 225.872 | V | QP | 51.73 | -10.06 | 41.67 | 46 | -4.33 |
| 401.002 | V | QP | 45.67 | -4.58 | 41.09 | 46 | -4.91 |
| 424.85 | V | QP | 44.12 | -4.02 | 40.1 | 46.0 | -5.9 |
| 737.67 | V | QP | 37.4 | 1.52 | 38.92 | 46.0 | -7.08 |
| 922.846 | V | QP | 39.73 | 3.93 | 43.66 | 46.0 | -2.34 |
| <hr/> | | | | | | | |
| 175.5511 | H | QP | 46.79 | -10.48 | 36.31 | 43.5 | -7.19 |
| 325.2505 | H | QP | 49.49 | -7.07 | 42.42 | 46 | -3.58 |
| 401.002 | H | QP | 49.21 | -4.58 | 44.63 | 46 | -1.37 |
| 424.8497 | H | QP | 46.72 | -4.02 | 42.7 | 46 | -3.3 |
| 830.2605 | H | QP | 40.12 | 2.89 | 43.01 | 46.0 | -2.99 |
| 919.982 | H | QP | 38.52 | 3.9 | 42.42 | 46.0 | -3.58 |

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

5. EIRP Limit=-27dBm=68.2dBuV/m



Above 1 GHz

TX / IEEE

Operation Mode: 802.11a(5150~5250MHz) / CH Low

Test Date: April 8, 2007

Temperature: 20°C

Tested by: ruth

Humidity: 70 % RH

Polarity: Ver. / Hor.

| Frequency (MHz) | Ant.Pol. (H/V) | Reading (Peak) (dBuV) | Reading (Average) (dBuV) | Correction Factor (dB/m) | Result (Peak) (dBuV/m) | Result (Average) (dBuV/m) | Limit (Peak) (dBuV/m) | Limit (Average) (dBuV/m) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------------|--------------------------------|--------------------------------|------------------------------|---------------------------------|-----------------------------|--------------------------------|----------------|---------|
| 1812.23 | V | 46.87 | 45.26 | 1.39 | 48.26 | 46.65 | 88.20 | 68.20 | -21.55 | average |
| 10365.06 | V | 37 | 34.96 | 15.06 | 52.06 | 50.02 | 88.20 | 68.20 | -18.18 | average |
| 15539.26 | V | 30.88 | 28.86 | 20.03 | 50.91 | 48.89 | 74.00 | 54.00 | -5.11 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| <hr/> | | | | | | | | | | |
| 1820.23 | H | 48.26 | 43.34 | 1.39 | 49.65 | 44.73 | 88.20 | 68.20 | -23.47 | average |
| 10366.23 | H | 37.95 | 36 | 15.06 | 53.01 | 51.06 | 88.20 | 68.20 | -17.14 | average |
| 15540.26 | H | 31.03 | 29.95 | 20.03 | 51.06 | 49.98 | 74.00 | 54.00 | -4.02 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



TX / IEEE

Operation Mode: 802.11a(5150~5250MHz) / CH Middle**Test Date:** April 8, 2007**Temperature:** 20°C**Tested by:** ruth**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

| Frequency (MHz) | Ant.Pol. (H/V) | Reading (Peak) (dBuV) | Reading (Average) (dBuV) | Correction Factor (dB/m) | Result (Peak) (dBuV/m) | Result (Average) (dBuV/m) | Limit (Peak) (dBuV/m) | Limit (Average) (dBuV/m) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------------|--------------------------------|--------------------------------|------------------------------|---------------------------------|-----------------------------|--------------------------------|----------------|---------|
| 1906.32 | V | 46.67 | 44.94 | 1.32 | 47.99 | 46.26 | 88.20 | 68.20 | -21.94 | average |
| 10396.26 | V | 36.03 | 34.65 | 15.03 | 51.06 | 49.68 | 88.20 | 68.20 | -18.52 | average |
| 15601.92 | V | 28.24 | 26.93 | 20.05 | 48.29 | 46.98 | 74.00 | 54.00 | -7.02 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| | | | | | | | | | | |
| 1910.03 | H | 47.27 | 43.34 | 1.32 | 48.59 | 47.06 | 88.20 | 68.20 | -21.14 | average |
| 10400.03 | H | 36.03 | 34.12 | 15.03 | 51.06 | 49.15 | 88.20 | 68.20 | -19.05 | average |
| 15602.30 | H | 29.22 | 27.25 | 20.04 | 49.26 | 47.29 | 74.00 | 54.00 | -6.71 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



TX / IEEE

Operation Mode: 802.11a(5150~5250MHz)/ CH High**Test Date:** April 8, 2007**Temperature:** 20°C**Tested by:** ruth**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

| Frequency (MHz) | Ant.Pol. (H/V) | Reading (Peak) (dBuV) | Reading (Average) (dBuV) | Correction Factor (dB/m) | Result (Peak) (dBuV/m) | Result (Average) (dBuV/m) | Limit (Peak) (dBuV/m) | Limit (Average) (dBuV/m) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------------|--------------------------------|--------------------------------|------------------------------|---------------------------------|-----------------------------|--------------------------------|----------------|---------|
| 1829.32 | V | 48.34 | 46.74 | 1.31 | 49.65 | 48.05 | 88.20 | 68.20 | -20.15 | average |
| 10479.65 | V | 39.05 | 35.26 | 15 | 54.05 | 50.26 | 88.20 | 68.20 | -17.94 | average |
| 15719.26 | V | 32.23 | 29.98 | 20.03 | 52.26 | 50.01 | 74.00 | 54.00 | -3.99 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| <hr/> | | | | | | | | | | |
| 1902.32 | H | 48.69 | 45.97 | 1.32 | 50.01 | 47.29 | 88.20 | 68.20 | -20.91 | average |
| 10480.03 | H | 38.98 | 36.06 | 15 | 53.98 | 51.06 | 88.20 | 68.20 | -17.14 | average |
| 15720.23 | H | 31.26 | 29.29 | 20.03 | 51.29 | 49.32 | 74.00 | 54.00 | -4.68 | average |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |
| N/A | | | | | | | | | | |

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

PEAK POWER SPECTRAL DENSITY (15.407)

LIMIT

- For the band 5.15-5.25 GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 50mW or $4\text{dBm} + 10\log B$, where B is the 26dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4dBm in any 1MHz band.
- For the band 5.25-5.35 GHz and 5.47-5.725GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10\log B$, where B is the 26dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 11dBm in any 1MHz band.


If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|----------------|--------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Low-Loss RF Cable | Huber + Suhner | Sucoflex 104 | N/A | N/A |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The test is performed in accordance with <FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices> – Part 15, Subpart E, August 2002, Method 2.

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
- Set RBW = 1MHz, VBW = 3MHz, Span = 30MHz, Sweep time = Auto.
- Record the maximum reading.
- The above procedure is repeated until all the channels are recorded.



TEST RESULTS

No non-compliance noted

Tested by: Ruth

Base mode


5150~5250MHz

| Channel | Frequency (MHz) | PPSD (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------------|------------|-------------|-------------|
| Low | 5180 | 2.55 | 4.00 | -1.44 |
| Middle | 5200 | 1.42 | 4.00 | -2.58 |
| High | 5240 | 2.35 | 4.00 | -1.65 |


Test Data Plots

PPSD

5150~5250 CH Low




CH Mid



CH High

* Agilent 12:52:40 Apr 2, 2007



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

Mkr → CF

More
1 of 2

File Operation Status, A:\SCREEN007.GIF file saved

CONDUCTED UNDESIRABLE EMISSION (15.407)**LIMIT**


Transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27dBm / MHz. Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

The provisions of §15.205 apply to intentional radiators operating under this section.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|----------------|--------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Low-Loss RF Cable | Huber + Suhner | Sucoflex 104 | N/A | N/A |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration**TEST PROCEDURE**

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 1 MHz. The video bandwidth is set to 1 MHz. Peak detection measurements are compared to the average EIRP limit, adjusted for the maximum antenna gain. If necessary, additional average detection measurements are made.

Measurements are made over the 30 MHz to 40 GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted

(Note: Maximum antenna gain =3.5 dBi, therefore there is no reduction due to antenna gain.)


Tested by: Ruth

Test Data Plots

Conducted Spurious Emissions

5150~5250MHz CH Low

* Agilent 15:18:31 Mar 28, 2007



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search


Pk-Pk Search

Mkr → CF

More 1 of 2

Copyright 2000-2004 Agilent Technologies

* Agilent 15:19:06 Mar 28, 2007



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search


Pk-Pk Search

Mkr → CF

More 1 of 2

Copyright 2000-2004 Agilent Technologies



Agilent 15:20:01 Mar 28, 2007



Copyright 2000-2004 Agilent Technologies


CH Middle

Agilent 12:57:40 Apr 2, 2007




Copyright 2000-2004 Agilent Technologies

Agilent 13:06:59 Apr 2, 2007




Copyright 2000-2004 Agilent Technologies


Agilent 13:00:48 Apr 2, 2007



Copyright 2000-2004 Agilent Technologies

CH High
Agilent 12:57:54 Apr 2, 2007



- Peak Search**
- Next Peak**
- Next Pk Right**
- Next Pk Left**
- Min Search**
- Pk-Pk Search**
- Mkr → CF**
- More**
1 of 2

Copyright 2000-2004 Agilent Technologies
Agilent 13:05:54 Apr 2, 2007


- Trace**
- Trace**
1 2 3
- Clear Write**
- Max Hold**
- Min Hold**
- View**
- Blank**

Copyright 2000-2004 Agilent Technologies

Agilent 13:01:10 Apr 2, 2007





FREQUENCY STABILITY (15.407)

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

Referring to the theory of operation, the crystal used to set the frequency has a temperature coefficient of +/- 20 ppm over the specified rated temperature range. For a transmitter fundamental frequency of 5.24 GHz, this corresponds to +/- 104.8 kHz.

TEST RESULTS

No non-compliance noted

| Channel Frequency (MHz) | Measured Frequency (MHz) | Delta Frequency (kHz) | 20 ppm Limit (\pm kHz) | Margin (kHz) |
|-------------------------|--------------------------|-----------------------|---------------------------|--------------|
| 5240 | 5239.974 | -26.00 | 104.80 | -80.40 |

Note: An examination of the band-edge plots shows that the emission will stay within the authorized band over the entire temperature range.

26 DB EMISSION BANDWIDTH (15.407)

LIMIT


For purposes of this subpart, the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

MEASUREMENT EQUIPMENT USED

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|----------------|--------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Low-Loss RF Cable | Huber + Suhner | Sucoflex 104 | N/A | N/A |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
3. Mark the peak frequency and -26dBc (upper and lower) frequency.
4. Repeat until all the rest channels were investigated.



TEST RESULTS

No non-compliance noted

Tested by: Ruth

5150~5250MHz


| Channel | Frequency (MHz) | Bandwidth (kHz) |
|----------------|----------------------------|----------------------------|
| Low | 5180 | 32117 |
| Middle | 5200 | 35716 |
| High | 5240 | 35134 |

TEST DATA PLOTS



5150~5250MHz Band

CH Low

* Agilent 13:08:58 Mar 30, 2007



CH Mid

*** Agilent 13:11:30 Apr 3, 2007**

CH High
*** Agilent 13:12:49 Apr 3, 2007**


PEAK EXCURSION (15.407)

LIMIT

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the peak transmit power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.


MEASUREMENT EQUIPMENT USED

Remark

| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|----------------|--------------|---------------|-----------------|
| Spectrum Analyzer | Agilent | E4446A | MY44020154 | 11/16/2008 |
| Low-Loss RF Cable | Huber + Suhner | Sucoflex 104 | N/A | N/A |

: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The test is performed in accordance with <FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices> – Part 15, Subpart E, August 2002.

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to spectrum.
3. Trace A, Set RBW = 1MHz, VBW = 3MHz, Span = 50MHz, Max. hold.
4. Trace B, Set RBW = 1MHz, VBW = 30kHz, Span = 50MHz, Max. hold.
5. Delta Mark trace A Maximum frequency and trace B same frequency.
6. Repeat the above procedure until measurements for all frequencies were complete.



TEST RESULTS

No non-compliance noted

Tested by: Ruth

5150~5250MHz

| Channel | Frequency (MHz) | Peak Excursion (dB) | Limit (dB) | Margin (dB) |
|---------|-----------------|---------------------|------------|-------------|
| Low | 5180 | 7.10 | 13 | -5.90 |
| Middle | 5200 | 6.61 | | -6.39 |
| High | 5240 | 6.64 | | -6.36 |

(Note: Maximum antenna gain = 3.5 dBi, therefore there is no reduction due to antenna gain.)


Test Data Plots

Peak Excursion

5150~5250MHz Band

CH Low

* Agilent 15:29:04 Apr 1, 2007




| |
|---------------------------|
| Marker |
| Select Marker |
| 1 2 3 4 |
| Marker Trace |
| Auto 1 2 3 |
| Readout, Frequency |
| Marker Table |
| On Off |
| Marker All Off |
| |
| More |
| 2 of 2 |

Copyright 2000-2004 Agilent Technologies

CH Middle

* Agilent 13:30:21 Apr 3, 2007




| |
|---------------------------|
| Marker |
| Select Marker |
| 1 2 3 4 |
| Marker Trace |
| Auto 1 2 3 |
| Readout, Frequency |
| Marker Table |
| On Off |
| Marker All Off |
| |
| More |
| 2 of 2 |

Copyright 2000-2004 Agilent Technologies

CH High

Agilent 13:28:28 Apr 3, 2007



POWERLINE CONDUCTED EMISSION (15.407)

LIMIT

For an intentional radiator, which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band of 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range of 0.15 MHz to 0.50 MHz). The limits at a specific frequency range is listed as follows:


| Frequency Range (MHz) | Limit (dB μ V) | |
|--------------------------|--------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

| Conducted Emission Test Site A (10m chamber) | | | | |
|--|--------------|--------------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| EMI Test Receiver | R&S | ESI26 | 100068 | 01/21/2008 |
| EMC Analyzer | Agilent | E7402A | US41160329 | 01/21/2008 |
| LISN | FCC | FCC-LISN-50-50-2-M | 01067 | N/A |
| LISN (EUT) | FCC | FCC-LISN-50-50-2-M | 01068 | 07/29/2008 |
| FOUR BALANCED TELECOM PAIRS ISN | FCC | FCC-TLISN-T8-02 | 20165 | 08/30/2007 |
| 4-WIRE ISN | R&S | ENY41 | 830663/024 | 08/30/2007 |
| Double 2-Wire ISN | R&S | ENY22 | 830661/027 | 08/30/2007 |
| TRANSIENT LIMITER | SCHAFFNER | CFL9206 | 1710 | 05/19/2008 |
| EMI Monitor control box | FCC | 0-SVDC | N/A | N/A |

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

TEST RESULTS

No non-compliance noted

Test Data

Model: H3C WA2110-AG

Test Mode: Normal Link

Temperature: 25°C

Humidity: 50% RH

Tested by:ruth

Test Results: Pass

| Frequency (KHz) | QP Reading (dBuV) | AV Reading (dBuV) | Corr. factor (dB) | QP Result (dBuV) | AV Result (dBuV) | QP Limit (dBuV) | AV Limit (dBuV) | QP Margin (dB) | AV Margin (dB) | Note |
|-----------------|-------------------|-------------------|-------------------|------------------|------------------|-----------------|-----------------|----------------|----------------|------|
| 190.2 | 26.06 | 25.94 | 10.36 | 36.42 | 36.3 | 64.85 | 54.85 | -28.43 | -18.55 | L1 |
| 231.4 | 24.75 | 25.09 | 10.36 | 35.11 | 35.45 | 63.67 | 53.67 | -28.56 | -18.22 | L1 |
| 329.8 | 28.54 | 28.33 | 10.4 | 38.94 | 38.73 | 60.86 | 50.86 | -21.92 | -12.13 | L1 |
| 1023.8 | 8.65 | 7.71 | 10.43 | 19.08 | 18.14 | 56.00 | 46.00 | -36.92 | -27.86 | L1 |
| 1646.7 | 8.92 | 8.74 | 10.48 | 19.4 | 19.22 | 56.00 | 46.00 | -36.60 | -26.78 | L1 |
| 17812.5 | 5.6 | 11.02 | 12.04 | 17.64 | 23.06 | 60.00 | 50.00 | -42.36 | -26.94 | L1 |
| | | | | | | | | | | |
| 183.9 | 24.15 | 18.32 | 10.4 | 34.55 | 28.72 | 65.03 | 55.03 | -30.48 | -26.31 | L2 |
| 235.1 | 23.93 | 23.43 | 10.39 | 34.32 | 33.82 | 63.57 | 53.57 | -29.25 | -19.75 | L2 |
| 331.3 | 21.3 | 21.81 | 10.4 | 31.7 | 32.21 | 60.82 | 50.82 | -29.12 | -18.61 | L2 |
| 375.9 | 25.48 | 26.59 | 10.4 | 35.88 | 36.99 | 59.55 | 49.55 | -23.67 | -12.56 | L2 |
| 987.5 | 9.05 | 7.87 | 10.42 | 19.47 | 18.29 | 56.00 | 46.00 | -36.53 | -27.71 | L2 |
| 1908.1 | 11.62 | 10.94 | 10.49 | 22.11 | 21.43 | 56.00 | 46.00 | -33.89 | -24.57 | L2 |

(The chart below shows the highest readings taken from the final data)

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

Note:

Freq. = Emission frequency in KHz

Factor (dB) = cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER (The TRANSIENT LIMITER included 10 dB ATTENUATION)

Amptd dBuV = Uncorrected Analyzer/Receiver reading + cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER,
if it > 0.5 dB

Limit dBuV = Limit stated in standard


Margin dB = Reading in reference to limit

Calculation Formula

$$\text{Margin (dB)} = \text{Amptd (dBuV)} - \text{Limit (dBuV)}$$

Test Plot

Conducted emissions (Line 1)



Test Plot

Conducted emissions (Line 2)

