

# **FCC RF Exposure Report**

FCC ID : U6Y-M120000017

Equipment : 802.11a/n/ac 4x4 WiFi module

Model No. : M120000017

Brand Name : Panasonic

Applicant : Panasonic Avionics Corporation

Address : 26200 ENTERPRISE WAY, LAKE FOREST, CA

92630-8400 USA

Standard : 47 CFR FCC Part 2.1091

Received Date : Nov. 24, 2016

Tested Date : Dec. 05, 2016 ~ Mar. 17, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FA6N2402 Page: 1 of 6



# **Table of Contents**

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	6

Report No.: FA6N2402

Page : 2 of 6



# **Release Record**

Report No.	Version	Description	Issued Date
FA6N2402	Rev. 01	Initial issue	Mar. 30, 2017

Report No.: FA6N2402 Page: 3 of 6



### 1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

### 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)	
300~1500	F/1500	30	
1500~100000	1.0	30	

### 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

Report No.: FA6N2402 Page: 4 of 6



### 1.3 MPE EVALUATION RESULTS

### **MPE Evaluation of Single Transmission**

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm²)		
Non-beamforming mode							
5180~5240	21.14	5.9	20	0.101	1		
5260~5320	21.21	5.6	20	0.095	1		
5500~5700	23.23	5.7	20	0.155	1		
5745~5825	24.65	5.6	20	0.211	1		
Beamforming mode							
5180~5240 <sup>Note</sup>	18.21	11.33	20	0.179	1		
5260~5320 Note	18.58	11.08	20	0.184	1		
5500~5700 Note	19.19	10.77	20	0.197	1		
5745~5825 <sup>Note</sup>	24.00	10.72	20	0.590	1		

#### Note:

1. For beamforming mode:

For 5150~5250 MHz band

Directional gain =  $10 * log((10^{4/20} + 10^{5.4/20} + 10^{5.9/20} + 10^{5.8/20})^2/4) = 11.33 dBi$ 

For 5250 ~ 5350 MHz band

Directional gain =  $10 * log((10^{4.4/20} + 10^{5.4/20} + 10^{4.8/20} + 10^{5.6/20})^2/4) = 11.08 dBi$ 

For 5470 ~ 5725MHz band

Directional gain =  $10 * log((10^{4.2/20} + 10^{4.5/20} + 10^{4.5/20} + 10^{5.7/20})^2/4) = 10.77 dBi$ 

For 5745~5850 MHz band

Directional gain =  $10 * log((10^{4.8/20} + 10^{4.1/20} + 10^{4.2/20} + 10^{5.6/20})^2/4) = 10.72 dBi$ 

Report No.: FA6N2402

Page : 5 of 6



## 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FA6N2402 Page: 6 of 6