

TEST REPORT

Product : Digital Blood Pressure Monitor
Trade mark : microlife
Model/Type reference : BP3GK1-4B
Serial Number : N/A
Report Number : EED32M00340301
FCC ID : U7I-BP3GK1-4B
Date of Issue : Dec. 22, 2020
Test Standards : 47 CFR Part 15Subpart C
Test result : PASS

Prepared for:

Microlife Corporation

9F, 431, RuiGuang Road, NeiHu, Taipei 11492, Taiwan

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

bill Lu

bill Lu

Reviewed by:

Aaron Ma

Aaron Ma

Approved by:

David Wang

David Wang

Date:

Dec. 22, 2020



Check No.: 4538065840

2 Version

Version No.	Date	Description
00	Dec. 22, 2020	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15Subpart C Section 15.207	ANSI C63.10-2013	N/A
Conducted Peak Output Power	47 CFR Part 15Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15Subpart C Section 15.247 (e)	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.


4 Content

1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENT	4
5 TEST REQUIREMENT	5
5.1 TEST SETUP.....	5
5.1.1 For Conducted test setup.....	5
5.1.2 For Radiated Emissions test setup.....	5
5.1.3 For Conducted Emissions test setup.....	6
5.2 TEST ENVIRONMENT.....	6
5.3 TEST CONDITION.....	6
6 GENERAL INFORMATION	7
6.1 CLIENT INFORMATION.....	7
6.2 GENERAL DESCRIPTION OF EUT.....	7
6.3 DESCRIPTION OF SUPPORT UNITS.....	9
6.4 TEST LOCATION.....	9
6.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
6.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	9
6.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, $K=2$).....	9
7 EQUIPMENT LIST	10
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	12
Appendix A): 6dB Occupied Bandwidth.....	15
Appendix B): Conducted Peak Output Power.....	20
Appendix C): Band-edge for RF Conducted Emissions.....	23
Appendix D): RF Conducted Spurious Emissions.....	26
Appendix E): Power Spectral Density.....	31
Appendix F): Antenna Requirement.....	34
Appendix G): Restricted bands around fundamental frequency (Radiated).....	35
Appendix H) Radiated Spurious Emissions.....	44
PHOTOGRAPHS OF TEST SETUP	48
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	50

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup Conducted Emissions setup



5.2 Test Environment

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test channel:

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
GFSK	2402MHz ~2480 MHz	Channel 0	Channel 19	Channel 39
		2402MHz	2440MHz	2480MHz
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.			

6 General Information

6.1 Client Information

Applicant:	Microlife Corporation
Address of Applicant:	9F, 431, RuiGuang Road, NeiHu, Taipei 11492, Taiwan
Manufacturer:	ONBO Electronic (Shenzhen) Co., Ltd.
Address of Manufacturer:	No.138, Huasheng Road, Langkou Community, Dalang Street, Longhua District, Shenzhen, China
Factory:	ONBO Electronic (Shenzhen) Co., Ltd.
Address of Factory:	No.138, Huasheng Road, Langkou Community, Dalang Street, Longhua District, Shenzhen, China

6.2 General Description of EUT

Product Name:	Digital Blood Pressure Monitor
Model No.(EUT):	BP3GK1-4B
Trade mark:	microlife
Power Supply:	2*AAA Battery 3.0V
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.2 (BLE)
Modulation Technique:	DSSS
Modulation Type:	GFSK
Number of Channel:	40
Test Power Grade:	10
Test Software of EUT:	Nrfgo
Antenna Type and Gain:	Type: Chip Antenna Gain: 0dBi
Test Voltage:	DC 3.0V
Sample Received Date:	Dec. 07, 2020
Sample tested Date:	Dec. 07, 2020 to Dec. 18, 2020

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

6.3 Description of Support Units

The EUT has been tested independently

6.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

6.5 Abnormalities from Standard Conditions

None.

6.6 Other Information Requested by the Customer

None.

6.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

7 Equipment List

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
RSE Automatic test software	JS Tonscend	JS36-RSE	10166	---	---
Receiver	Keysight	N9038A	MY57290136	03-05-2020	03-04-2021
Spectrum Analyzer	Keysight	N9020B	MY57111112	03-05-2020	03-04-2021
Spectrum Analyzer	Keysight	N9030B	MY57140871	03-05-2020	03-04-2021
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-25-2018	04-24-2021
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-25-2018	04-24-2021
Horn Antenna	ETS-LINDGREN	3117	00057407	07-10-2018	07-09-2021
Preamplifier	EMCI	EMC184055SE	980596	05-20-2020	05-19-2021
Preamplifier	EMCI	EMC001330	980563	04-22-2020	04-21-2021
Preamplifier	JS Tonscend	980380	EMC051845SE	01-09-2020	01-08-2021
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	04-27-2020	04-26-2021
Fully Anechoic Chamber	TDK	FAC-3	---	01-17-2018	01-16-2021
Filter bank	JS Tonscend	JS0806-F	188060094	04-10-2018	04-09-2021
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05-24-2019	05-23-2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	05-16-2020	05-15-2021
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-25-2018	04-24-2021
Receiver	R&S	ESCI7	100938-003	10-16-2020	10-15-2021
Multi device Controller	maturó	NCD/070/107 1112	---	---	---
Temperature/ Humidity Indicator	Shanghai qixiang	HM10	1804298	06-29-2020	06-28-2021
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:


Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix A)
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	N/A
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix H)

**Duty Cycle
Result Table**

Mode	Channel	Duty Cycle [%]	Limit	Verdict
BLE	LCH	69.66	---	PASS
BLE	MCH	69.63	---	PASS
BLE	HCH	69.57	---	PASS

Test Graph





Appendix A): 6dB Occupied Bandwidth

Test Limit

According to §15.247(a)(2) and RSS-247 section 5.2(a)

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------

Occupied Bandwidth(99%) : For reporting purposes only.

Test Procedure

Test method Refer as KDB 558074 D01 , section 8.1 and ANSI 63.10:2013 clause 6.9.2 & 6.9.3.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 30kHz, VBW = 100kHz and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.


Test Setup



Test Result


Mode	Channel	6dB Bandwidth [MHz]	99% OBW[MHz]	Verdict
BLE	LCH	0.688	1.6277	PASS
BLE	MCH	0.704	1.6300	PASS
BLE	HCH	0.688	1.1947	PASS

Test Graphs
6 dB Bandwidth





Occupied Bandwidth(99%)



<p>MCH</p>		<p>Frequency</p> <p>Center Freq 2.44000000 GHz</p> <p>CF Step 400.000 kHz</p> <p>Freq Offset 0 Hz</p>
<p>HCH</p>		<p>Frequency</p> <p>Center Freq 2.48000000 GHz</p> <p>CF Step 400.000 kHz</p> <p>Freq Offset 0 Hz</p>

Appendix B): Conducted Peak Output Power

Test Limit

According to §15.247(b) and RSS-247 section 5.4(d)

Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 30dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] <input type="checkbox"/> Point-to-point operation
-------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Procedure

Test method Refer as KDB 558074 D01 , section 9.1.2.

1. The EUT RF output connected to spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT.
3. Spectrum analyzer settings are as follows:
 - a) Set the $RBW \geq DTS$ bandwidth.
 - b) Set $VBW \geq [3 \times RBW]$.
 - c) Set $span \geq [3 \times RBW]$.
 - d) Sweep time = auto couple.
 - e) Detector = peak.
 - f) Trace mode = max hold.
 - g) Allow trace to fully stabilize.
 - h) Use peak marker function to determine the peak amplitude level
4. Measure and record the result in the test report.

Test Setup



Test Result

Mode	Channel	Conduct Peak Power[dBm]	Verdict
BLE	LCH	-0.65	PASS
BLE	MCH	-0.71	PASS
BLE	HCH	-1.38	PASS

Test Graphs

Graphs	
LCH	<p>Key parameters for LCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.40200000 GHz Mkr1: 2.40180500 GHz, -0.650 dBm Span: 6.000 MHz Res BW: 2.0 MHz VBW: 6.0 MHz Sweep: 1.067 ms (8001 pts)
MCH	<p>Key parameters for MCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.44000000 GHz Mkr1: 2.43979600 GHz, -0.707 dBm Span: 6.000 MHz Res BW: 2.0 MHz VBW: 6.0 MHz Sweep: 1.067 ms (8001 pts)
HCH	<p>Key parameters for HCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.48000000 GHz Mkr1: 2.47974950 GHz, -1.379 dBm Span: 6.000 MHz Res BW: 2.0 MHz VBW: 6.0 MHz Sweep: 1.067 ms (8001 pts)

Appendix C): Band-edge for RF Conducted Emissions

Test Limit

According to §15.247(d) and RSS-247 section 5.5

In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Test Procedure

Test method Refer as KDB 558074 D01, Section 11.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


Test Setup



Result Table

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	LCH	-1.10	-34.75	-21.10	PASS
BLE	HCH	-1.83	-38.42	-21.83	PASS

Test Graphs



Appendix D): RF Conducted Spurious Emissions

Test Limit

According to §15.247(d) and RSS-247 section 5.5

In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Test Procedure

Test method Refer as KDB 558074 D01 , Section 11.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Setup




Result Table

Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
BLE	LCH	-1.28	<Limit	PASS
BLE	MCH	-1.19	<Limit	PASS
BLE	HCH	-2.03	<Limit	PASS

Test Graphs







Appendix E): Power Spectral Density

Test Limit

According to §15.247(e) and RSS-247 section 5.2(b)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 8dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi [Limit = 8 – (DG – 6)] <input type="checkbox"/> Point-to-point operation :
-------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Procedure

Test method Refer as KDB 558074 D01 , Section 10.2

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.

Measure and record the result of power spectral density. in the test report.

Test Setup



Result Table

Mode	Channel	PSD [dBm]	Verdict
BLE	LCH	-8.38	PASS
BLE	MCH	-8.35	PASS
BLE	HCH	-7.67	PASS

Test Graphs

Graphs	
LCH	<p>Key parameters for LCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.40200000 GHz Mkr1: 2.402 027 96 GHz, -8.381 dBm Span: 1.376 MHz Res BW: 10 kHz VBW: 30 kHz Sweep: 14.00 ms (30000 pts)
MCH	<p>Key parameters for MCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.44000000 GHz Mkr1: 2.440 024 57 GHz, -8.346 dBm Span: 1.408 MHz Res BW: 10 kHz VBW: 30 kHz Sweep: 14.00 ms (30000 pts)
HCH	<p>Key parameters for HCH graph:</p> <ul style="list-style-type: none"> Center Freq: 2.48000000 GHz Mkr1: 2.480 021 03 GHz, -7.673 dBm Span: 1.376 MHz Res BW: 10 kHz VBW: 30 kHz Sweep: 14.00 ms (30000 pts)

Appendix F): Antenna Requirement


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.


Appendix G): Restricted bands around fundamental frequency (Radiated)

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	<p>Below 1GHz test procedure as below:</p> <p>Test method Refer as KDB 558074 D01 , Section 12.1</p> <ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel <p>Above 1GHz test procedure as below:</p> <ol style="list-style-type: none"> Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter). . Test the EUT in the lowest channel , the Highest channel The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. Repeat above procedures until all frequencies measured was complete. 				
Limit:	Frequency	Limit (dB μ V/m @3m)	Remark		
	30MHz-88MHz	40.0	Quasi-peak Value		
	88MHz-216MHz	43.5	Quasi-peak Value		
	216MHz-960MHz	46.0	Quasi-peak Value		
	960MHz-1GHz	54.0	Quasi-peak Value		
	Above 1GHz	54.0	Average Value		
		74.0	Peak Value		

Test plot as follows:

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	47.92	50.42	74.00	23.58	Pass	Horizontal
2	2402.1941	32.26	13.31	-43.12	84.26	86.71	74.00	-12.71	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	48.39	50.89	74.00	23.11	Pass	Vertical
2	2401.7698	32.26	13.31	-43.12	71.46	73.91	74.00	0.09	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	36.12	38.62	54.00	15.38	Pass	Horizontal
2	2402.0105	32.26	13.31	-43.12	46.46	48.91	54.00	5.09	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	36.15	38.65	54.00	15.35	Pass	Vertical
2	2402.0168	32.26	13.31	-43.12	44.19	46.64	54.00	7.36	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2479.7447	32.37	13.39	-43.10	82.38	85.04	74.00	-11.04	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	48.19	50.84	74.00	23.16	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2480.2553	32.37	13.39	-43.10	69.55	72.21	74.00	1.79	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	48.41	51.06	74.00	22.94	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2480.0000	32.37	13.39	-43.10	47.62	50.28	54.00	3.72	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	36.19	38.84	54.00	15.16	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		

Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity
1	2480.0000	32.37	13.39	-43.10	43.65	46.31	54.00	7.69	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	36.17	38.82	54.00	15.18	Pass	Vertical

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

Appendix H) Radiated Spurious Emissions

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

Test Procedure:

Below 1GHz test procedure as below:
 Test method Refer as KDB 558074 D01, Section 12.1

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

Limit:	Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Radiated Spurious Emissions test Data:

During the test, the Radiated Spurious Emissions from 30MHz to 1GHz was performed in all modes with all channels, GFSK, Channel 2440MHz was selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Radiated Emission below 1GHz

Mode:			BLE GFSK Transmitting					Channel:		2440	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	48.0438	13.20	0.78	-31.96	46.42	28.44	40.00	11.56	Pass	H	PK
2	84.1314	8.05	1.06	-31.98	53.66	30.79	40.00	9.21	Pass	H	PK
3	119.8310	9.23	1.30	-32.07	48.71	27.17	43.50	16.33	Pass	H	PK
4	168.2388	8.35	1.52	-31.96	49.70	27.61	43.50	15.89	Pass	H	PK
5	299.9780	13.20	2.06	-31.40	49.70	33.56	46.00	12.44	Pass	H	PK
6	419.9790	15.72	2.45	-31.84	45.50	31.83	46.00	14.17	Pass	H	PK
7	36.5967	11.21	0.67	-31.38	48.29	28.79	40.00	11.21	Pass	V	PK
8	59.9760	11.60	0.90	-31.80	43.88	24.58	40.00	15.42	Pass	V	PK
9	95.9666	10.35	1.13	-31.97	58.19	37.70	43.50	5.80	Pass	V	PK
10	143.9864	7.34	1.41	-31.99	61.19	37.95	43.50	5.55	Pass	V	PK
11	179.9770	9.00	1.58	-31.99	57.23	35.82	43.50	7.68	Pass	V	PK
12	600.0290	19.00	2.96	-31.50	42.37	32.83	46.00	13.17	Pass	V	PK

Transmitter Emission above 1GHz

Mode:			BLE GFSK Transmitting					Channel:		2402	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	2075.5076	31.81	3.57	-43.19	50.84	43.03	74.00	30.97	Pass	H	PK
2	3857.0571	33.69	4.36	-43.04	49.76	44.77	74.00	29.23	Pass	H	PK
3	4804.1203	34.50	4.55	-42.80	56.74	52.99	74.00	21.01	Pass	H	PK
4	6907.2605	36.06	5.87	-42.25	49.35	49.03	74.00	24.97	Pass	H	PK
5	9215.4144	37.66	6.49	-42.05	49.04	51.14	74.00	22.86	Pass	H	PK
6	11004.5336	38.60	7.61	-41.99	48.45	52.67	74.00	21.33	Pass	H	PK
7	1798.4798	30.37	3.32	-42.71	55.27	46.25	74.00	27.75	Pass	V	PK
8	3706.0471	33.56	4.25	-43.05	49.50	44.26	74.00	29.74	Pass	V	PK
9	4803.1202	34.50	4.55	-42.80	51.90	48.15	74.00	25.85	Pass	V	PK
10	6103.2069	35.82	5.26	-42.58	49.80	48.30	74.00	25.70	Pass	V	PK
11	7206.2804	36.31	5.81	-42.16	49.06	49.02	74.00	24.98	Pass	V	PK
12	9234.4156	37.65	6.55	-42.04	48.59	50.75	74.00	23.25	Pass	V	PK

Mode:			BLE GFSK Transmitting					Channel:		2440	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1817.0817	30.49	3.34	-42.75	50.43	41.51	74.00	32.49	Pass	H	PK
2	2954.9955	33.13	4.41	-43.10	51.19	45.63	74.00	28.37	Pass	H	PK
3	4879.1253	34.50	4.80	-42.80	54.29	50.79	74.00	23.21	Pass	H	PK
4	6662.2442	35.96	5.45	-42.40	49.43	48.44	74.00	25.56	Pass	H	PK
5	8361.3574	36.54	6.21	-42.05	49.21	49.91	74.00	24.09	Pass	H	PK
6	10336.4891	38.27	6.90	-42.03	49.45	52.59	74.00	21.41	Pass	H	PK
7	1799.0799	30.37	3.32	-42.71	53.77	44.75	74.00	29.25	Pass	V	PK
8	3055.0037	33.22	4.82	-43.10	50.62	45.56	74.00	28.44	Pass	V	PK
9	3940.0627	33.75	4.34	-43.01	49.97	45.05	74.00	28.95	Pass	V	PK
10	4998.1332	34.50	4.82	-42.80	51.63	48.15	74.00	25.85	Pass	V	PK
11	7320.2880	36.42	5.85	-42.14	52.04	52.17	74.00	21.83	Pass	V	PK
12	10143.4762	38.00	6.86	-42.07	48.24	51.03	74.00	22.97	Pass	V	PK

Mode:			BLE GFSK Transmitting					Channel:		2480	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2157.3157	31.92	3.65	-43.17	50.52	42.92	74.00	31.08	Pass	H	PK
2	3901.0601	33.72	4.34	-43.02	50.01	45.05	74.00	28.95	Pass	H	PK
3	4960.1307	34.50	4.82	-42.80	51.41	47.93	74.00	26.07	Pass	H	PK
4	5934.1956	35.69	5.24	-42.60	49.97	48.30	74.00	25.70	Pass	H	PK
5	7439.2960	36.54	5.85	-42.11	49.59	49.87	74.00	24.13	Pass	H	PK
6	9250.4167	37.65	6.60	-42.05	48.88	51.08	74.00	22.92	Pass	H	PK
7	1798.0798	30.37	3.32	-42.72	55.25	46.22	74.00	27.78	Pass	V	PK
8	2558.1558	32.49	4.09	-43.10	51.23	44.71	74.00	29.29	Pass	V	PK
9	2935.1935	33.10	4.39	-43.10	50.67	45.06	74.00	28.94	Pass	V	PK
10	4960.1307	34.50	4.82	-42.80	50.67	47.19	74.00	26.81	Pass	V	PK
11	7440.2960	36.54	5.85	-42.11	51.01	51.29	74.00	22.71	Pass	V	PK
12	11439.5626	38.86	7.39	-42.00	48.93	53.18	74.00	20.82	Pass	V	PK

NOTE:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.