嘉光科技股份有限公司

承認書

APPROVAL SHEET

品 名:	Antenna
MODEL NAME .	
料 號:	AT5020-B2R8HAAT/LF
PART NUMBER	
客戶名稱:	鴻邦電子
CUSTOMER	
供應商:	GainForce
VENDOR _	
使用機種:	
MODEL	
聯 絡 人:_	陳 仕 軒
聯絡電話:((02) 2880-1838 / (755) 23115592
附件:	
ACCESSORIES	規格書 ■樣品
	SPECIFICATION SAMPLE
	圖樣 □檢驗報告
. 1	DRAWING TEST REPORT

認可狀況: (APPROVED STATUS) 214 6.16





6/30

AT5020 Series

Multilayer Chip Antenna

Features

- Monolithic SMD with small, low-profile and light-weight type.
- Wide bandwidth

Applications

- ❖Bluetooth/Wireless LAN/Home RF
- ❖ISM band 2.4GHz applications

Specifications

Part Number	Operating Frequency (MHz)	Peak Gain (XZ-V)	Average Gain (XZ-V)	VSWR	Impedance
AT5020	2400 2500			ACT RESULT COMPANY OF THE SECOND	
B2R8HAA_	2400 ~ 2500	0 dBi typ.	-1 dBi typ.	2 max.	50 Ω

Q'ty/Reel (pcs)

Operating Temperature Range

Storage Temperature Range

Storage Period Power Capacity : 2,000pcs : -40 ~ +85 °C

: +5 ~ +35 °C, Humidity 45~75%RH

: 12 months max.

: 2W max.

Part Number

AT	<u>5020</u>	-	B	2R8	HAA		
1	2		3	4	(5)	6	7

① Туре	AT : Antenna	② Dimensions (L × W)	5.0× 2.0 mm
③ Material Code	В	Initial center frequency	2R8=2800MHz
⑤ Specification Code	HAA	© Packaging	T: Tape & Reel B: Bulk
② Soldering	=lead-containing /LF=lead-free		

Terminal Configuration




PERSON	Ellegistical state	S APPENDANCE	20.4 - û	50
No.	Terminal Name	No.	Terminal Name	0/
①	Feeding Point	2	NC CB.	20




Dimensions and Recommended PC Board Pattern

Unit: mm


7/3>



(a) Without Matching Circuits



(b) With Matching Circuits



*Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.






Typical Electrical Characteristics (T=25°C)


❖Test Board

8/50





❖Return Loss


(a) Without Matching Circuits



(b) With Matching Circuits










AT5020-B2R8HAAT/LF REV:2 PAGE:3/8




9/40













Taping Specifications

❖Tape & Reel Dimensions (Unit: mm) vs. Quantity (pcs)



Туре	Α	A'	В	С	D	E	F	Т	Quantity/per reel	Tape material
AT5020	4.0±	4.0±	2.4±	5.4±	2.0±	5.5±	12.0±	1.20±	0.000	Plastic
A13020	0.1	0.1	0.1	0.1	0.05	0.1	0.1	0.1	2,000pcs	(Embossed)

❖Reel Dimensions (Unit: mm)




Π
W5

Label: Customer's Name,
ACX P/N, Q'ty, Date,
ACX Corp.


Туре	W2	W3	W4	W5
AT5020	178±1	60±1	1.4±0.2	17±0.5

❖Leader and Trailer Tape





❖Peel-off Force



Peel-off force should be in the range of 0.1 – 0.6 N at a peel-off speed of 300 \pm 10 mm/min .

❖Storage Conditions

- (1) Temperature: 15 ~35℃, relative humidity (RH): 45~75%.
- (2) Non-corrosive environment

Notes

The contents of this data sheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.






Mechanical & Environmental Characteristics

Item	Requirements	Procedure
Solderability	 No apparent damage More than 95% of the terminal electrode shall be covered with new solder 	
Soldering strength (Termination Adhesion)	1. 1kg minimum	 Solder specimen onto test jig. Apply push force at 0.5mm/s until electrode pads are peeled off or ceramic are broken. Pushing force is applied to longitude direction
Deflection (Substrate Bending)	No apparent damage	 Solder specimen onto test jig (FR4, 0.8mm) using the recommend soldering profile. Apply a bending force of 1mm deflection Pressure Rod R230 90mm
Heat/Humidity Resistance	No apparent damage Fulfill the electrical specification after test	1. Temperature: 85± 2°C 2. Humidity: 90% ~ 95% RH 3. Duration: 1000±48hrs 4. Recovery: 1-2hrs
Thermal shock	Fulfill the electrical specification after test	. One cycle/step 1 : 125 ± 5°C for 30 min step 2 : - 40 ± 5°C for 30 min . No of cycles : 100 . Recovery:1-2 hrs
Low Temperature Resistance	No apparent damage 1.	Temperature: -40°± 5 °C Duration: 500 ±24hrs

Soldering Conditions

Typical Soldering Profile for Lead-free Process Reflow Soldering:



Notes

The contents of this data sheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.

Advanced Ceramic X Corp.

16 Tzu Chiang Road, Hsinchu Industrial District Hsinchu Hsien 303, Taiwan

TEL:886-3-5987008 FAX:886-3-5987001

E-mail: acx@acxc.com.tw http://www.acxc.com.tw









No.: CE/2013/55890

Date: 2013/06/07

Page: 1 of 7

ADVANCED CERAMIC X (ACX) CORPORATION

16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

The following sample(s) was/were submitted and identified by/on behalf of the applicant as :

Sample Submitted By Sample Description

: ADVANCED CERAMIC X (ACX) CORPORATION

: MULTILAYER LTCC-B COMPONENTS (CERAMIC BODY)

Style/Item No.

: AD SERIES, AT SERIES, BD SERIES, BF SERIES, BL SERIES, BM SERIES, BW SERIES, CD SERIES, CF SERIES, CP SERIES, DM SERIES, DP SERIES, DS SERIES, EF SERIES, ES SERIES, FA SERIES, FB SERIES, FD SERIES, FM SERIES, GS SERIES, HI SERIES, HF SERIES, HM SERIES, HS SERIES, LF SERIES, OM SERIES, OS SERIES, PD SERIES, NF SERIES, QS SERIES,

SF SERIES, TS SERIES, TP SERIES, LTCC SUBSTRATES

Sample Receiving Date

Testing Period

: 2013/05/31

2013/05/31 TO 2013/06/07

Test Requested

: (1) As specified by client, with reference to RoHS Directive 2011/65/EU Annex II to determine Cadmium, Lead, Mercury, Cr(VI), PBBs, PBDEs contents in the submitted

(2) As specified by client, to test Halogen-Fluorine, Chlorine, Bromine, Iodine contents in the submitted sample.

Test Method

Please refer to next page(s).

Test Result(s)

Please refer to next page(s).





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ass.com/un/Terma-and-Conditions.csp2 drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.



No.: CE/2013/55890

Date: 2013/06/07

Page: 2 of 7

ADVANCED CERAMIC X (ACX) CORPORATION

16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

Test Result(s)

PART NAME No.1

MULTILAYER LTCC-B COMPONENTS (CERAMIC BODY)

Test Item(s)	Unit	Method	MDL	Result
				No.1
Cadmium (Cd)	mg/kg	With reference to IEC 62321: 2008 and performed by ICP-AES.	2	n.d.
Lead (Pb)	mg/kg	With reference to IEC 62321: 2008 and performed by ICP-AES.	2	57400
Mercury (Hg)	mg/kg	With reference to IEC 62321: 2008 and performed by ICP-AES.	2	n.d.
Hexavalent Chromium Cr(VI)	mg/kg	With reference to IEC 62321: 2008 and performed by UV-VIS.	2	n.d.
Sum of PBBs			-	n.d.
Monobromobiphenyl	-		5	n.d.
Dibromobiphenyl		With reference to IEC 62321: 2008 and performed by GC/MS.	5	n.d.
Tribromobiphenyl			5	n.d.
Tetrabromobiphenyl			5	n.d.
Pentabromobiphenyl			5	n.d.
Hexabromobiphenyl			5	n.d.
Heptabromobiphenyl			5	n.d.
Octabromobiphenyl			5	n.d.
Nonabromobiphenyl			5	n.d.
Decabromobiphenyl			5	n.d.
Sum of PBDEs	mg/kg		-	n.d.
Monobromodiphenyl ether			5	n.d.
Dibromodiphenyl ether		2	5	n.d.
ribromodiphenyl ether			5 (1	n.d.
etrabromodiphenyl ether	7		5	n.d.
entabromodiphenyl ether	7	<i>f</i>	5. 5. 作用	n.d.
lexabromodiphenyl ether	7	-	5	n.d.
leptabromodiphenyl ether	7	History	25.4 -00	0 5n.d.
ctabromodiphenyl ether	7	9 2000 1	5	
onabromodiphenyl ether			5_	0 n.d.
ecabromodiphenyl ether	7 1		17.5	o HT.d.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at 100 per part of the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

The state of the s



No.: CE/2013/55890

Date: 2013/06/07

Page: 3 of 7

ADVANCED CERAMIC X (ACX) CORPORATION

16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

Test Item(s)	Unit	Method	MDL	Result
rest item(s)	Oim	Offit Wethod		No.1
Halogen				
Halogen-Fluorine (F) (CAS No.: 14762-94-8)			50	n.d.
Halogen-Chlorine (CI) CAS No.: 22537-15-1)		With reference to BS EN 14582:2007.	50	n.d.
Halogen-Bromine (Br) (CAS No.: 10097-32-2)	mg/kg	Analysis was performed by IC.	50	n.d.
Halogen-Iodine (I) CAS No.: 14362-44-8)			50	n.d.

Note:

1. mg/kg = ppm; 0.1wt% = 1000ppm

2. n.d. = Not Detected

3. MDL = Method Detection Limit

4. " - " = Not Regulated





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.accessible.com/pany-service/com/pany-servi



No.: CE/2013/55890


Date: 2013/06/07

Page: 4 of 7

ADVANCED CERAMIC X (ACX) CORPORATION

16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

- 1) These samples were dissolved totally by pre-conditioning method according to below flow chart. (Cr⁶⁺ test method excluded)
- 2) Name of the person who made measurement: Climbgreat Yang



Note**: (1) For non-metallic material, add alkaline digestion reagent and heat to 90-95-

(2) For metallic material, add pure water and heat to boiling.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.service.com/and.for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.service.com/and-formation-out-and-formation-out



No.: CE/2013/55890


Date: 2013/06/07

Page: 5 of 7

ADVANCED CERAMIC X (ACX) CORPORATION
16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

PBB/PBDE analytical FLOW CHART

- Name of the person who made measurement: Roman Wong
- Name of the person in charge of measurement: Troy Chang



文件管制中小了。 20.4-60-05 HN 0/ PAGE: 0/8

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at into the conditions of the conditions for Electronic Documents at https://www.new.org.company.



No.: CE/2013/55890


Date: 2013/06/07

Page: 6 of 7

ADVANCED CERAMIC X (ACX) CORPORATION 16, TZU CHIANG ROAD, HSINCHU INDUSTRIAL DISTRICT, HSINCHU HSIEN, TAIWAN 303

Analytical flow chart of halogen content

- Name of the person who made measurement: Rita Chen
- Name of the person in charge of measurement: Troy Chang





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sts.com/en/Terms-and-Conditions.cspc drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained become reflects the Company's to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.