

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Drone Aero Stunt LED operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: -3.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is -3.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 92.2 dB μ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS*D) ^2 / 30] mW = -3.03dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 90.7dB μ V/m at 3m in the frequency 2465MHz

The EIRP = [(FS*D) ^2 / 30] mW = -4.53dBm

which is within the production variation.

The maximum conducted output power specified is 0dBm= 1.000mW

The source- based time-averaging conducted output power

=1.000* Duty cycle mW <1.000 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.465) mW

= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 9.2754ms

Effective period of the cycle = 0.6522ms

DC =0.6522ms / 9.2754ms =0.0703 or 7.03%