

FCC REPORT

Certification

Applicant Name:
GS Instech Co., Ltd.**Date of Issue:**
February 13, 2019**Address:**
70, Gilpa-ro 71beon-gil, Nam-gu, Inchen, Korea**Location of test lab:**
HCT CO., LTD.,
74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA**Report No.:** HCT-RF-1902-FC026**FCC ID:** U88-B50KR**APPLICANT:** GS Instech Co., Ltd.**Model:** B-50KR**EUT Type:** In-building RF repeater**Frequency Range:**

Band Name	Downlink (MHz)	Uplink (MHz)
Lower 700 MHz	734 ~ 746	704 ~ 716
Upper 700 MHz	746 ~ 756	777 ~ 787
Cellular	869 ~ 894	824 ~ 849
AWS-1	2 110 ~ 2 155	1 710 ~ 1 755
Broadband PCS	1 930 ~ 1 995	1 850 ~ 1 915

Output Power: 15 dBm (DL) / 20 dBm (UL)**Date of Test:** October 24, 2018 ~ February 11, 2019**FCC Rule Parts:** CFR 47 Part 2, Part 22, Part 24, Part 27

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.



Report prepared by : Kwang il Yoon
Engineer of telecommunication testing center



Approved by : Jong Seok Lee
Manager of telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1902-FC026	February 13, 2019	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
1.1. APPLICANT INFORMATION	4
1.2. PRODUCT INFORMATION	4
1.3. TEST INFORMATION.....	4
2. FACILITIES AND ACCREDITATIONS.....	5
2.1. FACILITIES	5
2.2. EQUIPMENT.....	5
3. TEST SPECIFICATIONS	6
3.1. STANDARDS.....	6
3.2. ADDITIONAL DESCRIPTIONS ABOUT TEST	7
3.3. MEASUREMENTUNCERTAINTY	9
3.4. STANDARDS ENVIRONMENTAL TEST CONDITIONS.....	9
3.5. TEST DIAGRAMS	10
4. TEST EQUIPMENTS	11
5. TEST RESULT	12
5.1. AGC THRESHOLD.....	12
5.2. OUT-OF-BAND REJECTION	14
5.3. INPUT-VERSUS-OUTPUT SIGNAL COMPARISON	20
5.4. MEAN OUTPUT POWER AND AMPLIFIER/BOOSTER GAIN	47
5.5. OUT-OF-BAND/OUT-OF-BLOCK EMISSIONS AND SPURIOUS EMISSIONS.....	60
5.6. RADIATED SPURIOUS EMISSIONS	253
6. Annex A_EUT AND TEST SETUP PHOTO	255

1. GENERAL INFORMATION

1.1. APPLICANT INFORMATION

Company Name	GS Instech Co., Ltd.
Company Address	70, Gilpa-ro 71beon-gil, Nam-gu, Inchen, Korea

1.2. PRODUCT INFORMATION

EUT Type	In-building RF repeater		
Power Supply	110 ~ 220 V AC, AC/DC Adaptor Output : 7.5 Vdc X 5.4 Amps		
Frequency Range	Band Name	Downlink (MHz)	Uplink (MHz)
	Lower 700 MHz	734 ~ 746	704 ~ 716
	Upper 700 MHz	746 ~ 756	777 ~ 787
	Cellular	869 ~ 894	824 ~ 849
	AWS-1	2 110 ~ 2 155	1 710 ~ 1 755
	Broadband PCS	1 930 ~ 1 995	1 850 ~ 1 915
Tx Output Power	15 dBm (DL) / 20 dBm (UL)		
Antenna Specification	Service (DL) Dome Antenna : 5 dBi (698 ~ 960 MHz / 1 710 ~ 2 700 MHz) Donor (UL) Yagi Antenna : 9 dBi (698 ~ 960 MHz) / 11 dBi (1 710 ~ 2 700 MHz)		

1.3. TEST INFORMATION

FCC Rule Parts	CFR 47 Part 2, Part 22, Part 24, Part 27
Measurement Standards	KDB 935210 D05 v01r02, ANSI C63.26-2015
Test Location	HCT CO., LTD. 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

2. FACILITIES AND ACCREDITATIONS

2.1. FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4 (Version: 2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

2.2. EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

3. TEST SPECIFICATIONS

3.1. STANDARDS

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 2, Part 22, Part 24 and Part 27.

Description	Reference	Results
AGC threshold	KDB 935210 D05 v01r02 3.2	Compliant
Out-of-band rejection	KDB 935210 D05 v01r02 3.3	Compliant
Input-versus-output signal comparison	§2.1049	Compliant
Mean output power and amplifier/booster gain	§2.1046, §22.913, §24.232, §27.50(b),(c),(d)	Compliant
Out-of-band/out-of-block and spurious emissions	§2.1051, §22.917, §24.238, §27.53(c),(f),(g),(h)	Compliant
Spurious emissions radiated	§2.1053	Compliant

3.2. ADDITIONAL DESCRIPTIONS ABOUT TEST

Except for the following cases, EUT was tested under normal operating conditions.

: Out-of-band rejection test requires maximum gain condition without AGC

The test was generally based on the method of KDB 935210 D05 v01r02 and only followed ANSI C63.26-2015 if there was no test method in KDB standard.

EUT was tested with following modulated signals provide by applicant.

Band Name	Tested signals
Lower 700 MHz	LTE 10 MHz
Upper 700 MHz	LTE 10 MHz
Cellular	CDMA, 1xEV-DO, LTE 5 MHz
Broadband PCS	CDMA, 1xEV-DO, LTE 20 MHz
AWS-1	LTE 10 MHz

The frequency stability measurement has been omitted in accordance with section 3.7 of KDB 935210 D05 v01r02.

: It can be confirmed through input-versus-output signal comparison test that EUT does not alter the input signal.

The tests results included actual loss value for attenuator and cable combination as shown in the table below.

: Input Path

Correction factor table					
Frequency (MHz)	Factor (dB)	Frequency (MHz)	Factor (dB)	Frequency (MHz)	Factor (dB)
500	0.972	1 100	1.291	2 200	2.067
550	0.890	1 200	1.564	2 300	2.099
600	1.055	1 300	1.588	2 400	2.226
650	1.134	1 400	1.588	2 500	2.241
700	1.167	1 500	1.744	2 600	2.295
750	1.163	1 600	1.895	2 700	2.158
800	1.204	1 700	1.769	2 800	2.172
850	1.188	1 800	1.775	2 900	2.377
900	1.187	1 900	1.806	3 000	2.655
950	1.240	2 000	1.967	-	-
1 000	1.223	2 100	2.008	-	-

: Output Path

Correction factor table			
Frequency (MHz)	Factor (dB)	Frequency (MHz)	Factor (dB)
2	20.975	9 000	22.740
10	20.391	9 500	22.153
30	20.073	10 000	24.544
50	20.022	10 500	23.789
100	20.007	11 000	23.800
200	20.093	11 500	23.470
300	20.388	12 000	23.312
400	20.448	12 500	23.643
500	20.555	13 000	22.867
600	20.598	13 500	24.509
700	20.668	14 000	24.278
750	20.646	14 500	22.686
800	20.666	15 000	23.690
850	20.661	15 500	23.261
900	20.636	16 000	23.564
1 000	20.655	16 500	24.124
1 500	20.998	17 000	23.494
2 000	21.165	17 500	24.199
2 500	21.384	18 000	23.910
3 000	21.675	19 000	24.397
3 500	21.691	20 000	25.216
4 000	21.830	21 000	26.594
4 500	21.619	22 000	26.103
5 000	21.827	23 000	27.272
5 500	22.056	24 000	27.122
6 000	22.183	25 000	28.000
6 500	22.851	26 000	27.297
7 000	22.214	26 500	29.124
7 500	22.442	-	-
8 000	22.425	-	-
8 500	22.240	-	-

3.3. MEASUREMENT UNCERTAINTY



Description	Reference	Results
AGC threshold	-	±0.87 dB
Out-of-band rejection	-	±0.58 MHz
Input-versus-output signal comparison	OBW > 5 MHz	±0.58 MHz
Mean output power and amplifier/booster gain	-	±0.87 dB
Out-of-band/out-of-block and spurious emissions	-	±1.08 dB
Spurious emissions radiated	$f \leq 1 \text{ GHz}$	±4.80 dB
	$f > 1 \text{ GHz}$	±6.07 dB

* Coverage factor $k = 2$, Confidence levels of 95 %

3.4. STANDARDS ENVIRONMENTAL TEST CONDITIONS

Temperature	+15 °C to +35 °C
Relative humidity	30 % to 60 %
Air pressure	860 mbar to 1 060 mbar

3.5. TEST DIAGRAMS



4. TEST EQUIPMENTS

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Agilent	N9020A / Spectrum Analyzer	09/05/2018	Annual	MY46471250
Agilent	N5182A / Signal Generator	08/09/2018	Annual	MY50140312
Agilent	N5182A / Signal Generator	08/30/2018	Annual	MY46240523
Agilent	8498A / Attenuator	09/06/2018	Annual	51162
KEITHLEY	S46 / Switch	N/A	N/A	1088024
Deayoung ENT	DFSS60 / AC Power Supply	04/05/2018	Annual	1003030-1
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Emco	2090 / Controller	N/A	N/A	060520
Ets	- / Turn Table	N/A	N/A	N/A
Rohde&Schwarz	- / Loop Antenna	04/19/2017	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/06/2017	Biennial	760
Schwarzbeck	BBHA 9120D / Horn Antenna	06/30/2017	Biennial	9120D-1300
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/25/2017	Biennial	BBHA9170124
Rohde&Schwarz	FSP / Spectrum Analyzer	09/19/2018	Annual	836650/016
Wainwright Instruments	WHKX10-900-1000-15000-40SS / High Pass Filter	07/20/2018	Annual	5
Wainwright Instruments	WHKX10-2700-3000-18000-40SS / High Pass Filter	07/20/2018	Annual	3
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL26405040 / Power Amplifier	07/10/2018	Annual	19660

5. TEST RESULT

5.1. AGC THRESHOLD

Test Requirement:

KDB 935210 D05 v01r02

Testing at and above the AGC threshold is required.

Test Procedures:

Measurements were in accordance with the test methods section 3.2 of KDB 935210 D05 v01r02.

In the case of fiber-optic distribution systems, the RF input port of the equipment under test (EUT) refers to the RF input of the supporting equipment RF to optical convertor; see also descriptions and diagrams for typical DAS booster systems in KDB Publication 935210 D02

Devices intended to be directly connected to an RF source (donor port) only need to be evaluated for any over-the-air transmit paths.

- a) Connect a signal generator to the input of the EUT.
- b) Connect a spectrum analyzer or power meter to the output of the EUT using appropriate attenuation as necessary.
- c) The signal generator should initially be configured to produce either of the required test signals.
- d) Set the signal generator frequency to the center frequency of the EUT operating band.
- e) While monitoring the output power of the EUT, measured using the methods of ANSI C63.26-2015 subclause 5.2.4.4.1, increase the input level until a 1 dB increase in the input signal power no longer causes a 1 dB increase in the output signal power.
- f) Record this level as the AGC threshold level.
- g) Repeat the procedure with the remaining test signal.

Output power measurement in subclause 5.2.4.4.1 of ANSI C63.26

- a) Set span to $2 \times$ to $3 \times$ the OBW.
- b) Set RBW = 1% to 5% of the OBW.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
- e) Sweep time: auto-couple
- f) Detector = power averaging (rms).
- g) If the EUT can be configured to transmit continuously, then set the trigger to free run.
- h) Omit
- i) Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To

accurately determine the average power over multiple symbols, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.

j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function, with the band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Test Results:

Test Band	Link	Signal	Center Frequency (MHz)	AGC Threshold Level (dBm)	Output Level (dBm)
Lower 700 MHz	Uplink	LTE 10 MHz	710.00	-45	19.28
	Downlink	LTE 10 MHz	740.00	-50	15.00
Upper 700 MHz	Uplink	LTE 10 MHz	781.50	-45	19.58
	Downlink	LTE 10 MHz	751.00	-50	15.38
Cellular	Uplink	CDMA	836.50	-45	19.99
		LTE 5 MHz	836.50	-45	19.76
	Downlink	CDMA	881.50	-50	14.79
		LTE 5 MHz	881.50	-50	14.91
AWS-1	Uplink	LTE 10 MHz	1732.50	-50	19.89
	Downlink	LTE 10 MHz	2132.50	-55	15.08
Broadband PCS	Uplink	CDMA	1882.50	-50	20.20
		LTE 20 MHz	1882.50	-50	20.23
	Downlink	CDMA	1962.50	-55	15.33
		LTE 20 MHz	1962.50	-55	14.73

5.2. OUT-OF-BAND REJECTION

Test Requirement:

KDB 935210 D05 v01r02

Out-of-band rejection required.



Test Procedures:

Measurements were in accordance with the test methods section 3.3 of KDB 935210 D05 v01r02.

Adjust the internal gain control of the EUT to the maximum gain for which equipment certification is sought.

- a) Connect a signal generator to the input of the EUT.
- b) Configure a swept CW signal with the following parameters:
 - 1) Frequency range = $\pm 250\%$ of the passband, for each applicable CMRS band.
 - 2) Level = a sufficient level to affirm that the out-of-band rejection is > 20 dB above the noise floor and will not engage the AGC during the entire sweep.
 - 3) Dwell time = approximately 10 ms.
 - 4) Number of points = $\text{SPAN}/(\text{RBW}/2)$.
- c) Connect a spectrum analyzer to the output of the EUT using appropriate attenuation.
- d) Set the span of the spectrum analyzer to the same as the frequency range of the signal generator.
- e) Set the resolution bandwidth (RBW) of the spectrum analyzer to be 1 % to 5 % of the EUT passband, and the video bandwidth (VBW) shall be set to $\geq 3 \times \text{RBW}$.
- f) Set the detector to Peak Max-Hold and wait for the spectrum analyzer's spectral display to fill.
- g) Place a marker to the peak of the frequency response and record this frequency as f_0 .
- h) Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the -20 dB down amplitude, to determine the 20 dB bandwidth.
- i) Capture the frequency response of the EUT.
- j) Repeat for all frequency bands applicable for use by the EUT.


Test Results:



Lower + Upper 700 MHz / Downlink




Cellular / Uplink



Cellular / Downlink




AWS-1 / Uplink




AWS-1 / Downlink



Broadband PCS / Uplink





5.3. INPUT-VERSUS-OUTPUT SIGNAL COMPARISON

Test Requirement:**§2.1049 Measurements required: Occupied bandwidth.**

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the specified conditions of § 2.1049 (a) through (i) as applicable.

Test Procedures:

Measurements were in accordance with the test methods section 3.4 of KDB 935210 D05 v01r02.

- a) Connect a signal generator to the input of the EUT.
- b) Configure the signal generator to transmit the AWGN signal.
- c) Configure the signal amplitude to be just below the AGC threshold level (see 3.2), but not more than 0.5 dB below.
- d) Connect a spectrum analyzer to the output of the EUT using appropriate attenuation.
- e) Set the spectrum analyzer center frequency to the center frequency of the operational band under test. The span range of the spectrum analyzer shall be between 2 times to 5 times the emission bandwidth (EBW) or alternatively, the OBW.
- f) The nominal RBW shall be in the range of 1 % to 5 % of the anticipated OBW, and the VBW shall be $\geq 3 \times$ RBW.
- g) Set the reference level of the instrument as required to preclude the signal from exceeding the maximum spectrum analyzer input mixer level for linear operation. In general, the peak of the spectral envelope must be more than $[10 \log (OBW / RBW)]$ below the reference level. Steps f) and g) may require iteration to enable adjustments within the specified tolerances.
- h) The noise floor of the spectrum analyzer at the selected RBW shall be at least 36 dB below the reference level.
- i) Set spectrum analyzer detection function to positive peak.
- j) Set the trace mode to max hold.
- k) Determine the reference value: Allow the trace to stabilize. Set the spectrum analyzer marker to the highest amplitude level of the displayed trace (this is the reference value) and record the associated frequency as f_0 .
- l) Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the -26 dB down amplitude. The 26 dB EBW (alternatively OBW) is the positive frequency difference between the two markers. If the spectral envelope crosses the -26 dB down amplitude at multiple points, the lowest or highest frequency shall be selected as the frequencies that are the furthest removed from the center frequency at which the spectral envelope crosses the -26 dB down amplitude point.

- m) Repeat steps e) to l) with the input signal connected directly to the spectrum analyzer (i.e., input signal measurement).
- n) Compare the spectral plot of the input signal (determined from step m) to the output signal (determined from step l) to affirm that they are similar (in passband and rolloff characteristic features and relative spectral locations), and include plot(s) and descriptions in test report.
- o) Repeat the procedure [steps e) to n)] with the input signal amplitude set to 3 dB above the AGC threshold.
- p) Repeat steps e) to o) with the signal generator set to the narrowband signal.
- q) Repeat steps e) to p) for all frequency bands authorized for use by the EUT.

Test Results:

Tabular data of Output Occupied Bandwidth

Test Band	Link	Signal	Center Frequency (MHz)	99 % OBW (MHz)	26 dB OBW (MHz)
Lower 700 MHz	Uplink	LTE 10 MHz	710.00	9.0237	9.937
	Downlink	LTE 10 MHz	740.00	9.0085	10.00
Upper 700 MHz	Uplink	LTE 10 MHz	781.50	9.0464	9.859
	Downlink	LTE 10 MHz	751.00	8.9554	9.971
Cellular	Uplink	CDMA	836.50	1.2381	1.365
		LTE 5 MHz	836.50	4.5236	5.054
	Downlink	CDMA	881.50	1.2393	1.370
		LTE 5 MHz	881.50	4.5039	5.016
AWS-1	Uplink	LTE 10 MHz	1732.50	9.0127	9.922
	Downlink	LTE 10 MHz	2132.50	9.0134	10.01
Broadband PCS	Uplink	CDMA	1882.50	1.2386	1.370
		LTE 20 MHz	1882.50	18.000	19.99
	Downlink	CDMA	1962.50	1.2411	1.364
		LTE 20 MHz	1962.50	18.002	20.09

Tabular data of Input Occupied Bandwidth

Test Band	Link	Signal	Center Frequency (MHz)	99 % OBW (MHz)	26 dB OBW (MHz)
Lower 700 MHz	Uplink	LTE 10 MHz	710.00	8.9884	10.01
	Downlink	LTE 10 MHz	740.00	9.0106	10.03
Upper 700 MHz	Uplink	LTE 10 MHz	781.50	9.0287	9.861
	Downlink	LTE 10 MHz	751.00	9.0004	9.990
Cellular	Uplink	CDMA	836.50	1.2424	1.370
		LTE 5 MHz	836.50	4.5125	5.017
	Downlink	CDMA	881.50	1.2443	1.360
		LTE 5 MHz	881.50	4.5123	5.033
AWS-1	Uplink	LTE 10 MHz	1732.50	8.9925	10.00
	Downlink	LTE 10 MHz	2132.50	9.0161	9.948
Broadband PCS	Uplink	CDMA	1882.50	1.2413	1.362
		LTE 20 MHz	1882.50	18.017	19.81
	Downlink	CDMA	1962.50	1.2372	1.360
		LTE 20 MHz	1962.50	17.955	19.90

Tabular data of 3 dB above the AGC threshold Output Occupied Bandwidth



Test Band	Link	Signal	Center Frequency (MHz)	99 % OBW (MHz)	26 dB OBW (MHz)
Lower 700 MHz	Uplink	LTE 10 MHz	710.00	9.0270	10.02
	Downlink	LTE 10 MHz	740.00	8.9864	9.958
Upper 700 MHz	Uplink	LTE 10 MHz	781.50	9.0098	9.837
	Downlink	LTE 10 MHz	751.00	8.9566	9.926
Cellular	Uplink	CDMA	836.50	1.2368	1.364
		LTE 5 MHz	836.50	4.5189	5.041
	Downlink	CDMA	881.50	1.2425	1.362
		LTE 5 MHz	881.50	4.5078	5.042
AWS-1	Uplink	LTE 10 MHz	1732.50	8.9978	9.924
	Downlink	LTE 10 MHz	2132.50	9.0057	10.03
Broadband PCS	Uplink	CDMA	1882.50	1.2402	1.360
		LTE 20 MHz	1882.50	18.020	19.95
	Downlink	CDMA	1962.50	1.2423	1.366
		LTE 20 MHz	1962.50	18.031	19.96

Measured Occupied Bandwidth Comparison


Test Band	Link	Signal	Variant of Input and output Occupied Bandwidth (%)	Variant of Input and 3 dB above the AGC threshold output Occupied Bandwidth (%)
Lower 700 MHz	Uplink	LTE 10 MHz	-0.709	0.140
	Downlink	LTE 10 MHz	-0.209	-0.668
Upper 700 MHz	Uplink	LTE 10 MHz	-0.020	-0.243
	Downlink	LTE 10 MHz	-0.190	-0.641
Cellular	Uplink	CDMA	-0.365	-0.438
		LTE 5 MHz	0.737	0.478
	Downlink	CDMA	0.735	0.147
		LTE 5 MHz	-0.338	0.179
AWS-1	Uplink	LTE 10 MHz	-0.780	-0.760
	Downlink	LTE 10 MHz	0.593	0.804
Broadband PCS	Uplink	CDMA	0.587	-0.147
		LTE 20 MHz	0.909	0.707
	Downlink	CDMA	0.294	0.441
		LTE 20 MHz	0.955	0.302

* Change in input-output OBW is less than $\pm 5\%$.


Plot data of Occupied Bandwidth





Output / Upper 700 MHz / Uplink / LTE 10 MHz




Output / Upper 700 MHz / Downlink / LTE 10 MHz








Output / Cellular / Downlink / CDMA




Output / Cellular / Downlink / LTE 5 MHz







Output / Broadband PCS / Uplink / CDMA



Output / Broadband PCS / Uplink / LTE 20 MHz



Output / Broadband PCS / Downlink / CDMA



Output / Broadband PCS / Downlink / LTE 20 MHz

