

## FCC MPE REPORT

### Certification

**Applicant Name:**  
GS Instech Co., Ltd.

**Date of Issue:**  
October 12, 2018

**Address:**  
70, Gilpa-ro 71beon-gil, Nam-gu, Inchen, Korea

**Location of test lab:**  
HCT CO., LTD.,  
74, Seoicheon-ro 578beon-gil, Majang-myeon,  
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-RF-1810-FC011-R1

**FCC ID:** U88CC-A18

**APPLICANT:** GS Instech Co., Ltd.

**Model:** CC-A18

**EUT Type:** Industrial RF Repeater

**Frequency Range:** 2 110 MHz ~ 2 155 MHz (DL) / 1 710 MHz ~ 1 755 MHz (UL)

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



**Report prepared by : Kwang Il Yoon**  
Engineer of telecommunication testing center



**Approved by : Jong Seok Lee**  
Manager of telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1810-FC011	October 10, 2018	- First Approval Report
HCT-RF-1810-FC011-R1	October 12, 2018	- We recalculated with the change of Antenna Gain.

# RF Exposure Statement

## 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

## 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 3. RESULTS

#### 3-1. LTE 10 MHz Downlink

Average output Power at antenna input terminal	18.260	dBm
Average output Power at antenna input terminal	66.988	mW
Prediction distance	20.00	cm
Prediction frequency	2132.50	MHz
Antenna Gain(typical)	4.000	dBi
Antenna Gain(numeric)	2.512	-
Power density at prediction frequency( S)	0.033476	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm <sup>2</sup>

#### 2.1091

EIRP	22.26 (dBm)
ERP	20.11 (dBm)
ERP	0.103 (W)
ERP Limit	3.00 (W)
MARGIN	14.66 (dB)

3-2. LTE 10 MHz Uplink

Average output Power at antenna input terminal	18.140	dBm
Average output Power at antenna input terminal	65.163	mW
Prediction distance	20.00	cm
Prediction frequency	1715.00	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.051610	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm <sup>2</sup>

2.1091

EIRP	24.14 (dBm)
ERP	21.99 (dBm)
ERP	0.158 (W)
ERP Limit	3.00 (W)
MARGIN	12.78 (dB)