



Dates of Tests: July. 20 ~ July 28, 2009

Test Report S/N: LR500190907I

Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.

**USD-FZ750BC**

APPLICANT

**Firmtech co., Ltd**

<b>Equipment Class</b>	:	<b>Digital Transmission System (DTS)</b>
<b>Manufacturing Description</b>	:	<b>Zigbee Embedded Module</b>
<b>Manufacturer</b>	:	<b>Firmtech co.,Ltd</b>
<b>Model name</b>	:	<b>FZ750BC</b>
<b>Variant Model name</b>	:	<b>FZ760BC</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	:	<b>2405MHz ~ 2480MHz</b>
<b>Max. Output Power</b>	:	<b>Max 8.85dBm - Conducted</b>
<b>Data of issue</b>	:	<b>July 28, 2009</b>

This test report is issued under the authority of:

The test was supervised by:




Dong -Min JUNG, Technical Manager

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

---

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S .....	3
2. INFORMATION'S ABOUT TEST ITEM .....	4
3. TEST REPORT .....	5
3.1 SUMMARY OF TESTS .....	5
3.2 TECHNICAL CHARACTERISTICS TEST .....	6
3.2.1 6dB BANDWIDTH .....	6
3.2.2 PEAK OUTPUT POWER .....	9
3.2.3 POWER SPECTRAL DENSITY .....	12
3.2.4 BAND – EDGE & SPURIOUS .....	15
3.2.5 FIELD STRENGTH OF HARMONICS .....	21
3.2.6 AC CONDUCTED EMISSIONS .....	24
<b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS .....	27

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2009-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2010-05-03	IC filing

## 2. Information's about test item

### 2-1 Applicant & Manufacturer

Company name : Firmtech co., Ltd  
 Address : B-606, Ssang IT Twin Tower, Sangdaewon-dong, 442-5, Jungwon-gu,  
 Seongnam-si, Gyeonggi-do, Korea 462-120  
 Tel / Fax : TEL No : +82-31-719-4812 / FAX No : +82-31-719-4834

### 2-2 Equipment Under Test (EUT)

Trade name : Zigbee Embedded Module  
 FCC ID : U8D-FZ750BC  
 Model name : FZ750BC  
 Variant Model name : FZ760BC  
 Serial number : Identical prototype  
 Date of receipt : July 19, 2009  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip antenna with Max. 1.428dBi gain  
 Frequency Range : 2405MHz ~ 2480MHz  
 RF output power : Max 8.85dBm - Conducted  
 Number of channels : 16  
 Channel spacing : 5MHz  
 Type of Modulation : O-QPSK  
 Power Source : DC 3.3V

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2405	2445	2480

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	PP17L	04465	DELL

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8dBm @ 3kHz		C
15.247(d)	Band Edge & Spurious	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### → Antenna Requirement

The Firmtech co., Ltd. FCC ID: U8D-FZ750BC unit complies with the requirement of §15.203. The antenna is connected to inside of EUT. And type is Chip antenna.

The sample was tested according to the following specification:  
FCC Parts 15.247; ANSI C-63.4-2003

## 3.2 Technical Characteristics Test

### 3.2.1 6 dB Bandwidth

#### Procedure:

The bandwidth at 6dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 30 MHz

VBW = 300 kHz (VBW  $\geq$  RBW)

Sweep = auto

Trace = max hold

Detector function = peak

#### Measurement Data:

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	1.577	Complies
2445	1.563	Complies
2480	1.577	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

6 dB Bandwidth > 500kHz

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

### Low Channel



### Mid Channel



## High Channel





### 3.2.2 Peak Output Power Measurement

#### Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1MHz

Span = auto

VBW = 3MHz (VBW  $\geq$  RBW)

Sweep = auto

Detector function = peak

#### Measurement Data:


Frequency (MHz)	Test Results	
	Measured Bandwidth (dBm)	Result
2405	8.85	Complies
2445	8.84	Complies
2480	8.49	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

Peak output power	< 1W
-------------------	------


### Low Channel



### Mid Channel



## High Channel



### 3.2.3 Power Spectral Density

#### Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz

Span = 300 kHz

VBW = 10 kHz

Sweep = 1000 sec

Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Test Results	
	Measured Bandwidth (dBm)	Result
2405	-4.53	Complies
2445	-4.54	Complies
2480	-5.14	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

Power Spectral Density	< 8dBm @ 3kHz BW
------------------------	------------------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


### Low Channel



### Mid Channel



## High Channel



### 3.2.4 Band - edge

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 40 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK:

RBW = VBW = 1MHz, Sweep=Auto

Average:

RBW = 1MHz, VBW=10Hz, Sweep=Auto

Measurement Distance:

3m

Polarization:


Horizontal / Vertical

#### Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

### Band-edge : Conducted Measurements





### Band-edges in the restricted band 2483.5 ~ 2500 MHz measurement

- Document DA 00-705 Marker Delta Method


Frequency (MHz)	Detect mode	Pol.	Reading (dBuV/m)	T.F (dB)	Step 1 Data	delta	Step 3 Data	Limit
2462	PK	H	97.38	5.8	103.18	49.48	53.70	74
	AV	H	95.14	5.8	100.94	49.48	51.46	54

Note) Step 1 = Reading + T.F


(T.F = Ant.F + Cable loss – PreAmp Gain)

Step 3 = Step 1 – Delta Value


**Low channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



**Mid channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



**High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



### 3.2.5 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

VBW ≥ RBW

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- See next pages for actual measured data.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

#### Minimum Standard: FCC Part 15.109

Frequency (MHz)	Limit (uV/m) @ 10m
30 ~ 88	90
88 ~ 216	150
216 ~ 960	210
Above 960	300

**Measurement Data:**


Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
1482	45.25	1466	45.38	1504	46.16
1926	49.56	1964	50.05	2003	51.64
2884	43.22	2922	42.14	2960	40.56
4810	38.25	4890	39.43	4960	35.12
Measurement uncertainty		$\pm 6$ dB			

**Radiated Emissions – WIRELESS Mode**



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: FZ750BC TEST MODE: WIRELESS mode  
Temp Humi : 25 / 56 Tested by: KIM.K.I



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	85.00	-17.20	30.40	40.00	9.60	141	27	HORIZONTAL
2	121.90	-13.87	34.43	43.50	9.07	140	26	HORIZONTAL
3	197.86	-12.45	32.85	43.50	10.65	256	55	HORIZONTAL
4	264.88	-9.71	35.89	46.00	10.11	100	208	VERTICAL
5	663.88	-1.70	38.60	46.00	7.40	100	287	VERTICAL
6	998.68	3.09	39.59	54.00	14.41	100	75	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.6 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

##### Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

##### Class A

Frequency Range	quasi-peak	Average
0.15 ~ 0.5 MHz	79 dBuV	66 dBuV
0.5 ~ 30 MHz	73 dBuV	60 dBuV




**AC Conducted Emissions – WIRELESS – Line**



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : F2750BC Phase : LINE  
 -----  
 Test Mode : WIRELESS mode Test Power : 120 / 60  
 -----  
 Temp./Humi. : 24 / 65 Test Engineer : KIM.K.I  
 -----

Data: 396 File: D:\Conducted Data\2009\LTA\_Conduction\_0907\_2.EMI (402) Date: 2009-07-28



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.209	38.69	25.89	9.62	48.31	35.51	63.24	53.24	14.94	17.74
0.278	33.17	25.17	9.65	42.82	34.82	60.88	50.88	18.05	16.05
0.317	30.67	24.17	9.69	40.36	33.86	59.79	49.79	19.43	15.93
0.410	33.16	16.36	9.68	42.84	26.04	57.65	47.65	14.81	21.61
0.627	31.44	17.24	9.78	41.22	27.02	56.00	46.00	14.78	18.98
0.913	25.25	13.45	9.80	35.04	23.24	56.00	46.00	20.96	22.76

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


**AC Conducted Emissions – WIRELESS – Neutral**



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : F2750BC Phase : NEUTRAL  
 Test Mode : WIRELESS mode Test Power : 120 / 60  
 Temp./Humi. : 24 / 65 Test Engineer : KIM.K.I

Data: 398 File: D:\Conducted Data\2009\LTA\_Conduction\_0907\_2.EMI (402) Date: 2009-07-28



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
0.208	37.99	23.49	9.64	47.63	33.13	63.28	53.28	15.65	20.15
0.276	31.47	24.37	9.64	41.11	34.01	60.94	50.94	19.82	16.92
0.309	28.87	20.97	9.64	38.51	30.61	60.00	50.00	21.49	19.39
0.417	31.46	17.06	9.73	41.19	26.79	57.51	47.51	16.32	20.72
0.629	29.74	18.04	9.79	39.53	27.83	56.00	46.00	16.47	18.17
0.908	21.85	14.65	9.81	31.65	24.45	56.00	46.00	24.35	21.55

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-10
2	Spectrum Analyzer	8563E	3425A02505	HP	Apr-10
3	Spectrum Analyzer	8594E	3710A04074	HP	Oct-09
4	Signal Generator	8648C	3623A02597	HP	Apr-10
5	Signal Generator	83711B	US34490456	HP	Apr-10
6	Attenuator (3dB)	8491A	37822	HP	Oct-09
7	Attenuator (10dB)	8491A	63196	HP	Oct-09
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-09
9	EMI Test Receiver	ESVD	843748/001	R&S	Apr-10
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Apr-10
14	Test Receiver	ESHS10	828404/009	R&S	Apr-10
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-09
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-09
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-09
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-09
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Apr-10
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	RF Switch	MP59B	6200414971	ANRITSU	-
27	Power Divider	11636A	6243	HP	Oct-09
28	DC Power Supply	6622A	3448A03079	HP	Oct-09
29	Frequency Counter	5342A	2826A12411	HP	Apr-10
30	Power Meter	EPM-441A	GB32481702	HP	Apr-10
31	Power Sensor	8481A	2702A64048	HP	Apr-10
32	Audio Analyzer	8903B	3729A18901	HP	Oct-09
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-09
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	Oct-09
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Stop Watch	HS-3	601Q09R	CASIO	Apr-10
37	LISN	ENV216	100408	R&S	Oct-09