



FCC TEST REPORT (15.247)

REPORT NO.: RF130927E06

MODEL NO.: AP One In-Wall, AP One InWall, Flex AP, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo902

FCC ID: U8G-P1902

RECEIVED: Sep. 27, 2013

TESTED: Nov. 07, 2013 to Feb. 19, 2014

ISSUED: Feb. 27, 2014

APPLICANT: Pismo Labs Technology Limited

ADDRESS: FLAT/RM A5, 5/F, HK SPINNERS IND BLDG PHASE 6, 481 CASTLE PEAK ROAD, CHEUNG SHA WAN, HONG KONG.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD	5
1. CERTIFICATION	6
2. SUMMARY OF TEST RESULTS	7
2.1 MEASUREMENT UNCERTAINTY	8
3. GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	12
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	13
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	16
3.4 DUTY CYCLE OF TEST SIGNAL	17
3.5 DESCRIPTION OF SUPPORT UNITS.....	19
3.6 CONFIGURATION OF SYSTEM UNDER TEST	20
4. TEST TYPES AND RESULTS (FOR 2.4GHz, 2.400 ~ 2.4835GHz Band)	21
4.1 CONDUCTED EMISSION MEASUREMENT	21
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	21
4.1.2 TEST INSTRUMENTS.....	21
4.1.3 TEST PROCEDURES	22
4.1.4 DEVIATION FROM TEST STANDARD	22
4.1.5 TEST SETUP	22
4.1.6 EUT OPERATING CONDITIONS	23
4.1.7 TEST RESULTS	24
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	26
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	26
4.2.2 TEST INSTRUMENTS.....	27
4.2.3 TEST PROCEDURES	28
4.2.4 DEVIATION FROM TEST STANDARD	28
4.2.5 TEST SETUP	29
4.2.6 EUT OPERATING CONDITIONS	29
4.2.7 TEST RESULTS	30
4.3 6dB BANDWIDTH MEASUREMENT	43
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	43
4.3.2 TEST INSTRUMENTS.....	43
4.3.3 TEST PROCEDURE.....	43
4.3.4 DEVIATION FROM TEST STANDARD	43
4.3.5 TEST SETUP	43
4.3.6 EUT OPERATING CONDITIONS	43
4.3.7 TEST RESULTS	44
4.4 CONDUCTED OUTPUT POWER MEASUREMENT	46
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	46
4.4.2 INSTRUMENTS.....	46
4.4.3 TEST PROCEDURES	46
4.4.4 DEVIATION FROM TEST STANDARD	47
4.4.5 TEST SETUP	47
4.4.6 EUT OPERATING CONDITIONS	47
4.4.7 TEST RESULTS	48
4.5 AVERAGE OUTPUT POWER.....	49
4.5.1 FOR REFERENCE.....	49
4.5.2 TEST INSTRUMENTS.....	49
4.5.3 TEST PROCEDURES	49
4.5.4 TEST SETUP	49
4.5.5 EUT OPERATING CONDITIONS	49



4.5.6	TEST RESULTS	50
4.6	POWER SPECTRAL DENSITY MEASUREMENT	51
4.6.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	51
4.6.2	TEST INSTRUMENTS.....	51
4.6.3	TEST PROCEDURE.....	51
4.6.4	DEVIATION FROM TEST STANDARD	51
4.6.5	TEST SETUP	51
4.6.6	EUT OPERATING CONDITION	51
4.6.7	TEST RESULTS	52
4.7	CONDUCTED OUT-BAND EMISSION MEASUREMENT	55
4.7.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	55
4.7.2	TEST INSTRUMENTS.....	55
4.7.3	TEST PROCEDURE.....	55
4.7.4	DEVIATION FROM TEST STANDARD	56
4.7.5	TEST SETUP	56
4.7.6	EUT OPERATING CONDITION	56
4.7.7	TEST RESULTS	56
5.	TEST TYPES AND RESULTS (FOR 5gHz, 5.725~5.850GHz Band).....	65
5.1	CONDUCTED EMISSION MEASUREMENT	65
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	65
5.1.2	TEST INSTRUMENTS.....	65
5.1.3	TEST PROCEDURES	66
5.1.4	DEVIATION FROM TEST STANDARD	66
5.1.5	TEST SETUP	66
5.1.6	EUT OPERATING CONDITIONS	67
5.1.7	TEST RESULTS	68
5.2	RADIATED AND BANDEDGE EMISSION MEASUREMENT	70
5.2.1	LIMITS OF RADIATED AND BANDEDGE EMISSION MEASUREMENT	70
5.2.2	TEST INSTRUMENTS.....	71
5.2.3	TEST PROCEDURES	72
5.2.4	DEVIATION FROM TEST STANDARD	72
5.2.5	TEST SETUP	73
5.2.6	EUT OPERATING CONDITIONS	73
5.2.7	TEST RESULTS	74
5.3	6dB BANDWIDTH MEASUREMENT	83
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	83
5.3.2	TEST INSTRUMENTS.....	83
5.3.3	TEST PROCEDURE.....	83
5.3.4	DEVIATION FROM TEST STANDARD	83
5.3.5	TEST SETUP	83
5.3.6	EUT OPERATING CONDITIONS	84
5.3.7	TEST RESULTS	85
5.4	CONDUCTED OUTPUT POWER MEASUREMENT	87
5.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	87
5.4.2	INSTRUMENTS.....	87
5.4.3	TEST PROCEDURES	87
5.4.4	DEVIATION FROM TEST STANDARD	88
5.4.5	TEST SETUP	88
5.4.6	EUT OPERATING CONDITIONS	88
5.4.7	TEST RESULTS	89
5.5	AVERAGE OUTPUT POWER.....	90
5.5.1	FOR REFERENCE.....	90
5.5.2	TEST INSTRUMENTS.....	90



A D T

5.5.3	TEST PROCEDURES	90
5.5.4	TEST SETUP	90
5.5.5	EUT OPERATING CONDITIONS	90
5.5.6	TEST RESULTS	91
5.6	POWER SPECTRAL DENSITY MEASUREMENT	92
5.6.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	92
5.6.2	TEST INSTRUMENTS.....	92
5.6.3	TEST PROCEDURE.....	92
5.6.4	DEVIATION FROM TEST STANDARD	92
5.6.5	TEST SETUP	92
5.6.6	EUT OPERATING CONDITION	92
5.6.7	TEST RESULTS	93
5.7	CONDUCTED OUT-BAND EMISSION MEASUREMENT	95
5.7.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	95
5.7.2	TEST INSTRUMENTS.....	95
5.7.3	TEST PROCEDURE.....	95
5.7.4	DEVIATION FROM TEST STANDARD	96
5.7.5	TEST SETUP	96
5.7.6	EUT OPERATING CONDITION	96
5.7.7	TEST RESULTS	96
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	103
7.	INFORMATION ON THE TESTING LABORATORIES	104
8.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	105



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130927E06	Original release	Feb. 27, 2014



A D T

1. CERTIFICATION

PRODUCT: Pepwave / Peplink / Pismo Wireless Product

BRAND NAME: Pepwave / Peplink / Pismo

MODEL NO.: AP One In-Wall, AP One InWall, Flex AP, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo902


TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: Pismo Labs Technology Limited

TESTED: Nov. 07, 2013 to Feb. 19, 2014

STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2009

The above equipment (Model: AP One In-Wall) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Feb. 27, 2014
(Lori Chung, Specialist)

APPROVED BY :  , **DATE:** Feb. 27, 2014
(May Chen, Manager)



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 2.4GHz, 2400~2483.5MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -0.46 dB at 0.52109MHz
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.2 dB at 2483.50MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

For 5GHz, 5725~5850MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -2.66 dB at 0.51328MHz
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.1 dB at 11650.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

NOTE:

The EUT was operating in 2.400 ~ 2.4835GHz, 5.15~5.25GHz and 5.725~5.850GHz frequencies band. This report was recorded the RF parameters including 2.400 ~ 2.4835GHz and 5.725~5.850GHz. For the 5.15~5.25GHz RF parameters was recorded in another test report.



A D T

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 dB
Radiated emissions (30MHz-1GHz)	5.43 dB
Radiated emissions (1GHz -6GHz)	3.72 dB
Radiated emissions (6GHz -18GHz)	4.00 dB
Radiated emissions (18GHz -40GHz)	4.11 dB



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Pepwave / Peplink / Pismo Wireless Product
MODEL NO.	AP One In-Wall, AP One InWall, Flex AP, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo902
POWER SUPPLY	DC 43-57V from POE
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS,OFDM
TRANSFER RATE	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 300Mbps
OPERATING FREQUENCY	For 15.407 5GHz: 5.18 ~ 5.24GHz
	For 15.247 2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.745 ~ 5.825GHz
NUMBER OF CHANNEL	For 15.407 4 for 802.11a, 802.11n (HT20) 2 for 802.11n (HT40)
	For 15.247 (2.4GHz) 11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
	For 15.247 (5GHz) 5 for 802.11a, 802.11n (HT20) 2 for 802.11n (HT40)



A D T

MAXIMUM OUTPUT POWER	<p>For 15.407 802.11a: 33.911mW 802.11n (HT20): 34.679mW 802.11n (HT40): 47.170mW For 15.247(2.4GHz) 802.11b: 494.988mW 802.11g: 855.093mW 802.11n (HT20): 871.033mW 802.11n (HT40): 641.297mW For 15.247(5GHz) 802.11a: 237.716mW 802.11n (HT20): 237.716mW 802.11n (HT40): 234.980mW</p>
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

- The EUT has eleven model names, which are identical to each other in all aspects except for the following information:

Product Name	Brand	Model No.	Different
Pepwave / Peplink / Pismo Wireless Product	Pepwave / Peplink / Pismo	AP One In-Wall	For marketing requirement
		AP One InWall	
		Flex AP	
		MAX	
		Surf Pro	
		AP One	
		AP Pro	
		Device Connector	
		Express	
		Balance	
		Pismo902	

From the above models, model: **AP One In-Wall** was selected as representative model for the test and its data was recorded in this report.

- 2.4GHz and 5GHz technology can transmit at same time.

3. The EUT must be supplied with a POE (Only for test, not for sale) as following table:

Brand	Model No.	Spec.
PHIHONG	POE36U-1AT-R	AC I/P: 100-240V, 50/60Hz DC O/P: 56V, 0.6A

4. The EUT incorporates a MIMO without beam forming function.

MODULATION MODE	TX/RX FUNCTION
802.11a	2TX/2RX
802.11b	2TX/2RX
802.11g	2TX/2RX
802.11n (HT20)	2TX/2RX
802.11n (HT40)	2TX/2RX

5. The antennas provided to the EUT, please refer to the following table:

For 2.4GHz						
Transmitter Circuit	Brand	Model	Antenna Type	Gain (dBi) (Include cable loss)	Connecter Type	Frequency range (MHz to MHz)
Chain (0)	Pulse	W3008C	Chip	2.2	NA	2400 ~ 2500
Chain (1)	Pulse	W3008C	Chip	2.2	NA	2400 ~ 2500
For 5GHz						
Transmitter Circuit	Brand	Model	Antenna Type	Gain (dBi) (Include cable loss)	Connecter Type	Frequency range (MHz to MHz)
Chain (0) (Left)	SmartAnt	ADV05-220580	Embedded	2.64	IPEX	5150 ~ 5250
				4.27	IPEX	5725 ~ 5850
Chain (1) (Right)	SmartAnt	ADV05-220580	Embedded	3.27	IPEX	5150 ~ 5250
				1.87	IPEX	5725 ~ 5850

6. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
7. The emission of the simultaneous operation (2.4GHz & 5GHz) has been evaluated and no non-compliance was found.
8. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

Operated in 5725 ~ 5850MHz band:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11n (HT40):

CHANNEL	FREQUENCY
151	5755 MHz
159	5795 MHz



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

Note: The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on X-plane.

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
For 2.4 GHz 802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5
802.11a	149 to 165	149	OFDM	BPSK	6

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
For 2.4 GHz 802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5
802.11a	149 to 165	149	OFDM	BPSK	6



A D T

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5



A D T

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
PLC	21deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin
RE<1G	25deg. C, 68%RH	120Vac, 60Hz	Andy Ho
RE ³ 1G	23deg. C, 68%RH	120Vac, 60Hz	Tim Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Chilin Lee
OB	25deg. C, 60%RH	120Vac, 60Hz	Chilin Lee

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

558074 D01 DTS Meas Guidance v03r01

662911 D01 Multiple Transmitter Output v02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

3.4 DUTY CYCLE OF TEST SIGNAL

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.


If duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11b: Duty cycle = 8.175 ms/8.225 ms = 0.994

802.11g: Duty cycle = 1.359 ms/1.414 ms = 0.961, Duty factor = $10 * \log(1/0.961) = 0.2$

802.11n (HT20): Duty cycle = 1.27 ms/1.327 ms = 0.957, Duty factor = $10 * \log(1/0.957) = 0.2$

802.11n (HT40): Duty cycle = 0.63 ms/0.67 ms = 0.94, Duty factor = $10 * \log(1/0.94) = 0.3$






A D T

If duty cycle of test signal is < 98%, duty factor shall be considered.

802.11a: Duty cycle = 1.359 ms/1.41 ms = 0.964, Duty factor = $10 * \log(1/0.964) = 0.2$

802.11n (HT20): Duty cycle = 1.269 ms/1.317 ms = 0.964, Duty factor = $10 * \log(1/0.964) = 0.2$

802.11n (HT40): Duty cycle = 0.629 ms/0.661 ms = 0.952, Duty factor = $10 * \log(1/0.952) = 0.2$





A D T

3.5 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
3	HUB	ZyXEL	ES-116P	S060H0200021 5	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP Cable (10m)
2	UTP Cable (10m)
3	UTP Cable (10m)

NOTE: All power cords of the above support units are non shielded (1.8m).

3.6 CONFIGURATION OF SYSTEM UNDER TEST





4. TEST TYPES AND RESULTS (FOR 2.4GHz, 2.400 ~ 2.4835GHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100287	Feb. 28, 2013	Feb. 27, 2014
Line-Impedance Stabilization Network (for EUT) ROHDE & SCHWARZ	NSLK-8127	5127-523	Oct. 02, 2013	Oct. 01, 2014
Line-Impedance Stabilization Network (for Peripheral) ROHDE & SCHWARZ	ENV216	100071	Nov. 13, 2013	Nov. 12, 2014
RF Cable (JYEBAO)	5DFB	COACAB-001	May 27, 2013	May 26, 2014
50 ohms Terminator	50	3	Oct. 17, 2013	Oct. 16, 2014
50 ohms Terminator	N/A	EMC-04	Oct. 17, 2013	Oct. 16, 2014
Software ADT	BV ADT_Cond_V7.3.7 .3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. Tested Date: Jan. 06, 2014

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE:

1. The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



A D T

4.1.6 EUT OPERATING CONDITIONS

1. Place the EUT on testing table.
2. Prepare computer system (support unit 1) to act as communication partner.
3. The communication partner runs test program “artgui.exe[ver2.3]” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
--------------	----------	--------------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.19687	0.06	47.30	45.23	47.36	45.29	63.74
2	0.25938	0.07	45.94	45.70	46.01	45.77	61.45	51.45	-15.44	-5.68
3	0.52109	0.11	45.17	43.74	45.28	43.85	56.00	46.00	-10.72	-2.15
4	2.91797	0.25	41.47	32.09	41.72	32.34	56.00	46.00	-14.28	-13.66
5	6.66916	0.39	47.50	46.16	47.89	46.55	60.00	50.00	-12.11	-3.45
6	10.79297	0.48	46.96	44.93	47.44	45.41	60.00	50.00	-12.56	-4.59

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
--------------	-------------	--------------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19687	0.05	48.96	46.98	49.01	47.03	63.74	53.74	-14.73	-6.71
2	0.52109	0.12	46.96	45.42	47.08	45.54	56.00	46.00	-8.92	-0.46
3	2.64844	0.20	40.62	29.79	40.82	29.99	56.00	46.00	-15.18	-16.01
4	6.59363	0.34	47.80	46.69	48.14	47.03	60.00	50.00	-11.86	-2.97
5	11.89453	0.51	46.24	44.07	46.75	44.58	60.00	50.00	-13.25	-5.42
6	23.12891	0.86	45.44	43.00	46.30	43.86	60.00	50.00	-13.70	-6.14

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 RADIATED EMISSION AND BANDEGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 16, 2013	Jan. 15, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Mar. 25, 2013	Mar. 24, 2014
RF Cable	NA	CHHCAB_001	Oct. 06, 2013	Oct. 05, 2014
Spectrum Analyzer R&S	FSV40	100964	July 15, 2013	July 14, 2014
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 27, 2012	Nov. 26, 2013
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 29, 2013	Oct. 28, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5. The CANADA Site Registration No. is IC 7450H-3.
6. Tested Date: Nov. 07, 2013

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	87.81	36.6 QP	40.0	-3.4	1.50 H	218	55.22	-18.61
2	226.57	32.8 QP	46.0	-13.2	1.00 H	119	48.18	-15.39
3	500.01	41.3 QP	46.0	-4.7	2.00 H	39	48.35	-7.06
4	700.03	35.7 QP	46.0	-10.3	2.00 H	37	38.98	-3.32
5	899.99	35.6 QP	46.0	-10.4	1.50 H	336	35.15	0.44
6	1000.00	38.0 QP	54.0	-16.0	1.50 H	290	36.04	1.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	73.80	38.7 QP	40.0	-1.3	1.00 V	183	54.76	-16.03
2	500.01	40.8 QP	46.0	-5.2	1.00 V	77	47.83	-7.06
3	600.02	43.2 QP	46.0	-2.8	1.00 V	39	48.03	-4.80
4	700.03	37.0 QP	46.0	-9.0	1.00 V	360	40.28	-3.32
5	799.99	35.5 QP	46.0	-10.5	1.50 V	0	36.61	-1.13
6	899.99	36.5 QP	46.0	-9.5	1.50 V	34	36.09	0.44

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.24	57.5 PK	74.0	-16.5	1.05 H	341	23.99	33.51
2	2386.24	53.0 AV	54.0	-1.0	1.05 H	341	19.49	33.51
3	*2412.00	105.8 PK			1.05 H	341	72.21	33.59
4	*2412.00	103.4 AV			1.05 H	341	69.81	33.59
5	4824.00	47.7 PK	74.0	-26.3	1.04 H	175	4.52	43.18
6	4824.00	35.7 AV	54.0	-18.3	1.04 H	175	-7.48	43.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.7 PK	74.0	-23.3	1.00 V	308	17.17	33.53
2	2390.00	44.2 AV	54.0	-9.8	1.00 V	308	10.67	33.53
3	*2412.00	97.3 PK			1.00 V	308	63.71	33.59
4	*2412.00	94.3 AV			1.00 V	308	60.71	33.59
5	4824.00	48.6 PK	74.0	-25.4	1.00 V	96	5.42	43.18
6	4824.00	37.3 AV	54.0	-16.7	1.00 V	96	-5.88	43.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	108.0 PK			1.06 H	180	74.33	33.67
2	*2437.00	106.2 AV			1.06 H	180	72.53	33.67
3	4874.00	50.7 PK	74.0	-23.3	1.00 H	76	7.46	43.24
4	4874.00	43.4 AV	54.0	-10.6	1.00 H	76	0.16	43.24
5	7311.00	56.5 PK	74.0	-17.5	1.78 H	193	8.43	48.07
6	7311.00	46.7 AV	54.0	-7.3	1.78 H	193	-1.37	48.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.4 PK			1.11 V	274	66.73	33.67
2	*2437.00	97.5 AV			1.11 V	274	63.83	33.67
3	4874.00	57.0 PK	74.0	-17.0	1.00 V	15	13.76	43.24
4	4874.00	53.0 AV	54.0	-1.0	1.00 V	15	9.76	43.24
5	7311.00	58.1 PK	74.0	-15.9	1.07 V	77	10.03	48.07
6	7311.00	49.0 AV	54.0	-5.0	1.07 V	77	0.93	48.07

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.0 PK			1.04 H	196	71.26	33.74
2	*2462.00	102.7 AV			1.04 H	196	68.96	33.74
3	2487.80	57.4 PK	74.0	-16.6	1.04 H	196	23.57	33.83
4	2487.80	52.9 AV	54.0	-1.1	1.04 H	196	19.07	33.83
5	4924.00	48.4 PK	74.0	-25.6	1.27 H	12	5.13	43.27
6	4924.00	37.2 AV	54.0	-16.8	1.27 H	12	-6.07	43.27
7	7386.00	54.1 PK	74.0	-19.9	1.07 H	284	5.70	48.40
8	7386.00	42.7 AV	54.0	-11.3	1.07 H	284	-5.70	48.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	97.9 PK			1.00 V	307	64.16	33.74
2	*2462.00	93.6 AV			1.00 V	307	59.86	33.74
3	2483.50	51.0 PK	74.0	-23.0	1.00 V	0	17.19	33.81
4	2483.50	44.1 AV	54.0	-9.9	1.00 V	0	10.29	33.81
5	4924.00	49.0 PK	74.0	-25.0	1.01 V	301	5.73	43.27
6	4924.00	38.5 AV	54.0	-15.5	1.01 V	301	-4.77	43.27
7	7386.00	54.4 PK	74.0	-19.6	1.00 V	49	6.00	48.40
8	7386.00	43.1 AV	54.0	-10.9	1.00 V	49	-5.30	48.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.5 PK	74.0	-3.5	1.06 H	155	36.97	33.53
2	2390.00	49.9 AV	54.0	-4.1	1.06 H	155	16.37	33.53
3	*2412.00	105.2 PK			1.06 H	155	71.61	33.59
4	*2412.00	94.6 AV			1.06 H	155	61.01	33.59
5	4824.00	49.0 PK	74.0	-25.0	1.03 H	225	5.82	43.18
6	4824.00	37.6 AV	54.0	-16.4	1.03 H	225	-5.58	43.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.6 PK	74.0	-13.4	1.08 V	324	27.07	33.53
2	2390.00	42.5 AV	54.0	-11.5	1.08 V	324	8.97	33.53
3	*2412.00	97.4 PK			1.08 V	324	63.81	33.59
4	*2412.00	87.8 AV			1.08 V	324	54.21	33.59
5	4824.00	49.8 PK	74.0	-24.2	1.00 V	97	6.62	43.18
6	4824.00	37.8 AV	54.0	-16.2	1.00 V	97	-5.38	43.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	1.00 H	144	34.17	33.53
2	2390.00	46.5 AV	54.0	-7.5	1.00 H	144	12.97	33.53
3	*2437.00	113.2 PK			1.00 H	144	79.53	33.67
4	*2437.00	101.1 AV			1.00 H	144	67.43	33.67
5	2483.50	73.1 PK	74.0	-0.9	1.00 H	144	39.29	33.81
6	2483.50	51.1 AV	54.0	-2.9	1.00 H	144	17.29	33.81
7	4874.00	54.7 PK	74.0	-19.3	1.20 H	140	11.46	43.24
8	4874.00	41.7 AV	54.0	-12.3	1.20 H	140	-1.54	43.24
9	7311.00	56.9 PK	74.0	-17.1	1.09 H	255	8.83	48.07
10	7311.00	45.4 AV	54.0	-8.6	1.09 H	255	-2.67	48.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.2 PK	74.0	-12.8	1.05 V	324	27.67	33.53
2	2390.00	42.4 AV	54.0	-11.6	1.05 V	324	8.87	33.53
3	*2437.00	105.0 PK			1.05 V	324	71.33	33.67
4	*2437.00	94.0 AV			1.05 V	324	60.33	33.67
5	2483.50	68.5 PK	74.0	-5.5	1.05 V	324	34.69	33.81
6	2483.50	44.8 AV	54.0	-9.2	1.05 V	324	10.99	33.81
7	4874.00	62.7 PK	74.0	-11.3	1.00 V	10	19.46	43.24
8	4874.00	50.2 AV	54.0	-3.8	1.00 V	10	6.96	43.24
9	7311.00	60.4 PK	74.0	-13.6	1.07 V	75	12.33	48.07
10	7311.00	48.0 AV	54.0	-6.0	1.07 V	75	-0.07	48.07

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.9 PK			1.01 H	212	73.16	33.74
2	*2462.00	95.7 AV			1.01 H	212	61.96	33.74
3	2483.50	73.2 PK	74.0	-0.8	1.01 H	212	39.39	33.81
4	2483.50	50.3 AV	54.0	-3.7	1.01 H	212	16.49	33.81
5	4924.00	49.0 PK	74.0	-25.0	1.00 H	211	5.73	43.27
6	4924.00	37.4 AV	54.0	-16.6	1.00 H	211	-5.87	43.27
7	7386.00	54.3 PK	74.0	-19.7	1.00 H	205	5.90	48.40
8	7386.00	42.3 AV	54.0	-11.7	1.00 H	205	-6.10	48.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.3 PK			1.09 V	315	64.56	33.74
2	*2462.00	88.5 AV			1.09 V	315	54.76	33.74
3	2483.50	60.0 PK	74.0	-14.0	1.07 V	323	26.19	33.81
4	2483.50	42.2 AV	54.0	-11.8	1.07 V	323	8.39	33.81
5	4924.00	49.1 PK	74.0	-24.9	1.00 V	105	5.83	43.27
6	4924.00	37.4 AV	54.0	-16.6	1.00 V	105	-5.87	43.27
7	7386.00	54.6 PK	74.0	-19.4	1.00 V	122	6.20	48.40
8	7386.00	42.2 AV	54.0	-11.8	1.00 V	122	-6.20	48.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.5 PK	74.0	-1.5	1.08 H	168	38.97	33.53
2	2390.00	49.0 AV	54.0	-5.0	1.08 H	168	15.47	33.53
3	*2412.00	103.6 PK			1.08 H	168	70.01	33.59
4	*2412.00	93.2 AV			1.08 H	168	59.61	33.59
5	4824.00	47.5 PK	74.0	-26.5	1.03 H	223	4.32	43.18
6	4824.00	36.2 AV	54.0	-17.8	1.03 H	223	-6.98	43.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.8 PK	74.0	-18.2	1.05 V	324	22.27	33.53
2	2390.00	38.5 AV	54.0	-15.5	1.05 V	324	4.97	33.53
3	*2412.00	96.7 PK			1.05 V	324	63.11	33.59
4	*2412.00	86.3 AV			1.05 V	324	52.71	33.59
5	4824.00	48.8 PK	74.0	-25.2	1.00 V	84	5.62	43.18
6	4824.00	36.8 AV	54.0	-17.2	1.00 V	84	-6.38	43.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.7 PK	74.0	-4.3	1.05 H	169	36.17	33.53
2	2390.00	47.9 AV	54.0	-6.1	1.05 H	169	14.37	33.53
3	*2437.00	112.6 PK			1.05 H	342	78.93	33.67
4	*2437.00	101.0 AV			1.05 H	342	67.33	33.67
5	2483.50	73.8 PK	74.0	-0.2	1.05 H	202	39.99	33.81
6	2483.50	51.6 AV	54.0	-2.4	1.05 H	202	17.79	33.81
7	4874.00	55.2 PK	74.0	-18.8	1.55 H	335	11.96	43.24
8	4874.00	42.4 AV	54.0	-11.6	1.55 H	335	-0.84	43.24
9	7311.00	56.7 PK	74.0	-17.3	1.40 H	309	8.63	48.07
10	7311.00	44.2 AV	54.0	-9.8	1.40 H	309	-3.87	48.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.1 PK	74.0	-12.9	1.08 V	324	27.57	33.53
2	2390.00	40.8 AV	54.0	-13.2	1.08 V	324	7.27	33.53
3	*2437.00	104.7 PK			1.08 V	324	71.03	33.67
4	*2437.00	94.0 AV			1.08 V	324	60.33	33.67
5	2483.50	63.5 PK	74.0	-10.5	1.08 V	324	29.69	33.81
6	2483.50	42.3 AV	54.0	-11.7	1.08 V	324	8.49	33.81
7	4874.00	60.4 PK	74.0	-13.6	1.00 V	12	17.16	43.24
8	4874.00	47.1 AV	54.0	-6.9	1.00 V	12	3.86	43.24
9	7311.00	57.9 PK	74.0	-16.1	1.43 V	322	9.83	48.07
10	7311.00	44.8 AV	54.0	-9.2	1.43 V	322	-3.27	48.07

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.6 PK			1.02 H	144	71.86	33.74
2	*2462.00	94.3 AV			1.02 H	144	60.56	33.74
3	2483.50	73.6 PK	74.0	-0.4	1.02 H	144	39.79	33.81
4	2483.50	47.5 AV	54.0	-6.5	1.02 H	144	13.69	33.81
5	4924.00	47.6 PK	74.0	-26.4	1.05 H	228	4.33	43.27
6	4924.00	36.2 AV	54.0	-17.8	1.05 H	228	-7.07	43.27
7	7386.00	56.1 PK	74.0	-17.9	1.40 H	301	7.70	48.40
8	7386.00	42.4 AV	54.0	-11.6	1.40 H	301	-6.00	48.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.3 PK			1.03 V	325	64.56	33.74
2	*2462.00	87.5 AV			1.03 V	325	53.76	33.74
3	2483.50	61.4 PK	74.0	-12.6	1.03 V	325	27.59	33.81
4	2483.50	41.1 AV	54.0	-12.9	1.03 V	325	7.29	33.81
5	4924.00	48.6 PK	74.0	-25.4	1.00 V	86	5.33	43.27
6	4924.00	36.6 AV	54.0	-17.4	1.00 V	86	-6.67	43.27
7	7386.00	55.9 PK	74.0	-18.1	1.49 V	314	7.50	48.40
8	7386.00	42.6 AV	54.0	-11.4	1.49 V	314	-5.80	48.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.6 PK	74.0	-4.4	1.62 H	337	36.07	33.53
2	2390.00	52.6 AV	54.0	-1.4	1.62 H	337	19.07	33.53
3	*2422.00	100.1 PK			1.62 H	337	66.48	33.62
4	*2422.00	90.1 AV			1.62 H	337	56.48	33.62
5	4844.00	47.4 PK	74.0	-26.6	1.05 H	219	4.20	43.20
6	4844.00	36.1 AV	54.0	-17.9	1.05 H	219	-7.10	43.20
7	7266.00	55.6 PK	74.0	-18.4	1.41 H	288	7.69	47.91
8	7266.00	42.0 AV	54.0	-12.0	1.41 H	288	-5.91	47.91

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.7 PK	74.0	-9.3	1.07 V	325	31.17	33.53
2	2390.00	42.1 AV	54.0	-11.9	1.07 V	325	8.57	33.53
3	*2422.00	93.7 PK			1.07 V	325	60.08	33.62
4	*2422.00	83.0 AV			1.07 V	325	49.38	33.62
5	4844.00	48.7 PK	74.0	-25.3	1.06 V	82	5.50	43.20
6	4844.00	36.5 AV	54.0	-17.5	1.06 V	82	-6.70	43.20
7	7266.00	56.1 PK	74.0	-17.9	1.43 V	316	8.19	47.91
8	7266.00	42.8 AV	54.0	-11.2	1.43 V	316	-5.11	47.91

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.2 PK	74.0	-6.8	1.06 H	200	33.67	33.53
2	2390.00	48.5 AV	54.0	-5.5	1.06 H	200	14.97	33.53
3	*2437.00	108.1 PK			1.04 H	151	74.43	33.67
4	*2437.00	96.1 AV			1.04 H	151	62.43	33.67
5	2483.50	73.8 PK	74.0	-0.2	1.03 H	150	39.99	33.81
6	2483.50	52.2 AV	54.0	-1.8	1.03 H	150	18.39	33.81
7	4874.00	47.8 PK	74.0	-26.2	1.03 H	214	4.56	43.24
8	4874.00	36.4 AV	54.0	-17.6	1.03 H	214	-6.84	43.24
9	7311.00	56.4 PK	74.0	-17.6	1.39 H	305	8.33	48.07
10	7311.00	42.5 AV	54.0	-11.5	1.39 H	305	-5.57	48.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.0 PK	74.0	-16.0	1.06 V	326	24.47	33.53
2	2390.00	39.3 AV	54.0	-14.7	1.06 V	326	5.77	33.53
3	*2437.00	98.1 PK			1.06 V	326	64.43	33.67
4	*2437.00	87.5 AV			1.06 V	326	53.83	33.67
5	2483.50	63.6 PK	74.0	-10.4	1.06 V	326	29.79	33.81
6	2483.50	44.2 AV	54.0	-9.8	1.06 V	326	10.39	33.81
7	4874.00	49.1 PK	74.0	-24.9	1.03 V	88	5.86	43.24
8	4874.00	36.9 AV	54.0	-17.1	1.03 V	88	-6.34	43.24
9	7311.00	56.5 PK	74.0	-17.5	1.45 V	306	8.43	48.07
10	7311.00	43.0 AV	54.0	-11.0	1.45 V	306	-5.07	48.07

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.3 PK			1.00 H	181	68.59	33.71
2	*2452.00	91.1 AV			1.00 H	181	57.39	33.71
3	2483.50	71.3 PK	74.0	-2.7	1.00 H	181	37.49	33.81
4	2483.50	53.4 AV	54.0	-0.6	1.00 H	181	19.59	33.81
5	4904.00	47.0 PK	74.0	-27.0	1.05 H	231	3.73	43.27
6	4904.00	35.8 AV	54.0	-18.2	1.05 H	231	-7.47	43.27
7	7356.00	56.0 PK	74.0	-18.0	1.43 H	299	7.73	48.27
8	7356.00	42.5 AV	54.0	-11.5	1.43 H	299	-5.77	48.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	95.1 PK			1.04 V	325	61.39	33.71
2	*2452.00	84.2 AV			1.04 V	325	50.49	33.71
3	2483.50	70.0 PK	74.0	-4.0	1.04 V	325	36.19	33.81
4	2483.50	46.9 AV	54.0	-7.1	1.04 V	325	13.09	33.81
5	4904.00	48.5 PK	74.0	-25.5	1.00 V	93	5.23	43.27
6	4904.00	36.5 AV	54.0	-17.5	1.00 V	93	-6.77	43.27
7	7356.00	56.3 PK	74.0	-17.7	1.49 V	309	8.03	48.27
8	7356.00	42.8 AV	54.0	-11.2	1.49 V	309	-5.47	48.27

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	10.13	10.12	0.5	PASS
6	2437	10.15	10.16	0.5	PASS
11	2462	10.14	10.16	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	16.42	16.41	0.5	PASS
6	2437	16.42	16.43	0.5	PASS
11	2462	16.45	16.47	0.5	PASS

802.11n (HT20)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.66	17.57	0.5	PASS
6	2437	17.64	17.62	0.5	PASS
11	2462	17.68	17.64	0.5	PASS

802.11n (HT40)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
3	2422	36.52	36.51	0.5	PASS
6	2437	36.56	36.50	0.5	PASS
9	2452	36.53	36.50	0.5	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b / Chain 1 / CH1




802.11g / Chain 1 / CH1



802.11n (HT20) / Chain 1 / CH1



802.11n (HT40) / Chain 1 / CH9



4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT \leq 4;

Array Gain = 0 dB (i.e., no array gain) for channel widths \geq 40 MHz for any NANT;

Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT \geq 5.

For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter Anritsu	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor Anritsu	MA2411B	0738172	May 20, 2013	May 19, 2014

- Note:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. Tested date : Feb. 19, 2014

4.4.3 TEST PROCEDURES

The peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.




A D T

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



A D T

4.4.7 TEST RESULTS

802.11b

CHAN.	FREQUE NCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	21.47	22.16	304.718	24.84	30	PASS
6	2437	23.86	24.01	494.988	26.95	30	PASS
11	2462	22.01	21.75	308.479	24.89	30	PASS

802.11g

CHAN.	FREQUE NCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	24.61	25.21	620.962	27.93	30	PASS
6	2437	26.10	26.51	855.093	29.32	30	PASS
11	2462	23.61	24.03	482.545	26.84	30	PASS

802.11n (HT20)

CHAN.	FREQUE NCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	24.03	24.32	523.326	27.19	30	PASS
6	2437	26.37	26.41	871.033	29.40	30	PASS
11	2462	22.96	23.34	413.471	26.16	30	PASS

802.11n (HT40)

CHAN.	FREQUE NCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
3	2422	23.87	23.89	488.687	26.89	30	PASS
6	2437	25.01	25.11	641.297	28.07	30	PASS
9	2452	23.87	23.78	482.562	26.84	30	PASS



A D T

4.5 AVERAGE OUTPUT POWER

4.5.1 FOR REFERENCE.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor	MA2411B	0738172	May 20, 2013	May 19, 2014


Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014

4.5.3 TEST PROCEDURES

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS

Same as Item 4.3.6



A D T

4.5.6 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	19.21	19.96	182.451	22.61
6	2437	21.85	22.91	348.543	25.42
11	2462	19.96	20.36	207.726	23.17

802.11g

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	17.67	17.63	116.422	20.66
6	2437	23.74	24.53	520.384	27.16
11	2462	16.01	16.32	82.757	19.18

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	17.01	16.74	97.440	19.89
6	2437	23.69	24.01	485.652	26.86
11	2462	15.27	14.97	65.056	18.13

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
3	2422	16.27	16.01	82.266	19.15
6	2437	18.42	18.01	132.743	21.23
9	2452	16.67	15.96	85.898	19.34



A D T

4.6 POWER SPECTRAL DENSITY MEASUREMENT

4.6.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP 40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014


4.6.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6



A D T

4.6.7 TEST RESULTS

802.11b

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	1	2412	-4.39	3.01	-1.38	8	PASS
	6	2437	-2.30	3.01	0.71	8	PASS
	11	2462	-2.87	3.01	0.14	8	PASS
1	1	2412	-3.30	3.01	-0.29	8	PASS
	6	2437	-1.24	3.01	1.77	8	PASS
	11	2462	-4.01	3.01	-1.00	8	PASS

NOTE: Directional gain = $-3.91\text{dBi} + 10\log(2) = -0.9\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11g

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	1	2412	-6.13	3.01	-3.12	8	PASS
	6	2437	0.73	3.01	3.74	8	PASS
	11	2462	-7.00	3.01	-3.99	8	PASS
1	1	2412	-7.92	3.01	-4.91	8	PASS
	6	2437	0.10	3.01	3.11	8	PASS
	11	2462	-6.91	3.01	-3.90	8	PASS

NOTE: Directional gain = $-3.91\text{dBi} + 10\log(2) = -0.9\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11n (HT20)

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	1	2412	-6.07	3.01	-3.06	8	PASS
	6	2437	0.02	3.01	3.03	8	PASS
	11	2462	-6.13	3.01	-3.12	8	PASS
1	1	2412	-6.18	3.01	-3.17	8	PASS
	6	2437	-1.51	3.01	1.50	8	PASS
	11	2462	-10.92	3.01	-7.91	8	PASS

NOTE: Directional gain = $-3.91\text{dBi} + 10\log(2) = -0.9\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.



A D T

802.11n (HT40)

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	3	2422	-7.97	3.01	-4.96	8	PASS
	6	2437	-4.56	3.01	-1.55	8	PASS
	9	2452	-5.43	3.01	-2.42	8	PASS
1	3	2422	-11.97	3.01	-8.96	8	PASS
	6	2437	-6.55	3.01	-3.54	8	PASS
	9	2452	-7.26	3.01	-4.25	8	PASS


NOTE: 1. Directional gain = $-3.91\text{dBi} + 10\log(2) = -0.9\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b / Chain 1 / CH6




802.11g / Chain 0 / CH6



802.11n (HT20) / Chain 0 / CH6



802.11n (HT40) / Chain 0 / CH6



4.7 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP 40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014

4.7.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



4.7.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.7.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T



802.11b:

Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge







A D T



Chain 1 CH 1




CH 6




CH 11



CH 1 Band edge



CH 11 Band edge







A D T



802.11g:

Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge







A D T



Chain 1 CH 1




CH 6




CH 11



CH 1 Band edge



CH 11 Band edge







A D T



802.11n (HT20):

Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge







A D T



Chain 1 CH 1




CH 6




CH 11



CH 1 Band edge



CH 11 Band edge







A D T



802.11n (HT40):

Chain 0



CH 3




CH 6




CH 9



CH 3 Band edge





CH 9 Band edge







A D T



Chain 1 CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge





A D T

5. TEST TYPES AND RESULTS (FOR 5GHz, 5.725~5.850GHz Band)

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100287	Feb. 28, 2013	Feb. 27, 2014
Line-Impedance Stabilization Network (for EUT) ROHDE & SCHWARZ	NSLK-8127	5127-523	Oct. 02, 2013	Oct. 01, 2014
Line-Impedance Stabilization Network (for Peripheral) ROHDE & SCHWARZ	ENV216	100071	Nov. 13, 2013	Nov. 12, 2014
RF Cable (JYEBAO)	5DFB	COACAB-001	May 27, 2013	May 26, 2014
50 ohms Terminator	50	3	Oct. 17, 2013	Oct. 16, 2014
50 ohms Terminator	N/A	EMC-04	Oct. 17, 2013	Oct. 16, 2014
Software ADT	BV ADT_Cond_V7.3.7 .3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. Tested Date: Jan. 06, 2014

5.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.


NOTE:

1. The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.1.6 EUT OPERATING CONDITIONS

Same as the 4.1.6


5.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
--------------	----------	--------------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19747	0.06	48.01	46.23	48.07	46.29	63.72	53.72	-15.65	-7.43
2	0.26288	0.08	46.66	46.04	46.74	46.12	61.34	51.34	-14.60	-5.22
3	0.51328	0.11	45.94	43.23	46.05	43.34	56.00	46.00	-9.95	-2.66
4	2.73438	0.23	41.73	32.91	41.96	33.14	56.00	46.00	-14.04	-12.86
5	6.60938	0.39	47.68	46.24	48.07	46.63	60.00	50.00	-11.93	-3.37
6	11.46484	0.51	45.23	42.42	45.74	42.93	60.00	50.00	-14.26	-7.07

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
--------------	-------------	--------------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19687	0.05	48.72	46.51	48.77	46.56	63.74	53.74	-14.97	-7.18
2	0.52109	0.12	46.67	43.11	46.79	43.23	56.00	46.00	-9.21	-2.77
3	0.90781	0.14	41.94	38.18	42.08	38.32	56.00	46.00	-13.92	-7.68
4	2.71094	0.20	41.46	32.34	41.66	32.54	56.00	46.00	-14.34	-13.46
5	6.60366	0.34	47.43	46.36	47.77	46.70	60.00	50.00	-12.23	-3.30
6	11.89462	0.51	46.22	44.05	46.73	44.56	60.00	50.00	-13.27	-5.44

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T

5.2 RADIATED AND BANDEGE EMISSION MEASUREMENT

5.2.1 LIMITS OF RADIATED AND BANDEGE EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

5.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 16, 2013	Jan. 15, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Mar. 25, 2013	Mar. 24, 2014
RF Cable	NA	CHHCAB_001	Oct. 06, 2013	Oct. 05, 2014
Spectrum Analyzer R&S	FSV40	100964	July 15, 2013	July 14, 2014
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 27, 2012	Nov. 26, 2013
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 29, 2013	Oct. 28, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: Nov. 07, 2013

5.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

5.2.4 DEVIATION FROM TEST STANDARD


No deviation

5.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.2.6 EUT OPERATING CONDITIONS

Same as the 4.1.6

5.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11a

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	87.81	35.5 QP	40.0	-4.5	2.00 H	244	54.11	-18.61
2	226.57	31.8 QP	46.0	-14.2	1.00 H	282	47.22	-15.39
3	500.01	42.1 QP	46.0	-3.9	1.55 H	178	49.19	-7.06
4	700.03	37.2 QP	46.0	-8.8	1.00 H	301	40.54	-3.32
5	899.99	36.1 QP	46.0	-10.0	1.00 H	247	35.61	0.44
6	1000.00	39.0 QP	54.0	-15.0	1.00 H	211	37.09	1.94

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	73.81	38.8 QP	40.0	-1.2	1.00 V	114	54.83	-16.03
2	500.01	40.8 QP	46.0	-5.2	1.00 V	221	47.89	-7.06
3	600.02	43.4 QP	46.0	-2.6	1.00 V	244	48.23	-4.80
4	700.03	37.2 QP	46.0	-8.8	1.00 V	255	40.52	-3.32
5	799.99	36.7 QP	46.0	-9.3	1.00 V	243	37.84	-1.13
6	899.99	38.5 QP	46.0	-7.5	1.50 V	106	38.07	0.44

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

TX_High

ABOVE 1GHz DATA

802.11a

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	113.9 PK			1.25 H	264	69.42	44.48
2	*5745.00	104.1 AV			1.25 H	264	59.62	44.48
3	11490.00	63.8 PK	74.0	-10.2	1.33 H	205	12.18	51.62
4	11490.00	50.0 AV	54.0	-4.0	1.33 H	205	-1.62	51.62

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	107.8 PK			1.85 V	244	63.32	44.48
2	*5745.00	97.8 AV			1.85 V	244	53.32	44.48
3	11490.00	65.8 PK	74.0	-8.2	1.35 V	127	14.18	51.62
4	11490.00	53.7 AV	54.0	-0.3	1.35 V	127	2.08	51.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * " : Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.0 PK			1.23 H	78	74.48	44.52
2	*5785.00	109.2 AV			1.23 H	78	64.68	44.52
3	11570.00	63.0 PK	74.0	-11.0	1.33 H	202	11.51	51.49
4	11570.00	50.2 AV	54.0	-3.8	1.33 H	202	-1.29	51.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	112.8 PK			1.54 V	144	68.28	44.52
2	*5785.00	102.5 AV			1.54 V	144	57.98	44.52
3	11570.00	66.7 PK	74.0	-7.3	1.33 V	131	15.21	51.49
4	11570.00	53.8 AV	54.0	-0.2	1.33 V	131	2.31	51.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	118.4 PK			1.27 H	73	73.81	44.59
2	*5825.00	108.8 AV			1.27 H	73	64.21	44.59
3	11650.00	62.9 PK	74.0	-11.1	1.33 H	200	11.49	51.41
4	11650.00	50.2 AV	54.0	-3.8	1.33 H	200	-1.21	51.41

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	112.5 PK			1.50 V	129	67.91	44.59
2	*5825.00	102.1 AV			1.50 V	129	57.51	44.59
3	11650.00	66.1 PK	74.0	-7.9	1.32 V	130	14.69	51.41
4	11650.00	53.2 AV	54.0	-0.8	1.32 V	130	1.79	51.41

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

802.11n (HT20)

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	110.4 PK			1.24 H	77	65.92	44.48
2	*5745.00	99.0 AV			1.24 H	77	54.52	44.48
3	11490.00	64.9 PK	74.0	-9.1	1.36 H	184	13.28	51.62
4	11490.00	50.8 AV	54.0	-3.2	1.36 H	184	-0.82	51.62

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	103.3 PK			1.88 V	319	58.82	44.48
2	*5745.00	93.9 AV			1.88 V	319	49.42	44.48
3	11490.00	68.0 PK	74.0	-6.0	1.35 V	127	16.38	51.62
4	11490.00	53.8 AV	54.0	-0.2	1.35 V	127	2.18	51.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	108.8 PK			1.50 H	17	64.28	44.52
2	*5785.00	99.0 AV			1.50 H	17	54.48	44.52
3	11570.00	64.6 PK	74.0	-9.4	1.37 H	190	13.11	51.49
4	11570.00	50.7 AV	54.0	-3.3	1.37 H	190	-0.79	51.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	104.4 PK			2.00 V	318	59.88	44.52
2	*5785.00	95.4 AV			2.00 V	318	50.88	44.52
3	11570.00	67.5 PK	74.0	-6.5	1.33 V	129	16.01	51.49
4	11570.00	53.7 AV	54.0	-0.3	1.33 V	129	2.21	51.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	108.9 PK			1.68 H	199	64.31	44.59
2	*5825.00	100.1 AV			1.68 H	199	55.51	44.59
3	11650.00	64.7 PK	74.0	-9.3	1.35 H	204	13.29	51.41
4	11650.00	51.1 AV	54.0	-2.9	1.35 H	204	-0.31	51.41

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	105.7 PK			2.00 V	143	61.11	44.59
2	*5825.00	95.6 AV			2.00 V	143	51.01	44.59
3	11650.00	67.5 PK	74.0	-6.5	1.34 V	129	16.09	51.41
4	11650.00	53.9 AV	54.0	-0.1	1.34 V	129	2.49	51.41

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

802.11n (HT40)

CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	107.1 PK			1.00 H	86	62.61	44.49
2	*5755.00	96.4 AV			1.00 H	86	51.91	44.49
3	11510.00	62.5 PK	74.0	-11.5	1.34 H	205	10.89	51.61
4	11510.00	50.5 AV	54.0	-3.5	1.34 H	205	-1.11	51.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	100.9 PK			1.00 V	214	56.41	44.49
2	*5755.00	91.1 AV			1.00 V	214	46.61	44.49
3	11510.00	66.4 PK	74.0	-7.6	1.34 V	234	14.79	51.61
4	11510.00	53.7 AV	54.0	-0.3	1.34 V	234	2.09	51.61

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	114.5 PK			1.51 H	259	69.96	44.54
2	*5795.00	104.2 AV			1.51 H	259	59.66	44.54
3	11590.00	63.9 PK	74.0	-10.1	1.35 H	201	12.46	51.44
4	11590.00	50.6 AV	54.0	-3.4	1.35 H	201	-0.84	51.44

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	108.7 PK			1.83 V	245	64.16	44.54
2	*5795.00	98.4 AV			1.83 V	245	53.86	44.54
3	11590.00	65.7 PK	74.0	-8.3	1.32 V	237	14.26	51.44
4	11590.00	53.8 AV	54.0	-0.2	1.32 V	237	2.36	51.44

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014


5.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

5.3.4 DEVIATION FROM TEST STANDARD

No deviation

5.3.5 TEST SETUP





A D T

5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

5.3.7 TEST RESULTS

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
149	5745	16.06	16.32	0.5	PASS
157	5785	16.11	16.34	0.5	PASS
165	5825	16.15	16.33	0.5	PASS

802.11n (HT20)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
149	5745	16.12	16.34	0.5	PASS
157	5785	17.10	16.10	0.5	PASS
165	5825	17.31	16.74	0.5	PASS


802.11n (HT40)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
151	5755	36.01	35.88	0.5	PASS
159	5795	35.86	35.84	0.5	PASS



A D T

SPECTRUM PLOT OF WORST VALUE



5.4 CONDUCTED OUTPUT POWER MEASUREMENT

5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 5725 –5850 MHz band: 1 Watt (20dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT \leq 4;

Array Gain = 0 dB (i.e., no array gain) for channel widths \geq 40 MHz for any NANT;

Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT \geq 5.

For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

5.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power meter Anritsu	ML2495A	0824006	May 20, 2013	May 19, 2014
Power sensor Anritsu	MA2411B	0738172	May 20, 2013	May 19, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Feb. 19, 2014


5.4.3 TEST PROCEDURES

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation.

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

Same as Item 5.3.6



A D T

5.4.7 TEST RESULTS

802.11a

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
149	5745	20.70	20.80	237.716	23.76	30	PASS
157	5785	20.40	20.50	221.850	23.46	30	PASS
165	5825	20.10	20.20	207.042	23.16	30	PASS

802.11n (HT20)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
149	5745	20.70	20.80	237.716	23.76	30	PASS
157	5785	20.58	20.56	228.051	23.58	30	PASS
165	5825	20.30	20.36	215.795	23.34	30	PASS

802.11n (HT40)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
151	5755	20.70	20.70	234.980	23.71	30	PASS
159	5795	20.50	20.50	224.404	23.51	30	PASS



A D T

5.5 AVERAGE OUTPUT POWER

5.5.1 FOR REFERENCE.

5.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor	MA2411B	0738172	May 20, 2013	May 19, 2014


Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014

5.5.3 TEST PROCEDURES

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

5.5.4 TEST SETUP



5.5.5 EUT OPERATING CONDITIONS

Same as Item 5.3.6



A D T

5.5.6 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
149	5745	17.90	18.80	137.518	21.38
157	5785	17.50	18.60	128.678	21.10
165	5825	16.86	17.40	103.483	20.15

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
149	5745	18.50	19.67	163.478	22.13
157	5785	18.40	19.00	148.616	21.72
165	5825	18.00	18.60	135.540	21.32

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
151	5755	19.26	19.70	177.658	22.50
159	5795	19.10	19.65	173.540	22.39

5.6 POWER SPECTRAL DENSITY MEASUREMENT

5.6.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP 40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014


5.6.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6



A D T

5.6.7 TEST RESULTS

802.11a

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	149	5745	-5.13	3.01	-2.12	7.84	PASS
	157	5785	-7.44	3.01	-4.43	7.84	PASS
	165	5825	-8.62	3.01	-5.61	7.84	PASS
1	149	5745	-6.14	3.01	-3.13	7.84	PASS
	157	5785	-5.25	3.01	-2.24	7.84	PASS
	165	5825	-8.03	3.01	-5.02	7.84	PASS

NOTE: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.16\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.16-6) = 7.84\text{dBm}$.

802.11n (HT20)

TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	149	5745	-4.58	3.01	-1.57	7.84	PASS
	157	5785	-6.57	3.01	-3.56	7.84	PASS
	165	5825	-6.03	3.01	-3.02	7.84	PASS
1	149	5745	-5.14	3.01	-2.13	7.84	PASS
	157	5785	-4.38	3.01	-1.37	7.84	PASS
	165	5825	-5.64	3.01	-2.63	7.84	PASS

NOTE: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.16\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.16-6) = 7.84\text{dBm}$.

802.11n (HT40)


TX CHAIN	CHANNEL	FREQUENCY (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	151	5755	-8.26	3.01	-5.25	7.84	PASS
	159	5795	-6.45	3.01	-3.44	7.84	PASS
1	151	5755	-6.85	3.01	-3.84	7.84	PASS
	159	5795	-7.25	3.01	-4.24	7.84	PASS

NOTE: 1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.16\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.16-6) = 7.84\text{dBm}$.



A D T

SPECTRUM PLOT OF WORST VALUE





A D T

5.7 CONDUCTED OUT-BAND EMISSION MEASUREMENT

5.7.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP 40	100036	Jan. 21, 2014	Jan. 20, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Jan. 21, 2014

5.7.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

5.7.4 DEVIATION FROM TEST STANDARD

No deviation

5.7.5 TEST SETUP



5.7.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.7.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

802.11a:



Chain 0 CH 149




CH 157




CH 165



CH 149 Band edge





CH 165 Band edge







A D T



Chain 1 CH 149




CH 157




CH 165



CH 149 Band edge



CH 165 Band edge







A D T



802.11n (HT20):

Chain 0



CH 149




CH 157




CH 165



CH 149 Band edge





CH 165 Band edge







A D T



Chain 1 CH 149




CH 157




CH 165



CH 149 Band edge



CH 165 Band edge







A D T



802.11n (HT40):

Chain 0


CH 151




CH 159



CH 151 Band edge





CH 159 Band edge







A D T


Chain 1 CH 151




CH 159



CH 151 Band edge



CH 159 Band edge





A D T

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---