Model: MAX BR1 Mini Core LTEA

Product Code:MAX-BR1-MINI-LTEA-W-T-M Serial No.:2932-32CA-6D27 LAN MAC:00-1A-DD-EF-1C-40 PEPWAVE

Default Access https://192.168.50.1	Username: admin Password: admin		
Input : 12V - 48V - , 12W max (Terminal Block) Input : 802.3AF (LAN2/WAN) Input : 12V - 48V -, 12W max (DC Jack)			

FCC ID: U8G-P1930LITER6M Contains FCC ID: N7NMC7455 Contains IC: 2417C-MC7455 CAN ICES-003(A)/NMB-003(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model: MAX BR1 Mini Core

Product Code:MAX-BR1-MINI-LTE-US-T-M Serial No.:2932-32CA-6D27 LAN MAC:00-1A-DD-EF-1C-40



Default Access https://192.168.50.1	Username: admin Password: admin		
Input : 12V - 48V - , 12W max (Terminal Block Input : 802.3AF (LAN2/WAN) Input : 12V - 48V -, 12W max (DC Jack)			

FCC ID: U8G-P1930LITER6M Contains FCC ID: RI7LE910CXNF Contains IC: 5131A-LE910CXNF CAN ICES-003(A)/NMB-003(A)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Label location

