

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Email: ee.shenzhen@sgs.com

Page: 1 of 186

Report No.: HKES150900180701

2.4G WIFI FCC REPORT

Application No: HKES1509001807PS

Applicant: Pismo Labs Technology Limited

Product Name: Pepwave/Peplink/Pismo Wireless Product

Model No.(EUT): Surf SOHO

Add Model No.: Surf SOHO LTE, MAX, Surf Pro, AP Pro, Device Connector, Express,

Balance, Pismo 734, CarFi, Flex AP, Pismo 934

FCC ID: U8G-P1934S

Standards: 47 CFR Part 15, Subpart C (2014)

 Date of Receipt:
 2015-09-30

 Date of Test:
 2015-10-03

 Date of Issue:
 2015-10-09

Test Result: PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Report No.: HKES150900180701

Page: 2 of 186

2 Version

Revision Record							
Version Chapter Date Modifier Remark							
00		2015-10-09		Original			

Authorized for issue by:		
Tested By	Brix Chen	2015-10-03
	(Bill Chen) /Project Engineer	Date
Prepared By	Dovis Chen	2015-10-09
	(Doris Chen) /Clerk	Date
Checked By	Sen. Lu.	2015-10-09
	(Sen Lv) /Reviewer	Date



Report No.: HKES150900180701

Page: 3 of 186

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10: 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10: 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10: 2013 KDB662911 D01Multiple Transmitter Output v02r01	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10: 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10: 2013 KDB662911 D01Multiple Transmitter Output v02r01	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10: 2013 KDB662911 D01Multiple Transmitter Output v02r01	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10: 2013 KDB662911 D01Multiple Transmitter Output v02r01	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10: 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

Remark:

Model No.: Surf SOHO, Surf SOHO LTE, MAX, Surf Pro, AP Pro, Device Connector, Express, Balance, Pismo 734, CarFi, Flex AP, Pismo 934

Only the Model Surf SOHO was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only the item number is different.



Report No.: HKES150900180701

Page: 4 of 186

4 Contents

			Page
1	COV	ER PAGE	1
2	VER	SION	2
3	TES	T SUMMARY	3
4	CON	TENTS	4
5		ERAL INFORMATION	
Э	GEN		
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT AND MODE	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TES	T RESULTS AND MEASUREMENT DATA	12
	6.1	ANTENNA REQUIREMENT	12
	6.2	CONDUCTED EMISSIONS	
	6.3	CONDUCTED PEAK OUTPUT POWER	
	6.4	6DB Occupy Bandwidth	
	6.5	Power Spectral Density	
	6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS.	
	6.7	RF CONDUCTED SPURIOUS EMISSIONS	
	6.8	RADIATED SPURIOUS EMISSIONS.	
	6.8.1		_
	6.8.2		
	6.9	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PHO	TOGRAPHS - EUT TEST SETUP	
	7.1	RADIATED EMISSION	
	7.2	RADIATED SPURIOUS EMISSION	186
	7.3	CONDUCTED EMISSION	186
8	PHO	TOGRAPHS - EUT CONSTRUCTIONAL DETAILS	186



Report No.: HKES150900180701

Page: 5 of 186

5 General Information

5.1 Client Information

Applicant:	Pismo Labs Technology Limited				
Address of Applicant:	Unit A5, 5/F, HK Spinners Ind. Bldg., Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong				

5.2 General Description of EUT

Product Name:	Pepwave/Peplink/Pismo Wireless Product				
Model No.:	Surf SOHO				
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz				
	IEEE 802.11n(H	T40): 2422MHz to 2452MHz			
Channel Numbers:	IEEE 802.11b/g,	, IEEE 802.11n HT20: 11 Channels			
	IEEE 802.11n H	T40: 7 Channels			
Channel Separation:	5MHz				
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)				
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)				
	IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM,				
	QPSK,BPSK)				
Sample Type:	Fixed production	١			
Antenna Type:	PIFA				
Antenna Gain:	2.15dBi				
Power Supply:	Adapter: Input: AC 100V-240V 50-60Hz 600mA				
	Output: DC 12V 2000mA				
	Output cable: 146cm (Unshielded with a ferrite core)				



Report No.: HKES150900180701

Page: 6 of 186

Operation Frequency each of channel(802.11b/g/n HT20)										
Channel	Fr	equency	Channe	Frequency	Channel	Fre	quency	Char	nnel	Frequency
1	24	112MHz	4	2427MHz	7	244	12MHz	10)	2457MHz
2	24	417MHz	5	2432MHz	8	244	17MHz	11	1	2462MHz
3	24	122MHz	6	2437MHz	9	245	2452MHz			
Operation F	requ	ency each	of channe	el(802.11n HT40)					
Channel Frequency				Channel	Frequen	су	Chan	nel	F	Frequency
1		2422	ИНz	4	2437MF	lHz 7				2452MHz
2	·	2427	MHz	5	2442MF	lz				
3		2432	ИНz	6	2447MH	lz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

, ,	
Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz



Report No.: HKES150900180701

Page: 7 of 186

5.3 Test Environment and Mode

Operating Environment:	Operating Environment:						
Temperature:	25.0 °C						
Humidity:	52 % RH						
Atmospheric Pressure:	1010mbar						
Test mode:							
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all						
	kind of data rate.						

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: HKES150900180701

Page: 8 of 186

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

· A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCC

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: HKES150900180701

Page: 9 of 186

5.10Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2014-10-24	2015-10-24			
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T8-02	SEL0162	2015-08-30	2016-08-30			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T4-02	SEL0163	2015-08-30	2016-08-30			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T2-02	SEL0164	2015-08-30	2016-08-30			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13			
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13			
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24			
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24			
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			



Report No.: HKES150900180701

Page: 10 of 186

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory	Cal. date	Cal.Due date
	3m			No.	(yyyy-mm-dd)	(yyyy-mm-dd)
1	Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2015-11-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13



Report No.: HKES150900180701

Page: 11 of 186

RF connected test							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)	
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24	
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2014-10-24	2015-10-24	
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24	2015-10-24	
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13	
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13	
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13	
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25	
8	Band filter	amideon	82346	SEL0094	2015-05-13	2016-05-13	
9	POWER METER	R&S	NRVS	SEL0144	2014-10-24	2015-10-24	
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25	
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24	2015-10-24	



Report No.: HKES150900180701

Page: 12 of 186

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard 47 CFR Part 15C Section 15.203 /247(c) requirement:


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.15dBi.



Report No.: HKES150900180701

Page: 13 of 186


6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	150kHz to 30MHz					
Limit:	Limit (dBuV)					
	Frequency range (MHz)	Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	5-30	60	50			
	* Decreases with the logarithm	n of the frequency.	-			
Test Procedure:	 The mains terminal disturbance voltage test was conducted in a shielded room. The EUT was connected to AC power source through a LISN 1 (Line 					
	Impedance Stabilization Network) which provides a $50\Omega/50\mu H + 5\Omega$ linear					
	impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference					
	plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables a					
	single LISN provided the road. 3) The tabletop EUT was place ground reference plane. was	c table 0.8m above to arrangement, the E				
	placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference of the EUT shall be 0.4 m from the vertical ground vertical ground reference plane was bonded to the reference plane. The LISN 1 was placed 0.8 m from unit under test and bonded to a ground reference plane. This between the closest points of the LISN 1 and the Extreme the EUT and associated equipment was at least 0.8 in order to find the maximum emission, the relative equipment and all of the interface cables must be a ANSI C63.10: 2013 on conducted measurement.					



Report No.: HKES150900180701

Page: 14 of 186





Report No.: HKES150900180701


Page: 15 of 186

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:



Site : Shielding Room

Condition : 47 CFR PART15C AV CE LINE

Job.No : 1807PS Test Mode : TX


	Freq		LISN Factor				Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @ 2 @ 3 @ 4 @	0.16155 0.19758 0.39553 0.46122	0.01	9.82 9.83 9.85 9.86	37.04 31.70	46.89 41.56	53.71 47.95	-6.82 -6.38	Peak Peak
5 @ 6 @	2.636 5.005	0.02		27.20 28.54				



Report No.: HKES150900180701

Page: 16 of 186

Neutral Line:



Site : Shielding Room

Condition : 47 CFR PART15C AV CE NEUTRAL

Job.No : 1807PS Test Mode : TX

		Freq		LISN Factor				Over Limit	Remark
		MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	@	0.16677	0.02	9.81	41.69	51.52	55.12	-3.60	Peak
2	@	0.20075	0.02	9.85	39.25	49.12	53.58	-4.46	Peak
3	@	0.22918	0.02	9.85	34.89	44.76	52.48	-7.72	Peak
4	@	0.39553	0.01	9.87	33.03	42.91	47.95	-5.04	Peak
5	@	1.269	0.02	10.05	27.34	37.41	46.00	-8.59	Peak
6	@	5.005	0.01	10.13	28.08	38.22	50.00	-11.78	Peak

Notes:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: HKES150900180701

Page: 17 of 186

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)					
Test Method:	ANSI C63.10 2013					
	KDB662911 D01Multiple Transmitter Output v02r01					
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table					
	Ground Reference Plane					
	Remark:					
	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.					
Test Instruments:	Refer to section 5.10 for details.					
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates					
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).					
Limit:	30dBm					
Test Results:	Pass					



Report No.: HKES150900180701

Page: 18 of 186

Pre-scan under all rate at the lowest channel of antenna1								
Mode		802	.11b					
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	20.43	20.41	20.39	20.40				
Mode				802	2.11g			
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	23.44	22.95	22.98	22.90	22.91	23.22	23.21	23.00
Mode				802.11	n(HT20)			
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	25.24	25.10	25.21	25.14	25.10	25.09	25.10	25.20
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power (dBm)	25.50	25.11	25.15	25.13	25.10	25.23	25.10	25.19

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).



Report No.: HKES150900180701

Page: 19 of 186

Measurement Data

surement Data						
		802.11	b mode		,	
Test channel	Peak C	output Power (dBm)	Limit (dBm)	Result	
	Antenna	1 Ar	ntenna 2			
Lowest	19.99		19.70	30.00	Pass	
Middle	19.17		18.07	30.00	Pass	
Highest	20.43		16.89	30.00	Pass	
		802.11	g mode			
Test channel	Peak C	output Power (dBm)	Limit (dBm)	Result	
	Antenna	1 Ar	ntenna 2			
Lowest	23.44		22.74	30.00	Pass	
Middle	21.84		22.16	30.00	Pass	
Highest	21.86		21.37	30.00	Pass	
		802.11n(l	HT20)mode			
Test channel	Peak C	utput Power (dBm)	Limit (dBm)	Result	
	Antenna 1	Antenna 2	Total			
Lowest	22.24	22.22	25.24	30.00	Pass	
Middle	21.24	21.83	24.56	30.00	Pass	
Highest	21.57	21.17	24.38	30.00	Pass	
802.11n(HT40)mode						
Test channel	Peak C	Peak Output Power (Limit (dBm)	Result	
	Antenna 1	Antenna 2	Total			
Lowest	22.61	22.05	25.35	30.00	Pass	
Middle	22.82	22.14	25.50	30.00	Pass	
Highest	22.20	22.35	25.29	30.00	Pass	




Report No.: HKES150900180701

Page: 20 of 186

Test plot as follows:

Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode: 802.11b Test channel: Middle








Report No.: HKES150900180701

Page: 21 of 186

Test mode: 802.11b Test channel: Highest










Report No.: HKES150900180701

Page: 22 of 186

Test mode: 802.11g Test channel: Middle











Report No.: HKES150900180701

Page: 23 of 186

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode: 802.11n(HT20) Test channel: Middle






Report No.: HKES150900180701

Page: 24 of 186

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES150900180701

Page: 25 of 186

Test mode: 802.11n(HT40) Test channel: Middle



Test mode: 802.11n(HT40) Test channel: Highest






Report No.: HKES150900180701


Page: 26 of 186

Antenna 2

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Middle







Report No.: HKES150900180701

Page: 27 of 186

Test mode: 802.11b Test channel: Highest










Report No.: HKES150900180701

Page: 28 of 186

Test mode: 802.11g Test channel: Middle



Test mode: 802.11g Test channel: Highest







Report No.: HKES150900180701

Page: 29 of 186

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode: 802.11n(HT20) Test channel: Middle







Report No.: HKES150900180701

Page: 30 of 186

Test mode: 802.11n(HT20) Test channel: Highest



Test mode:	802.11n(HT40)	Tost channel:	Lowest
TEST HIDGE.	002.1111(11140)	l est channel:	Lowest









Report No.: HKES150900180701

Page: 31 of 186

Test mode: 802.11n(HT40) Test channel: Middle



Test mode: 802.11n(HT40) Test channel: Highest






Report No.: HKES150900180701

Page: 32 of 186

6.4 6dB Occupy Bandwidth





Report No.: HKES150900180701

Page: 33 of 186

Measurement Data

Antenna 1

	Antenna						
802.11b mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	10.11	≥500	Pass				
Middle	10.14	≥500	Pass				
Highest	9.09	≥500	Pass				
	802.11g mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	16.50	≥500	Pass				
Middle	16.65	≥500	Pass				
Highest	14.25	≥500	Pass				
	802.11n(HT20) mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	17.76	≥500	Pass				
Middle	17.88	≥500	Pass				
Highest	14.85	≥500	Pass				
802.11n(HT40)mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	36.54	≥500	Pass				
Middle	36.60	≥500	Pass				
Highest	34.20	≥500	Pass				



Report No.: HKES150900180701

Page: 34 of 186

Antenna 2

802.11b mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	10.11	≥500	Pass			
Middle	10.17	≥500	Pass			
Highest	10.62	≥500	Pass			
	802.11g mode					
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	16.50	≥500	Pass			
Middle	16.56	≥500	Pass			
Highest	15.87	≥500	Pass			
	802.11n(HT20) mode					
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	17.76	≥500	Pass			
Middle	17.82	≥500	Pass			
Highest	15.60	≥500	Pass			
802.11n(HT40)mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	36.60	≥500	Pass			
Middle	36.60	≥500	Pass			
Highest	32.04	≥500	Pass			




Report No.: HKES150900180701


Page: 35 of 186


Test plot as follows:

Antenna 1

Test mode: 80	802.11b	Test channel:	Lowest
---------------	---------	---------------	--------











Report No.: HKES150900180701

Page: 36 of 186

Test mode: 802.11b Test channel: Highest











Report No.: HKES150900180701

Page: 37 of 186

Test mode: 802.11g Test channel: Middle












Report No.: HKES150900180701

Page: 38 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 39 of 186

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES150900180701

Page: 40 of 186

Test mode: 802.11n(HT40) Test channel: Middle



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------









Report No.: HKES150900180701


Page: 41 of 186

Antenna 2

Test mode: 802.11b Test channel: Lowest











Report No.: HKES150900180701

Page: 42 of 186

Test mode: 802.11b Test channel: Highest











Report No.: HKES150900180701

Page: 43 of 186

Test mode: 802.11g Test channel: Middle











Report No.: HKES150900180701

Page: 44 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 45 of 186

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES150900180701

Page: 46 of 186

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: HKES150900180701

Page: 47 of 186

6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)		
Test Method:	ANSI C63.10 2013		
	KDB662911 D01Multiple Transmitter Output v02r01		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Test Instruments:	Refer to section 5.10 for details.		
Exploratory Test Mode:			
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).		
Limit:	≤8.00dBm/3kHz		
Test Results:	Pass		



Report No.: HKES150900180701

Page: 48 of 186

Measurement Data

easurement Data		802.	11b mode		
Test channel	Power Spec	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna	1 Ar	ntenna 2		
Lowest	-6.73		-7.57	≤8.00	Pass
Middle	-8.51		-8.53	≤8.00	Pass
Highest	-5.92		-9.72	≤8.00	Pass
		802.	11g mode		
Test channel	Power Spec	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna	ntenna 1 Antenna 2			
Lowest	-11.49		-11.83	≤8.00	Pass
Middle	-11.88	-11.88 -12.43		≤8.00	Pass
Highest	-10.59		-12.07	≤8.00	Pass
		802.11n	(HT20) mode		
Test channel	Power Spec	ctral Density	(dBm/3kHz)	Limit (dBm/3kHz)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-10.43	-8.57	-6.39	≤8.00	Pass
Middle	-12.58	-11.85	-9.19	≤8.00	Pass
Highest	-11.77	-10.59	-8.13	≤8.00	Pass
		802.11n	(HT40) mode		
Test channel	Power Spec	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-14.22	-14.59	-11.39	≤8.00	Pass
Middle	-12.76	-12.48	-9.61	≤8.00	Pass
Highest	-12.91	-12.73	-9.81	≤8.00	Pass




Report No.: HKES150900180701

Page: 49 of 186


Test plot as follows:

Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------











Report No.: HKES150900180701

Page: 50 of 186

Test mode: 802.11b Test channel: Highest



Test mode: 802.11g Test channel: Lowest







Report No.: HKES150900180701

Page: 51 of 186

Test mode: 802.11g Test channel: Middle











Report No.: HKES150900180701

Page: 52 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 53 of 186

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES150900180701

Page: 54 of 186

Test mode: 802.11n(HT40) Test channel: Middle











Report No.: HKES150900180701

Page: 55 of 186

Antenna 2











Report No.: HKES150900180701

Page: 56 of 186

Test mode: 802.11b Test channel: Highest











Report No.: HKES150900180701

Page: 57 of 186

Test mode: 802.11g Test channel: Middle











Report No.: HKES150900180701

Page: 58 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 59 of 186

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES150900180701

Page: 60 of 186

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: HKES150900180701

Page: 61 of 186

6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)		
Test Method:	ANSI C63.10 2013		
	KDB662911 D01Multiple Transmitter Output v02r01		
Test Setup:	Spectrum Analyzer Non-Conducted Table Ground Reference Plane Remark:		
Exploratory Test Mode:	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer. Transmitting with all kind of modulations, data rates		
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)		
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Instruments Used:	Refer to section 5.10 for details.		
Test Results:	Pass		
	Noted: According to KDB662911 D01Multiple Transmitter Output v02r01, section E) 3) a)(iii), Final value = Measure value + 10 log(Nant). Where (Nant) is the number of output		




Report No.: HKES150900180701

Page: 62 of 186


Test plot as follows:

Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------











Report No.: HKES150900180701

Page: 63 of 186

Test mode: 802.11g Test channel: Lowest











Report No.: HKES150900180701

Page: 64 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 65 of 186

Test mode: 802.11n(HT40) Test channel: Lowest










Report No.: HKES150900180701


Page: 66 of 186

Antenna 2













Report No.: HKES150900180701

Page: 67 of 186

Test mode: 802.11g Test channel: Lowest











Report No.: HKES150900180701

Page: 68 of 186

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES150900180701

Page: 69 of 186

Test mode: 802.11n(HT40) Test channel: Lowest









Report No.: HKES150900180701

Page: 70 of 186

6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)		
Test Method:	ANSI C63.10 2013		
	KDB662911 D01Multiple Transmitter Output v02r01		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates		
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).		
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread		
	spectrum intentional radiator is operating, the radio frequency power that is		
	produced by the intentional radiator shall be at least 20 dB below that in the		
	100 kHz bandwidth within the band that contains the highest level of the		
	desired power, based on either an RF conducted or a radiated measurement.		
Instruments Used:	Refer to section 5.10 for details.		
Test Results:	Pass		
	Noted: According to KDB662911 D01Multiple Transmitter Output v02r01, section E) 3) a)(iii), Final value = Measure value + 10 log(N _{ANT}).		
	Where (Nant) is the number of output		




Report No.: HKES150900180701

Page: 71 of 186

Test plot as follows: Antenna 1


Test mode: 802.11b Test channel: Lowest





Report No.: HKES150900180701


Page: 72 of 186





Report No.: HKES150900180701

Page: 73 of 186






Report No.: HKES150900180701

Page: 74 of 186








Report No.: HKES150900180701


Page: 75 of 186





Report No.: HKES150900180701

Page: 76 of 186






Report No.: HKES150900180701

Page: 77 of 186








Report No.: HKES150900180701


Page: 78 of 186





Report No.: HKES150900180701

Page: 79 of 186






Report No.: HKES150900180701

Page: 80 of 186






"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701


Page: 81 of 186





Report No.: HKES150900180701

Page: 82 of 186






Report No.: HKES150900180701

Page: 83 of 186








Report No.: HKES150900180701


Page: 84 of 186





Report No.: HKES150900180701

Page: 85 of 186






Report No.: HKES150900180701

Page: 86 of 186








Report No.: HKES150900180701


Page: 87 of 186





Report No.: HKES150900180701

Page: 88 of 186






Report No.: HKES150900180701

Page: 89 of 186






"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701

Page: 90 of 186




"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701

Page: 91 of 186






Report No.: HKES150900180701

Page: 92 of 186








Report No.: HKES150900180701


Page: 93 of 186





Report No.: HKES150900180701

Page: 94 of 186






Report No.: HKES150900180701

Page: 95 of 186








Report No.: HKES150900180701


Page: 96 of 186





Report No.: HKES150900180701

Page: 97 of 186






Report No.: HKES150900180701

Page: 98 of 186








Report No.: HKES150900180701


Page: 99 of 186





Report No.: HKES150900180701

Page: 100 of 186






"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701


Page: 101 of 186





Report No.: HKES150900180701


Page: 102 of 186





Report No.: HKES150900180701

Page: 103 of 186






Report No.: HKES150900180701

Page: 104 of 186








Report No.: HKES150900180701


Page: 105 of 186





Report No.: HKES150900180701

Page: 106 of 186






Report No.: HKES150900180701

Page: 107 of 186

Antenna 2


Test mode: 802.11b Test channel: Lowest





Report No.: HKES150900180701


Page: 108 of 186





Report No.: HKES150900180701

Page: 109 of 186






Report No.: HKES150900180701

Page: 110 of 186






"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701


Page: 111 of 186





Report No.: HKES150900180701

Page: 112 of 186






Report No.: HKES150900180701

Page: 113 of 186








Report No.: HKES150900180701


Page: 114 of 186





Report No.: HKES150900180701

Page: 115 of 186






Report No.: HKES150900180701

Page: 116 of 186








Report No.: HKES150900180701


Page: 117 of 186





Report No.: HKES150900180701

Page: 118 of 186






Report No.: HKES150900180701

Page: 119 of 186








Report No.: HKES150900180701

Page: 120 of 186




"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701

Page: 121 of 186






Report No.: HKES150900180701

Page: 122 of 186








Report No.: HKES150900180701


Page: 123 of 186





Report No.: HKES150900180701

Page: 124 of 186






Report No.: HKES150900180701

Page: 125 of 186








Report No.: HKES150900180701


Page: 126 of 186





Report No.: HKES150900180701

Page: 127 of 186






Report No.: HKES150900180701

Page: 128 of 186








Report No.: HKES150900180701


Page: 129 of 186





Report No.: HKES150900180701

Page: 130 of 186






Report No.: HKES150900180701

Page: 131 of 186








Report No.: HKES150900180701


Page: 132 of 186





Report No.: HKES150900180701

Page: 133 of 186






Report No.: HKES150900180701

Page: 134 of 186








Report No.: HKES150900180701


Page: 135 of 186





Report No.: HKES150900180701

Page: 136 of 186






Report No.: HKES150900180701

Page: 137 of 186








Report No.: HKES150900180701


Page: 138 of 186





Report No.: HKES150900180701

Page: 139 of 186






Report No.: HKES150900180701

Page: 140 of 186

Test mode: 802.11n(HT40) Test channel: Highest




"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701


Page: 141 of 186





Report No.: HKES150900180701

Page: 142 of 186



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701

Page: 143 of 186

6.8 Radiated Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency				
	emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				



Report No.: HKES150900180701

Page: 144 of 186

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: HKES150900180701

Page: 145 of 186

		method as specified and then reported in a data sheet.
		g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel
		h. Repeat above procedures until all frequencies measured was complete.
Exploratory	Test	Transmitting with all kind of modulations, data rates.
Mode:		Transmitting mode
Final Test Mode:		Pretest the EUT at Transmitting mode
		Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
		For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case.
		Only the worst case is recorded in the report.
Instruments Used:	·	Refer to section 5.10 for details.
Test Results:		Pass




Report No.: HKES150900180701

Page: 146 of 186

6.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)								
Test mode:	Transmitting	Vertical						



Condition: FCC PART 15C 3m 3142C Vertical

Job No. : 1807PS Test mode: TX mode


	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.95	0.60	17.61	27.35	47.52	38.38	40.00	-1.62
2	45.53	0.72	10.66	27.30	53.82	37.90	40.00	-2.10
3	80.36	1.10	7.74	27.23	56.53	38.14	40.00	-1.86
4	174.42	1.36	9.68	26.79	50.71	34.96	43.50	-8.54
5	274.19	1.79	12.78	26.47	50.70	38.80	46.00	-7.20
6	996.50	3.70	24.16	26.33	41.39	42.92	54.00	-11.08



Report No.: HKES150900180701

Page: 147 of 186





Condition: FCC PART 15C 3m 3142C Horizontal

Job No. : 1807PS Test mode: TX mode

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	125.01	1.26	7.80	27.04	48.73	30.75	43.50	-12.75
2	177.51	1.37	9.80	26.78	47.88	32.27	43.50	-11.23
3	199.99	1.40	10.20	26.70	47.69	32.59	43.50	-10.91
4	257.42	1.71	12.45	26.51	48.12	35.77	46.00	-10.23
5	375.94	2.13	16.01	26.97	44.85	36.02	46.00	-9.98
6	449.56	2.41	16.89	27.44	42.97	34.83	46.00	-11.17



Report No.: HKES150900180701

Page: 148 of 186

6.8.2 Transmitter emission above 1GHz

Test mode	э:	802.11b	Test c	hannel:	Lowest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Li (dBuV/	I I imit	Polarization
3721.784	6.84	33.09	38.84	45.06	46.15	74	-27.85	Vertical
4824.000	6.46	34.72	39.24	50.71	52.65	74	-21.35	Vertical
5904.828	7.93	36.12	39.19	46.09	50.95	74	-23.05	Vertical
7236.000	8.96	35.60	39.06	45.18	50.68	74	-23.32	Vertical
9648.000	9.97	37.45	37.91	40.61	50.12	74	-23.88	Vertical
12208.390	10.93	38.96	38.88	42.04	53.05	74	-20.95	Vertical
3594.760	6.91	32.99	38.78	45.20	46.32	74	-27.68	Horizontal
4824.000	6.46	34.72	39.24	49.93	51.87	74	-22.13	Horizontal
5947.702	8.00	36.20	39.19	45.50	50.51	74	-23.49	Horizontal
7236.000	8.96	35.60	39.06	43.77	49.27	74	-24.73	Horizontal
9648.000	9.97	37.45	37.91	40.62	50.13	74	-23.87	Horizontal
12494.320	11.3	39.22	39.12	40.18	51.63	74	-22.37	Horizontal

Test mode	э:	802.11b	Test c	hannel:	Middle		Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)		nit Line BuV/m)	Over Limit (dB)	Polarization
3743.387	6.83	33.11	38.85	43.64	44.73		74	-29.27	Vertical
4874.000	6.57	34.77	39.26	44.56	46.64		74	-27.36	Vertical
5999.562	8.08	36.30	39.18	44.73	49.93		74	-24.07	Vertical
7311.000	9.06	35.52	39.06	43.98	49.50		74	-24.50	Vertical
9748.000	9.91	37.76	37.85	40.19	50.01		74	-23.99	Vertical
12639.790	10.77	39.26	39.24	41.99	52.78		74	-21.22	Vertical
3684.279	6.86	33.06	38.82	44.32	45.42		74	-28.58	Horizontal
4874.000	6.57	34.77	39.26	44.35	46.43		74	-27.57	Horizontal
6202.582	8.03	36.08	39.16	45.92	50.87		74	-23.13	Horizontal
7311.000	9.06	35.52	39.06	44.14	49.66		74	-24.34	Horizontal
9748.000	9.91	37.76	37.85	40.20	50.02	74		-23.98	Horizontal
12208.390	10.93	38.96	38.88	41.16	52.17		74	-21.83	Horizontal



Report No.: HKES150900180701

Page: 149 of 186

Test mode	e:	802.11b	Test c	hannel:	Highest	Ren	nark:	Peak
Frequency (MHz)	Cabl Loss (dB)	s Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3819.990	6.79	33.19	38.88	44.14	45.24	74	-28.76	Vertical
4924.000	6.68	34.82	39.28	45.61	47.83	74	-26.17	Vertical
6043.124	8.07	36.25	39.18	44.68	49.82	74	-24.18	Vertical
7386.000	9.16	35.44	39.05	44.19	49.74	74	-24.26	Vertical
9848.000	9.85	38.06	37.79	40.47	50.59	74	-23.41	Vertical
12297.040	11.0	6 39.07	38.95	41.03	52.21	74	-21.79	Vertical
3620.861	6.90	33.02	38.79	44.08	45.21	74	-28.79	Horizontal
4924.000	6.68	34.82	39.28	45.27	47.49	74	-26.51	Horizontal
6311.218	8.01	35.94	39.15	45.22	50.02	74	-23.98	Horizontal
7386.000	9.16	35.44	39.05	43.74	49.29	74	-24.71	Horizontal
9848.000	9.85	38.06	37.79	40.46	50.58	74	-23.42	Horizontal
12332.670	11.1	1 39.12	38.98	40.72	51.97	74	-22.03	Horizontal

Test mode	e:		802.11g	Test c	hannel:	Lowest		Rem	ark:	Peak
Frequency (MHz)	_	ble ss B)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)		Over Limit (dB)	Polarization
3678.952	6.8	87	33.06	38.82	44.47	45.58	7	74	-28.42	Vertical
4824.000	6.4	46	34.72	39.24	47.58	49.52	7	74	-24.48	Vertical
6202.582	8.0	03	36.08	39.16	45.42	50.37	7	74	-23.63	Vertical
7236.000	8.9	96	35.60	39.06	43.11	48.61	7	74	-25.39	Vertical
9648.000	9.9	97	37.45	37.91	41.19	50.70	7	74	-23.30	Vertical
12621.510	10.	85	39.26	39.22	41.69	52.58	7	74	-21.42	Vertical
3700.306	6.8	35	33.08	38.83	44.62	45.72	7	74	-28.28	Horizontal
4824.000	6.4	46	34.72	39.24	48.35	50.29	7	74	-23.71	Horizontal
6202.582	8.0	03	36.08	39.16	45.89	50.84	7	74	-23.16	Horizontal
7236.000	8.9	96	35.60	39.06	43.56	49.06	74		-24.94	Horizontal
9648.000	9.9	97	37.45	37.91	41.08	50.59	74		-23.41	Horizontal
12297.040	11.	.06	39.07	38.95	40.10	51.28	7	74	-22.72	Horizontal



Report No.: HKES150900180701

Page: 150 of 186

Test mode	e:	802.11g	Test c	hannel:	Middle	Ren	nark:	Peak
Frequency (MHz)	Cabl Loss (dB)	s Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3776.027	6.81	33.13	38.86	46.40	47.48	74	-26.52	Vertical
4874.000	6.57	34.77	39.26	45.38	47.46	74	-26.54	Vertical
6202.582	8.03	36.08	39.16	45.73	50.68	74	-23.32	Vertical
7311.000	9.06	35.52	39.06	43.94	49.46	74	-24.54	Vertical
9748.000	9.91	37.76	37.85	40.26	50.08	74	-23.92	Vertical
12548.680	11.1	5 39.24	39.16	40.45	51.68	74	-22.32	Vertical
3705.664	6.85	33.08	38.83	44.07	45.17	74	-28.83	Horizontal
4874.000	6.57	34.77	39.26	45.16	47.24	74	-26.76	Horizontal
6016.949	8.08	36.28	39.18	44.56	49.74	74	-24.26	Horizontal
7311.000	9.06	35.52	39.06	43.56	49.08	74	-24.92	Horizontal
9748.000	9.91	37.76	37.85	40.97	50.79	74	-23.21	Horizontal
12102.870	10.7	7 38.83	38.79	41.14	51.95	74	-22.05	Horizontal

Test mode	e:		802.11g	Test c	hannel:	Highest	Rer	nark:	Peak
Frequency (MHz)	Cab Los (dE	SS	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3652.432	6.8	38	33.04	38.81	44.42	45.53	74	-28.47	Vertical
4924.000	6.6	88	34.82	39.28	45.32	47.54	74	-26.46	Vertical
5999.562	8.0	8(36.30	39.18	44.92	50.12	74	-23.88	Vertical
7386.000	9.1	6	35.44	39.05	44.58	50.13	74	-23.87	Vertical
9848.000	9.8	35	38.06	37.79	40.57	50.69	74	-23.31	Vertical
12458.220	11.3	30	39.21	39.09	40.12	51.54	74	-22.46	Vertical
3694.956	6.8	36	33.07	38.83	44.12	45.22	74	-28.78	Horizontal
4924.000	6.6	88	34.82	39.28	44.79	47.01	74	-26.99	Horizontal
6095.816	8.0)6	36.19	39.17	44.54	49.62	74	-24.38	Horizontal
7386.000	9.1	6	35.44	39.05	44.72	50.27	74	-23.73	Horizontal
9848.000	9.8	35	38.06	37.79	40.65	50.77	74	-23.23	Horizontal
12314.840	11.0	09	39.09	38.97	40.40	51.61	74	22.39	Horizontal



Report No.: HKES150900180701

Page: 151 of 186

Test mode	e: 80)2.11n(HT20)	Test c	hannel:	Lowest	R	emark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Lin (dBuV/m	ı ıımıt	Polarization
3647.151	6.88	33.04	38.81	44.64	45.75	74	-28.25	Vertical
4824.000	6.46	34.72	39.24	48.83	50.77	74	-23.23	Vertical
6016.949	8.08	36.28	39.18	44.76	49.94	74	-24.06	Vertical
7236.000	8.96	35.60	39.06	44.49	49.99	74	-24.01	Vertical
9648.000	9.97	37.45	37.91	40.90	50.41	74	-23.59	Vertical
12548.680	11.15	39.24	39.16	40.93	52.16	74	-21.84	Vertical
3903.804	6.74	33.33	38.91	45.34	46.50	74	-27.50	Horizontal
4824.000	6.46	34.72	39.24	49.37	51.31	74	-22.69	Horizontal
6175.716	8.04	36.11	39.17	45.27	50.25	74	-23.75	Horizontal
7236.000	8.96	35.60	39.06	43.56	49.06	74	-24.94	Horizontal
9648.000	9.97	37.45	37.91	40.62	50.13	74	-23.87	Horizontal
12639.790	10.77	39.26	39.24	41.47	52.26	74	-21.74	Horizontal

Test mode	e: 8	802.1	1n(HT20)	Test cl	nannel:	Middle		Rem	ark:	Peak
Frequency (MHz)	Cabl Loss (dB)	s	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)		nit Line BuV/m)	Over Limit (dB)	Polarization
3737.975	6.83	3	33.10	38.84	44.32	45.41		74	-28.59	Vertical
4874.000	6.57	7	34.77	39.26	44.69	46.77		74	-27.23	Vertical
6175.716	8.04	1	36.11	39.17	45.56	50.54		74	-23.46	Vertical
7311.000	9.06	3	35.52	39.06	44.17	49.69		74	-24.31	Vertical
9748.000	9.91	1	37.76	37.85	40.82	50.64		74	-23.36	Vertical
12603.270	10.9	2	39.25	39.21	40.86	51.82		74	-22.18	Vertical
3678.952	6.87	7	33.06	38.82	44.44	45.55		74	-28.45	Horizontal
4874.000	6.57	7	34.77	39.26	45.10	47.18		74	-26.82	Horizontal
6095.816	8.06	3	36.19	39.17	44.72	49.80		74	-24.20	Horizontal
7311.000	9.06	6	35.52	39.06	43.95	49.47		74	-24.53	Horizontal
9748.000	9.91	1	37.76	37.85	40.41	50.23	74		-23.77	Horizontal
12208.390	10.9	3	38.96	38.88	41.45	52.46		74	-21.54	Horizontal



Report No.: HKES150900180701

Page: 152 of 186

Test mode	e: 80	2.11n(HT20)	Test c	hannel:	Highest	Rei	mark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3770.567	6.81	33.13	38.86	44.01	45.09	74	-28.91	Vertical
4924.000	6.68	34.82	39.28	45.29	47.51	74	-26.49	Vertical
6069.413	8.06	36.22	39.18	45.22	50.32	74	-23.68	Vertical
7386.000	9.16	35.44	39.05	45.07	50.62	74	-23.38	Vertical
9848.000	9.85	38.06	37.79	40.33	50.45	74	-23.55	Vertical
12120.390	10.79	38.85	38.80	42.08	52.92	74	-21.08	Vertical
3909.457	6.74	33.34	38.91	44.30	45.47	74	-28.53	Horizontal
4924.000	6.68	34.82	39.28	45.50	47.72	74	-26.28	Horizontal
6292.980	8.01	35.96	39.15	45.36	50.18	74	-23.82	Horizontal
7386.000	9.16	35.44	39.05	44.44	49.99	74	-24.01	Horizontal
9848.000	9.85	38.06	37.79	40.38	50.50	74	-23.50	Horizontal
12314.840	11.09	39.09	38.97	41.20	52.41	74	-21.59	Horizontal

Test mode	e: {	302.11n(HT40) Test c	hannel:	Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Factor	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	nit Line BuV/m)	Over Limit (dB)	Polarization
3776.027	6.81	33.13	38.86	44.16	45.24	74	-28.76	Vertical
4844.000	6.51	34.74	39.25	45.45	47.45	74	-26.55	Vertical
5879.252	7.89	36.07	39.20	45.30	50.06	74	-23.94	Vertical
7266.000	9.00	35.57	39.06	43.43	48.94	74	-25.06	Vertical
9688.000	9.94	37.57	37.88	40.14	49.77	74	-24.23	Vertical
12155.510	10.8	5 38.90	38.83	41.91	52.83	74	-21.17	Vertical
3684.279	6.86	33.06	38.82	44.61	45.71	74	-28.29	Horizontal
4844.000	6.51	34.74	39.25	45.46	47.46	74	-26.54	Horizontal
6087.002	8.06	36.20	39.17	44.60	49.69	74	-24.31	Horizontal
7266.000	9.00	35.57	39.06	44.52	50.03	74	-23.97	Horizontal
9688.000	9.94	37.57	37.88	40.07	49.70	74	-24.30	Horizontal
12190.740	10.90	38.94	38.86	41.39	52.37	74	-21.63	Horizontal



Report No.: HKES150900180701

Page: 153 of 186

Test mode	e: 80	2.11n(HT40)	Test c	hannel:	Middle	Rem	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3765.116	6.82	33.12	38.86	44.50	45.58	74	-28.42	Vertical
4874.000	6.57	34.77	39.26	44.77	46.85	74	-27.15	Vertical
6122.333	8.05	36.16	39.17	44.80	49.84	74	-24.16	Vertical
7311.000	9.06	35.52	39.06	44.28	49.80	74	-24.20	Vertical
9748.000	9.91	37.76	37.85	40.13	49.95	74	-24.05	Vertical
12314.840	11.09	39.09	38.97	40.33	51.54	74	-22.46	Vertical
3765.116	6.82	33.12	38.86	44.13	45.21	74	-28.79	Horizontal
4874.000	6.57	34.77	39.26	45.81	47.89	74	-26.11	Horizontal
6140.076	8.05	36.15	39.17	45.19	50.22	74	-23.78	Horizontal
7311.000	9.06	35.52	39.06	45.07	50.59	74	-23.41	Horizontal
9748.000	9.91	37.76	37.85	40.88	50.70	74	-23.30	Horizontal
12621.510	10.85	39.26	39.22	41.48	52.37	74	-21.63	Horizontal

Test mode	e: 8	02.11n(HT40)	Test c	hannel:	Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	it Line uV/m)	Over Limit (dB)	Polarization
3898.160	6.74	33.32	38.91	44.42	45.57	74	-28.43	Vertical
4904.000	6.64	34.81	39.27	46.16	48.34	74	-25.66	Vertical
6122.333	8.05	36.16	39.17	44.62	49.66	74	-24.34	Vertical
7356.000	9.12	35.47	39.05	44.37	49.91	74	-24.09	Vertical
9808.000	9.88	37.94	37.81	40.22	50.23	74	-23.77	Vertical
12137.940	10.82	38.87	38.82	41.00	51.87	74	-22.13	Vertical
3711.030	6.85	33.08	38.83	44.62	45.72	74	-28.28	Horizontal
4904.000	6.64	34.81	39.27	44.99	47.17	74	-26.83	Horizontal
6148.967	8.05	36.14	39.17	45.02	50.04	74	-23.96	Horizontal
7356.000	9.12	35.47	39.05	44.69	50.23	74	-23.77	Horizontal
9808.000	9.88	37.94	37.81	40.26	50.27	74	-23.73	Horizontal
12102.870	10.77	38.83	38.79	41.40	52.21	74	-21.79	Horizontal



Report No.: HKES150900180701

Page: 154 of 186

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: HKES150900180701

Page: 155 of 186

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10 2013	ANSI C63.10 2013							
Test Site:	Measurement Distance: 3r	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark						
	30MHz-88MHz	40.0	Quasi-peak Value						
	88MHz-216MHz	43.5	Quasi-peak Value						
	216MHz-960MHz	46.0	Quasi-peak Value						
	960MHz-1GHz	54.0	Quasi-peak Value						
	Above 1GHz	54.0	Average Value						
	Above IGHZ	74.0	Peak Value						
Test Setup:			<u> </u>						






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: HKES150900180701

Page: 156 of 186

Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.					
	b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.					
	c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.					
	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.					
	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.					
	f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel					
	g. Test the EUT in the lowest channel, the Highest channel					
	h. Repeat above procedures until all frequencies measured was complete.					
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.					
	Transmitting mode.					
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;					
	6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)					
	Only the worst case is recorded in the report.					
Instruments Used:	Refer to section 5.10 for details					
Test Results:	Pass					




Report No.: HKES150900180701

Page: 157 of 186

Test plot as follows:

Worse case mode: 802.11b Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2412 Band edge

: B

Cable Ant Preamp Read Limit Over
Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dBuV dBuV/m dBuV/m dBuV/m dB


1 pk 2390.00 4.90 32.35 38.46 54.98 53.77 74.00 -20.23 2 pp 2414.72 4.93 32.42 38.46 108.54 107.43 74.00 33.43



Report No.: HKES150900180701

Page: 158 of 186

Worse case mode: 802.11b Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2412 Band edge

: B

2414.72

Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 47.35 46.14 74.00 -27.86 1 pk 2390.00


4.93 32.42 38.46 97.60 96.49 74.00 22.49



Report No.: HKES150900180701

Page: 159 of 186

Worse case mode: 802.11b Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2462 Band edge

: B

Cable Ant Preamp Read Limit Over Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dB/w dBuV/m dBuV/m dBuV/m dB


1 pp 2459.47 5.00 32.43 38.46 106.00 104.97 74.00 30.97 2 pk 2483.50 5.03 32.44 38.47 49.35 48.35 74.00 -25.65



Report No.: HKES150900180701

Page: 160 of 186

Worse case mode: 802.11b Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2462 Band edge

: B

Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 5.00 32.43 38.46 95.03 94.00 74.00 20.00 1 pp 2459.52 2483.50 5.03 32.44 38.47 43.58 42.58 74.00 -31.42






Report No.: HKES150900180701

Page: 161 of 186

Worse case mode: 802.11g Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2412 Band edge

: G


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 69.79 68.58 74.00 1 pk 2390.00 2418.99 4.94 32.42 38.46 112.56 111.46 74.00 37.46



Report No.: HKES150900180701

Page: 162 of 186

Worse case mode: 802.11g Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2412 Band edge

: G

2415.39

Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 57.37 56.16 74.00 -17.84 1 pk 2390.00

4.94 32.42 38.46 100.71 99.61 74.00 25.61



Report No.: HKES150900180701

Page: 163 of 186

Worse case mode: 802.11g Test channel: Lowest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2412 Band edge

: 0


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB/m dB dB 4.90 32.35 38.46 50.06 48.85 1 av 2390.00 54.00 -5.15 2419.55 4.94 32.42 38.46 102.25 101.15 54.00 47.15



Report No.: HKES150900180701

Page: 164 of 186

Worse case mode: 802.11g Test channel: Lowest Remark: Average Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2412 Band edge

: 0


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB/m dB dB 4.90 32.35 38.46 43.16 41.95 1 av 2390.00 54.00 -12.05 2419.55 4.94 32.42 38.46 91.16 90.06 54.00 36.06



Report No.: HKES150900180701

Page: 165 of 186

Worse case mode: 802.11g Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2462 Band edge

: 0

2483.50

Cable Ant Preamp Read Limit Over
Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dB/m dB dBUV/m dBUV/m dBUV/m dB

1 pp 2454.61 4.99 32.43 38.46 113.00 111.96 74.00 37.96


5.03 32.44 38.47 61.70 60.70 74.00 -13.30



Report No.: HKES150900180701

Page: 166 of 186

Worse case mode: 802.11g Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2462 Band edge

: G


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 99.88 1 pp 2456.69 32.43 38.46 98.84 74.00 24.84 2483.50 5.03 32.44 38.47 54.46 53.46 74.00 -20.54



Report No.: HKES150900180701

Page: 167 of 186

Worse case mode: 802.11g Test channel: Highest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2462 Band edge

: G


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB dB 4.99 32.43 38.46 102.56 101.52 1 pp 2454.56 54.00 47.52 2483.50 5.03 32.44 38.47 45.09 44.09 54.00 -9.91



Report No.: HKES150900180701

Page: 168 of 186

Worse case mode: 802.11g Test channel: Highest Remark: Average Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2462 Band edge

: G


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 38.46 89.68 88.64 1 pp 2456.64 54.00 34.64 2483.50 5.03 32.44 38.47 41.13 40.13 54.00 -13.87



Report No.: HKES150900180701

Page: 169 of 186

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB dB 4.90 32.35 38.46 72.20 70.99 74.00 1 pk 2390.00 2417.97 4.94 32.42 38.46 112.02 110.92 74.00 36.92



Report No.: HKES150900180701

Page: 170 of 186

802.11n(HT20) Test channel: Peak Worse case mode: Lowest Remark: Horizontal



: chamber

2 pp

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2412 Band edge

: N20

Cable Ant Preamp 0ver Read Limit Loss Factor Factor Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 56.59 1 pk 2390.00 55.38 74.00 -18.62 2406.64 4.92 32.41 38.46 99.96 98.83 74.00 24.83






Report No.: HKES150900180701

Page: 171 of 186

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 52.11 50.90 2390.00 54.00 2418.88 4.94 32.42 38.46 102.56 101.46 54.00 47.46



Report No.: HKES150900180701

Page: 172 of 186

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Average Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB/m dB dB 4.90 32.35 38.46 43.51 42.30 54.00 -11.70 2390.00 2406.42 4.92 32.41 38.46 89.84 88.71 54.00 34.71 2 pp



Report No.: HKES150900180701

Page: 173 of 186

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2462 Band edge

: N20

Cable Ant Preamp Read Limit Over
Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dBuV dBuV/m dBuV/m dBuV/m dB


1 pp 2455.30 4.99 32.43 38.46 111.39 110.35 74.00 36.35 2 pk 2483.50 5.03 32.44 38.47 60.37 59.37 74.00 -14.63



Report No.: HKES150900180701

Page: 174 of 186

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 1 pp 2457.73 38.46 97.14 96.10 74.00 22.10 2483.50 5.03 32.44 38.47 54.20 53.20 74.00 -20.80



Report No.: HKES150900180701

Page: 175 of 186

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 38.46 100.87 99.83 1 pp 2455.50 54.00 45.83 5.03 32.44 38.47 44.56 43.56 54.00 -10.44 2483.50



Report No.: HKES150900180701

Page: 176 of 186

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Average Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 38.46 87.73 86.69 1 pp 2456.10 54.00 32.69 2483.50 5.03 32.44 38.47 41.37 40.37 54.00 -13.63



Report No.: HKES150900180701

Page: 177 of 186

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2422 Band edge

: N40


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 60.08 58.87 1 pk 2390.00 74.00 -15.13 2 pp 2417.07 4.94 32.42 38.46 97.61 96.51 74.00 22.51



Report No.: HKES150900180701

Page: 178 of 186

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2422 Band edge

: N40


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 54.96 53.75 1 pk 2390.00 74.00 -20.25 2419.63 4.94 32.42 38.46 90.97 89.87 74.00 15.87



Report No.: HKES150900180701

Page: 179 of 186

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2422 Band edge

: N40


Ant Preamp Read 0ver Cable Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.90 32.35 38.46 44.99 43.78 1 av 2390.00 54.00 -10.22 2418.35 4.94 32.42 38.46 87.06 85.96 54.00 31.96



Report No.: HKES150900180701

Page: 180 of 186

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Average Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2422 Band edge

: N40

Ant Preamp 0ver Cable Read Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB/m dB dB 4.90 32.35 1 av 2390.00 38.46 41.83 40.62 54.00 -13.38 2 pp 2415.93 4.94 32.42 38.46 80.62 79.52 54.00 25.52






Report No.: HKES150900180701

Page: 181 of 186

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 1807PS

Mode: : 2452 Band edge

: N40


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB dB 4.98 32.43 1 pp 2451.44 38.46 97.64 96.59 74.00 22.59 2483.50 5.03 32.44 38.47 69.92 68.92 74.00



Report No.: HKES150900180701

Page: 182 of 186

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Peak Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 1807PS

Mode: : 2452 Band edge

: N40


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 38.46 85.68 84.64 74.00 10.64 1 pp 2451.49 2483.50 5.03 32.44 38.47 58.76 57.76 74.00 -16.24



Report No.: HKES150900180701

Page: 183 of 186

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Average Vertical



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: : 1807PS

Mode: : 2452 Band edge

: N40


Cable Ant Preamp Read 0ver Limit Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 4.99 32.43 38.46 87.58 86.54 1 pp 2453.27 54.00 32.54 2483.50 5.03 32.44 38.47 47.25 46.25 54.00 -7.75



Report No.: HKES150900180701

Page: 184 of 186

Worse case mode: | 802.11n(HT40) | Test channel: | Highest | Remark: | Average | Horizontal



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 1807PS

Mode: : 2452 Band edge

: N40

				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2450.54 2483.50	pp av

Note.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: HKES150900180701

Page: 185 of 186

7 Photographs - EUT Test Setup

Test model No.: Surf SOHO

7.1 Radiated Emission







Report No.: HKES150900180701

Page: 186 of 186

7.2 Radiated Spurious Emission



7.3 Conducted Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for HKES1509001807PS.