

Report No.: HKES160300051102

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 191

### **FCC REPORT**

Application No: HKES1603000511IT

Applicant: Pismo Labs Technology Limited

Product Name: Peplink/ Pepwave/ Pismo Labs wireless product

**Model No.(EUT):** AP One Enterprise,

Add Model No.: AP One Enterprise DUO, Pismo AC1DUO

FCC ID: U8G-P1AC1DUO

Standards: 47 CFR Part 15, Subpart C (2015)

**Date of Receipt:** 2016-03-24

**Date of Test:** 2016-03-24 to 2016-03-28

**Date of Issue:** 2016-05-17

Test Result: PASS \*

. \* In the configuration tested, the EUT complied with the standards specified above.

### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: HKES160300051102

Page: 2 of 191

### 2 Version

Revision Record								
Version Chapter Date Modifier Remark								
00		2016-05-17		Original				

Authorized for issue by:		
	Benson Woma	2016-03-28
Tested By	(Benson Wang) /Project Engineer	Date
	Joyce Shi	2016-05-17
Prepared By	(Joyce Shi) /Clerk	Date
	Eric Fu	2016-05-17
Checked By	(Eric Fu) /Reviewer	Date



Report No.: HKES160300051102

Page: 3 of 191

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious47 CFR Part 15, Subpart CEmissions15.205/15.209		ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS



Report No.: HKES160300051102

Page: 4 of 191

### 4 Contents

			Page
1	CO	VER PAGE	1
2	VEI	RSION	2
3	TES	ST SUMMARY	3
4		NTENTS	4
4			
5	GE	NERAL INFORMATION	5
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT AND MODE	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7 5.8	DEVIATION FROM STANDARDS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	
6	TES	ST RESULTS AND MEASUREMENT DATA	11
	6.1	Antenna Requirement	11
	6.2	CONDUCTED EMISSIONS	
	6.3	CONDUCTED PEAK OUTPUT POWER	
	6.4	6DB OCCUPY BANDWIDTH	
	6.5	Power Spectral Density	
	6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.7	RF CONDUCTED SPURIOUS EMISSIONS	
	6.8 <i>6.8</i> .	RADIATED SPURIOUS EMISSIONS	
	6.8.		
	6.9	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	OTOGRAPHS - EUT TEST SETUP	190
	7.1	CONDUCTED EMISSION	100
	7.1	RADIATED EMISSION	
	7.3	RADIATED Spurious Emission	
8	PH	OTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	191



Report No.: HKES160300051102

Page: 5 of 191

### 5 General Information

### 5.1 Client Information

Applicant:	Pismo Labs Technology Limited
Address of Applicant:	FLAT/RM A5, 5/F HK SPINNERS IND BLDG PHASE 6, 481 CASTLE PEAK ROAD, CHEUNG SHA WAN, HONG KONG

### 5.2 General Description of EUT

Product Name:	Peplink/ Pepwave/ Pismo Labs wireless product
Model No.:	AP One Enterprise
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK)
	IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
	IEEE for 802.11n (HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
	IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Number:	IEEE 802.11b/g, IEEE 802.11n(HT20): 13 Channels
	IEEE 802.11n(HT40): 7 Channels
Channels Step:	Channels with 5MHz step
Antenna Type:	MIMO*3
Antenna Gain:	Max. 3.80dBi
Power Supply:	Powered by POE
	POE Model: POE31U-1AT
	INPUT: 100-240V, 0.8A, 50/60Hz
	OUTPUT: DC 56V, 0.536A
	PIN 3, 6 DC56V
	PIN 1, 2 RETURN

#### Remark:

Model No.: AP One Enterprise, AP One Enterprise DUO, Pismo AC1DUO

Only the model AP One Enterprise was tested, since the circuit design, PCB layout, electrical components used, internal wiring and functions were identical for the above models, only different on model names for the marketing requirement.



Report No.: HKES160300051102

Page: 6 of 191

Operation Frequency each of channel(802.11b/g/n HT20)										
Channel	Fr	equency	Channe	Frequency	Channel	Fre	quency Chan		nnel	Frequency
1	24	112MHz	4	2427MHz	7	244	442MHz 1		)	2457MHz
2	24	117MHz	5	2432MHz	8	244	47MHz 11		1	2462MHz
3	24	122MHz	6	2437MHz	9	2452MHz				
Operation F	requ	ency each	of channe	el(802.11n HT40	)					
Channe		Frequ	ency	Channel	Frequen	су	Chan	nel	ſ	Frequency
3 2422MHz		6	2437MF	2437MHz				2452MHz		
4 2427MHz		7	2442MF	lz						
5 2432MHz			8	2447MF	lz					

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

### For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

#### For 802.11n (HT40):

, ,	
Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz



Report No.: HKES160300051102

Page: 7 of 191

### 5.3 Test Environment and Mode

Operating Environment:	Operating Environment:						
Temperature:	25.0 °C						
Humidity:	55% RH						
Atmospheric Pressure:	1020 mbar						
Test mode:							
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all						
	kind of data rate.						

### 5.4 Description of Support Units

The EUT has been tested independent unit.

### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: HKES160300051102

Page: 8 of 191

### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### · CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

### • FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

### Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

### 5.7 Deviation from Standards

None.

### 5.8 Abnormalities from Standard Conditions

None.

### 5.9 Other Information Requested by the Customer

None.



Report No.: HKES160300051102

Page: 9 of 191

### 5.10Equipment List

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS- LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2015-09-16	2016-09-16
3	BiConiLog Antenna (26-3000MHz)	ETS- LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
4	Double-ridged horn (1-18GHz)	ETS- LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
5	Horn Antenna (18-26GHz)	ETS- LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2016-04-25	2017-04-25
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13



Report No.: HKES160300051102

Page: 10 of 191

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2015-10-09	2016-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Low Noise Amplifier	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2015-10-09	2016-10-09
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

	RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2015-10-17	2016-10-17
3	Barometer	ChangChun	DYM3	SEM002-01	2015-05-13	2016-05-13
4	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
5	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2015-10-09	2016-10-09



Report No.: HKES160300051102

Page: 11 of 191

### 6 Test results and Measurement Data

### 6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**





Report No.: HKES160300051102

Page: 12 of 191



The antenna is integrated antenna and no consideration of replacement. The best case gain of the antenna is 3.80dBi, directional gain is 8.57dBi.



Report No.: HKES160300051102

Page: 13 of 191


### 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207				
Test Method:	ANSI C63.10: 2013, section 6	.2			
Test Frequency Range:	150kHz to 30MHz				
Limit:	F (AUL.)	Limit (c	lBuV)		
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
	* Decreases with the logarithm	n of the frequency.		1	
Test Procedure:	<ol> <li>The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>The tabletop EUT was placed upon a non-metallic table 0.8m above the</li> </ol>				
	ground reference plane. And for floor-standing arrangement, the was placed on the horizontal ground reference plane,  4) The test was performed with a vertical ground reference plane. The of the EUT shall be 0.4 m from the vertical ground reference plane vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other unit the EUT and associated equipment was at least 0.8 m from the LISM 1 in order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according ANSI C63.10: 2013 on conducted measurement.				



Report No.: HKES160300051102

Page: 14 of 191





Report No.: HKES160300051102


Page: 15 of 191

#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

### Live Line:



Site : Shielding Room
Condition : CE LINE
Job.No : 05111T
Test Mode : TX


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.20075	0.02	9.60	38.06	47.68	63.58	-15.90	QP
2	0.20075	0.02	9.60	29.26	38.88	53.58	-14.70	Average
3	0.35015	0.01	9.59	40.27	49.87	58.96	-9.09	QP
4	0.35015	0.01	9.59	31.24	40.84	48.96	-8.12	Average
5	1.535	0.02	9.59	37.55	47.16	56.00	-8.84	QP
6 @	1.535	0.02	9.59	35.18	44.79	46.00	-1.21	Average
7	2.309	0.02	9.63	35.49	45.14	56.00	-10.86	QP
8	2.309	0.02	9.63	32.37	42.02	46.00	-3.98	Average
9	3.074	0.02	9.62	30.83	40.47	56.00	-15.53	QP
10	3.074	0.02	9.62	26.12	35.76	46.00	-10.24	Average
11	3.472	0.02	9.63	29.26	38.90	56.00	-17.10	QP
12	3.472	0.02	9.63	24.25	33.89	46.00	-12.11	Average



Report No.: HKES160300051102

Page: 16 of 191

#### Neutral Line:



Site : Shielding Room Condition : CE NEUTRAL Job.No : 0511IT Test Mode : TX

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.34463	0.01	9.62	41.23	50.86	59.09	-8.23	QP
2	0.34463	0.01	9.62	33.91	43.54	49.09	-5.55	Average
3	1.544	0.02	9.64	36.14	45.80	56.00	-10.20	QP
4 @	1.544	0.02	9.64	35.14	44.80	46.00	-1.20	Average
5	2.309	0.02	9.67	32.71	42.40	56.00	-13.60	QP
6	2.309	0.02	9.67	29.70	39.39	46.00	-6.61	Average
7	3.090	0.02	9.67	29.24	38.93	56.00	-17.07	QP
8	3.090	0.02	9.67	26.43	36.12	46.00	-9.88	Average
9	3.472	0.02	9.68	29.54	39.23	56.00	-16.77	QP
10	3.472	0.02	9.68	24.62	34.32	46.00	-11.68	Average
11	28.302	0.03	10.20	25.61	35.84	60.00	-24.16	QP
12	28.302	0.03	10.20	17.70	27.93	50.00	-22.07	Average

#### Notes:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: HKES160300051102

Page: 17 of 191

### 6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)				
Test Method:	ANSI C63.10 2013, section 11.9.1.2				
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark:  Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Test Instruments:	Refer to section 5.10 for details				
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates				
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;				
	6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)				
Limit:	Antenna gain below 6dBi: 30dBm (802.11 b & g)				
	Antenna gain greater than 6dBi :				
	Not exceed 30dBm - 2.57 (directional gain-6) = 27.43dBm (802.11 n)				
Test Results:	Pass				



Report No.: HKES160300051102

Page: 18 of 191

Pre-scan under all rate at lowest channel 1								
Mode		802	.11b			_		
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	8.56	8.50	8.53	8.51				
Mode				802	2.11g			
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	14.50	14.48	14.49	14.37	14.40	14.42	14.43	14.42
Mode				802.11	n(HT20)			
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	18.33	18.29	18.30	18.32	18.30	18.31	18.32	18.30
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power (dBm)	18.41	18.39	18.35	18.30	18.32	18.40	18.40	18.37

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).



Report No.: HKES160300051102

Page: 19 of 191

#### **Measurement Data**

	802.11b mode						
Test channel	Pe	Peak Output Power (dBm)			Limit (dPm)	Result	
rest chamilei	Ant	i. 1 A	Ant. 2 Ant. 3		Limit (dBm)	nesuit	
Lowest	6.9	97 7	7.48	7.80	30.00	Pass	
Middle	6.4	41 7	7.86	7.97	30.00	Pass	
Highest	7.5	57 8	3.05	8.56	30.00	Pass	
			80	02.11g mod	de		
Test channel	Pe	ak Outpu	ıt Power	(dBm)	Limit (dBm)	Result	
rest chamilei	Ant	i. 1 A	nt. 2	Ant. 3	Littit (dbitt)	nesuit	
Lowest	11.	65 1	2.46	13.27	30.00	Pass	
Middle	11.	63 1	3.47	13.48	30.00	Pass	
Highest	12.	88 1	3.60	14.50	30.00	Pass	
			802.	11n(HT20)r	node		
Test channel	Pea	Peak Output Power (dBm)			Limit (dBm)	Result	
rest channel	Ant. 1	Ant. 2	Ant. 3	3 Total	Lillill (dbill)	nesuit	
Lowest	11.82	12.63	12.93	17.26	27.43	Pass	
Middle	11.51	13.26	13.07	17.45	27.43	Pass	
Highest	12.83	13.45	14.28	18.33	27.43	Pass	
			802.	11n(HT40)r	node		
Test channel	Pea	ık Output	Power	(dBm)	Limit (dBm)	Result	
rest channel	Ant. 1	Ant. 2	Ant. 3	3 Total	LIIIII (UDIII)	nesuit	
Lowest	13.06	13.67	14.11	18.41	27.43	Pass	
Middle	12.12	13.41	13.50	17.83	27.43	Pass	
Highest	11.56	13.10	12.62	17.24	27.43	Pass	




Report No.: HKES160300051102

Page: 20 of 191

### Test plot as follows:

### Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------











Report No.: HKES160300051102

Page: 21 of 191













Report No.: HKES160300051102

Page: 22 of 191





Test mode: 802.11g Test channel: Highest







Report No.: HKES160300051102

Page: 23 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 24 of 191





Test mode: 802.11n(HT40) Test channel: Lowest







Report No.: HKES160300051102

Page: 25 of 191

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: HKES160300051102


Page: 26 of 191

#### Antenna 2

Test mode:	802.11b	Test channel:	Lowest
1 COL III COC.	002.110	1 Cot onamici.	LOWCOL



Test mode: 802.11b Test channel: Middle






Report No.: HKES160300051102

Page: 27 of 191

Test mode: 802.11b Test channel: Highest



Test mode: 802.11g Test channel: Lowest







Report No.: HKES160300051102

Page: 28 of 191

Test mode: 802.11g Test channel: Middle



Test mode: 802.11g Test channel: Highest







Report No.: HKES160300051102

Page: 29 of 191

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------







Report No.: HKES160300051102

Page: 30 of 191

Test mode: 802.11n(HT20) Test channel: Highest



Test mode: 802.11n(HT40) Test channel: Lowest








Report No.: HKES160300051102

Page: 31 of 191











Report No.: HKES160300051102


Page: 32 of 191

#### Antenna 3

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Middle






Report No.: HKES160300051102

Page: 33 of 191

Test mode: 802.11b Test channel: Highest



Test mode: 802.11g Test channel: Lowest







Report No.: HKES160300051102

Page: 34 of 191













Report No.: HKES160300051102

Page: 35 of 191

Test mode: 802.11n(HT20) Test channel: Lowest



Test mode:	802.11n(HT20)	Test channel:	Middle
100011100001	002(20)	1 001 0114111011	madio







Report No.: HKES160300051102

Page: 36 of 191

Test mode: 802.11n(HT20) Test channel: Highest



Test mode: 802.11n(HT40) Test channel: Lowest







Report No.: HKES160300051102

Page: 37 of 191

Test mode: 802.11n(HT40) Test channel: Middle










Report No.: HKES160300051102

Page: 38 of 191

### 6.4 6dB Occupy Bandwidth





Report No.: HKES160300051102

Page: 39 of 191

#### **Measurement Data**

#### Antenna 1

Antenna i						
802.11b mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	7.11	≥500	Pass			
Middle	7.08	≥500	Pass			
Highest	7.62	≥500	Pass			
802.11g mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	16.23	≥500	Pass			
Middle	16.38	≥500	Pass			
Highest	16.41	≥500	Pass			
802.11n(HT20) mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	17.22	≥500	Pass			
Middle	17.61	≥500	Pass			
Highest	17.64	≥500	Pass			
802.11n(HT40)mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result			
Lowest	35.58	≥500	Pass			
Middle	35.28	≥500	Pass			
Highest	36.48	≥500	Pass			



Report No.: HKES160300051102

Page: 40 of 191

#### Antenna 2

802.11b mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	6.63	≥500	Pass				
Middle	6.15	≥500	Pass				
Highest	7.08	≥500	Pass				
	802.11g mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	15.78	≥500	Pass				
Middle	13.26	≥500	Pass				
Highest	16.41	≥500	Pass				
802.11n(HT20) mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	16.41	≥500	Pass				
Middle	13.89	≥500	Pass				
Highest	17.37	≥500	Pass				
802.11n(HT40)mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	32.70	≥500	Pass				
Middle	20.82	≥500	Pass				
Highest	29.58	≥500	Pass				



Report No.: HKES160300051102

Page: 41 of 191

#### Antenna 3

802.11b mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	7.11	≥500	Pass				
Middle	7.11	≥500	Pass				
Highest	7.62	≥500	Pass				
	802.11g mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	16.38	≥500	Pass				
Middle	16.41	≥500	Pass				
Highest	16.50	≥500	Pass				
	802.11n(HT20) mode						
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	17.37	≥500	Pass				
Middle	17.64	≥500	Pass				
Highest	17.67	≥500	Pass				
802.11n(HT40)mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	35.82	≥500	Pass				
Middle	35.28	≥500	Pass				
Highest	35.88	≥500	Pass				




Report No.: HKES160300051102

Page: 42 of 191


#### Test plot as follows:

#### Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode: 802.11b Test channel: Middle







Report No.: HKES160300051102

Page: 43 of 191

Test mode: 802.11b Test channel: Highest











Report No.: HKES160300051102

Page: 44 of 191

Test mode: 802.11g Test channel: Middle












Report No.: HKES160300051102

Page: 45 of 191

Test mode: 802.11n(HT20) Test channel: Lowest












Report No.: HKES160300051102

Page: 46 of 191

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES160300051102

Page: 47 of 191










Report No.: HKES160300051102


Page: 48 of 191

#### Antenna 2

Test mode: 802.11b Test channel: Lowest











Report No.: HKES160300051102

Page: 49 of 191

Test mode: 802.11b Test channel: Highest











Report No.: HKES160300051102

Page: 50 of 191

Test mode: 802.11g Test channel: Middle











Report No.: HKES160300051102

Page: 51 of 191

Test mode: 802.11n(HT20) Test channel: Lowest












Report No.: HKES160300051102

Page: 52 of 191

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES160300051102

Page: 53 of 191

Test mode: 802.11n(HT40) Test channel: Middle











Report No.: HKES160300051102


Page: 54 of 191

#### Antenna 3

Test mode: 802.11b Test channel: Lowest











Report No.: HKES160300051102

Page: 55 of 191

Test mode: 802.11b Test channel: Highest











Report No.: HKES160300051102

Page: 56 of 191

Test mode: 802.11g Test channel: Middle











Report No.: HKES160300051102

Page: 57 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 58 of 191

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES160300051102

Page: 59 of 191

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: HKES160300051102

Page: 60 of 191

#### 6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)			
Test Method:	ANSI C63.10 2013, section 11.10.2			
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark:  Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.			
Test Instruments:	Refer to section 5.10 for details			
Exploratory Test Mode:				
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)			
Limit:	Antenna gain below 6dBi: 8dBm/3kHz (802.11 b & g)  Antenna gain greater than 6dBi:  Not exceed 8dBm/3kHz - 2.57 (directional gain-6) = 5.43dBm (802.11 n)			
Test Results:	Pass			



Report No.: HKES160300051102

Page: 61 of 191

#### **Measurement Data**

802.11b mode						
Test channel	Power S	Spectral Density (dBm/3kHz)		Limit (dBm/3kHz) Result		
	Ant.1	An	t.2	Ant.3	,	
Lowest	-8.49	-6.	85	-7.66	≤8.00	Pass
Middle	-8.63	-9.	43	-9.84	≤8.00	Pass
Highest	-8.84	-9.	99	-11.08	≤8.00	Pass
			802.11	g mode		
Test channel	Power S	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result	
	Ant.1	An	t.2	Ant.3		
Lowest	-14.10	-15	.60	-16.24	≤8.00	Pass
Middle	-17.64	-16	.43	-17.60	≤8.00	Pass
Highest	-16.11	-16	.30	-17.83	≤8.00	Pass
802.11n(HT20) mode						
Test channel	Power S	pectral De	ensity (d	Bm/3kHz)	Limit (dBm/3kHz)	Result
	Ant.1	Ant.2	Ant.3	Total		
Lowest	-13.19	-15.84	-16.79	-10.22	≤5.43	Pass
Middle	-16.62	-16.59	-16.38	-11.76	≤5.43	Pass
Highest	-16.75	-18.39	-18.30	-12.97	≤5.43	Pass
802.11n(HT40) mode						
Test channel	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result		
	Ant.1	Ant.2	Ant.3	Total		
Lowest	-17.36	-18.34	-18.56	-13.28	≤5.43	Pass
Middle	-16.67	-19.55	-17.70	-13.05	≤5.43	Pass
Highest	-19.45	-21.20	-18.89	-14.97	≤5.43	Pass




Report No.: HKES160300051102

Page: 62 of 191


#### Test plot as follows:

#### Antenna 1

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode: 802.11b Test channel: Middle








Report No.: HKES160300051102

Page: 63 of 191

Test mode: 802.11b Test channel: Highest












Report No.: HKES160300051102

Page: 64 of 191

Test mode: 802.11g Test channel: Middle












Report No.: HKES160300051102

Page: 65 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 66 of 191

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES160300051102

Page: 67 of 191

Test mode: 802.11n(HT40) Test channel: Middle










Report No.: HKES160300051102


Page: 68 of 191

#### Antenna 2

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Middle







Report No.: HKES160300051102

Page: 69 of 191

Test mode: 802.11b Test channel: Highest












Report No.: HKES160300051102

Page: 70 of 191

Test mode: 802.11g Test channel: Middle












Report No.: HKES160300051102

Page: 71 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 72 of 191

Test mode: 802.11n(HT20) Test channel: Highest











Report No.: HKES160300051102

Page: 73 of 191

Test mode: 802.11n(HT40) Test channel: Middle










Report No.: HKES160300051102


Page: 74 of 191

#### Antenna 3

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode: 802.11b Test channel: Middle







Report No.: HKES160300051102

Page: 75 of 191

Test mode: 802.11b Test channel: Highest











Report No.: HKES160300051102

Page: 76 of 191

Test mode: 802.11g Test channel: Middle












Report No.: HKES160300051102

Page: 77 of 191

Test mode: 802.11n(HT20) Test channel: Lowest












Report No.: HKES160300051102

Page: 78 of 191

Test mode: 802.11n(HT20) Test channel: Highest












Report No.: HKES160300051102

Page: 79 of 191

Test mode: 802.11n(HT40) Test channel: Middle









Report No.: HKES160300051102

Page: 80 of 191

#### 6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10 2013, section 11.13.2	
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark:  Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates	
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;	
	6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread	
	spectrum intentional radiator is operating, the radio frequency power that is	
	produced by the intentional radiator shall be at least 20 dB below that in the	
	100 kHz bandwidth within the band that contains the highest level of the	
	desired power, based on either an RF conducted or a radiated measurement.	
Instruments Used:	Refer to section 5.10 for details	
	Pass	
Test Results:	rd55	




Report No.: HKES160300051102

Page: 81 of 191


#### Test plot as follows:

#### Antenna 1

Test mode: 802.11b Test channel: Lowest











Report No.: HKES160300051102

Page: 82 of 191

Test mode: 802.11g Test channel: Lowest











Report No.: HKES160300051102

Page: 83 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 84 of 191

Test mode: 802.11n(HT40) Test channel: Lowest










Report No.: HKES160300051102


Page: 85 of 191

#### Antenna 2

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Highest







Report No.: HKES160300051102

Page: 86 of 191

Test mode: 802.11g Test channel: Lowest











Report No.: HKES160300051102

Page: 87 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 88 of 191

Test mode: 802.11n(HT40) Test channel: Lowest










Report No.: HKES160300051102


Page: 89 of 191

#### Antenna 3

Test mode: 802.11b Test channel: Lowest



Test mode: 802.11b Test channel: Highest







Report No.: HKES160300051102

Page: 90 of 191

Test mode: 802.11g Test channel: Lowest











Report No.: HKES160300051102

Page: 91 of 191

Test mode: 802.11n(HT20) Test channel: Lowest











Report No.: HKES160300051102

Page: 92 of 191

Test mode: 802.11n(HT40) Test channel: Lowest









Report No.: HKES160300051102

Page: 93 of 191

#### 6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10 2013, section 11.11	
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark:	
Exploratory Test Mode:	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.  Transmitting with all kind of modulations, data rates	
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;	
	6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread	
	spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	





Report No.: HKES160300051102

Page: 94 of 191

#### Test plot as follows: Antenna 1


Test mode: 802.11b Test channel: Lowest








Report No.: HKES160300051102











Report No.: HKES160300051102









Report No.: HKES160300051102

Page: 97 of 191


Test mode: 802.11b Test channel: Highest








Report No.: HKES160300051102 Page: 98 of 191











Report No.: HKES160300051102









Report No.: HKES160300051102

Page: 100 of 191


Test mode: 802.11g Test channel: Middle








Report No.: HKES160300051102 Page: 101 of 191











Report No.: HKES160300051102 Page: 102 of 191









Report No.: HKES160300051102

Page: 103 of 191


Test mode: 802.11n(HT20) Test channel: Lowest








Report No.: HKES160300051102 Page: 104 of 191











Report No.: HKES160300051102 Page: 105 of 191









Report No.: HKES160300051102

Page: 106 of 191


Test mode: 802.11n(HT20) Test channel: Highest








Report No.: HKES160300051102 Page: 107 of 191











Report No.: HKES160300051102 Page: 108 of 191








Report No.: HKES160300051102

Page: 109 of 191



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


997 MHz/

Stop 10 GHz


Start 30 MHz



Report No.: HKES160300051102 Page: 110 of 191










Report No.: HKES160300051102 Page: 111 of 191







Report No.: HKES160300051102

Page: 112 of 191

#### Antenna 2


Test mode: 802.11b Test channel: Lowest








Report No.: HKES160300051102 Page: 113 of 191











Report No.: HKES160300051102 Page: 114 of 191









Report No.: HKES160300051102

Page: 115 of 191


Test mode: 802.11b Test channel: Highest








Report No.: HKES160300051102 Page: 116 of 191





Test mode:	802.11g	Test channel:	Lowest





Report No.: HKES160300051102 Page: 117 of 191









Report No.: HKES160300051102

Page: 118 of 191


Test mode: 802.11g Test channel: Middle








Report No.: HKES160300051102 Page: 119 of 191











Report No.: HKES160300051102 Page: 120 of 191









Report No.: HKES160300051102

Page: 121 of 191


Test mode: 802.11n(HT20) Test channel: Lowest








Report No.: HKES160300051102











Report No.: HKES160300051102 Page: 123 of 191









Report No.: HKES160300051102

Page: 124 of 191


Test mode: 802.11n(HT20) Test channel: Highest








Report No.: HKES160300051102











Report No.: HKES160300051102 Page: 126 of 191








Report No.: HKES160300051102


Page: 127 of 191


Test mode: 802.11n(HT40) Test channel: Middle






Report No.: HKES160300051102







Report No.: HKES160300051102 Page: 129 of 191



<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."





Report No.: HKES160300051102

Page: 130 of 191

#### Antenna 3


Test mode: 802.11b Test channel: Lowest








Report No.: HKES160300051102 Page: 131 of 191











Report No.: HKES160300051102 Page: 132 of 191









Report No.: HKES160300051102

Page: 133 of 191


Test mode: 802.11b Test channel: Highest








Report No.: HKES160300051102 Page: 134 of 191





Test mode: 802.11g Test channel: Lowest





Report No.: HKES160300051102









Report No.: HKES160300051102

Page: 136 of 191


Test mode: 802.11g Test channel: Middle








Report No.: HKES160300051102 Page: 137 of 191











Report No.: HKES160300051102 Page: 138 of 191








Report No.: HKES160300051102

Page: 139 of 191



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


997 MHz/

Start 30 MHz


Stop 10 GHz



Report No.: HKES160300051102 Page: 140 of 191











Report No.: HKES160300051102 Page: 141 of 191









Report No.: HKES160300051102

Page: 142 of 191


Test mode: 802.11n(HT20) Test channel: Highest








Report No.: HKES160300051102 Page: 143 of 191











Report No.: HKES160300051102 Page: 144 of 191









Report No.: HKES160300051102

Page: 145 of 191


Test mode: 802.11n(HT40) Test channel: Middle








Report No.: HKES160300051102 Page: 146 of 191











Report No.: HKES160300051102





#### Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: HKES160300051102

Page: 148 of 191

#### 6.8 Radiated Spurious Emissions


Test Requirement:	47 CFR Part 15C Section	n 15.209 and 15.20	05						
Test Method:	ANSI C63.10 2013, secti	on 11.12.2.7							
Test Site:	Measurement Distance:	3m (Semi-Anecho	ic Chamber)						
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark				
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak				
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average				
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak				
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak				
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average				
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak				
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak				
	Above 1GHz	Peak	1MHz	3MHz	Peak				
	Above IGHZ	Peak	1MHz	10Hz	Average				
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)				
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300				
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30				
	1.705MHz-30MHz	30	-	-	30				
	30MHz-88MHz	100	40.0	Quasi-peak	3				
	88MHz-216MHz	150	43.5	Quasi-peak	3				
	216MHz-960MHz	200	46.0	Quasi-peak	3				
	960MHz-1GHz	500	54.0	Quasi-peak	3				
	Above 1GHz	500	54.0	Average	3				
	Note: 15.35(b), Unless of	•		•					
	emissions is 20dB above the maximum permitted average emission limit								
	applicable to the equipment under test. This peak limit applies to the total peak								
	emission level rad	iated by the device	9.						



Report No.: HKES160300051102

Page: 149 of 191

#### Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



Report No.: HKES160300051102

Page: 150 of 191

	g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
	h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel				
	i. Repeat above procedures until all frequencies measured was complete.				
	Transmitting with all kind of modulations, data rates.				
Mode:					
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;				
	6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case				
	of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)				
	For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case.				
	Only the worst case is recorded in the report.				
Instruments Used:	Refer to section 5.10 for details				
Test Results:	Pass				




Report No.: HKES160300051102

Page: 151 of 191

#### 6.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical



Condition: 3m VERTICAL

Job No. : 511IT Test mode: Tx Mode


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	30.96	0.60	18.36	27.35	42.45	34.06	40.00	-5.94
2	39.71	0.60	13.34	27.32	46.68	33.30	40.00	-6.70
3	62.87	0.80	7.11	27.26	53.26	33.91	40.00	-6.09
4	89.28	1.10	8.73	27.22	50.57	33.18	43.50	-10.32
5	125.01	1.26	8.00	27.04	51.58	33.80	43.50	-9.70
6	878.32	3.52	22.85	26.89	35.70	35.18	46.00	-10.82



Report No.: HKES160300051102

Page: 152 of 191

Test mode: Transmitting Horizontal



Condition: 3m HORIZONTAL

Job No. : 511IT Test mode: Tx Mode

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.42	0.60	18.72	27.36	32.29	24.25	40.00	-15.75
2	34.88	0.60	15.96	27.34	35.57	24.79	40.00	-15.21
3	62.00	0.80	7.14	27.26	48.61	29.29	40.00	-10.71
4	350.48	2.06	15.51	26.79	42.45	33.23	46.00	-12.77
5	539.48	2.64	18.75	27.63	37.86	31.62	46.00	-14.38
6 pp	599.32	2.70	19.68	27.54	40.56	35.40	46.00	-10.60



Report No.: HKES160300051102

Page: 153 of 191

#### 6.8.2 Transmitter emission above 1GHz

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3770.567	32.78	7.73	38.47	48.05	50.09	74	-23.91	Vertical
4824.000	34.12	8.90	38.75	45.64	49.91	74	-24.09	Vertical
6140.076	34.77	10.38	38.78	45.90	52.27	74	-21.73	Vertical
7236.000	35.58	10.69	37.63	42.13	50.77	74	-23.23	Vertical
9648.000	37.10	12.52	36.29	35.63	48.96	74	-25.04	Vertical
12603.270	37.90	14.44	37.75	38.07	52.66	74	-21.34	Vertical
3825.521	32.93	7.75	38.49	45.15	47.34	74	-26.66	Horizontal
4824.000	34.12	8.90	38.75	46.45	50.72	74	-23.28	Horizontal
6034.386	34.72	10.52	38.91	45.38	51.71	74	-22.29	Horizontal
7236.000	35.58	10.69	37.63	42.77	51.41	74	-22.59	Horizontal
9648.000	37.10	12.52	36.29	35.62	48.95	74	-25.05	Horizontal
12658.090	37.93	14.60	37.80	38.28	53.01	74	-20.99	Horizontal

Test mode:	802.1	11b	Test ch	annel:	Middle	Remark	:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3770.567	32.78	7.73	38.47	45.90	47.94	74	-26.06	Vertical
4874.000	34.17	8.97	38.76	46.06	50.44	74	-23.56	Vertical
6087.002	34.74	10.45	38.85	45.92	52.26	74	-21.74	Vertical
7311.000	35.54	10.72	37.59	41.36	50.03	74	-23.97	Vertical
9748.000	37.10	12.58	36.16	39.85	53.37	74	-20.63	Vertical
12639.790	37.92	14.55	37.79	38.61	53.29	74	-20.71	Vertical
3803.444	32.90	7.74	38.49	45.65	47.80	74	-26.20	Horizontal
4874.000	34.17	8.97	38.76	46.09	50.47	74	-23.53	Horizontal
6140.076	34.77	10.38	38.78	45.77	52.14	74	-21.86	Horizontal
7311.000	35.54	10.72	37.59	41.96	50.63	74	-23.37	Horizontal
9748.000	37.10	12.58	36.16	39.64	53.16	74	-20.84	Horizontal
12639.790	37.92	14.55	37.79	38.99	53.67	74	-20.33	Horizontal



12603.270

37.90

### SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: HKES160300051102

-20.26

74

Horizontal

Page: 154 of 191

Test mode:	802.1	11b	Test ch	annel:	Highest	Remark	:	Peak	
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n	
3825.521	32.93	7.75	38.49	45.38	47.57	74	-26.43	Vertical	
4924.000	34.22	9.04	38.77	45.95	50.44	74	-23.56	Vertical	
6122.333	34.76	10.40	38.80	45.60	51.96	74	-22.04	Vertical	
7386.000	35.51	10.75	37.56	41.45	50.15	74	-23.85	Vertical	
9848.000	37.15	12.63	36.03	39.55	53.30	74	-20.70	Vertical	
12603.270	37.90	14.44	37.75	37.97	52.56	74	-21.44	Vertical	
3825.521	32.93	7.75	38.49	45.97	48.16	74	-25.84	Horizontal	
4924.000	34.22	9.04	38.77	46.42	50.91	74	-23.09	Horizontal	
6087.002	34.74	10.45	38.85	45.71	52.05	74	-21.95	Horizontal	
7386.000	35.51	10.75	37.56	41.96	50.66	74	-23.34	Horizontal	
9848.000	37.15	12.63	36.03	38.79	52.54	74	-21.46	Horizontal	

39.15

53.74

37.75

14.44

Test mode:	8	802.1	11g	Test ch	annel:	Lowest Remark:		Peak	
Frequency (MHz)	Anter facto (dB/	ors	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3770.567	32.7	78	7.73	38.47	46.22	48.26	74	-25.74	Vertical
4824.000	34.1	12	8.90	38.75	48.88	53.15	74	-20.85	Vertical
5999.562	34.7	70	10.56	38.96	45.99	52.29	74	-21.71	Vertical
7236.000	35.5	58	10.69	37.63	42.85	51.49	74	-22.51	Vertical
9648.000	37.1	10	12.52	36.29	36.58	49.91	74	-24.09	Vertical
12603.270	37.9	90	14.44	37.75	38.53	53.12	74	-20.88	Vertical
3915.118	33.0	)2	7.78	38.53	46.01	48.28	74	-25.72	Horizontal
4824.000	34.1	12	8.90	38.75	49.57	53.84	74	-20.16	Horizontal
6016.949	34.7	71	10.54	38.94	45.65	51.96	74	-22.04	Horizontal
7236.000	35.5	58	10.69	37.63	43.64	52.28	74	-21.72	Horizontal
9648.000	37.1	10	12.52	36.29	34.83	48.16	74	-25.84	Horizontal
12639.790	37.9	92	14.55	37.79	38.92	53.60	74	-20.40	Horizontal



Report No.: HKES160300051102

Page: 155 of 191

Test mode:	802.11g	Test channel:	Middle	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3803.444	32.90	7.74	38.49	45.69	47.84	74	-26.16	Vertical
4874.000	34.17	8.97	38.76	45.61	49.99	74	-24.01	Vertical
6140.076	34.77	10.38	38.78	45.79	52.16	74	-21.84	Vertical
7311.000	35.54	10.72	37.59	41.84	50.51	74	-23.49	Vertical
9748.000	37.10	12.58	36.16	39.11	52.63	74	-21.37	Vertical
12530.530	37.83	14.24	37.68	39.14	53.53	74	-20.47	Vertical
3814.467	32.91	7.75	38.49	45.39	47.56	74	-26.44	Horizontal
4874.000	34.17	8.97	38.76	47.31	51.69	74	-22.31	Horizontal
6140.076	34.77	10.38	38.78	45.99	52.36	74	-21.64	Horizontal
7311.000	35.54	10.72	37.59	41.59	50.26	74	-23.74	Horizontal
9748.000	37.10	12.58	36.16	39.60	53.12	74	-20.88	Horizontal
12603.270	37.90	14.44	37.75	38.15	52.74	74	-21.26	Horizontal

Test mode: 802.11g		11g	Test ch	annel:	Highest	Remark	:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3915.118	33.02	7.78	38.53	46.29	48.56	74	-25.44	Vertical
4924.000	34.22	9.04	38.77	47.18	51.67	74	-22.33	Vertical
6265.724	34.80	10.22	38.61	46.38	52.79	74	-21.21	Vertical
7386.000	35.51	10.75	37.56	41.60	50.30	74	-23.70	Vertical
9848.000	37.15	12.63	36.03	39.85	53.60	74	-20.40	Vertical
12676.420	37.94	14.65	37.82	37.75	52.52	74	-21.48	Vertical
4018.425	33.15	7.83	38.56	47.36	49.78	74	-24.22	Horizontal
4924.000	34.22	9.04	38.77	47.31	51.80	74	-22.20	Horizontal
6016.949	34.71	10.54	38.94	46.20	52.51	74	-21.49	Horizontal
7386.000	35.51	10.75	37.56	41.76	50.46	74	-23.54	Horizontal
9848.000	37.15	12.63	36.03	39.99	53.74	74	-20.26	Horizontal
12566.850	37.87	14.34	37.72	37.77	52.26	74	-21.74	Horizontal



Report No.: HKES160300051102

Page: 156 of 191

Test mode: 802.11n(HT20) Test channel:	Lowest	Remark:	Peak	l
--	--------	---------	------	---

Frequency	Antenna factors	Cable loss	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Polarizatio
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	n
3770.567	32.78	7.73	38.47	46.52	48.56	74	-25.44	Vertical
4824.000	34.12	8.90	38.75	45.57	49.84	74	-24.16	Vertical
6122.333	34.76	10.40	38.80	45.75	52.11	74	-21.89	Vertical
7236.000	35.58	10.69	37.63	42.65	51.29	74	-22.71	Vertical
9648.000	37.10	12.52	36.29	35.15	48.48	74	-25.52	Vertical
12603.270	37.90	14.44	37.75	38.42	53.01	74	-20.99	Vertical
3870.060	32.97	7.77	38.51	45.42	47.65	74	-26.35	Horizontal
4824.000	34.12	8.90	38.75	48.83	53.10	74	-20.90	Horizontal
5999.562	34.70	10.56	38.96	45.93	52.23	74	-21.77	Horizontal
7236.000	35.58	10.69	37.63	42.49	51.13	74	-22.87	Horizontal
9648.000	37.10	12.52	36.29	35.46	48.79	74	-25.21	Horizontal
12639.790	37.92	14.55	37.79	38.83	53.51	74	-20.49	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak
------------	---------------	---------------	--------	---------	------

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3825.521	32.93	7.75	38.49	45.23	47.42	74	-26.58	Vertical
4874.000	34.17	8.97	38.76	46.90	51.28	74	-22.72	Vertical
5964.939	34.61	10.46	38.95	46.10	52.22	74	-21.78	Vertical
7311.000	35.54	10.72	37.59	42.41	51.08	74	-22.92	Vertical
9748.000	37.10	12.58	36.16	39.01	52.53	74	-21.47	Vertical
12603.270	37.90	14.44	37.75	38.61	53.20	74	-20.80	Vertical
3892.524	32.99	7.77	38.52	45.89	48.13	74	-25.87	Horizontal
4874.000	34.17	8.97	38.76	47.50	51.88	74	-22.12	Horizontal
5794.797	34.20	9.98	38.93	46.50	51.75	74	-22.25	Horizontal
7311.000	35.54	10.72	37.59	41.26	49.93	74	-24.07	Horizontal
9748.000	37.10	12.58	36.16	39.46	52.98	74	-21.02	Horizontal
12639.790	37.92	14.55	37.79	38.81	53.49	74	-20.51	Horizontal



12639.790

Test mode:

37.92

14.55

37.79

802.11n(HT40) | Test channel: | Lowest

#### SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: HKES160300051102

Page: 157 of 191

Test mode:		802.1	1n(HT20)	Test ch	annel:	Highest	Highest Remark:		Peak
Frequency (MHz)	fac	enna ctors 3/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3792.453	32	2.87	7.74	38.48	45.55	47.68	74	-26.32	Vertical
4924.000	34	.22	9.04	38.77	47.37	51.86	74	-22.14	Vertical
6016.949	34	.71	10.54	38.94	45.49	51.80	74	-22.20	Vertical
7386.000	35	5.51	10.75	37.56	42.20	50.90	74	-23.10	Vertical
9848.000	37	'.15	12.63	36.03	40.01	53.76	74	-20.24	Vertical
12530.530	37	'.83	14.24	37.68	38.88	53.27	74	-20.73	Vertical
3770.567	32	2.78	7.73	38.47	46.49	48.53	74	-25.47	Horizontal
4924.000	34	.22	9.04	38.77	46.61	51.10	74	-22.90	Horizontal
6034.386	34	.72	10.52	38.91	45.58	51.91	74	-22.09	Horizontal
7386.000	35	5.51	10.75	37.56	41.42	50.12	74	-23.88	Horizontal
9848.000	37	'.15	12.63	36.03	39.80	53.55	74	-20.45	Horizontal

37.79

52.47

74

Remark:

-21.53

Horizontal

Peak

rest mode.	002.	1111(11140)	1 001 011	ariirior.	LOWCOL	Homan.		1 Car
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3995.234	33.10	7.81	38.56	47.71	50.06	74	-23.94	Vertical
4844.000	34.14	8.92	38.76	45.82	50.12	74	-23.88	Vertical
6104.642	34.75	10.42	38.82	45.66	52.01	74	-21.99	Vertical
7266.000	35.57	10.70	37.61	42.34	51.00	74	-23.00	Vertical
9688.000	37.10	12.54	36.24	37.16	50.56	74	-23.44	Vertical
12639.790	37.92	14.55	37.79	38.77	53.45	74	-20.55	Vertical
3803.444	32.90	7.74	38.49	46.36	48.51	74	-25.49	Horizontal
4844.000	34.14	8.92	38.76	46.15	50.45	74	-23.55	Horizontal
6016.949	34.71	10.54	38.94	45.64	51.95	74	-22.05	Horizontal
7266.000	35.57	10.70	37.61	41.07	49.73	74	-24.27	Horizontal
9688.000	37.10	12.54	36.24	36.43	49.83	74	-24.17	Horizontal
12603.270	37.90	14.44	37.75	39.10	53.69	74	-20.31	Horizontal



Report No.: HKES160300051102

Page: 158 of 191

Test mode:	802.11n(HT40)	Test channel:	Middle	Remark:	Peak
	\ /				

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3770.567	32.78	7.73	38.47	45.95	47.99	74	-26.01	Vertical
4874.000	34.17	8.97	38.76	46.27	50.65	74	-23.35	Vertical
6140.076	34.77	10.38	38.78	45.56	51.93	74	-22.07	Vertical
7311.000	35.54	10.72	37.59	41.61	50.28	74	-23.72	Vertical
9748.000	37.10	12.58	36.16	38.98	52.50	74	-21.50	Vertical
12639.790	37.92	14.55	37.79	37.75	52.43	74	-21.57	Vertical
3792.453	32.87	7.74	38.48	45.38	47.51	74	-26.49	Horizontal
4874.000	34.17	8.97	38.76	46.24	50.62	74	-23.38	Horizontal
6122.333	34.76	10.40	38.80	45.26	51.62	74	-22.38	Horizontal
7311.000	35.54	10.72	37.59	41.59	50.26	74	-23.74	Horizontal
9748.000	37.10	12.58	36.16	39.34	52.86	74	-21.14	Horizontal
12603.270	37.90	14.44	37.75	38.60	53.19	74	-20.81	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak
------------	---------------	---------------	---------	---------	------

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarizatio n
3770.567	32.78	7.73	38.47	48.97	51.01	74	-22.99	Vertical
4904.000	34.21	9.01	38.77	46.07	50.52	74	-23.48	Vertical
6104.642	34.75	10.42	38.82	45.47	51.82	74	-22.18	Vertical
7356.000	35.52	10.74	37.57	41.30	49.99	74	-24.01	Vertical
9808.000	37.11	12.61	36.08	39.40	53.04	74	-20.96	Vertical
12639.790	37.92	14.55	37.79	37.52	52.20	74	-21.80	Vertical
3814.467	32.91	7.75	38.49	44.73	46.90	74	-27.10	Horizontal
4904.000	34.21	9.01	38.77	46.42	50.87	74	-23.13	Horizontal
6034.386	34.72	10.52	38.91	45.90	52.23	74	-21.77	Horizontal
7356.000	35.52	10.74	37.57	42.52	51.21	74	-22.79	Horizontal
9808.000	37.11	12.61	36.08	39.85	53.49	74	-20.51	Horizontal
12603.270	37.90	14.44	37.75	38.42	53.01	74	-20.99	Horizontal



Report No.: HKES160300051102

Page: 159 of 191

#### Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: HKES160300051102

Page: 160 of 191

#### 6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section	15.209 and 15.205						
Test Method:	ANSI C63.10 2013, section	n 6.10.5						
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark					
	30MHz-88MHz	40.0	Quasi-peak Value					
	88MHz-216MHz	43.5	Quasi-peak Value					
	216MHz-960MHz	46.0	Quasi-peak Value					
	960MHz-1GHz	54.0	Quasi-peak Value					
	Above 1GHz	54.0 Average Value						
	Above IGHZ	74.0	Peak Value					
Test Setup:								






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: HKES160300051102

Page: 161 of 191

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.  b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.  c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.  d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.  e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.  f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel , the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Final Test Mode:  Transmitting with all kind of modulations, data rates.  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11n(HTA0)  Only the worst case is recorded in the report.  Instruments Used:  Refer to section 5.10 for details		
1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.  c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.  d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.  e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.  f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel , the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Transmitting with all kind of modulations, data rates.  Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.	Test Procedure:	meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest
antenna, which was mounted on the top of a variable-height antenna tower.  d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.  e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.  f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel , the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Transmitting with all kind of modulations, data rates.  Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.		1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest
ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.  e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.  f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel , the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Transmitting with all kind of modulations, data rates.  Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used:  Refer to section 5.10 for details		antenna, which was mounted on the top of a variable-height antenna
and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.  f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel, the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Transmitting with all kind of modulations, data rates.  Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Refer to section 5.10 for details		ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make
Specified Bandwidth with Maximum Hold Mode.  g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel, the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode: Transmitting with all kind of modulations, data rates.  Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;  6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20)  7 (Although Pre-scan, find the 1mbps)  8 (Although Pre-scan for the issue worst case of 802.11b;  9 (Although Pre-scan for the issue worst case of 802.11b;  10 (Although Pre-scan for the issue worst case of 802.11b;  11 (Although Pre-scan for the issue worst case of 802.11b;  12 (Although Pre-scan for the issue worst case of 802.11b;  13 (Although Pre-scan for the issue worst case of 802.11b;  14 (Although Pre-scan for the issue worst case of 802.11b;  15 (Although Pre-scan for the issue worst case of 802.11b;  16 (Although Pre-scan for the issue worst case of 802.11b;  17 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case of 802.11b;  18 (Although Pre-scan for the issue worst case		and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to
transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel  h. Test the EUT in the lowest channel, the Highest channel  i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode:  Transmitting with all kind of modulations, data rates.  Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;  6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used:  Refer to section 5.10 for details		
i. Repeat above procedures until all frequencies measured was complete.  Exploratory Test Mode: Transmitting with all kind of modulations, data rates.  Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used: Refer to section 5.10 for details		transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for
complete.  Exploratory Test Mode: Transmitting with all kind of modulations, data rates.  Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;  6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used: Refer to section 5.10 for details		h. Test the EUT in the lowest channel, the Highest channel
Final Test Mode:  Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;  6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used:  Refer to section 5.10 for details		
6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)  Only the worst case is recorded in the report.  Instruments Used: Refer to section 5.10 for details	Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40) Only the worst case is recorded in the report.  Instruments Used: Refer to section 5.10 for details	Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b;
Instruments Used: Refer to section 5.10 for details		case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40)
Test Results: Pass		
	Test Results:	Pass




Report No.: HKES160300051102

Page: 162 of 191

Test plot as follows:

Worse case mode: 802.11b Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 0511IT

Mode: : 2412 Band edge

: B


Cable Ant Preamp 0ver Read Limit Freq Loss Factor Factor Level Level Line Limit MHz dB dB/m dBuV dBuV/m dBuV/m dB 38.11 51.91 47.71 74.00 -26.29 2390.00 28.57 5.36 28.66 38.11 106.43 102.34 74.00 28.34 2413.14



Report No.: HKES160300051102

Page: 163 of 191

Worse case mode: 802.11b Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2412 Band edge

: B


Ant Preamp 0ver Cable Read Limit Freq Loss Factor Factor Level Level Line Limit dB dB/m dBuV dBuV/m dBuV/m MHz dB 2390.00 5.34 28.57 38.11 54.08 49.88 74.00 -24.12 5.35 28.65 38.11 108.88 104.77 74.00 30.77 2411.24



Report No.: HKES160300051102

Page: 164 of 191

Worse case mode: 802.11b Test channel: Highest Remark: Peak Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2462 Band edge

: B


	Freq						Limit Line	
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2461.01							
2	2483.50	5.41	28.98	38.12	52.88	49.15	74.00	-24.85



Report No.: HKES160300051102

Page: 165 of 191

Worse case mode: 802.11b Test channel: Highest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2462 Band edge

: B


	Limit Line						Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	
30.08	74.00	104.08	107.92	38.12	28.89	5.39	2463.00	1 рр
-23.52	74.00	50.48	54.21	38.12	28.98	5.41	2483.50	2



Report No.: HKES160300051102

Page: 166 of 191

Worse case mode: 802.11g Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 0511IT

Mode: : 2412 Band edge

: G


	Freq				Read Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pp	2390.00 2416.74							



Report No.: HKES160300051102

Page: 167 of 191

Worse case mode: 802.11g Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2412 Band edge

: G


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit dB dB/m dBuV dBuV/m dBuV/m 5.34 28.57 38.11 60.59 56.39 2414.72 5.36 28.67 38.11 105.27 101.19 74.00 27.19



Report No.: HKES160300051102

Page: 168 of 191

Worse case mode: 802.11g Test channel: Lowest Remark: Average Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2412 Band edge

: G


				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2390.00	l ) nn



Report No.: HKES160300051102

Page: 169 of 191

Test channel: Worse case mode: 802.11g Lowest Remark: Average Horizontal



Condition: 3m Horizontal

: 0511IT Job No:

: 2412 Band edge Mode:


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit dB dB/m dBuV dBuV/m dBuV/m 5.34 28.57 38.11 42.39 38.19 2414.94 5.36 28.67 38.11 94.58 90.50 54.00 36.50



Report No.: HKES160300051102

Page: 170 of 191

Worse case mode: 802.11g Test channel: Highest Remark: Peak Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2462 Band edge

: G


	Limit Line						Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2469.53 2483.50	



Report No.: HKES160300051102

Page: 171 of 191

Worse case mode: 802.11g Test channel: Highest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2462 Band edge

: G


	Limit Line						Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2469.33	



Report No.: HKES160300051102

Page: 172 of 191

Worse case mode: 802.11g Test channel: Highest Remark: Average Vertical



Condition: 3m Vertical Job No: : 0511IT

Mode: : 2462 Band edge

: G


	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2469.63 2483.50							



Report No.: HKES160300051102

Page: 173 of 191

Worse case mode: 802.11g Test channel: Highest Remark: Average Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2462 Band edge

: G


				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2469.53 2483.50	



Report No.: HKES160300051102

Page: 174 of 191

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 0511IT

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Loss Factor Factor Freq Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m 2390.00 5.34 28.57 38.11 66.10 61.90 74.00 -12.10 2 pp 2415.61 38.11 103.32 5.36 28.67 99.24 74.00 25.24



Report No.: HKES160300051102

Page: 175 of 191

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Line Limit Level MHz dB dB/m dB dBuV dBuV/m dBuV/m 2390.00 5.34 28.57 38.11 66.32 62.12 74.00 -11.88 2416.96 5.36 28.68 38.11 103.51 99.44 74.00 25.44



Report No.: HKES160300051102

Page: 176 of 191

Worse case mode: 802.11n(HT20) Test channel: Lowest Remark: Average Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2412 Band edge

: N20


	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pp	2390.00 2415.61							



Report No.: HKES160300051102

Page: 177 of 191

Worse case mode: | 802.11n(HT20) | Test channel: | Lowest | Remark: | Average | Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2412 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dΒ 38.11 46.99 42.79 54.00 -11.21 2390.00 5.34 28.57 2 pp 2413.59 5.36 28.66 38.11 91.62 87.53 54.00 33.53



Report No.: HKES160300051102

Page: 178 of 191

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Peak Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2462 Band edge

: N20


	Limit Line						Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	_
							2468.93 2483.50	



Report No.: HKES160300051102

Page: 179 of 191

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit MHz dB dB/m dΒ dBuV dBuV/m dBuV/m 38.12 104.38 100.50 74.00 26.50 2454.41 5.39 28.85 2483.50 5.41 28.98 38.12 65.02 61.29 74.00 -12.71



Report No.: HKES160300051102

Page: 180 of 191

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Average Vertical



Condition: 3m Vertical Job No: : 0511IT

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Line Limit dB dBuV dBuV/m dBuV/m dB MHz dB/m dΒ 2469.13 5.40 28.92 38.12 93.80 90.00 54.00 2 2483.50 5.41 28.98 38.12 54.63 50.90 54.00



Report No.: HKES160300051102

Page: 181 of 191

Worse case mode: 802.11n(HT20) Test channel: Highest Remark: Average Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2462 Band edge

: N20


Cable Ant Preamp Read Limit 0ver Loss Factor Factor Limit Level Level Line Freq MHz dB dB/m dB dBuV dBuV/m dBuV/m 1 pp 2464.15 5.39 28.90 38.12 93.42 89.59 54.00 35.59 28.98 38.12 49.44 45.71 54.00 2483.50 5.41



Report No.: HKES160300051102

Page: 182 of 191

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2422 Band edge

: N40


Freq						Limit Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
2390.00 2439.36							



Report No.: HKES160300051102

Page: 183 of 191

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2422 Band edge

: N40


	Freq						Limit Line	
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2390.00 2438.49							



Report No.: HKES160300051102

Page: 184 of 191

Worse case mode: 802.11n(HT40) Test channel: Lowest Remark: Average Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2422 Band edge

: N40


				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-
							2390.00	1 2 nn



Report No.: HKES160300051102

Page: 185 of 191

Worse case mode: | 802.11n(HT40) | Test channel: | Lowest | Remark: | Average | Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2422 Band edge

: N40


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Line Limit Level dB dBuV dBuV/m dBuV/m MHz dB/m dB 2390.00 5.34 28.57 38.11 51.38 47.18 54.00 -6.82 2 pp 2439.93 5.38 28.79 38.11 89.72 85.78 54.00 31.78



Report No.: HKES160300051102

Page: 186 of 191

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Peak Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2452 Band edge

: N40


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Line Limit dB dBuV dBuV/m dBuV/m dB MHz dB/m dΒ 2441.21 5.38 28.79 38.11 103.59 99.65 74.00 2483.50 5.41 28.98 38.12 69.63 65.90



Report No.: HKES160300051102

Page: 187 of 191

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2452 Band edge

: N40


Freq							Over Limit
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
 2439.82 2483.50							



Report No.: HKES160300051102

Page: 188 of 191

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Average Vertical



Condition: 3m Vertical

Job No: : 0511IT

Mode: : 2452 Band edge

: N40


Freq						Limit Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
 2441.62 2483.50							



Report No.: HKES160300051102

Page: 189 of 191

Worse case mode: 802.11n(HT40) Test channel: Highest Remark: Average Horizontal



Condition: 3m Horizontal

Job No: : 0511IT

Mode: : 2452 Band edge

: N40

	Freq						Limit Line	
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2440.10 2483.50							

#### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: HKES160300051102

Page: 190 of 191

#### 7 Photographs - EUT Test Setup

Test model No.: AP One Enterprise,

#### 7.1 Conducted Emission



#### 7.2 Radiated Emission






Report No.: HKES160300051102

Page: 191 of 191

#### 7.3 Radiated Spurious Emission



#### 8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for HKES1603000511IT.