






Test Report No:  
2330881R-RFUSV17S-A

## RF EXPOSURE EVALUATION DECLARATION

Product Name	Peplink Pepwave Wireless Product
Brand Name	 <b>PEPWAVE</b>
Model No.	UBR Plus UBR-PLUS-LTEA-US-T-PRM
FCC ID	U8G-P1AC200
Applicant's Name / Address	PISMO LABS TECHNOLOGY LIMITED A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Hong Kong
Manufacturer's Name / Address	PISMO LABS TECHNOLOGY LIMITED A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Hong Kong
Test Method Requested, Standard	FCC CFR Title 47 Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Verdict Summary	IN COMPLIANCE
Documented By	 Amelia Wu
Approved By	 Rueyyan Lin
Date of Receipt	Mar. 24, 2023
Date of Issue	Jul. 19, 2023
Report Version	V1.0

## INDEX

---

	page
Competences and Guarantees.....	3
General Conditions.....	3
Revision History.....	4
1. General Information.....	5
1.1. EUT Description.....	5
1.2. Testing Location Information.....	6
2. RF Exposure Evaluation.....	7
2.1. Test Limit.....	7
2.2. Test Result of RF Exposure Evaluation.....	9

## Competences and Guarantees

---

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## General Conditions

---

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

## Revision History

---

Version	Description	Issued Date
V1.0	Initial issue of report	Jul. 19, 2023

## 1. General Information


### 1.1. EUT Description

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
WiFi 2.4 GHz	2400 ~ 2483.5	2412 ~ 2462	802.11b: DSSS 802.11g/n/ac: OFDM
WiFi 5 GHz	5150 ~ 5250 5725 ~ 5850	5180 ~ 5240 5745 ~ 5825	802.11a/n/ac: OFDM

The EUT contains two of the same WWAN module, and the detail as below.

Brand Name	Model	FCC ID	Bands	Operating Frequency Range (MHz)	Function			
AirPrime	EM7411	N7NEM74B	WCDMA Band 2	Uplink: 1850 ~ 1910 Downlink: 1930 ~ 1990	WCDMA / HSDPA / DC-HSDPA / HSUPA / HSPA+			
			WCDMA Band 4	Uplink: 1710 ~ 1755 Downlink: 2110 ~ 2115				
			WCDMA Band 5	Uplink: 824 ~ 849 Downlink: 869 ~ 894				
						Bands	Operating Frequency Range (MHz)	Modulation Type
			LTE Band 2	Uplink: 1850 ~ 1910 Downlink: 1930 ~ 1990	QPSK / 16QAM / 64QAM			
			LTE Band 4	Uplink: 1710 ~ 1755 Downlink: 2110 ~ 2115				
			LTE Band 5	Uplink: 824 ~ 849 Downlink: 869 ~ 894				
			LTE Band 7	Uplink: 2500 ~ 2570 Downlink: 2620 ~ 2690				
			LTE Band 12	Uplink: 699 ~ 716 Downlink: 729 ~ 746				
			LTE Band 13	Uplink: 777 ~ 787 Downlink: 746 ~ 756				
			LTE Band 14	Uplink: 788 ~ 798 Downlink: 758 ~ 768				
			LTE Band 25	Uplink: 1850 ~ 1915 Downlink: 1930 ~ 1995				
			LTE Band 26	Uplink: 824 ~ 849 Downlink: 859 ~ 894				
			LTE Band 41	Uplink: 2496 ~ 2690 Downlink: 2496 ~ 2690				
			LTE Band 42	Uplink: 3400 ~ 3600 Downlink: 3400 ~ 3600				
			LTE Band 43	Uplink: 3600 ~ 3800 Downlink: 3600 ~ 3800				
			LTE Band 48	Uplink: 3550 ~ 3700 Downlink: 3550 ~ 3700				
			LTE Band 66	Uplink: 1710 ~ 1780 Downlink: 2110 ~ 2200				
LTE Band 71	Uplink: 663 ~ 698 Downlink: 617 ~ 652							

The difference for each model is shown as below:

Brand Name		Model No.	Description
	PEP WAVE	UBR Plus	There is nothing different of two models, just for different marketing use.
		UBR-PLUS-LTEA-US-T-PRM	

From the above models, model: UBR Plus was selected as representative model for the test and its data was recorded in this report.

Note: The above EUT information is declared by the manufacturer.

## 1.2. Testing Location Information

Testing Location Information		
Test Laboratory : DEKRA Testing and Certification Co., Ltd.		
1 (TAF: 3024)	ADD: No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001      FAX: +886-3-582-8958	
2 (TAF: 3024)	ADD: No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001      FAX: +886-3-582-8958	
Test site number for address 1 includes HC-SR02. Test site number for address 2 includes HC-CB02, HC-CB03, HC-CB04, HC-SR10 and HC-SR12.		

## 2. RF Exposure Evaluation

### 2.1. Test Limit

(A) Test Limit for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Test Limit for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz; \*Plane-wave equivalent power density

Power Density (S) is calculated by the following formula:

$$S = (P \cdot G) / 4\pi R^2$$

where:

S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

$\pi$  = 3.1416

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



## 2.2. Test Result of RF Exposure Evaluation

### Exposure Environment: General Population / Uncontrolled Exposure

Evaluation Mode	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Test Result (PASS/FAIL)
WiFi 2.4 GHz	29.780	950.605	0.189	1.000	PASS
WiFi 5 GHz Band 1	30.470	1114.295	0.222	1.000	PASS
WiFi 5 GHz Band 4	16.910	49.091	0.010	1.000	PASS
WCDMA Band 2	26.12	409.261	0.081	1.000	PASS
WCDMA Band 4	25.84	383.707	0.076	1.000	PASS
WCDMA Band 5	22.60	181.970	0.036	0.549	PASS
LTE Band 2	26.12	409.261	0.081	1.000	PASS
LTE Band 4	25.84	383.707	0.076	1.000	PASS
LTE Band 5	22.60	181.970	0.036	0.549	PASS
LTE Band 7	21.29	134.586	0.027	1.000	PASS
LTE Band 12	22.30	169.824	0.034	0.466	PASS
LTE Band 13	22.30	169.824	0.034	0.518	PASS
LTE Band 14	22.30	169.824	0.034	0.525	PASS
LTE Band 25	26.12	409.261	0.081	1.000	PASS
LTE Band 26	22.30	169.824	0.034	0.543	PASS
LTE Band 41	21.29	134.586	0.027	1.000	PASS
LTE Band 42	18.89	77.446	0.015	1.000	PASS
LTE Band 43	18.82	76.208	0.015	1.000	PASS
LTE Band 48	18.78	75.509	0.015	1.000	PASS
LTE Band 66	25.84	383.707	0.076	1.000	PASS
LTE Band 71	22.47	176.604	0.035	0.442	PASS

Distance (cm): 20 for Maximum Permissible Exposure.

**Co-location****Conclusion:**

The formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

**CPD = Calculation power density**

**LPD = Limit of power density**

1. WiFi 2.4 GHz + WiFi 5 GHz + WWAN module 1: LTE + WWAN module 2: LTE function =  $0.189 + 0.222 + 0.081 + 0.081 = 0.573$ , therefore the maximum calculations of above situations are less than the "1" limit.
2. WiFi 2.4 GHz + WiFi 5 GHz + WWAN module 1: LTE + WWAN module 2: WCDMA function =  $0.189 + 0.222 + 0.081 + 0.081 = 0.573$ , therefore the maximum calculations of above situations are less than the "1" limit.
3. WiFi 2.4 GHz + WiFi 5 GHz + WWAN module 1: WCDMA + WWAN module 2: WCDMA function =  $0.189 + 0.222 + 0.081 + 0.081 = 0.573$ , therefore the maximum calculations of above situations are less than the "1" limit.

**Note:**

1. The above EUT information is declared by the manufacturer.
2. The results are evaluated using the maximum power.