Table 1 – Label Artwork

Model	Peplink
MAX BR1 IP55	Model: MAX BR1 IP55  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455 CAN ICES-3(A)/NMB-3(A)  Made in Taiwan  Made in Taiwan  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference and (2) this device must accord any interference or received including
MAX BR1 IP55	IVI ? interference that may cause undesired operation.
	Model: MAX BR1 IP55  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9 Contains IC: 2417C-MC7355
	CAN ICES-3(A)/NMB-3(A)  Made in Taiwan  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
MAX BR1 LTE IP55	••••
	Model: MAX BR1 LTE IP55  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9 Contains IC: 2417C-MC7355 CAN ICES-3(A)/NMB-3(A)  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model	Peplink
Pismo AC9	Model: Pismo AC9  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin Contains FCC ID: W8G-P1ACS IC: 20682-P1ACS
	Contains IC: 2417C-MC7458 CAN ICES-3(A)/NMB-3(A  Made in Taiwan  Whistory and the service of the
Pismo AC9	Model: Pismo AC9  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520
	Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC Contains FCC ID: N7NMC7358 IC: 20682-P1AC9 Contains IC: 2417C-MC7358 CAN ICES-3(A)/NMB-3(A  Made in Taiwan This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

Model	Pepwave
MAX BR1 IP55	Model: MAX BR1 IP55  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520
	Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455 CAN ICES-3(A)/NMB-3(A) This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must
ı	accept any interference received, including interference that may cause undesired operation.
MAX BR1 IP55	Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  Made in Taiwan  Miade in Taiwan
MAX BR1 LTE IP55	Model: MAX BR1 LTE IP55  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  Made in Taiwan  Miade i

Model	Pepwave
MAX BR1 LTEA IP55	Model: MAX BR1 LTEA IP55  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520
	Default Access Username: admin http://192.168.50.1 Password: admin FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455
	Made in Taiwan  Wilson Can ICES-3(A)/NMB-3(A)  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
PismoAC9	Model: PismoAC9  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin
	http://192.168.50.1 Password: admin  Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455 CAN ICES-3(A)/NMB-3(A)  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
PismoAC9	Model: PismoAC9  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520
	Default Access Username: admin http://192.168.50.1 Password: admin FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9 Contains IC: 2417C-MC7355 CAN ICES-3(A)/NMB-3(A)
	Made in Taiwan  Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model	Pepwave	
Pismo AC9	IVIAGE IN I AIWAN Rules. Op condition harmful ii accept an	FCC ID: U8G-P1A Contains FCC ID: N7NMC7- IC: 20682-P1A Contains IC: 2417C-MC74 CAN ICES-3(A)/NMB-3 The complies with Part 15 of the FCC Teration is subject to following two Second in the subject to following two The sub
Pismo AC9	IVIAGE IN I AIWAN Rules. Op condition harmful ii accept an	FCC ID: U8G-P1A Contains FCC ID: N7NMC73 IC: 20682-P1A Contains IC: 2417C-MC73 CAN ICES-3(A)/NMB-3 te complies with Part 15 of the FCC teration is subject to following two s: (1) This device may not cause therference, and (2) this device must y interference received, including the that may cause undesired operations.

Model	Pismo
MAX BR1 IP55	Model: MAX BR1 IP55  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455
	CAN ICES-3(A)/NMB-3(A)  Made in Taiwan  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
MAX BR1 IP55	Model: MAX BR1 IP55  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  Contains FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9 Contains IC: 2417C-MC7355
	CAN ICES-3(A)/NMB-3(A)  Made in Taiwan  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
MAX BR1 LTE IP55	Model: MAX BR1 LTE IP55  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin
	http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9 Contains IC: 2417C-MC7355 CAN ICES-3(A)/NMB-3(A) This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Model	Pismo
MAX BR1 LTEA IP55	Model: MAX BR1 LTEA IP55  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  Made in Taiwan  Made in Taiwan  Might a subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
PismoAC9	Model: PismoAC9  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin
	http://192.168.50.1 Password: admin  FCC ID: U8G-P1ACS Contains FCC ID: N7NMC7355 IC: 20682-P1ACS Contains IC: 2417C-MC7355 CAN ICES-3(A)/NMB-3(A)  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
PismoAC9	Model: PismoAC9  Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin
	IC: 20682-P1AC9 Contains IC: 2417C-MC7455 CAN ICES-3(A)/NMB-3(A)  Made in Taiwan IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII

Model	Pismo
Pismo AC9	Product Code: MAX-BR1-LTEA-W-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520  Default Access Username: admin http://192.168.50.1 Password: admin  FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7455 IC: 20682-P1AC9 Contains IC: 2417C-MC7455 CAN ICES-3(A)/NMB-3(A)  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must
	M?  accept any interference received, including interference that may cause undesired operation.
Pismo AC9	Model: Pismo AC9  Product Code: MAX-BR1-LTE-US-IP55 Serial No.: 2935-3E89-516F LAN MAC: 00-1A-DD-50-75-20 AP Password: DD507520
	Default Access Username: admin http://192.168.50.1 Password: admin Contains FCC ID: U8G-P1AC9 Contains FCC ID: N7NMC7355 IC: 20682-P1AC9
	Contains IC: 2417C-MC7355  CAN ICES-3(A)/NMB-3(A)  Made in Taiwan  This device complies with Part 15 of the FCC Rules. Operation is subject to following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Figure 1 - FCC / IC Label Location:



