







Test report No.: 2360564R-RFUSV03S-A

TEST REPORT

Product Name	Peplink Pepwave Wireless Product
Trademark	
Model and /or type reference	Dome Pro LR DOM-PRO-LR-5GN-PRM
FCC ID	U8G-P1AX05LR
Applicant's name / address	PISMO LABS TECHNOLOGY LIMITED A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Hong Kong
Manufacturer's name	PISMO LABS TECHNOLOGY LIMITED
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart E ANSI C63.4: 2014, ANSI C63.10: 2013 KDB Publication 789033
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / Joanne Lin)	
Tested By (Senior Engineer / Ivan Chuang)	
Approved By (Senior Engineer / Jack Hsu)	
Date of Receipt	2023/06/17
Date of Issue	2023/09/21
Report Version	V2.0

INDEX

Page

1. General Information	6
1.1. EUT Description	6
1.2. Tested System Details	8
1.3. Configuration of tested System	8
1.4. EUT Exercise Software	8
1.5. Test Facility	9
1.6. List of Test Equipment	10
1.7. Uncertainty	12
2. Conducted Emission	13
2.1. Test Setup	13
2.2. Limits	13
2.3. Test Procedure	14
2.4. Test Result of Conducted Emission	14
3. Maximum conducted output power	16
3.1. Test Setup	16
3.2. Limits	17
3.3. Test Procedure	19
3.4. Test Result of Maximum conducted output power	20
4. Maximum Power Spectral Density	38
4.1. Test Setup	38
4.2. Limits	38
4.3. Test Procedure	39
4.4. Test Result of Maximum Power Spectral Density	40
5. Radiated Emission	52
5.1. Test Setup	52
5.2. Limits	53
5.3. Test Procedure	54
5.4. Test Result of Radiated Emission	56
6. Band Edge	70
6.1. Test Setup	70

6.2. Limits	70
6.3. Test Procedure.....	71
6.4. Test Result of Band Edge.....	72
7. Occupied Bandwidth	86
7.1. Test Setup.....	86
7.2. Limits	86
7.3. Test Procedure.....	86
7.4. Test Result of Occupied Bandwidth.....	87
8. Duty Cycle.....	91
8.1. Test Setup.....	91
8.2. Test Procedure.....	91
8.3. Test Result of Duty Cycle	92

Appendix 1: EUT Test Photographs

Appendix 2: Product Photos-Please refer to the file: 2360564R-Product Photos

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions


1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
2360564R-RFUSV03S-A	V1.0	Initial issue of report.	2023/09/14
2360564R-RFUSV03S-A	V2.0	Test Conducted Emission	2023/09/21

1. General Information


1.1. EUT Description

Product Name	Peplink Pepwave Wireless Product
Trademark	
Model and /or type reference	Dome Pro LR DOM-PRO-LR-5GN-PRM
EUT Rated Voltage	802.3at PoE+ (without 802.3at PoE+output) 802.3bt PoE+ (with 802.3at PoE+output)
EUT Test Voltage	802.3bt PoE+
Frequency Range	802.11a/n/ac/ax-20 MHz: 5180-5240 MHz, 5745-5825 MHz 802.11n/ac/ax-40 MHz: 5190-5230 MHz, 5755-5795 MHz 802.11ac/ax-80 MHz: 5210 MHz, 5775 MHz
Number of Channels	802.11a/n/ac/ax-20 MHz: 9CH 802.11n/ac/ax-40 MHz: 4CH 802.11ac/ax-80 MHz: 2CH
Data Rate	802.11a: 6-54 Mbps 802.11n: up to 300 MHz 802.11ac: up to 866.7 MHz 802.11ax: up to 1201 MHz
Type of Modulation	802.11n/ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Channel Control	Auto

For Without Sell Accessories Information

PoE	Brand: BILLION M/N: BP035-560054QAX Input: AC 100-240V~50-60Hz, 0.8A Output: 56V=0.536A
-----	--

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1		MR-10 (WiFi-1)	Omni-directional	9.4 dBi for 5150-5250 MHz 8.9 dBi for 5725-5850 MHz
2		MR-10 (WiFi-2)		7.3 dBi for 5150-5250 MHz 9.0 dBi for 5725-5850 MHz

Note: The antenna of EUT is conform to FCC 15.203. The antenna gain as by the manufacturer provided.

For power CDD Directional gain	For PSD CDD Directional gain
9.4dBi for 5150-5250MHz 9.0dBi for 5725-5850MHz	11.42dBi for 5150-5250MHz 11.96dBi for 5725-5850MHz

For Power Directional gain	For PSD Directional gain
5150MHz-5250MHz: Directional gain = 9.4 dBi	5150MHz-5250MHz: Directional gain = 11.42dBi
5725MHz-5850MHz: Directional gain = 9.0 dBi	5725MHz-5850MHz: Directional gain = 11.96 dBi
(Directional gain = $G_{ANT\ MAX} + \text{Array Gain}$, Array Gain = 0 dB for $N_{ANT} \leq 4$)	Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}]$ dBi

802.11a/n/ac/ax-20 MHz Center Working Frequency of Each Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	40	5200	44	5220	48	5240
149	5745	153	5765	157	5785	161	5805
165	5825	--	--	--	--	--	--

802.11n/ac/ax-40 MHz Center Working Frequency of Each Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230	151	5755	159	5795

802.11ac/ax-80 MHz Center Working Frequency of Each Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	--	--	--	--
42	5210	155	5775	--	--	--	--

Note:

1. This device is a Peplink Pepwave Wireless Product with built-in WLAN, this report for 5GHz WLAN.
2. It's declared by manufacture about all models are electrically identical, different model names for marketing purpose.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test. The other channels are for reference only.
4. Lowest data rates are tested in each mode. Only worst case is shown in the report. (802.11a is 6Mbps, 802.11n/ac/ax is MCS0)
5. The CDD mode is presented in the power output test item. For other test items, CDD mode is the worst case for the final test and shown in this report.
6. The spectrum plot against conducted item only shows the worst case.
7. This device does not support partial RU function.
8. Since the product supports Client and Outdoor AP, the test is evaluated to meet the Client and Outdoor AP Limit respectively. Radiated emission and radiated emission band edge uses the Client limit performed test.
9. These tests were conducted on a sample for the purpose of demonstrating compliance of 802.11a/n/ac/ax transmitter with Part 15 Subpart E for Unlicensed National Information Infrastructure devices.

Test Mode	Mode 1	Transmit (802.11a)
		Transmit (802.11n-20 MHz)
		Transmit (802.11n-40 MHz)
		Transmit (802.11ac-20 MHz)
		Transmit (802.11ac-40 MHz)
		Transmit (802.11ac-80 MHz)
		Transmit (802.11ax-20 MHz)
		Transmit (802.11ax-40 MHz)
		Transmit (802.11ax-80 MHz)


1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 PoE Adapter	BILLION	BP035-560054QAX	N/A	N/A
2 Notebook PC	DELL	Latitude 5501	8JHGL13	N/A

Cable Type	Cable Description
A LAN Cable	Shielded, 20m, two PCS.

1.3. Configuration of tested System



1.4. EUT Exercise Software

1	Setup the EUT as shown in Section 1.3.
2	Execute software “QSPR Version 5.0-00197” on the Notebook PC.
3	Configure the test mode, the test channel, and the data rate.
4	Press “OK” to start the continuous Transmit.
5	Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Conducted Emission	Temperature (°C)	10~40 °C	24.5 °C
	Humidity (%RH)	10~90 %	53.6 %
Radiated Emission	Temperature (°C)	10~40 °C	23.0 °C
	Humidity (%RH)	10~90 %	62.0 %
Conductive	Temperature (°C)	10~40 °C	22.0 °C
	Humidity (%RH)	10~90 %	55.0 %

USA	FCC Registration Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

1.6. List of Test Equipment

For Conduction Measurements / HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Two-Line V-Network	R&S	ENV216	101306	2023/03/16	2024/03/15
V	Two-Line V-Network	R&S	ENV216	101307	2023/08/17	2024/08/16
V	Coaxial Cable	SUHNER	RG400 BNC	RF001	2023/01/10	2024/01/09

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103466	2022/12/22	2023/12/21
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2023/05/15	2024/05/14
V	Power Sensor	KEYSIGHT	N1923A	MY59240002	2023/05/18	2024/05/17
V	Power Sensor	KEYSIGHT	N1923A	MY59240003	2023/05/18	2024/05/17

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: RF Conducted Test Tools R3 V3.0.0.14.

For Radiated Measurements (9kHz-1G) / HY-CB03

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	AMETEK	HLA6121	49611	2023/02/21	2024/02/20
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0678	2021/09/23	2023/09/22
	Horn Antenna	Com-Power	AH-840	101100	2021/10/04	2023/10/03
	Horn Antenna	RF SPIN	DRH18-E	210507A18ES	2023/05/11	2024/05/10
	Pre-Amplifier	SGH	0301	20211007-10	2023/01/10	2024/01/09
	Pre-Amplifier	SGH	PRAMP118	20200701	2023/01/10	2024/01/09
	Pre-Amplifier	EMCI	EMC05820SE	980310	2023/01/10	2024/01/09
	Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
	Coaxial Cable	EMCI	EMC102-KM-K M-600	1160314		
	Coaxial Cable	EMCI	EMC102-KM-K M-7000	170242		
	Filter	MICRO TRONICS	BRM50702	G269	2023/01/05	2024/01/04
	Filter	MICRO TRONICS	BRM50716	G196	2023/01/05	2024/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2022/12/05	2023/12/04
V	Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
V	Coaxial Cable	SGH	SGH18	2021005-1	2023/01/10	2024/01/09
	Coaxial Cable	SGH	SGH18	202108-4		
	Coaxial Cable	SGH	HA800	GD20110223-1		
	Coaxial Cable	SGH	HA800	GD20110222-3		

Note:

1. Bi-Log Antenna and Horn Antenna(AH-840) is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Radiated Measurements (1GHz-40GHz) / HY-CB01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
	Loop Antenna	AMETEK	HLA6121	49611	2023/02/21	2024/02/20
	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2023/08/09	2025/08/08
V	Horn Antenna	RF SPIN	DRH18-E	210802A18ES	2023/03/23	2024/03/22
V	Horn Antenna	Com-Power	AH-840	101101	2021/11/30	2023/11/29
V	Pre-Amplifier	SGH	0301	20211007-7	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC051845SE	980632	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980362	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
	Coaxial Cable	EMCI	EMC102-KM-K M-600	1160314		
	Coaxial Cable	EMCI	EMC102-KM-K M-7000	170242		
	Filter	MICRO TRONICS	BRM50702	G251	2023/01/05	2024/01/04
V	Filter	MICRO TRONICS	BRM50716	067	2023/01/05	2024/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2022/12/05	2023/12/04
V	Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
V	Coaxial Cable	SGH	SGH18	2021005-1	2023/01/10	2024/01/09
	Coaxial Cable	SGH	SGH18	202108-4		
	Coaxial Cable	SGH	HA800	GD20110223-1		
	Coaxial Cable	SGH	HA800	GD20110222-3		

Note:

1. Bi-Log Antenna and Horn Antenna(AH-840) is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
Conducted Emission	± 3.50 dB
Maximum conducted output power	Spectrum Analyzer: ± 2.14 dB Power Meter: ± 1.05 dB
Peak Power Spectral Density	± 2.14 dB
Radiated Emission	9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB
Band Edge	9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB
Occupied Bandwidth	± 1580.61 Hz
Duty Cycle	± 0.53 %

2. Conducted Emission

2.1. Test Setup



2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB μ V) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.


2.3. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50 μ H coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50 μ H coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4:2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.


2.4. Test Result of Conducted Emission



3. Maximun conducted output power


3.1. Test Setup

26dB Occupied Bandwidth




Conduction Power Measurement

Conduction Power Measurement (for 802.11an)



Conduction Power Measurement (for 802.11ac/ax)



3.2. Limits

For the band 5.15-5.25 GHz,

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W, provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, if transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, if transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point UNII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

The maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For CDD mode:

5150MHz-5250MHz: Directional gain = 9.4 dBi, Limit= 26.6dBm (Master)

5150MHz-5250MHz: Directional gain = 9.4 dBi, Limit= 20.6dBm (Slave)

5725MHz-5850MHz: Directional gain = 9.0 dBi, Limit= 27.0dBm

(Directional gain = $G_{ANT MAX} + \text{Array Gain}$, Array Gain = 0 dB for $N_{ANT} \leq 2$)

3.3. Test Procedure

As an alternative to FCC KDB-789033, the EUT maximum conducted output power was measured with an average power meter employing a video bandwidth greater than the 6dB BW of the emission under test. Maximum conducted output power was read directly from the meter across all data rates, and across three channels within each sub-band. Special care was used to make sure that the EUT was transmitting in continuous mode. This method exceeds the limitations of FCC KDB-789033, and provides more accurate measurements.

802.11an (BW \leq 40MHz) Maximum conducted output power using KDB 789033 section E)3)b) Method PM-G (Measurement using a gated RF average power meter)

Note: the power meter have a video bandwidth that is greater than or equal to the measurement bandwidth, (Anritsu/ MA2411B video bandwidth: 65MHz)

802.11ac (BW=80MHz) Maximum conducted output power using KDB 789033 section E)2)b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep).

When transmitted signals consist of two or more non-contiguous spectrum segments (e.g., 80+80 MHz mode) or when a single spectrum segment of a transmission crosses the boundary between two adjacent U-NII bands, KDB 644545 D03 section D) procedure is used for measurements.

3.4. Test Result of Maximum conducted output power

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11a)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	7.88	8.17	11.04	26.6
44	5220	7.83	8.16	11.01	26.6
48	5240	8.11	8.54	11.34	26.6
149	5745	23.76	23.85	26.82	27.0
157	5785	23.94	23.91	26.94	27.0
165	5825	23.79	23.86	26.84	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
36	5180	11.04	9.4	20.44	21
44	5220	11.01	9.4	20.41	21
48	5240	11.34	9.4	20.74	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11n-20 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	7.86	8.35	11.12	26.6
44	5220	7.89	8.38	11.15	26.6
48	5240	7.86	8.29	11.09	26.6
149	5745	23.76	23.85	26.82	27.0
157	5785	23.71	23.80	26.77	27.0
165	5825	23.77	23.82	26.81	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
36	5180	11.12	9.4	20.52	21
44	5220	11.15	9.4	20.55	21
48	5240	11.09	9.4	20.49	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11n-40 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	7.85	8.37	11.13	26.6
46	5230	7.89	8.51	11.22	26.6
151	5755	23.56	23.65	26.62	27.0
159	5795	23.72	23.64	26.69	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
38	5190	11.13	9.4	20.53	21
46	5230	11.22	9.4	20.62	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ac-20 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	7.88	8.36	11.14	26.6
44	5220	7.86	8.38	11.14	26.6
48	5240	7.81	8.29	11.07	26.6
149	5745	23.75	23.81	26.79	27.0
157	5785	23.71	23.82	26.78	27.0
165	5825	23.73	23.83	26.79	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
36	5180	11.14	9.4	20.54	21
44	5220	11.14	9.4	20.54	21
48	5240	11.07	9.4	20.47	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ac-40 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	7.89	8.35	11.14	26.6
46	5230	7.91	8.45	11.20	26.6
151	5755	23.62	23.69	26.67	27.0
159	5795	23.74	23.65	26.71	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
38	5190	11.14	9.4	20.54	21
46	5230	11.20	9.4	20.60	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ac-80 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
42	5210	7.78	8.31	11.06	26.6
155	5775	20.44	20.28	23.37	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
42	5210	11.06	9.4	20.46	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ax-20 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	7.92	8.42	11.19	26.6
44	5220	7.94	8.46	11.22	26.6
48	5240	7.91	8.35	11.15	26.6
149	5745	23.85	23.92	26.90	27.0
157	5785	23.81	23.89	26.86	27.0
165	5825	23.84	23.92	26.89	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
36	5180	11.19	9.4	20.59	21
44	5220	11.22	9.4	20.62	21
48	5240	11.15	9.4	20.55	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ax-40 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	7.94	8.44	11.21	26.6
46	5230	7.98	8.55	11.28	26.6
151	5755	23.71	23.69	26.71	27.0
159	5795	23.85	23.79	26.83	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
38	5190	11.21	9.4	20.61	21
46	5230	11.28	9.4	20.68	21

Product : Peplink Pepwave Wireless Product
 Test Item : Maximum conducted output power
 Test Mode : Transmit (802.11ax-80 MHz)-Master
 Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
42	5210	7.86	8.37	11.13	26.6
155	5775	20.51	20.38	23.46	27.0

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

E.I.R.P

Channel No.	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
42	5210	11.13	9.4	20.53	21

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11a)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	12.87	13.22	16.06	20.6
44	5220	12.96	13.34	16.16	20.6
48	5240	12.72	13.21	15.98	20.6

Note: Output Power Value (dBm) = $10 \cdot \text{LOG} (\text{Chain A(mW)} + \text{Chain B(mW)})$

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11n-20 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	13.49	13.88	16.70	20.6
44	5220	13.71	14.12	16.93	20.6
48	5240	14.01	14.38	17.21	20.6

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11n-40 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	14.56	14.86	17.72	20.6
46	5230	17.05	17.29	20.18	20.6

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ac-20 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	13.47	13.87	16.68	20.6
44	5220	13.72	14.11	16.93	20.6
48	5240	14.05	14.39	17.23	20.6

Note: Output Power Value (dBm) = $10 \cdot \text{LOG}(\text{Chain A(mW)} + \text{Chain B(mW)})$

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ac-40 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	14.62	14.83	17.74	20.6
46	5230	17.09	17.26	20.19	20.6

Note: Output Power Value (dBm) = $10 \cdot \text{LOG} (\text{Chain A(mW)} + \text{Chain B(mW)})$

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ac-80 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
42	5210	13.60	13.85	16.74	20.6

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ax-20 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
36	5180	13.53	13.93	16.74	20.6
44	5220	13.78	14.16	16.98	20.6
48	5240	14.06	14.45	17.27	20.6

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))

Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ax-40 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
38	5190	14.66	14.91	17.80	20.6
46	5230	17.19	17.35	20.28	20.6

Note: Output Power Value (dBm) = 10*LOG (Chain A(mW) + Chain B(mW))


Product : Peplink Pepwave Wireless Product
Test Item : Maximum conducted output power
Test Mode : Transmit (802.11ax-80 MHz)-Slave
Test Date : 2023/07/04

Channel No.	Frequency (MHz)	Chain A Power (dBm)	Chain B Power (dBm)	Output Power (dBm)	Output Power Limit (dBm)
42	5210	13.64	13.92	16.79	20.6

Note: Output Power Value (dBm) = $10 \cdot \text{LOG} (\text{Chain A(mW)} + \text{Chain B(mW)})$

4. Maximum Power Spectral Density

4.1. Test Setup



4.2. Limits

For the band 5.15-5.25 GHz,

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point UNII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

The maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

For CDD mode:

5150MHz-5250MHz: Directional gain = 11.42 dBi, Limit = 11.58dBm (Master)

5150MHz-5250MHz: Directional gain = 11.42 dBi, Limit = 5.58dBm (Slave)

5725MHz-5850MHz: Directional gain = 11.96dBi, Limit = 24.04dBm

Directional gain = $10 \log[(10G1/20 + 10G2/20)^2 / NANT]$ dBi

4.3. Test Procedure

The EUT was setup to ANSI C63.10, 2013; tested to UNII test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

The Peak Power Spectral Density using KDB 789033 section F) procedure, Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer.

SA-1 method is selected to run the test.

4.4. Test Result of Maximun Power Spectral Density

Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11a)-Master

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
36	5180	6	A	-4.29	0.17	-0.94	11.58	Pass
			B	-3.97				
44	5220	6	A	-3.84	0.17	-0.58	11.58	Pass
			B	-3.69				
48	5240	6	A	-4.01	0.17	-0.73	11.58	Pass
			B	-3.82				

Note:


1. Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Chain	PPSD (dBm)	Duty factor (dB)	Total PPSD (dBm)	Limit (dBm)	Result
149	5745	6	A	9.24	0.17	12.78	24.04	Pass
			B	9.93				
157	5785	6	A	9.92	0.17	13.06	24.04	Pass
			B	9.83				
165	5825	6	A	10.24	0.17	13.18	24.04	Pass
			B	9.74				

Note:


1. Total PPSD = PPSD + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 44 (Chain B):



Date: 4.JUL.2023 19:19:15

Channel 165 (Chain B):



Date: 8.SEP.2023 19:12:37

Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-20 MHz)-Master

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
36	5180	MCS0	A	-4.50	0.58	-0.61	11.58	Pass
			B	-3.92				
44	5220	MCS0	A	-4.26	0.58	-0.53	11.58	Pass
			B	-3.99				
48	5240	MCS0	A	-4.02	0.58	-0.46	11.58	Pass
			B	-4.08				

Note:


1. Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD (dBm)	Duty factor (dB)	Total PPSD (dBm)	Limit (dBm)	Result
149	5745	MCS0	A	8.90	0.58	12.47	24.04	Pass
			B	8.85				
157	5785	MCS0	A	9.08	0.58	12.84	24.04	Pass
			B	9.41				
165	5825	MCS0	A	9.92	0.58	13.29	24.04	Pass
			B	9.47				

Note:


1. Total PPSD = PPSD + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 36 (Chain B):



Date: 4.JUL.2023 19:14:45

Channel 165 (Chain B):



Date: 4.JUL.2023 19:09:42

Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-40 MHz)-Master

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
38	5190	MCS0	A	-6.68	0.25	-3.32	11.58	Pass
			B	-6.48				
46	5230	MCS0	A	-6.92	0.25	-3.61	11.58	Pass
			B	-6.83				

Note:


1. Total PPSD/MHz = PPSD/MHz +10*log 2 (two antennas) +Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD (dBm)	Duty factor (dB)	Total PPSD (dBm)	Limit (dBm)	Result
151	5755	MCS0	A	6.11	0.25	9.71	24.04	Pass
			B	6.77				
159	5795	MCS0	A	6.95	0.25	10.14	24.04	Pass
			B	6.80				

Note:


1. Total PPSD = PPSD +10*log 2 (two antennas) +Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 38 (Chain B):



Date: 4.JUL.2023 19:37:09

Channel 151 (Chain A):



Date: 4.JUL.2023 19:43:06

Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-80 MHz)-Master

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PSD/MHz (dBm)	Limit (dBm)	Result
42	5210	MCS0	A	-10.05	0.31	-6.51	11.58	Pass
			B	-9.62				

Note:


1. Total PSD/MHz = PSD/MHz +10*log 2 (two antennas) +Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD (dBm)	Duty factor (dB)	Total PSD (dBm)	Limit (dBm)	Result
155	5775	MCS0	A	-0.13	0.31	3.12	24.04	Pass
			B	-0.28				

Note:


1. Total PSD = PSD +10*log 2 (two antennas) +Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 42 (Chain B):



Date: 4.JUL.2023 19:44:47

Channel 155 (Chain A):



Date: 4.JUL.2023 19:47:57


Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11a)-Slave

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
36	5180	6	A	0.86	1.30	5.30	5.58	Pass
			B	1.12				
44	5220	6	A	1.06	1.30	5.44	5.58	Pass
			B	1.21				
48	5240	6	A	1.06	1.30	5.42	5.58	Pass
			B	1.16				

Note:

1. Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 44 (Chain B):



Date: 5.JUL.2023 15:55:38


Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-20 MHz)-Slave

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
36	5180	MCS0	A	1.55	0.58	5.27	5.58	Pass
			B	1.81				
44	5220	MCS0	A	1.58	0.58	5.32	5.58	Pass
			B	1.87				
48	5240	MCS0	A	1.96	0.58	5.53	5.58	Pass
			B	1.92				

Note:

1. Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) + Duty factor.
2. The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 48 (Chain A):



Date: 4.JUL.2023 20:20:42


Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-40 MHz)-Slave

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
38	5190	MCS0	A	-0.48	0.25	3.15	5.58	Pass
			B	0.23				
46	5230	MCS0	A	2.02	0.25	5.30	5.58	Pass
			B	2.05				

Note:

- Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) +Duty factor.
- The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 46 (Chain B):



Date: 4.JUL.2023 20:28:33


Product : Peplink Pepwave Wireless Product
 Test Item : Maximun Power Spectral Density
 Test Mode : Transmit (802.11ax-80 MHz)-Slave

Channel No.	Frequency (MHz)	Data Rate	Chain	PPSD/MHz (dBm)	Duty factor (dB)	Total PPSD/MHz (dBm)	Limit (dBm)	Result
42	5210	MCS0	A	-3.96	0.31	-0.24	5.58	Pass
			B	-3.19				

Note:

- Total PPSD/MHz = PPSD/MHz + 10*log 2 (two antennas) +Duty factor.
- The quantity 10*log 2 (two antennas) is added to the spectrum peak value according to document 662911 D01.

Channel 42 (Chain B):




Date: 4.JUL.2023 20:36:08


5. Radiated Emission

5.1. Test Setup


Radiated Emission Under 30MHz



Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



5.2. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dB μ V/m) = 20 log E field strength (μ V/m).

5.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according to FCC KDB-789033 test procedure for compliance to FCC 47CFR 15. 407 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9 kHz and 30 MHz~1 GHz is 120 kHz and above 1 GHz is 1 MHz.

Radiated emission measurements below 30 MHz are made using Loop Antenna and 30 MHz~1 GHz are made using broadband Bilog antenna and above 1 GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range from 9 kHz - 10 th Harmonic of fundamental was investigated.

RBW and VBW Parameter setting:

According to KDB 789033 section II.G.5 Procedure for Unwanted Maximum Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW \geq 3MHz.

According to KDB 789033 section II.G.6 Procedures for Average Unwanted Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW = 10Hz, when duty cycle \geq 98 %





VBW \geq 1/T, when duty cycle < 98 %





(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)





5GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11a	96.10	2.9600	338	500
802.11ax-20 MHz	87.50	5.4250	184	200
802.11ax-40 MHz	94.39	5.3800	186	200
802.11ax-80 MHz	93.08	5.3800	186	200





Note: Duty Cycle Refer to Section 8.





5.4. Test Result of Radiated Emission























































Test Result of Radiated Emission co-location










6. Band Edge

6.1. Test Setup

RF Radiated Measurement:



6.2. Limits

The provisions of Section 15.205 of this part apply to intentional radiators operating under this section. Radiated emissions which fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209:

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	$\mu\text{V/m @3m}$	$\text{dB}\mu\text{V/m@3m}$
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks:

1. RF Voltage ($\text{dB}\mu\text{V}$) = $20 \log$ RF Voltage (μV).
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

6.3. Test Procedure

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10:2013 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter is 120 kHz, above 1GHz are 1 MHz. The EUT was setup to ANSI C63.10, 2013; tested to UNII test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

RBW and VBW Parameter setting:

According to KDB 789033 section II.G.5 Procedure for Unwanted Maximum Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW \geq 3MHz.

According to KDB 789033 section II.G.6 Procedures for Average Unwanted Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW = 10Hz, when duty cycle \geq 98 %





VBW \geq 1/T, when duty cycle < 98 %





(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)





5GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11a	96.10	2.9600	338	500
802.11ax-20 MHz	87.50	5.4250	184	200
802.11ax-40 MHz	94.39	5.3800	186	200
802.11ax-80 MHz	93.08	5.3800	186	200





Note: Duty Cycle Refer to Section 8.





6.4. Test Result of Band Edge
































































7. Occupied Bandwidth

7.1. Test Setup



7.2. Limits

For the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

7.3. Test Procedure


The EUT was setup to ANSI C63.10, 2013; tested to UNII test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

7.4. Test Result of Occupied Bandwidth

Product : Peplink Pepwave Wireless Product
 Test Item : Occupied Bandwidth Data
 Test Mode : Transmit (802.11a)
 Test Date : 2023/07/04

Channel No.	Chain	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
149	A	5745	16304	>500	Pass
157	A	5785	15784	>500	Pass
165	A	5825	16024	>500	Pass
149	B	5745	16024	>500	Pass
157	B	5785	16024	>500	Pass
165	B	5825	15704	>500	Pass

Channel 165 (Chain B):




Date: 8.SEP.2023 19:13:49

Product : Peplink Pepwave Wireless Product
 Test Item : Occupied Bandwidth Data
 Test Mode : Transmit (802.11ax-20 MHz)
 Test Date : 2023/07/04

Channel No.	Chain	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
149	A	5745	18861	>500	Pass
157	A	5785	17902	>500	Pass
165	A	5825	18941	>500	Pass
149	B	5745	18182	>500	Pass
157	B	5785	16384	>500	Pass
165	B	5825	17822	>500	Pass

Channel 157 (Chain B):




Date: 8.SEP.2023 19:23:45

Product : Peplink Pepwave Wireless Product
 Test Item : Occupied Bandwidth Data
 Test Mode : Transmit (802.11ax-40 MHz)
 Test Date : 2023/07/04

Channel No.	Chain	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
151	A	5755	37642	>500	Pass
159	A	5795	37802	>500	Pass
151	B	5755	37722	>500	Pass
159	B	5795	38202	>500	Pass

Channel 151 (Chain A):




Date: 8.SEP.2023 19:30:21

Product : Peplink Pepwave Wireless Product
 Test Item : Occupied Bandwidth Data
 Test Mode : Transmit (802.11ax-80 MHz)
 Test Date : 2023/07/04

Channel No.	Chain	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
155	A	5775	73526	>500	Pass
155	B	5775	75924	>500	Pass


Channel 155 (Chain A):



Date: 4.JUL.2023 19:47:39

8. Duty Cycle

8.1. Test Setup



8.2. Test Procedure

The EUT was setup according to ANSI C63.10 2013; tested according to U-NII test procedure of KDB789033 for compliance to FCC 47CFR 15.407 requirements.

8.3. Test Result of Duty Cycle

Product : Peplink Pepwave Wireless Product
 Test Item : Duty Cycle
 Test Mode : Transmit


Duty Cycle Formula:

$$\text{Duty Cycle} = \text{Ton} / (\text{Ton} + \text{Toff})$$

$$\text{Duty Factor} = 10 \text{ Log} (1/\text{Duty Cycle})$$


Results:

5GHz band	Ton (ms)	Ton + Toff (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11a	2.9600	3.0800	96.10	0.17
802.11ax-20 MHz	5.4250	6.2000	87.50	0.58
802.11ax-40 MHz	5.3800	5.7000	94.39	0.25
802.11ax-80 MHz	5.3800	5.7800	93.08	0.31




06:48:53 30.06.2023

802.11a




04:06:00 03.07.2023

802.11ax-20 MHz



07:38:28 03.07.2023

802.11ax-40 MHz



08:55:02 03.07.2023

802.11ax-80 MHz