

# **RF Exposure Evaluation Declaration**

peplink PEPWAVE Wireless Product	
: PEPWAVE / peplink	
: Balance 20X Pro, BPL-021X-PRO-LTEA-Q-T-PRM	
: U8G-P1AX19	
	<ul> <li>peplink PEPWAVE Wireless Product</li> <li>PEPWAVE / peplink</li> <li>Balance 20X Pro, BPL-021X-PRO-LTEA-Q-T-PRM</li> <li>U8G-P1AX19</li> </ul>

Applicant	:	PISMO L	ABS	TECHNO	LOGY LIM	ITED			
Address	:	A8, 5/F,	ΗK	Spinners	Industrial	Building,	Phase	6,	481
		Castle Pe	eak F	Road, Che	ung Sha W	/an, Hong	Kong		

Date of Receipt	:Jul. 06, 2022
Issued Date	: Oct. 17, 2022
Report No.	: 2270136R-RFUSMPEV02-A
Report Version	: V2.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement. The test report shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.



>	DEKRA
---	-------

Product Name	:	peplink PEPWAVE Wireless Product
Applicant	:	PISMO LABS TECHNOLOGY LIMITED
Addroso		A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle
Address	•	Peak Road, Cheung Sha Wan, Hong Kong
Manufacturer	:	PISMO LABS TECHNOLOGY LIMITED
Address		A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle
Address	•	Peak Road, Cheung Sha Wan, Hong Kong
Brand Name	:	PEPWAVE / peplink
Model No.	:	Balance 20X Pro, BPL-021X-PRO-LTEA-Q-T-PRM
FCC ID	:	U8G-P1AX19
EUT Voltage	:	DC 12V (adapter)
Applicable Standard	:	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure
		evaluation: mobile devices.
		Exposure Compliance of Radiocommunication Apparatus (All
		Frequency Bands)
Laboratory Name	:	DEKRA Testing and Certification Co., Ltd.
		Hsin Chu Laboratory
Address	:	No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu
		County 310, Taiwan, R.O.C.
Test Result	:	Complied
Documented By	:	Ame lia wa
		(Amelia Wu / Project Specialist)
Approved By		Pupillan Lin
, approved by	•	ling day is Fir (
		(Rueyyan Lin / Supervisor)
The test results relate o	only to	o the samples tested.
The test report shall not	t be r	eproduced except in full without the written approval of DEKRA Testing
and Certification Co., Lt	d.	



# **Revision History**

Version	Description	Issued Date
V1.0	Initial issue of report	Sep. 28, 2022
V2.0	Revised the RF Exposure Evaluation of LTE Band 7, LTE Band 12,	
	LTE Band 30, LTE Band 38, LTE Band 41, LTE Band 41 (HPUE),	Oct. 17, 2022
	LTE Band 48, LTE Band 7C, LTE Band 38C and LTE Band 41C.	



#### **General Information** 1.

#### 1.1. **EUT General Information**

RF General Information							
Evaluation	Frequency Range	Operating Frequency	Modulation Type				
Mode	(MHz)	(MHz)					
WiFi 2.4 GHz	2400 ~ 2483.5	2412 ~ 2462	802.11b: DSSS 802.11g/n/ac: OFDM 802.11ax: OFDMA				
WiFi 5 GHz	5150 ~ 5250	5180 ~ 5240	802.11a/n/ac: OFDM				
	5725 ~ 5850	5745 ~ 5825	802.11ax: OFDMA				

# The EUT contains a WWAN module and the detail as below.

Brand Name	Model	FCC ID	Bands	Operating Frequency Range (MHz)	Function
			WCDMA Band 2	TX: 1852.4 ~ 1907.6 RX: 1932.4 ~ 1987.6	
			WCDMA Band 4	TX: 1712.4 ~ 1752.6 RX: 2112.4 ~ 2152.6	DC-HSDPA / HSUPA /
			WCDMA Band 5	TX: 826.4 ~ 846.6 RX: 871.4 ~ 891.6	/ NSFA+
			Bands	Operating Frequency Range (MHz)	Modulation Type
			LTE Band 2	Uplink: 1850 ~ 1910 Downlink: 1930 ~ 1990	
			LTE Band 4	Uplink: 1710 ~ 1755 Downlink: 2110 ~ 2115	
			LTE Band 5	Uplink: 824 ~ 849 Downlink: 869 ~ 894	
			LTE Band 7	Uplink: 2500 ~ 2570 Downlink: 2620 ~ 2690	
	LN920A12-WW		LTE Band 12	Uplink: 699 ~ 716 Downlink: 729 ~ 746	
		P20A12-WW RI7LN920 D20A12-WW RI7LN920 HTE Band 13 LTE Band 14 LTE Band 14 LTE Band 17 Uplin Dow LTE Band 25 Uplin Dow LTE Band 26 Uplin Dow LTE Band 26 Uplin Dow LTE Band 26 Uplin Dow LTE Band 26 Uplin Dow LTE Band 26 Uplin Dow LTE Band 30 Uplin Dow Uplin Dow Dow LTE Band 30 Uplin Dow Dow LTE Band 30 Uplin Dow	LTE Band 13	Uplink: 777 ~ 787 Downlink: 746 ~ 756	
Talit			LTE Band 14	Uplink: 788 ~ 798 Downlink: 758 ~ 768	
reiit			LTE Band 17	Uplink: 704 ~ 716 Downlink: 734 ~ 746	
			LTE Band 25	Uplink: 1850 ~ 1915 Downlink: 1930 ~ 1995	QPSK / 16QAM /
			LTE Band 26	Uplink: 824 ~ 849 Downlink: 859 ~ 894	64QAM
			LTE Band 26 (Part 90)	Uplink: 814 ~ 824 Downlink: 859 ~ 869	
			Uplink: 2305 ~ 2315 Downlink: 2350 ~ 2360		
			LTE Band 38	Uplink: 2570 ~ 2620 Downlink: 2570 ~ 2620	
			LTE Band 41	Uplink: 2496 ~ 2690 Downlink: 2496 ~ 2690	
		LTE Band 41 (HPUE) Uplink LTE Band 48 Uplink LTE Band 48 Uplink LTE Band 66 Uplink Downl	Uplink: 2496 ~ 2690 Downlink: 2496 ~ 2690		
			LTE Band 48	Uplink: 3550 ~ 3700 Downlink: 3550 ~ 3700	
			LTE Band 66	Uplink: 1710 ~ 1780 Downlink: 2110 ~ 2200	
			LTE Band 71	Uplink: 663 ~ 698 Downlink: 617 ~ 652	
Note: I T	E Band supports	CA Band: 5C	7C 38C and 41C		

Note: LIE Band supports CA Band: 5C, 7C, 38C and 41C.

TEL FAX



The brand name/model number in the following table are all refer to the identical product.

Brand Name	Description
PEPWAVE	
peplink	
Model No.	There is nothing different of two models, just for different marketing use.
Balance 20X Pro	
BPL-021X-PRO-LTEA-Q-T-PRM	

From the above models, model: Balance 20X Pro was selected as representative model for the test and its data was recorded in this report.

Note: The above EUT information is declared by the manufacturer.

: +886-3-582-8001	Page Number	:	5 of 10
: +886-3-582-8958	Issued Date	:	Oct. 17, 2022
	Report Version	:	V2.0



# 1.2. Test Facility

# Laboratory Information

USA	:	FCC Registration Number: TW3024
Canada		CAB identifier : TW3024

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: <u>http://www.dekra.com.tw</u>

lf you	i have any	comments,	please don't	hesitate to	contact us.	Our test	sites as below:
--------	------------	-----------	--------------	-------------	-------------	----------	-----------------

Test Laboratory	DEKRA Testing and Certification Co., Ltd.		
Address	1. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061,		
	Taiwan, R.O.C.		
	2. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061,		
	Taiwan, R.O.C.		
Phone number	1. +886-3-582-8001		
	2. +886-3-582-8001		
Fax number	1. +886-3-582-8958		
	2. +886-3-582-8958		
E mail address	info.tw@dekra.com		
Website	http://www.dekra.com.tw		
Note: Test site number for address 1 includes HC-SR02. Test site number for address 2 includes HC-CB02,			
HC-CB03, HC-CB04, HC-SR10 and HC-SR12.			

# 2. **RF Exposure Evaluation**

# 2.1. Test Limit

(A) Test Limit for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Test Limit for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz; \*Plane-wave equivalent power density



Power Density (S) is calculated by the following formula:

S=(P\*G) /4πR<sup>2</sup>

where:

S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

 $\pi = 3.1416$ 

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



# 2.2. Test Result of RF Exposure Evaluation

# Exposure Environment: General Population / Uncontrolled Exposure

	E.I.R.P	E.I.R.P	Power Density	Limit	Test Result
Evaluation Mode	(dBm)	(mW)	(mW/cm²)	(mW/cm²)	(PASS/FAIL)
WiFi 2.4 GHz	28.23	664.97	0.132	1.000	PASS
WiFi 5 GHz Band 1	22.89	194.36	0.039	1.000	PASS
WiFi 5 GHz Band 4	23.64	231.21	0.046	1.000	PASS
WCDMA Band 2	25.31	339.63	0.068	1.000	PASS
WCDMA Band 4	25.13	325.84	0.065	1.000	PASS
WCDMA Band 5	21.46	139.96	0.028	0.549	PASS
LTE Band 2	25.26	335.74	0.067	1.000	PASS
LTE Band 4	24.55	285.10	0.057	1.000	PASS
LTE Band 5	21.16	130.62	0.026	0.549	PASS
LTE Band 7	25.25	334.97	0.067	1.000	PASS
LTE Band 12	21.48	140.60	0.028	0.466	PASS
LTE Band 13	20.94	124.17	0.025	0.518	PASS
LTE Band 14	20.89	122.74	0.024	0.525	PASS
LTE Band 17	20.83	121.06	0.024	0.469	PASS
LTE Band 25	24.91	309.74	0.062	1.000	PASS
LTE Band 26	20.99	125.60	0.025	0.549	PASS
LTE Band 26 (Part 90)	21.10	128.82	0.026	0.543	PASS
LTE Band 30	18.04	63.68	0.013	1.000	PASS
LTE Band 38	25.16	328.10	0.065	1.000	PASS
LTE Band 41	27.56	570.16	0.113	1.000	PASS
LTE Band 41 (HPUE)	27.56	570.16	0.113	1.000	PASS
LTE Band 48	17.56	57.02	0.011	1.000	PASS
LTE Band 66	24.74	297.85	0.059	1.000	PASS
LTE Band 71	21.16	130.62	0.026	0.442	PASS
LTE Band 5C	22.04	159.96	0.032	0.549	PASS
LTE Band 7C	26.39	435.51	0.087	1.000	PASS
LTE Band 38C	25.88	387.26	0.077	1.000	PASS
LTE Band 41C	26.33	429.54	0.085	1.000	PASS

Distance (cm): 20 for Maximum Permissible Exposure.



### **Co-location**

#### **Conclusion:**

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

#### LPD = Limit of power density

- 1. WiFi 2.4 GHz function + WiFi 5 GHz function + WWAN WCDMA function = 0.132 + 0.046 + 0.068 = 0.246, therefore the maximum calculations of above situations are less than the "1" limit.
- 2. WiFi 2.4 GHz function + WiFi 5 GHz function + WWAN LTE function = 0.132 + 0.046 + 0.113 = 0.291, therefore the maximum calculations of above situations are less than the "1" limit.

#### Note:

- 1. The above EUT information is declared by the manufacturer.
- 2. The results are evaluated using the maximum power.