

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBCIC-WTW-P24100659A

FCC ID: U8G-P1MT01

Product: Peplink Pepwave Wireless Product

Brand:  PEPWAVE

Model No.: MAX BR1 Mini

Series Model: MAX-BR1-MINI-LTE-US-T-PRM, MAX-BR1-MINI-LTEA-US-T-PRM, MAX-BR1-MINI-LTE-US-DC-T-PRM, MAX-BR1-MINI-LTEA-US-DC-T-PRM, AP One Rugged, APO-AC-RUG, MAX BR1 Mini 5G, MAX-BR1-MINI-5GN-T-PRM, MAX-BR1-MINI-5GN-DC-T-PRM (refer to item 3.1 for more details)

Received Date: 2024/12/27

Test Date: 2025/1/22

Issued Date: 2025/2/19

Applicant: PISMO LABS TECHNOLOGY LIMITED

Address: A8, 5/F, HK Spinners Industrial Building, Phase 6, 481 Castle Peak Road, Cheung Sha Wan, Hong Kong

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by:



Date:

2025/2/19

Jeremy Lin / Project Engineer

This test report consists of 11 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Lena Wang / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Applicable RF Exposure Limit	5
3 Test Results	7
4 Conclusion.....	10
5 Information of the Testing Laboratories	11

Release Control Record

Issue No.	Description	Date Issued
MFBCIC-WTW-P24100659A	Original release.	2025/2/19

1 Certificate

Product: Peplink Pepwave Wireless Product

Brand: 

Test Model: MAX BR1 Mini

Series Model: MAX-BR1-MINI-LTE-US-T-PRM, MAX-BR1-MINI-LTEA-US-T-PRM,
MAX-BR1-MINI-LTE-US-DC-T-PRM, MAX-BR1-MINI-LTEA-US-DC-T-PRM, AP One Rugged,
APO-AC-RUG, MAX BR1 Mini 5G, MAX-BR1-MINI-5GN-T-PRM, MAX-BR1-MINI-5GN-DC-T-
PRM (refer to item 3.1 for more details)

Sample Status: Prototype

Applicant: PISMO LABS TECHNOLOGY LIMITED

Test Date: 2025/1/22

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Applicable RF Exposure Limit

§ 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

➤ Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	<30
1.34-30	824/f	2.19/f	(180/f ²)*	<30
30-300	27.5	0.073	0.2	<30
300-1,500	f/1500	<30
1,500-100,000	1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

➤ Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6

f = frequency in MHz. * = Plane-wave equivalent power density.

MPE-based Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.
- Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

RF Source frequency (MHz)	Minimum Distance		Threshold ERP (watts)
	$\lambda_L/ 2\pi$	$\lambda_H/ 2\pi$	
0.3-1.34	159 m–35.6 m		1,920 R ² .
1.34-30	35.6 m–1.6 m		3,450 R ² /f ² .
30-300	1.6 m–159 mm		3.83 R ² .
300-1,500	159 mm–31.8 mm		0.0128 R ² f.
1,500-100,000	31.8 mm–0.5 mm		19.2 R ² .
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.			

MPE-based Exemption – §1.1307(b)(3)(i)(B)

- For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

- Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_{th,i}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source i .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Exposure Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from [§ 1.1310 of this chapter](#).

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

3 Test Results

Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
---------------------------	--------------	------------	-----------

For Single RF Source

MPE-based Exemption §1.1307(b)(3)(i)(B)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
WLAN 2.4 GHz	2412-2462	176.604	3.15	222.331	20	3060	Pass
WLAN 5 GHz	5180-5320 5500-5825	147.231	4.76	268.534	20	3060	Pass

Note:

- This report is issued as a supplementary report to BV CPS report no.: MFBCIC-WTW-P24100659-2 R2. The differences compared with original report are listed as below. Therefore, the EUT is re-calculated MPE value in this report.
 - Adding WWAN Module: Quectel / RM520N-GL.
 - Adding Models: MAX BR1 Mini 5G, MAX-BR1-MINI-5GN-T-PRM, MAX-BR1-MINI-5GN-DC-T-PRM for 5G for marketing.
 - Adding New appearance (WWAN antenna connector*4, GPS cancel) for model: MAX BR1 Mini 5G, MAX-BR1-MINI-5GN-T-PRM and MAX-BR1-MINI-5GN-DC-T-PRM.
- The WLAN average power refer to report No.:FR250205A & FR250205B & FR250205C.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- Regarding the evaluation of the maximum exposure, the above operation mode is a representative mode selected after evaluation and based on the Maximum output power.

For WWAN module: RM520N-GL

For Single RF Source

MPE-based Exemption §1.1307(b)(3)(i)(B)					
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
WCDMA B2	1852.4-1907.6	469.894	20	3060	Pass
WCDMA B4	1712.4-1752.6	487.529	20	3060	Pass
WCDMA B5	826.4-846.6	379.315	20	1685.856	Pass
LTE B2	1850.7-1909.3	469.894	20	3060	Pass
LTE B4	1710.7-1754.3	487.529	20	3060	Pass
LTE B5	824.7-848.3	379.315	20	1682.388	Pass
LTE B7	2502.5-2567.5	395.367	20	3060	Pass
LTE B12	699.7-715.3	425.599	20	1427.388	Pass
LTE B13	779.5-784.5	460.257	20	1590.18	Pass
LTE B14	790.5-795.5	460.257	20	1612.62	Pass
LTE B17	706.5-713.5	425.599	20	1441.26	Pass
LTE B25	1850.7-1914.3	469.894	20	3060	Pass
LTE B26	814.7-823.3	379.315	20	1661.988	Pass
LTE B26	824.7-848.3	379.315	20	1682.388	Pass
LTE B30	2307.5-2312.5	68.391	20	3060	Pass

MPE-based Exemption §1.1307(b)(3)(i)(B)					
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
LTE B38	2572.5-2617.5	543.25	20	3060	Pass
LTE B41	2502.5-2687.5	727.779	20	3060	Pass
LTE B42	3452.5-3597.5	245.471	20	3060	Pass
LTE B43	3602.5-3797.5	272.27	20	3060	Pass
LTE B48	3552.5-3697.5	120.227	20	3060	Pass
LTE B66	1710.7-1779.3	487.529	20	3060	Pass
LTE B71	665.5-695.5	425.599	20	1357.62	Pass
NR B2	1852.5-1907.5	469.894	20	3060	Pass
NR B5	826.5-846.5	379.315	20	1686.06	Pass
NR B7	2502.5-2567.5	395.367	20	3060	Pass
NR B12	701.5-713.5	425.599	20	1431.06	Pass
NR B13	779.5-784.5	460.257	20	1590.18	Pass
NR B14	790.5-795.5	460.257	20	1612.62	Pass
NR B25	1852.5-1912.5	469.894	20	3060	Pass
NR B26	816.5-821.5	379.315	20	1665.66	Pass
NR B26	826.5-846.5	379.315	20	1686.06	Pass
NR B30	2307.5-2312.5	68.391	20	3060	Pass
NR B38	2575-2615	543.25	20	3060	Pass
NR B41	2501.01-2685	727.779	20	3060	Pass
NR B48	3555-3694.98	120.227	20	3060	Pass
NR B66	1712.5-1777.5	487.529	20	3060	Pass
NR B70	1697.5-1707.5	413.048	20	3060	Pass
NR B71	665.5-695.5	425.599	20	1357.62	Pass
NR B77	3555-3694.98	352.371	20	3060	Pass
NR B78	3455.01-3544.98	352.371	20	3060	Pass

Note:

1. The information and power evaluations regarding the certification modules contained by the EUT are primarily based on the manufacturer provided.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For Multiple RF Sources (Simultaneous Operations)

Multiple RF Sources (Simultaneous Operations)							
Exemption Evaluation					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio			
WLAN 2.4 GHz	2412-2462	222.331	3060	0.073	0.474	1	Pass
WLAN 5 GHz	5180-5320 5500-5825	268.534	3060	0.088			
LTE B71	665.5-695.5	425.599	1357.62	0.313			

Note:

1. After evaluation, the WiFi/WWAN antennas was used with the highest gain as the representative antenna for testing.
2. Regarding the evaluation of the maximum exposure, the above operation mode is a representative mode selected after evaluation and based on the Maximum ratio.

4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---