

# Label Info. & Location

## AP One AX

### Model: AP One AX

Product Code:APO-AX  
Serial No.:2938-6089-D1B7  
LAN MAC:A8-C0-EA-34-CA-20  
AP Password:EA34CA20



FCC ID: U8G-P1X02  
IC: 20682-P1X02  
CAN ICES-3(B)/NMB-3(B)

<b>Default Access</b> <a href="https://192.168.0.3">https://192.168.0.3</a>	Username: admin Password: public
--	-------------------------------------

Input : 12V DC , 2.5A ( DC jack )  
Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )

Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## AP One ENT AX

### Model: AP One ENT AX

Product Code:APO-AX  
Serial No.:2938-6089-D1B7  
LAN MAC:A8-C0-EA-34-CA-20  
AP Password:EA34CA20



FCC ID: U8G-P1X02  
IC: 20682-P1X02  
CAN ICES-3(B)/NMB-3(B)

<b>Default Access</b> <a href="https://192.168.0.3">https://192.168.0.3</a>	Username: admin Password: public
--	-------------------------------------

Input : 12V DC , 2.5A ( DC jack )  
Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )



Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

# Label Info. & Location

AP One Enterprise AX	APO-AX
<p><b><u>Model: AP One Enterprise AX</u></b></p> <p>Product Code:APO-AX            Serial No.:2938-6089-D1B7            LAN MAC:A8-C0-EA-34-CA-20            AP Password:EA34CA20</p> <div style="border: 1px solid black; padding: 2px; width: fit-content;"> <p><b>Default Access</b>      Username: admin  <a href="https://192.168.0.3">https://192.168.0.3</a> Password: public</p> </div> <p><b>Input : 12V DC , 2.5A ( DC jack )</b>  <b>Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )</b></p> <p>Made in Taiwan</p>  <p>M8 HW0</p>	<p><b><u>Model: APO-AX</u></b></p> <p>Product Code:APO-AX            Serial No.:2938-6089-D1B7            LAN MAC:A8-C0-EA-34-CA-20            AP Password:EA34CA20</p> <div style="border: 1px solid black; padding: 2px; width: fit-content;"> <p><b>Default Access</b>      Username: admin  <a href="https://192.168.0.3">https://192.168.0.3</a> Password: public</p> </div> <p><b>Input : 12V DC , 2.5A ( DC jack )</b>  <b>Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )</b></p> <p>Made in Taiwan</p>  <p>M8 HW0</p>



FCC ID: U8G-P1X02  
 IC: 20682-P1X02  
 CAN ICES-3(B)/NMB-3(B)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



FCC ID: U8G-P1X02  
 IC: 20682-P1X02  
 CAN ICES-3(B)/NMB-3(B)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

# Label Info. & Location

## APO-ENT-AX

### Model: APO-ENT-AX

Product Code:APO-AX  
Serial No.:2938-6089-D1B7  
LAN MAC:A8-C0-EA-34-CA-20  
AP Password:EA34CA20

**Default Access** Username: admin  
<https://192.168.0.3> Password: public

**Input : 12V DC , 2.5A ( DC jack )**  
**Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )**



FCC ID: U8G-P1X02  
IC: 20682-P1X02  
CAN ICES-3(B)/NMB-3(B)

Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## Peplink AP One AX

### Model: Peplink AP One AX

Product Code:APO-AX  
Serial No.:2938-6089-D1B7  
LAN MAC:A8-C0-EA-34-CA-20  
AP Password:EA34CA20

**Default Access** Username: admin  
<https://192.168.0.3> Password: public

**Input : 12V DC , 2.5A ( DC jack )**  
**Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )**



FCC ID: U8G-P1X02  
IC: 20682-P1X02  
CAN ICES-3(B)/NMB-3(B)

Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

# Label Info. & Location

## Peplink AP One Enterprise AX

### Model: Peplink AP One Enterprise AX

Product Code:APO-AX  
 Serial No.:2938-6089-D1B7  
 LAN MAC:A8-C0-EA-34-CA-20  
 AP Password:EA34CA20



<b>Default Access</b>	Username: admin
https://192.168.0.3 Password: public	

**Input : 12V DC , 2.5A ( DC jack )**  
**Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )**

FCC ID: U8G-P1X02  
 IC: 20682-P1X02  
 CAN ICES-3(B)/NMB-3(B)

Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## Pepwave AP One AX

### Model: Pepwave AP One AX

Product Code:APO-AX  
 Serial No.:2938-6089-D1B7  
 LAN MAC:A8-C0-EA-34-CA-20  
 AP Password:EA34CA20



<b>Default Access</b>	Username: admin
https://192.168.0.3 Password: public	

**Input : 12V DC , 2.5A ( DC jack )**  
**Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )**

FCC ID: U8G-P1X02  
 IC: 20682-P1X02  
 CAN ICES-3(B)/NMB-3(B)





Made in Taiwan



M8 HW0

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

# Label Info. & Location

Pepwave AP One Enterprise AX	PRB-11AX
<p><b><u>Model: Pepwave AP One Enterprise AX</u></b></p> <p>Product Code:APO-AX            Serial No.:2938-6089-D1B7            LAN MAC:A8-C0-EA-34-CA-20            AP Password:EA34CA20</p> <div data-bbox="891 432 1137 603">  </div> <p><b>Default Access</b>      Username: admin  <a href="https://192.168.0.3">https://192.168.0.3</a> Password: public</p> <p><b>Input : 12V DC , 2.5A ( DC jack )</b>  <b>Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )</b></p> <p>FCC ID: U8G-P1X02            IC: 20682-P1X02            CAN ICES-3(B)/NMB-3(B)</p> <p>Made in Taiwan</p>  <p>M8 HW0</p> <p><small>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</small></p>	<p><b><u>Model: PRB-11AX</u></b></p> <p>Product Code:APO-AX            Serial No.:2938-6089-D1B7            LAN MAC:A8-C0-EA-34-CA-20            AP Password:EA34CA20</p> <div data-bbox="1868 424 2181 635">  </div> <p><b>Default Access</b>      Username: admin  <a href="https://192.168.0.3">https://192.168.0.3</a> Password: public</p> <p><b>Input : 12V DC , 2.5A ( DC jack )</b>  <b>Input : 54V DC , 23W max ( POE injector ( 802.3af/at ) )</b></p> <p>FCC ID: U8G-P1X02            IC: 20682-P1X02            CAN ICES-3(B)/NMB-3(B)</p> <p>Made in Taiwan</p>  <p>M8 HW0</p> <p><small>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</small></p>

## Label Info. & Location

