

TEST REPORT

FCC ID: U8O-STB5-LTE

Product: Micronet SmarTab LTE

Model No.: Micronet SmarTab

Additional Model No.: N/A

Trade Mark: Micronet

Report No.: TCT180723E040

Issued Date: Sep. 06, 2018

Issued for:

Micronet

1865 West 2100 South, Suite 2, Salt Lake City, Utah, 84119 United States

Issued By:

Shenzhen Tongce Testing Lab.

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China**

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. Test Certification | 3 |
| 2. Test Result Summary | 3 |
| 3. EUT Description..... | 5 |
| 4. General Information..... | 8 |
| 4.1. Test environment and mode..... | 8 |
| 4.2. Test Mode..... | 11 |
| 4.3. Description of Support Units..... | 14 |
| 4.4. Configuration of Tested System | 14 |
| 4.5. Measurement Results Explanation Example..... | 14 |
| 5. Facilities and Accreditations | 15 |
| 5.1. Facilities | 15 |
| 5.2. Location | 15 |
| 5.3. Measurement Uncertainty..... | 15 |
| 6. Test Results and Measurement Data | 16 |
| 6.1. Conducted Output Power Measurement | 16 |
| 6.2. Peak to Average Ratio..... | 17 |
| 6.3. Band Edge and Conducted Spurious Emission Measurement | 19 |
| 6.4. Field Strength of Spurious Radiation Measurement | 21 |
| 6.5. Frequency Stability Measurement | 24 |

Appendix A: Photographs of Test Setup

Appendix B: Photographs of EUT

**Test Data: Refer to Appendix For LTE Band 2, Appendix For LTE Band 4,
Appendix For LTE Band 5, Appendix For LTE Band 12,
Appendix For LTE Band 17**

1. Test Certification

| | |
|------------------------------|--|
| Product: | Micronet SmarTab LTE |
| Model No.: | Micronet SmarTab |
| Additional Model: | N/A |
| Trade Mark: | Micronet |
| Applicant: | Micronet |
| Address: | 1865 West 2100 South, Suite 2, Salt Lake City, Utah, 84119 United States |
| Manufacturer: | Micronet |
| Address: | 1865 West 2100 South, Suite 2, Salt Lake City, Utah, 84119 United States |
| Date of Test: | Jul. 24, 2018 – Sep. 05, 2018 |
| Applicable Standards: | FCC CFR Title 47 Part 2 FCC CFR Title 47 Part22 FCC CFR Title 47 Part24 FCC CFR Title 47 Part27 |

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Jin Wang

Date:

Sep. 05, 2018

Reviewed By:



Beryl Zhao

Date:

Sep. 06, 2018

Approved By:



Tomsin

Date:

Sep. 06, 2018

2. Test Result Summary

| Requirement | CFR 47 Section | Result |
|---|---|--------|
| Conducted Output Power | §2.1046; §22.913; §24.232(c); §27.50(d); §27.50(c); §27.50(b); | PASS |
| Peak-to-Average Ratio | §2.1046; §24.232(d) §27.50(d); §27.50(c); §27.50(b); | PASS |
| Effective Radiated Power | §2.1046; §22.913; §24.232(c); §27.50(d); §27.50(c); §27.50(b); | PASS |
| Equivalent Isotropic Radiated Power | §2.1046; §22.913; §24.232(c); §27.50(d); §27.50(c); §27.50(b); | PASS |
| Occupied Bandwidth | §2.1049; §24.238(b); §27.53; | PASS |
| Band Edge | §2.1051; §22.917(a); §27.53(h); §27.53(c); §27.53(g); §24.238(a); | PASS |
| Conducted Spurious Emission | §2.1051; §22.917(a); §27.53(h); §27.53(g); §27.53(c); §24.238(a); | PASS |
| Field Strength of Spurious Radiation | §2.1053; §22.917(a); §27.53(g); §27.53(c); §27.53(h); §24.238(a); | PASS |
| Frequency Stability for Temperature & Voltage | §2.1055; §22.355; §27.54; §24.235; | PASS |

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

| | |
|---|---|
| Product: | Micronet SmarTab LTE |
| Model No.: | Micronet SmarTab |
| Additional Model: | N/A |
| Trade Mark: | Micronet |
| Hardware Version: | P1 |
| Software Version: | TREQ_5_0.1.14.2_20180527.1112 |
| Tx Frequency: | LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 17: 704 MHz ~ 716 MHz |
| Rx Frequency: | LTE Band 2: 1930MHz ~ 1990 MHz LTE Band 4: 2110 MHz ~ 2155 MHz LTE Band 5: 869 MHz ~ 894 MHz LTE Band 12: 729 MHz ~ 746 MHz LTE Band 17: 734 MHz ~ 746 MHz |
| Bandwidth: | LTE Band 2: 1.4MHz /3MHz /5MHz /10MHz /15MHz /20MHz LTE Band 4: 1.4MHz /3MHz /5MHz /10MHz /15MHz /20MHz LTE Band 5: 1.4MHz /3MHz /5MHz /10MHz LTE Band 12: 1.4MHz /3MHz /5MHz /10MHz LTE Band 17: 5MHz /10MHz |
| Maximum Output Power to Antenna: | LTE Band 2: 23.66dBm LTE Band 4: 23.44dBm LTE Band 5: 23.54dBm LTE Band 12: 23.24dBm LTE Band 17: 23.70dBm |
| 99% Occupied Bandwidth: | LTE Band 2: 17M9G7D LTE Band 4: 17M9G7D LTE Band 5: 8M95G7D LTE Band 12: 8M98G7D LTE Band 17: 8M99G7D |
| Type of Modulation: | QPSK/16QAM |
| Antenna Type: | PIFA Antenna |
| Antenna Gain: | LTE Band 2: 1.9dBi LTE Band 4: 1.9dBi LTE Band 5: 1.9dBi LTE Band 12: 1.9dBi LTE Band 17: 1.9dBi |
| Power Supply: | Rechargeable Li-ion Battery DC 3.7V |

Emission Designator

| LTE Band 2 | | QPSK | | 16QAM | |
|-------------|------------------------------|-----------------|------------------------------|-----------------|--|
| BW(MHz) | Emission Designator (99%OBW) | Maximum EIRP(W) | Emission Designator (99%OBW) | Maximum EIRP(W) | |
| 1.4 | 1M08G7D | 0.277 | 1M08W7D | 0.233 | |
| 3 | 2M69G7D | 0.294 | 2M69W7D | 0.257 | |
| 5 | 4M49G7D | 0.316 | 4M48W7D | 0.273 | |
| 10 | 8M95G7D | 0.358 | 8M95W7D | 0.309 | |
| 15 | 13M4G7D | 0.325 | 13M4W7D | 0.287 | |
| 20 | 17M9G7D | 0.360 | 17M9W7D | 0.275 | |
| LTE Band 4 | | QPSK | | 16QAM | |
| BW(MHz) | Emission Designator (99%OBW) | Maximum EIRP(W) | Emission Designator (99%OBW) | Maximum EIRP(W) | |
| 1.4 | 1M08G7D | 0.272 | 1M08W7D | 0.233 | |
| 3 | 2M69G7D | 0.279 | 2M69W7D | 0.252 | |
| 5 | 4M48G7D | 0.317 | 4M49W7D | 0.217 | |
| 10 | 8M95G7D | 0.327 | 8M95W7D | 0.284 | |
| 15 | 13M4G7D | 0.317 | 13M4W7D | 0.275 | |
| 20 | 17M9G7D | 0.342 | 17M9W7D | 0.257 | |
| LTE Band 5 | | QPSK | | 16QAM | |
| BW(MHz) | Emission Designator (99%OBW) | Maximum EIRP(W) | Emission Designator (99%OBW) | Maximum EIRP(W) | |
| 1.4 | 1M08G7D | 0.269 | 1M08W7D | 0.228 | |
| 3 | 2M69G7D | 0.305 | 2M69W7D | 0.260 | |
| 5 | 4M48G7D | 0.340 | 4M48W7D | 0.286 | |
| 10 | 8M95G7D | 0.350 | 8M95W7D | 0.301 | |
| LTE Band 12 | | QPSK | | 16QAM | |
| BW(MHz) | Emission Designator (99%OBW) | Maximum EIRP(W) | Emission Designator (99%OBW) | Maximum EIRP(W) | |
| 1.4 | 1M08G7D | 0.238 | 1M08W7D | 0.207 | |
| 3 | 2M69G7D | 0.293 | 2M68W7D | 0.253 | |
| 5 | 4M49G7D | 0.324 | 4M48W7D | 0.300 | |
| 10 | 8M98G7D | 0.327 | 8M98W7D | 0.288 | |

| LTE Band 17 | QPSK | | 16QAM | |
|-------------|------------------------------|-----------------|------------------------------|-----------------|
| BW(MHz) | Emission Designator (99%OBW) | Maximum EIRP(W) | Emission Designator (99%OBW) | Maximum EIRP(W) |
| 5 | 4M49G7D | 0.360 | 4M49W7D | 0.308 |
| 10 | 8M99G7D | 0.363 | 8M98W7D | 0.316 |

4. General Information

4.1. Test environment and mode

Operating Environment:

| | |
|-----------------------|-----------|
| Temperature: | 24.0 °C |
| Humidity: | 54 % RH |
| Atmospheric Pressure: | 1010 mbar |

Test Mode:

| | |
|-----------------|---|
| Operation mode: | Keep the EUT in continuous transmitting with modulation |
|-----------------|---|

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

Description Operation Frequency

| LTE Band 2(1.4MHz) | | LTE Band 2(3MHz) | |
|--------------------|-----------------|-------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 18607 | 1850.7 | 18615 | 1851.5 |
| 18900 | 1880 | 18900 | 1880 |
| 19193 | 1909.3 | 19185 | 1908.5 |
| LTE Band 2(5MHz) | | LTE Band 2(10MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 18625 | 1852.5 | 18650 | 1855 |
| 18900 | 1880 | 18900 | 1880 |
| 19175 | 1907.5 | 19150 | 1905 |
| LTE Band 2(15MHz) | | LTE Band 2(20MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 18675 | 1857.5 | 18700 | 1860 |
| 18900 | 1880 | 18900 | 1880 |
| 19125 | 1902.5 | 19100 | 1900 |

| LTE Band 4(1.4MHz) | | LTE Band 4(3MHz) | |
|--------------------|-----------------|-------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 19957 | 1710.7 | 19965 | 1711.5 |
| 20175 | 1732.5 | 20175 | 1732.5 |
| 20393 | 1754.3 | 20385 | 1753.5 |
| LTE Band 4(5MHz) | | LTE Band 4(10MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 19975 | 1712.5 | 20000 | 1715 |
| 20175 | 1732.5 | 20175 | 1732.5 |
| 20375 | 1752.5 | 20350 | 1750 |
| LTE Band 4(15MHz) | | LTE Band 4(20MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 20025 | 1717.5 | 20050 | 1720 |
| 20175 | 1732.5 | 20175 | 1732.5 |
| 20325 | 1747.5 | 20300 | 1745 |

| LTE Band 5(1.4MHz) | | LTE Band 5(3MHz) | |
|--------------------|-----------------|-------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 20407 | 824.7 | 20415 | 825.5 |
| 20525 | 836.5 | 20525 | 836.5 |
| 20643 | 848.3 | 20635 | 847.5 |
| LTE Band 5(5MHz) | | LTE Band 5(10MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 20425 | 826.5 | 20450 | 829 |
| 20525 | 836.5 | 20525 | 836.5 |
| 20625 | 846.5 | 20600 | 844 |

| LTE Band 12(1.4MHz) | | LTE Band 12(3MHz) | |
|---------------------|-----------------|--------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 23017 | 699.7 | 23025 | 700.5 |
| 23095 | 707.5 | 23095 | 707.5 |
| 23173 | 715.3 | 23165 | 714.5 |
| LTE Band 12(5MHz) | | LTE Band 12(10MHz) | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 23035 | 701.5 | 23060 | 704 |
| 23095 | 707.5 | 23095 | 707.5 |
| 23155 | 713.5 | 23130 | 711 |

| LTE Band 17(5MHz) | | LTE Band 17(10MHz) | |
|-------------------|-----------------|--------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 23755 | 706.5 | 23780 | 709 |
| 23790 | 710 | 23790 | 710 |
| 23825 | 713.5 | 23800 | 711 |

4.2. Test Mode

All modes and data rates and positions were investigated.
Test modes are chosen to be reported as the worst case configuration below:

| Test Mode | | |
|-------------|--|---|
| Band | Radiated TCs | Conducted TCs |
| LTE Band 2 | QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz) | 16QAM Link (1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz) |
| LTE Band 4 | QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz) | 16QAM Link (1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz) |
| LTE Band 5 | QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz) | 16QAM Link (1.4MHz / 3MHz / 5MHz / 10MHz) |
| LTE Band 12 | QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz) | 16QAM Link (1.4MHz / 3MHz / 5MHz / 10MHz) |
| LTE Band 17 | QPSK Link (5MHz / 10MHz) | 16QAM Link (5MHz / 10MHz) |

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas License Digital Systems v03 with maximum output power. Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

| Test Items | Band | Bandwidth (MHz) | | | | | | Modulation | | RB # | | | Test Channel | | |
|------------------------|------|-----------------|---|---|----|----|----|------------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 2 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 5 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 12 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 17 | - | - | v | v | - | - | v | v | v | v | v | v | v | v |
| Peak-to-Average Ratio | 2 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 5 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 12 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 17 | - | - | v | v | - | - | v | v | v | v | v | v | v | v |
| 26dB and 99% Bandwidth | 2 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 5 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 12 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 17 | - | - | v | v | - | - | v | v | v | v | v | v | v | v |

| Test Items | Band | Bandwidth (MHz) | | | | | | Modulation | | RB # | | | Test Channel | | |
|-----------------------------|------|-----------------|---|---|----|----|----|------------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 1 | Half | Full | L | M | H |
| Conducted Band Edge | 2 | v | v | v | v | v | v | v | v | v | v | v | v | - | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | - | v |
| | 5 | v | v | v | v | - | - | v | v | v | v | v | v | - | v |
| | 12 | v | v | v | v | - | - | v | v | v | v | v | v | - | v |
| | 17 | - | - | v | v | - | - | v | v | v | v | v | v | - | v |
| Conducted Spurious Emission | 2 | v | v | v | v | v | v | v | v | v | - | - | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | - | - | v | v | v |
| | 5 | v | v | v | v | - | - | v | v | v | - | - | v | v | v |
| | 12 | v | v | v | v | - | - | v | v | v | - | - | v | v | v |
| | 17 | - | - | v | v | - | - | v | v | v | - | - | v | v | v |
| Frequency Stability | 2 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 4 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 5 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 12 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 17 | - | - | v | - | - | - | v | v | v | - | - | v | v | v |

| | | | | | | | | | | | | | | | |
|----------------------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| E.R.P./ E.I.R.P. | 2 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 5 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 12 | v | v | v | v | - | - | v | v | v | v | v | v | v | v |
| | 17 | - | - | v | v | - | - | v | v | v | v | v | v | v | v |
| Radiated Spurious Emission | 2 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 4 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 5 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 12 | v | - | - | - | - | - | v | v | v | - | - | v | v | v |
| | 17 | - | - | v | - | - | - | v | v | v | - | - | v | v | v |
| Note | <p>1. The mark "v" means that this configuration is chosen for testing</p> <p>2. The mark "-" means that this bandwidth is not supported.</p> | | | | | | | | | | | | | | |

4.3. Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| / | / | / | / | / |

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4. Configuration of Tested System



4.5. Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level. The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab.

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

5.3. Measurement Uncertainty


The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | MU |
|-----|-------------------------------|---------------------------|
| 1 | Conducted Emission | $\pm 2.56\text{dB}$ |
| 2 | RF power, conducted | $\pm 0.12\text{dB}$ |
| 3 | Spurious emissions, conducted | $\pm 0.11\text{dB}$ |
| 4 | All emissions, radiated(<1G) | $\pm 3.92\text{dB}$ |
| 5 | All emissions, radiated(>1G) | $\pm 4.28\text{dB}$ |
| 6 | Temperature | $\pm 0.1^{\circ}\text{C}$ |
| 7 | Humidity | $\pm 1.0\%$ |

6. Test Results and Measurement Data

6.1. Conducted Output Power Measurement

6.1.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC part 27.50(c), FCC part 27.50(d) and FCC part 27.50(h), FCC part 24.232(c), FCC part 22.913; |
| Test Method: | FCC part 2.1046 |
| Limits: | LTE Band 2: 2W LTE Band 4: 1W LTE Band 5: 7W LTE Band 12: 3W LTE Band 17: 3W |
| Test Setup: |  <p>The diagram illustrates the test setup. On the left is a 'System Simulator' represented by a purple box with a screen and two buttons. A black cable connects it to a mobile phone on the right, which is labeled 'EUT'.</p> |
| Test Procedure: | <ol style="list-style-type: none"> 1. The transmitter output port was connected to the system simulator. 2. Set EUT at maximum power through system simulator. 3. Select lowest, middle, highest channels for each band and different modulation. 4. Measure and record the power level from the system simulator. |
| Test Result: | PASS |


6.1.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------------------|--------------|--------|---------------|-----------------|
| Wideband Radio Communication Tester | R&S | CMW500 | 114220 | Sep. 27, 2018 |
| RF cable (9kHz-40GHz) | TCT | RE-05 | N/A | Sep. 27, 2018 |
| Antenna Connector | TCT | RFC-02 | N/A | Sep. 27, 2018 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2. Peak to Average Ratio

6.2.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC part 2.1046; 22.913; 24.232; 27.50(d); 27.50(c); 27.50(b) |
| Test Method: | FCC KDB 971168 D01v03 |
| Limit: | The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB. |
| Test Setup: |  <p>The diagram illustrates the test setup. A System Simulator (represented by a purple monitor icon) and a Spectrum Analyzer (represented by a green monitor icon) are connected to a central Power Divider (represented by a black square icon). The Power Divider is then connected to the EUT (Equipment Under Test, represented by a mobile phone icon).</p> |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 5.7.1. 2. The EUT was connected to spectrum analyzer and system simulator via a power divider. 3. Set EUT to transmit at maximum output power. 4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. <p>Record the maximum PAPR level associated with a probability of 0.1%.</p> |
| Test Result: | PASS |


6.2.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------------------|--------------|--------|---------------|-----------------|
| Wideband Radio Communication Tester | R&S | CMW500 | 114220 | Sep. 27, 2018 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 27, 2018 |
| RF cable (9kHz-40GHz) | TCT | RE-05 | N/A | Sep. 27, 2018 |
| Antenna Connector | TCT | RFC-02 | N/A | Sep. 27, 2018 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement

6.3.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC part 27.53(h)(3) and FCC part 27.53(m)(6), FCC part 24.238(b) |
| Test Method: | FCC part 2.1049 |
| Limit: | N/A |
| Test Setup: |  <p>The diagram illustrates the test setup. A System Simulator (represented by a purple box) and a Spectrum Analyzer (represented by a green box) are connected to a Power Divider (represented by a black box). The Power Divider is then connected to the EUT (Equipment Under Test, represented by a mobile phone icon).</p> |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 4.2. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The 99% occupied bandwidth were measured, set RBW= 1% of OBW, VBW= 3*RBW, sample detector, trace maximum hold. 5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold. |
| Test Result: | PASS |


6.3.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------------------|--------------|--------|---------------|-----------------|
| Wideband Radio Communication Tester | R&S | CMW500 | 114220 | Sep. 27, 2018 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 27, 2018 |
| RF cable (9kHz-40GHz) | TCT | RE-05 | N/A | Sep. 27, 2018 |
| Antenna Connector | TCT | RFC-02 | N/A | Sep. 27, 2018 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.4. Band Edge and Conducted Spurious Emission Measurement

6.4.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC part 27.53(h), FCC part 27.53(g) , FCC part 27.53(m)(4), FCC part 24.238(a), 22.917(a) |
| Test Method: | FCC part2.1051 |
| Limit: | -13dBm |
| Test Setup: |  <p>The diagram shows a System Simulator (top) and a Spectrum Analyzer (bottom) connected to a central Power Divider. The Power Divider is then connected to the EUT (Equipment Under Test), represented by a mobile phone icon.</p> |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 6.0. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The band edges of low and high channels for the highest RF powers were measured. 5. The conducted spurious emission for the whole frequency range was taken. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power $P(\text{Watts}) = P(\text{W}) - [43 + 10\log(P)] (\text{dB}) = [30 + 10\log(P)] (\text{dBm}) - [43 + 10\log(P)] (\text{dB}) = -13\text{dBm}$. For Band 17, the limit line is derived from $55 + 10\log(P)$ dB below the transmitter power |
| Test Result: | PASS |



6.4.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------------------------|--------------|--------|---------------|-----------------|
| Wideband Radio Communication Tester | R&S | CMW500 | 114220 | Sep. 27, 2018 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 27, 2018 |
| RF cable (9kHz-40GHz) | TCT | RE-05 | N/A | Sep. 27, 2018 |
| Antenna Connector | TCT | RFC-02 | N/A | Sep. 27, 2018 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5. Field Strength of Spurious Radiation Measurement

6.5.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC part 27.53(g) ,FCC part 27.53(h), FCC part 27.53(m)(4), FCC part 22.917(a), 24.238(b) |
| Test Method: | FCC part 2.1053 |
| Limit: | 30MHz~20GHz -13dBm |
| Test setup: | <p>From 30MHz to 1GHz</p>  <p>Above 1GHz</p>  |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 5.8 and ANSI / TIA-603-D-2010Section 2.2.12. 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower. 4. The table was rotated 360 degrees to determine the position of the highest spurious emission. 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations. |

| | |
|---------------|---|
| | <ol style="list-style-type: none"> 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission. 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission. 9. Taking the record of output power at antenna port. 10. Repeat step 7 to step 8 for another polarization. 11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain 12. ERP (dBm) = EIRP - 2.15 13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts) $= P(W) - [43 + 10\log(P)] \text{ (dB)}$ $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$ $= -13\text{dBm}.$ For Band 17, the limit line is derived from $55 + 10\log(P)$ dB below the transmitter power |
| Test results: | PASS |


6.5.2. Test Instruments

| Radiated Emission Test Site (966) | | | | |
|-----------------------------------|--------------------|------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| System simulator | R&S | CMU200 | 111382 | Sep. 27, 2018 |
| Spectrum Analyzer | ROHDE&SCHW ARZ | R&S | FSQ | Sep. 27, 2018 |
| Signal Generator | HP | 83623B | 3614A00396 | Sep. 27, 2018 |
| Broadband Antenna | Schwarzbeck | VULB9163 | 340 | Sep. 27, 2018 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 631 | Sep. 27, 2018 |
| Broadband Antenna | Schwarzbeck | VULB9163 | 412 | Sep. 27, 2018 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 1201 | Sep. 27, 2018 |
| Horn Antenna | Schwarzbeck | BBH 9170 | 582 | Sep. 27, 2018 |
| Dipole Antenna | TCT | TCT-RF | N/A | Sep. 27, 2018 |
| Coax cable (9kHz-1GHz) | TCT | RE-low-01 | N/A | Sep. 27, 2018 |
| Coax cable (9kHz-40GHz) | TCT | RE-high-02 | N/A | Sep. 27, 2018 |
| Coax cable (9kHz-1GHz) | TCT | RE-low-03 | N/A | Sep. 27, 2018 |
| Coax cable (9kHz-40GHz) | TCT | RE-High-04 | N/A | Sep. 27, 2018 |
| Antenna Mast | Keleto | CC-A-4M | N/A | N/A |
| EMI Test Software | Shurple Technology | EZ-EMC | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6. Frequency Stability Measurement

6.6.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC part 27.54, FCC part 22.355, 24.235 |
| Test Method: | FCC Part 2.1055 |
| Limit: | ± 2.5 ppm |
| Test Setup: |  <p>The diagram illustrates the test setup. On the left, a 'System Simulator' is connected via a cable to an 'EUT' (Equipment Under Test) which is placed inside a 'Thermal Chamber'.</p> |
| Test Procedure: | <p>Test Procedures for Temperature Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 9.0. 2. The EUT was set up in the thermal chamber and connected with the system simulator. 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute. 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute. <p>Test Procedures for Voltage Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 9.0. 2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator. 3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT. 4. The variation in frequency was measured for the worst case. |
| Test Result: | PASS |

6.6.2. Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|---|--------------|-------------------|---------------|-----------------|
| Wideband Radio Communication Tester | R&S | CMW500 | 114220 | Sep. 27, 2018 |
| Programable tempratuce and humidity chamber | JQ | JQ-2000 | N/A | Sep. 27, 2018 |
| DC power supply | Kingrang | KR3005K 30V/5A | N/A | Sep. 27, 2018 |
| RF cable (9kHz-40GHz) | TCT | RE-04 | N/A | Sep. 27, 2018 |
| Antenna Connector | TCT | RFC-03 | N/A | Sep. 27, 2018 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

Appendix A: Photographs of Test Setup

Refer to test report TCT180723E017

Appendix B: Photographs of EUT

Refer to test report TCT180723E017

**Test Data for Appendix For LTE Band 2, Appendix For LTE Band 4,
Appendix For LTE Band 5, Appendix For LTE Band 12, Appendix For LTE
Band 17**

*******END OF REPORT*******