



Report No.: FA8N0224



# **RF Exposure Evaluation Report**

FCC ID : U94EARIS1218-T Equipment : Wireless Pedestal

Brand Name : Humantechnik

Model Name : Earis transmitter

Applicant : Adec & Partner AG

Staldenbachstrasse 30, 8808 Pfaeffikon, Switzerland

Manufacturer : Humantechnik GmbH

Im Woerth 25, 79576 Weil am Rhein, Germany

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Dec. 02, 2018, and testing was started from Jan. 14, 2019 and completed on Jan. 14, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5

Report Template No.: HE1-A3 Ver2.1 Report Version : 01

FCC ID: U94EARIS1218-T



## Radio Exposure Evaluation Report

## **Table of Contents**

HI	STO	RY OF THIS TEST REPORT	. 3
1.		GENERAL DESCRIPTION	. 4
	1.1.	EUT General Information	.4
	1.2.	Testing Location Information	.4
2		RF EXPOSURE EVALUATION	5
	2.1.	Applicable Standard	.5
		SAR evaluation	

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A3 Ver2.1 FCC ID: U94EARIS1218-T

Page Number : 2 of 5

Issued Date : Mar. 05, 2019

Report No.: FA8N0224

Report Version : 01

### HISTORY OF THIS TEST REPORT

Report No.: FA8N0224

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA8N0224	01	Initial issue of report	Mar. 05, 2019

Reviewed by: Jackson Tsai

Report Producer: Michelle Tsai

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Mar. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01

FCC ID: U94EARIS1218-T

### 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

	RF General Information					
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type			
2.4G SRD	2400-2483.5	2406-2478	FSK			

Report No.: FA8N0224

## 1.2. Testing Location Information

Testing Location							
$\boxtimes$	HWA YA	ADD	:	No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)			
		TEL	:	886-3-327-3456 FAX : 886-3-327-0973			
	Test site Designation No. TW1190 with FCC.						
	JHUBEI ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)						
		TEL	:	886-3-656-9065 FAX : 886-3-656-9085			
	Test site Designation No. TW0006 with FCC.						

TEL: 886-3-327-3456 Page Number : 4 of 5

Report Version

: 01

Report Template No.: HE1-A3 Ver2.1 FCC ID: U94EARIS1218-T



#### 2. RF EXPOSURE EVALUATION

#### 2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Report No.: FA8N0224

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

#### 2.2. SAR evaluation

- Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
  - [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Gain	Tolerance	Tune-up M	lax. Power	<b>Test Distance</b>	Frequency	Exclusion
(dBm)	(dBi)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
3.58	2.41	0.00	5.99	3.97	5	2.402	1.23

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 1.23 < 3, RF exposure evaluation is not required.

\_\_\_\_\_THE END\_\_\_\_

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Mar. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01

FCC ID: U94EARIS1218-T