120mm

For repair, return to: SimpliSafe, Inc.
1035 Cambridge St. Suite 18A, Cambridge MA 02141

NOT SUITABLE FOR INSTALLATION IN AREAS WHERE AIR VELOCITIES EXCEED 300 METERS PER MINUTE (985 FPM)

Model: SSSD1

Single Station Smoke Alarm

Compatible with SimpliSafe2 Alarm System (SSCS2)

Date of manufacture: xx/xx/xx

Smoke sensitivity range: 1.7% ~ 2.7%/ft obscuration. Maximum normal ambient temperature: 37.8ºC (100ºF). Push & hold test button to test weekly. Detector is for household smoke detection use only. For safety information and instructions see owner's manual (issue # SSD1-A).

ETL LISTED US

Intertek

Conforms to UL 268
Control # 4006914

FCC ID: U9K-SD1000
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Made in Taiwan

Use only CR123A replacement battery, available at retail stores (a different battery will have a detrimental effect on smoke alarm operation). CONSTANT EXPOSURES TO HIGH OR LOW TEMPERATURES/HUMIDITY MAY REDUCE BATTERY LIFE.