

For household use only. Pour usage domestique seulement.
For repair/pour l'entretien, return to/Retourner à: SimpliSafe, Inc.
100 Messina Drive Suite E Braintree, MA 02184

Model / Modèle : SSSD3

Smoke Detector / Détecteur de fumée
Compatible: SimpliSafe3 Alarm System (SSBS3)

Date / Daté: 2017/11/07

Sensitivity / Sensibilité : 1.7% ~ 2.7% / ft obstruction.
Push & hold test button to test weekly. Poussez et maintenez enfoncé bouton de test pour tester chaque semaine. For safety information, instructions and obscuration see owner's manual (issue# SSSD3 RK1). Pour des informations sur la sécurité et instructions voir le manuel du propriétaire (issue# SSSD3 RK1).

Made in Taiwan.
Fabriqué à Taïwan.

FCC ID : U9K-SD3000
IC : 20992-SD3000

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.



Intertek
4006914

Conforms To UL Std 268

Use only Panasonic CR123A (a different battery will have detrimental effect on smoke detector operation)
Utilisez seulement Panasonic CR123A (une batterie différente avoir un effet néfaste sur le fonctionnement du détecteur de fumée).
CONSTANT EXPOSURES TO HIGH OR LOW TEMPERATURES/ HUMIDITY MAY REDUCE BATTERY LIFE.
LES EXPOSITIONS CONSTANTES AUX TEMPERATURES HAUTES OU INFÉRIEURES / L'HUMIDITÉ PEUVENT RÉDUIRE LA VIE DE LA BATTERIE.

Test Weekly. Clean with a Dry Cloth

Alarm Response Time	
Flame	60-180 seconds
High CO	10-50 seconds
CO Alarm	4-10 seconds

Electrochemical Carbon Monoxide Alarm
Model No: SSC03-0 Type A Rating: ICC 4.5/AA's
Serial No: GH31732 Date of MFG: 2017 Aug 10
Alarm response time: 400 PPM within 4-10seconds
Owners Manual Issued w/ SSC03-0 W1

WARNING: Do not touch or Carbon Monoxide can't be seen or smelled. If alarm sounds, (1) Press test/silence button (2) Call 911 (3) immediately move to an area with fresh air (either outside or by an open window).

For repair return to:
SengcoBatt, Inc., 100
Mercury Dr., Suite E
Branford, MA, 02704

WARNING: Constant exposure to high or low temperatures or high humidity may reduce battery life. Use only Energizer R51AA alkaline batteries. Use of a different battery may have a detrimental effect on alarm operation. Unit requires a 3 min. warm-up after battery is inserted (during this time the Red and Green LEDs will flash once every 8 seconds). Battery replacement is indicated by the Green LED flashing.

CAUTION:

Do not attempt to open the alarm housing or tamper with the test button. Ensure correct

FCC ID: UBN-C03000

Do not use this alarm in any area where the alarm is not intended to be used. Do not use this alarm in any area where the alarm is not intended to be used. Do not use this alarm in any area where the alarm is not intended to be used.

Trouble Conditions

- Tempor: Yellow LED on steadily 1 chirp per minute.
- Low Battery: Yellow LED flashes once per minute, 1 chirp per minute.
- Low Sensitivity: Yellow LED flashes 2x per minute, 1 chirp per minute.
- Misfunction: Yellow LED flashes 3x per minute, 1 chirp per minute.
- End of Life: Yellow LED flashes 4x per minute, 1 chirp per minute.

Made in Taiwan