

14 § 15.247 (e) (i) and § 2.1091 - RF EXPOSURE

14.1 Applicable Standard

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

14.2 MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

14.2.3 Test Data

Maximum peak output power at antenna input terminal (dBm): 5.26

Maximum peak output power at antenna input terminal (mW): 3.36

Prediction distance (cm): 20

Prediction frequency (MHz): 2480

Maximum Antenna Gain, typical (dBi): 3

Maximum Antenna Gain (numeric): 1.995

Power density of prediction frequency at 20.0 cm (mW/cm²): 0.0013

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.00

14.3 Test Result

The power density level at 20 cm is 0.0013 mW/cm², which is below the uncontrolled exposure limit of 1.00 mW/cm² at 2480 MHz. The EUT is used at least 20cm away from user's body. It is determined as mobile equipment.