



Physical Address: Unit C, 6 Ascension Place, Mairangi Bay,
Auckland, New Zealand
Postal Address: PO Box 302340, North Harbour Postal Centre,
Auckland, New Zealand
Phone: +64 (9) 476 7124 Fax: +64 (9) 476 7128

Multi Prox (PRX-MULTI) Operational Description

This device is a 125 kHz Proximity Card and Pin Reader, designed to be used in Building Access, Security and Industrial Control applications.

The Multi-Prox will read and decode a 125 kHz proximity card when it is placed within 10cm of the device. It then outputs the information stored on the card in a Wiegand data stream through 2 open collector outputs on the external wiring interface (as described below). The Multi-Prox also outputs any key pressed on the keypad using the Wiegand data stream.

The user interface is a bi-colour LED and a buzzer. The state of the LED is controlled from the external wiring interface (as described below). The buzzer is also controlled from this interface, and is also activated for a short pulse when a Proximity Card is successfully read. The Multi-Prox has a 9 core external wiring interface that allows the Multi-Prox to connect to Building Access, Security and Industrial Control systems. This interface includes wires for: power, ground, 2 Wiegand outputs, 2 LED inputs, a Buzzer input and a special function input/output control.

Confidentiality and Privilege Notice This document and all associated page(s) is intended solely for the named addressee. The information contained in the page(s) is confidential and contains legally privileged information. If you are not the addressee indicated in this message (or responsible for delivery of the message to such person), you may not copy, re-transmit or deliver this message to anyone and you should destroy this message and kindly notify the sender by reply fax or phone. Confidentiality and legal privilege are not waived or lost by reason of mistaken delivery to you.