



## TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: NTT docomo P-01A

To: FCC Part 15.225: 2006 (Subpart C)

**Test Report Serial No:**  
RFI/RPT2/RP73958JD07A

**Supersedes Test Report Serial No:**  
RFI/RPT1/RP73958JD07A

<b>This Test Report Is Issued Under The Authority Of Steve Flooks, Service Leader:</b>		 pp Brian Watson
<b>Checked By:</b> Brian Watson		<b>Report Copy No: PDF01</b>
<b>Issue Date: 14 October 2008</b>	<b>Test Dates: 09 September 2008 to 23 September 2008</b>	

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields. This report may be copied in full. The results in this report apply only to the sample(s) tested.

**RFI Global Services Ltd**

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire RG23 8BG  
Telephone: +44 (0)1256 312000 Facsimile: +44 (0)1256 312001  
Email: [info@rfi-global.com](mailto:info@rfi-global.com) Website: [www.rfi-global.com](http://www.rfi-global.com)

Registered in England and Wales. Company number: 2117901

**Test of: NTT docomo P-01A**  
**To: FCC Part 15.225: 2006 (Subpart C)**

---

This page has been left intentionally blank.

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**Table of Contents**

1. Customer Information..... 4

2. Equipment Under Test (EUT) ..... 5

3. Test Specification, Methods and Procedures..... 8

4. Deviations from the Test Specification ..... 9

5. Operation of the EUT During Testing ..... 10

6. Summary of Test Results ..... 11

7. Measurements, Examinations and Derived Results ..... 12

8. Measurement Uncertainty ..... 24

Appendix 1. Test Equipment Used ..... 25

Appendix 2. Test Configuration Drawings..... 26

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **1. Customer Information**

<b>Company Name:</b>	Panasonic Mobile Communications Dev of Europe Ltd
<b>Address:</b>	Panasonic House Willoughby Road Bracknell Berkshire RG12 8FP United Kingdom
<b>Contact Name:</b>	Mr M Hargreaves

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **2. Equipment Under Test (EUT)**

The following information (with the exception of the Date of Receipt) has been supplied by the customer:

### **2.1. Identification of Equipment Under Test (EUT)**

<b>Description:</b>	Dual mode (W-CDMA FDDI/FDDV/ GSM900/1800/1900MHz) Cellular Mobile Telephone with RFID and Bluetooth
<b>Brand Name:</b>	NTT docomo
<b>Model Name or Number:</b>	P-01A
<b>Serial Number or Unique Product Identifier:</b>	359946010018134
<b>FCC ID Number:</b>	UCE208009A

<b>Description:</b>	FOMA USB Cable with Charge Function 01
<b>Model Name or Number:</b>	NTT docomo
<b>Serial Number:</b>	Not marked or stated
<b>Cable Length and Type:</b>	1.1 metre
<b>Connected to Port:</b>	USB

<b>Description:</b>	FOMA AC Adapter 01
<b>Brand Name:</b>	NTT docomo
<b>Model Name or Number:</b>	MAS-BH0008-A 002
<b>Serial Number:</b>	AC Charger #01
<b>Cable Length and Type:</b>	2.23 metre / multicore
<b>Connected to Port:</b>	Charger

<b>Description:</b>	Battery
<b>Brand Name:</b>	NTT
<b>Serial Number:</b>	P19

<b>Description:</b>	Flat-plug Stereo Earphone Set P01
<b>Brand Name:</b>	NTT docomo
<b>Model Name or Number:</b>	P01
<b>Cable Length and Type:</b>	1.8m / multi-core
<b>Connected to Port:</b>	AV Out port

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

Description:	DC Charger Cable
Model Name or Number:	FOMA DC Adapter 02
Cable Length and Type:	>2m extended.
Connected to Port:	Charger

Description:	Micro-SD Memory Card
Brand Name:	Panasonic
Model Name or Number:	None Stated
Serial Number:	None Stated
Cable Length and Type:	None Stated
Connected to Port:	Dedicated micro-SD card port

## **2.2. Description of EUT**

The equipment under test was a Dual mode (W-CDMA FDDI/FDDV/ GSM900/1800/1900MHz) Cellular Mobile Telephone with Bluetooth and RFID.

## **2.3. Modifications Incorporated in the EUT**

During the course of testing the EUT was not modified.

## **2.4. Support Equipment**

The following support equipment was used to exercise the EUT during testing:

Description:	Laptop PC
Model Name or Number:	SONY Vaio PCG-VX7/BD
Serial Number:	Serial number has been partially erased and cannot be read
Cable Length and Type:	Not Applicable
Connected to Port:	USB

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**2.5. Additional Information Related to Testing**

Power Supply Requirement:	Internal battery Supply of: 3.7V (nominal)		
Intended Operating Environment:	Within GSM Coverage UMTS coverage area		
Equipment Category:	Bluetooth, GSM/GPRS, Short Range Device, UMTS FDD I and UMTS band V		
Type of Unit:	Portable (Standalone battery powered device) Transceiver		
Transmit Frequency Range:	Not Applicable Single Frequency		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Single Channel	Not Applicable	13.56
Receive Frequency Range:	Not Applicable Single Frequency		
Receive Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Single Channel	Not Applicable	13.56

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

### **3. Test Specification, Methods and Procedures**

#### **3.1. Test Specifications**

<b>Reference:</b>	FCC Part 15 Subpart C: 2006 (Sections 15.225)
<b>Title:</b>	Code of Federal Regulations, Part 15 (47CFR225) Radio Frequency Devices.

#### **3.2. Methods and Procedures**

The methods and procedures used were as detailed in:

ANSI/TIA-603-B-2003

Land Mobile Communications Equipment, Measurements and performance Standards

ANSI C63.2 (1987)

Title: American National Standard for Instrumentation - Electromagnetic noise and field strength.

ANSI C63.4 (2001)

Title: American National Standard Methods of Measurement of Electromagnetic Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

ANSI C63.5 (1988)

Title: American National Standard for the Calibration of antennas used for Radiated Emission measurements in Electromagnetic Interference (EMI) control.

ANSI C63.7 (1988)

Title: American National Standard Guide for Construction of Open Area Test Sites for performing Radiated Emission Measurements.

CISPR 16-1: (1999)

Title: Specification For Radio Disturbance and Immunity Measuring Apparatus and Methods. Part 1: Radio Disturbance and Immunity Measuring Apparatus.

#### **3.3. Definition of Measurement Equipment**

The measurement equipment used complied with the requirements of the standards referenced in the Methods & Procedures section above. Appendix 1 contains a list of the test equipment used.



Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

#### **4. Deviations from the Test Specification**

There were no deviations from the test specification.

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **5. Operation of the EUT During Testing**

### **5.1. Operating Modes**

The EUT was tested in the following operating modes, unless otherwise stated:

- Idle
- Constantly transmitting at full power

### **5.2. Configuration and Peripherals**

The EUT was tested in the following configuration:

- The transmitter was enabled using a bespoke application on the Mobile handset
- Mains charger was connected to the EUT during Idle mode AC conducted and radiated spurious emissions testing.
- As the EUT was incapable of transmitting while charging no AC Mains Conducted Emissions (150 kHz to 30 MHz) was performed in transmit mode.

**Test of:** NTT docomo P-01A  
**To:** FCC Part 15.225: 2006 (Subpart C)

---

## **6. Summary of Test Results**

<b>Range of Measurements</b>	<b>FCC Part 15</b>	<b>Port Type</b>	<b>Result</b>
Receiver/Idle Mode AC Conducted Emissions (150 kHz to 30 MHz)	Section 15.107	AC Mains	Complied
Receiver/Idle Mode Radiated Spurious Emissions	Section 15.109	Enclosure	Complied
Transmitter Fundamental Field Strength	Section 15.225(a)	Antenna	Complied
Transmitter Radiated Spurious Emissions	Section 15.209	Enclosure	Complied
Transmitter Band Edge Radiated Emissions	Section 15.209	Antenna	Complied
Transmitter 20 dB Bandwidth	Section 2.1049	Antenna	Complied
Transmitter Frequency Stability (Temperature & Voltage Variation)	Section 15.225(c)	Antenna	Complied

### **6.1. Location of Tests**

All the measurements described in this report were performed at the premises of RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH.

### **6.2. Site Registration Number**

FCC: 209735

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **7. Measurements, Examinations and Derived Results**

### **7.1. General Comments**

7.1.1. This section contains test results only.

7.1.2. Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%.

Please refer to Section 8 for details of measurement uncertainties.

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **7.2. Test Results**

### **7.2.1. Receiver/Idle Mode AC Mains Conducted Emissions: Section 15.107**

Ambient Temperature: 26°C

Relative Humidity: 42%

7.2.1.1. Tests were performed in accordance with C63.4 Section 7 and relevant annexes.

7.2.1.2. Tests were performed to identify the maximum emission levels on the AC mains line of the EUT.

### **Results:**


#### **Quasi-Peak Detector Measurements on Live and Neutral Lines**

Frequency (MHz)	Line	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.186000	Live	41.5	64.2	22.7	Complied
0.285000	Live	36.8	60.7	23.9	Complied
0.501000	Live	34.8	56.0	21.2	Complied
0.568500	Live	30.2	56.0	25.8	Complied
0.699000	Live	34.6	56.0	21.4	Complied
0.798000	Live	35.0	56.0	21.0	Complied
1.000500	Live	34.3	56.0	21.7	Complied
1.099500	Live	34.4	56.0	21.6	Complied
1.761000	Live	39.0	56.0	17.0	Complied
1.851000	Live	38.8	56.0	17.2	Complied

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**Receiver/Idle Mode AC Mains Conducted Emissions: Section 15.107 (Continued)**



*Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.*

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**7.2.2. Receiver/Idle Mode Radiated Spurious Emissions: Section 15.109**

Ambient Temperature: 23°C

Relative Humidity: 35%

**7.2.3. Electric Field Strength Measurements (Frequency Range: 30 to 1000 MHz)**

7.2.3.1. Tests were performed in accordance with C63.4 Section 8 and relevant annexes.


7.2.3.2. Tests were performed to identify the maximum receiver or standby radiated emission levels.

**Results:**

Frequency (MHz)	Antenna Polarity	Q-P Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
25.250501	Vertical	45.1	69.5	15.7	Complied

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

Receiver/Idle Mode Radiated Spurious Emissions: Section 15.109 (Continued)



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.



#### **7.2.4. Transmitter Fundamental Field Strength: Section 15.225 (a)**

7.2.4.1. Tests were performed in accordance with C63.4 Section 8 and relevant annexes.

### Results:

Frequency (MHz)	Antenna Polarity	Q-P Level (dBμV/m)	Limit at 30 metres (dBμV/m)	Margin (dB)	Result
13.56	Loop edge on to EUT	61.0	124.0	63.0	Complied

Marker 1 [T1]

Ref Lvl 61.02 dBmV

102 dBmV 13.56093938 MHz

RBW 10 kHz VBW 30 kHz SWT 15 ms RF Att 50 dB Unit dBmV

Center 13.56 MHz 50 kHz/ Span 500 kHz

13.56093938 MHz

15.SEP.2008 14:07:59

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**7.2.5. Transmitter Radiated Spurious Emissions: Section 15.209**

Ambient Temperature: 22°C

Relative Humidity: 35%

**7.2.6. Electric Field Strength Measurements (Frequency Range: 9 kHz to 1000 MHz)**

7.2.6.1. Tests were performed in accordance with C63.4 Section 8 and relevant annexes.

7.2.6.2. Tests were performed to identify the maximum radiated spurious emission levels.

7.2.6.3. Limits below 30 MHz are specified at test distance of 30 metres, whilst below 0.49 MHz they are specified at a test distance of 300 metres. However as specified by section 15.31 (f)(2), measurements may be performed at a closer distance, and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

**Results:**



Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
40.6724	Vertical	27.9	40.0	12.1	Complied
67.7970	Vertical	35.7	40.0	4.3	Complied

**Note(s):**

1. The carrier is shown on the above plot at 13.5 MHz

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

Transmitter Radiated Spurious Emissions (Continued)



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

**7.2.7. Transmitter Radiated Emissions at Band Edges: Section 15.209**

Ambient Temperature: 25°C

Relative Humidity: 38%

7.2.7.1. Tests were performed in accordance with C63.4 Section 8 and relevant annexes.

7.2.7.2. Tests were performed to identify the maximum emissions level at the band edges of the frequency band that the EUT will operate over.

**Results:****Bottom Band Edge**


Frequency (MHz)	Q-P Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
13.553	5.1	80.5	75.4	Complied

**Top Band Edge**

Frequency (MHz)	Q-P Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
13.567	5.7	80.5	74.8	Complied

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

Transmitter Radiated Emissions at Band Edges (Continued)




Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.

### **7.2.8. Transmitter 20 dB Bandwidth**

Relative Humidity: 38%

7.2.8.2. This test is not required to show compliance to 15.225 but has been included for information in order to aid Industry Canada (IC) applications.

Transmitter 20 dB Bandwidth (Hz)
35.872



Test of: NTT docomo P-01A  
 To: FCC Part 15.225: 2006 (Subpart C)

### **7.2.9. Transmitter Frequency Stability (Temperature & Voltage Variation)**

Ambient Temperature: 25°C

Relative Humidity: 36%

7.2.9.1. Tests were performed in accordance with C63.4 Section 10.1.8.7 and 13.1.6 and relevant annexes

7.2.9.2. Tests were performed to identify the maximum frequency error of the EUT with variations in nominal operating voltage at an ambient temperature of 20°C.

7.2.9.3. Tests were performed in accordance with FCC Part 2.1055 but over the frequency range specified in FCC Part 15.

### **Results:**

#### **Maximum frequency error of the EUT with variations in ambient temperature**

Temp (°C)	Nominal Frequency	Measured Frequency	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
-20	13.56	13.559943	-57	0.0004	0.01	0.0096	Complied
20	13.56	13.559957	-43	0.0003	0.01	0.0097	Complied
50	13.56	13.559893	-107	0.0008	0.01	0.0092	Complied

#### **Maximum frequency error of the EUT with variations in nominal operating voltage at an ambient temperature of 20°C**

Supply Voltage (V)	Nominal Frequency	Measured Frequency	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
3.4	13.56	13.559958	-42	0.0003	0.01	0.0097	Complied
3.7	13.56	13.559957	-43	0.0003	0.01	0.0097	Complied
4.2	13.56	13.559957	-43	0.0003	0.01	0.0097	Complied

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---

## **8. Measurement Uncertainty**

8.1. No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently, the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

8.2. The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

8.3. The uncertainty of the result may need to be taken into account when interpreting the measurement results.

8.4. The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor, such that a confidence level of approximately 95% is maintained. For the purposes of this document “approximately” is interpreted as meaning “effectively” or “for most practical purposes”.

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±3.25 dB
Occupied Bandwidth	N/A	95%	±0.12 %
Frequency Stability	N/A	95%	±11.37 ppm
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	±3.53 dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	±5.26 dB

8.5. The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty, the published guidance of the appropriate accreditation body is followed.



Test of: NTT docomo P-01A  
 To: FCC Part 15.225: 2006 (Subpart C)

---

### **Appendix 1. Test Equipment Used**

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Last Calibrated	Cal. Interval (Months)
A007	Antenna	Rohde & Schwarz	HFH2-Z2	880 458/020	28 Feb 2008	12
A1299	Antenna	Schaffner	CBL6143	5094	28 Jul 2008	12
E013	Environmental Chamber	Sanyo	ATMOS chamber	None	Calibration not required	12
M1068	Thermometer	Iso-Tech	RS55	93102884	09 Jul 2008	12
M1124	Spectrum Analyser	Rohde & Schwarz	ESIB26	100046K	19 Feb 2008	12
M1229	Digital Multimeter	Fluke	179	87640015	09 May 2008	12
M1242	Spectrum Analyser	Rohde & Schwarz, Inc.	FSEM30	845986/022	29 Nov 2007	12
S0520	DC Power Supply Unit	GW instek	GPC-3030	E835141	Calibrated before use	12
K0002	3m RSE Chamber	Not Applicable	Not Applicable	Not Applicable	26 Aug 2008	12
K0004	Site Reference 4428	RFI Global Services Ltd	N/A	N/A	Calibration not required	12

**NB** In accordance with UKAS requirements, all the measurement equipment is on a calibration schedule.

Test of: NTT docomo P-01A  
To: FCC Part 15.225: 2006 (Subpart C)

---


## **Appendix 2. Test Configuration Drawings**

This appendix contains the following drawings:

Drawing Reference Number	Title
DRG\73958JD07\EMICON	Test configuration for measurement of conducted emissions.
DRG\73958JD07\EMIRAD	Test configuration for measurement of radiated emissions.

Test of: NTT docomo P-01A  
 To: FCC Part 15.225: 2006 (Subpart C)

DRG\73958JD07\EMICON



Test of: NTT docomo P-01A  
 To: FCC Part 15.225: 2006 (Subpart C)

DRG\73958JD07\EMIRAD

