



# TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: Softbank 940P

To: FCC Part 24: 2008 Subpart E

**Test Report Serial No:**  
RFI/RPT2/RP76194JD05A

**Supersedes Test Report Serial No:**  
RFI/RPT1/RP76194JD05A

<b>This Test Report Is Issued Under The Authority Of Brian Watson, Operations Director:</b>		pp 
<b>Checked By:</b>	R. Graham	
<b>Signature:</b>		
<b>Date of Issue:</b>	02 November 2009	

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

**RFI Global Services Ltd**

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire RG23 8BG  
Telephone: +44 (0)1256 312000 Facsimile: +44 (0)1256 312001  
Email: [info@rfi-global.com](mailto:info@rfi-global.com) Website: [www.rfi-global.com](http://www.rfi-global.com)

Registered in England and Wales. Company number:2117901

This page has been left intentionally blank.

**Table of Contents**

**1. Customer Information ..... 4**

**2. Summary of Testing ..... 5**

**3. Equipment Under Test (EUT) ..... 6**

**4. Operation and Monitoring of the EUT during Testing ..... 8**

**5. Measurements, Examinations and Derived Results ..... 9**

**6. Measurement Uncertainty ..... 27**

**Appendix 1. Test Equipment Used ..... 28**

**1. Customer Information**











<b>Company Name:</b>	Panasonic Mobile Communications Development of Europe Ltd
<b>Address:</b>	Panasonic House Willoughby Road Bracknell Berkshire RG12 8FP United Kingdom

## **2. Summary of Testing**

### **2.1. General Information**

<b>Specification Reference:</b>	47CFR24
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications) 2008: Part 24 Subpart E (Personal Communication Services)
<b>Site Registration:</b>	FCC: 209735
<b>Location of Testing:</b>	RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire RG24 8AH, United Kingdom
<b>Test Dates:</b>	12 October 2009 to 14 October 2009

### **2.2. Summary of Test Results**

<b>FCC Reference (CFR 47)</b>	<b>Measurement</b>	<b>Port Type</b>	<b>Result</b>
Part 15.107	Idle Mode AC Conducted Spurious Emissions	AC Mains	
Part 15.109	Idle Mode Radiated Spurious Emissions	Enclosure	
Part 15.207	Transmitter AC Conducted Spurious Emissions	AC Mains	
Part 24.232	Transmitter Effective Isotropic Radiated Power (EIRP)	Antenna	
Part 24.235	Transmitter Frequency Stability (Temperature & Voltage Variation)	Antenna	
Part 2.1049/24.238	Transmitter Occupied Bandwidth	Antenna	
Part 2.1053/24.238	Transmitter Out of Band Radiated Emissions	Antenna	
Part 2.1053/24.238	Transmitter Band Edge Radiated Emissions	Antenna	
<b>Key to Results</b>  = Complied  = Did not comply			

### **2.3. Methods and Procedures**

<b>Reference:</b>	ANSI/TIA-603-C-2004
<b>Title:</b>	Land Mobile Communications Equipment, Measurements and performance Standards
<b>Reference:</b>	ANSI C63.4 (2003)
<b>Title:</b>	American National Standard Methods of Measurement of Electromagnetic Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

### **2.4. Deviations from the Test Specification**

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

### **3. Equipment Under Test (EUT)**

#### **3.1. Identification of Equipment Under Test (EUT)**

<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	940P
<b>IMEI Number:</b>	004401220872242
<b>Hardware Version Number:</b>	Rev C
<b>Software Version Number:</b>	940PVA12
<b>FCC ID Number:</b>	UCE209020A

<b>Description:</b>	AC Charger
<b>Brand Name:</b>	Softbank
<b>Model Name or Number:</b>	ZTDAA1

<b>Description:</b>	Personal Hands Free
<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	ZTCK01

<b>Description:</b>	Personal Hands Free converter
<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	PMLAJI

<b>Description:</b>	DC Charger
<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	PMJAA1

<b>Description:</b>	Micro-SD Memory Card
<b>Brand Name:</b>	None Stated
<b>Model Name or Number:</b>	None Stated

<b>Description:</b>	USB Data Cable
<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	ZTFE01

<b>Description:</b>	Battery
<b>Brand Name:</b>	SoftBank
<b>Model Name or Number:</b>	PMBAS1

### **3.2. Description of EUT**

The equipment under test was a dual mode UMTS/GSM cellular handset with *Bluetooth* and RFID, with a retractable antenna.

### **3.3. Modifications Incorporated in the EUT**

No modifications were applied to the EUT during testing.

### **3.4. Additional Information Related to Testing**

Technology Tested:	PCS1900		
Type of Radio Device:	Transceiver		
Mode:	GSM/GPRS		
Modulation Type:	GMSK		
Channel Spacing:	200 kHz		
Power Supply Requirement(s):	Nominal	3.7 V	
	Minimum	3.4 V	
	Maximum	4.2 V	
Maximum Output Power (EIRP):	GSM	32.3 dBm	
	GPRS	30.0 dBm	
Transmit Frequency Range:	1850 to 1910 MHz		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	512	1850.2
	Middle	660	1879.8
	Top	810	1909.8
Receive Frequency Range:	1930 to 1990 MHz		
Receive Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	512	1930.2
	Middle	660	1959.8
	Top	810	1989.8

### **3.5. Support Equipment**

The following support equipment was used to exercise the EUT during testing:

Description:	Dummy battery
Model Name or Number:	Not stated
Serial Number:	Not stated

## **4. Operation and Monitoring of the EUT during Testing**

### **4.1. Operating Modes**

The EUT was tested in the following operating mode(s):

- Idle mode.
- Constantly transmitting at full power on bottom, centre and top channels as required.
- Occupied bandwidth, EIRP and band edge tests were performed with the EUT in GSM single timeslot circuit switched and GPRS Multislot Class 10 with the unit transmitting on two timeslots in the uplink.
- Transmitter radiated spurious emissions were checked in all modes during pre-scans. Circuit switched voice was found to be the worst case and all final measurements were performed with the EUT in this mode.

### **4.2. Configuration and Peripherals**

The EUT was tested in the following configuration(s):

- Connected to a GSM/GPRS system simulator, operating in transceiver mode
- Idle mode and transmitter mode radiated spurious emissions tests were performed with the mains charger connected to the EUT via 120 V AC 60 Hz supply with the retractable antenna extended, as this was found to be the worst case during pre-scans. All accessories were individually connected and measurements made during pre-scans to determine the worst case combination.
- EIRP was measured with the retractable antenna extended, as this was found to give the highest output level.
- The Micro-SD card was present in the EUT during all tests.



## **5. Measurements, Examinations and Derived Results**

### **5.1. General Comments**

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate *coverage factor* to provide a statistical confidence level of approximately 95%. Please refer to Section 6 Measurement Uncertainty *for* details.

## 5.2. Test Results

### 5.2.1. Idle Mode AC Conducted Spurious Emissions

#### Test Summary:

FCC Part:	15.107(a)
Test Method Used:	As detailed in ANSI C63.4 Section 7 and relevant annexes

#### Environmental Conditions:


Temperature (°C):	25
Relative Humidity (%):	27

#### Results: Quasi Peak Detector Measurements

Frequency (MHz)	Line	Quasi Peak Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.240000	Neutral	43.1	62.1	19.0	Complied
0.690000	Neutral	35.9	56.0	20.1	Complied
1.036500	Neutral	34.0	56.0	22.0	Complied
1.725000	Neutral	39.6	56.0	16.4	Complied
2.647500	Neutral	38.4	56.0	17.6	Complied
3.228000	Neutral	33.7	56.0	22.3	Complied

#### Results: Average Detector Measurements

Frequency (MHz)	Line	Average Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.235500	Live	28.2	52.3	24.1	Complied
0.690000	Neutral	20.2	46.0	25.8	Complied
1.036500	Neutral	18.2	46.0	27.8	Complied
1.603500	Live	26.3	46.0	19.7	Complied
2.535000	Neutral	22.4	46.0	23.6	Complied
3.228000	Neutral	18.2	46.0	27.8	Complied

**Idle Mode AC Conducted Spurious Emissions (continued)**

*Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.*

**5.2.2. Idle Mode Radiated Spurious Emissions****Test Summary:**


FCC Part:	15.109
Frequency Range:	30 MHz to 1000 MHz
Test Method Used:	As detailed in ANSI C63.4 Section 8 and relevant annexes

**Environmental Conditions:**

Temperature (°C):	27
Relative Humidity (%):	27

**Results:**

Frequency (MHz)	Antenna Polarity	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Result
37.203	Horizontal	29.3	40.0	10.7	Complied
53.222	Horizontal	37.9	40.0	2.1	Complied
72.486	Vertical	29.4	40.0	10.6	Complied
458.782	Horizontal	31.4	46.0	14.6	Complied



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.

**Idle Mode Radiated Spurious Emissions (continued)****Test Summary:**

<b>FCC Part:</b>	15.109
<b>Frequency Range:</b>	1 GHz to 12.75 GHz
<b>Test Method Used:</b>	As detailed in ANSI C63.4 Section 8 and relevant annexes

**Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	27




**Results:**

<b>Frequency (MHz)</b>	<b>Antenna Polarity</b>	<b>Peak Level (dB<math>\mu</math>V/m)</b>	<b>Average Limit (dB<math>\mu</math>V/m)</b>	<b>Margin (dB)</b>	<b>Result</b>
3.969940	Horizontal	47.2	54.0	6.8	Complied


**Note(s):**

1. No spurious emissions were detected above the noise floor of the measuring receiver; therefore, the highest peak noise floor reading of the measuring receiver was recorded as shown in the table above. The peak level was compared to the average limit as opposed to being compared to the peak limit because this is the more onerous limit.
2. All pre-scans were performed with a peak detector against the average limit apart from measurements made in the range of 8 to 12.75 GHz where pre-scans were performed with peak and average detectors and the applicable limit applied. This was due to the noise floor exceeding the average limit when using a peak detector.

Idle Mode Radiated Spurious Emissions (continued)



Peak detector



Average detector

**5.2.3. Transmitter AC Conducted Spurious Emissions****Test Summary:**

<b>FCC Part:</b>	15.207
<b>Test Method Used:</b>	As detailed in ANSI C63.4 Section 7 and relevant annexes

**Environmental Conditions:**


<b>Temperature (°C):</b>	25
<b>Relative Humidity (%):</b>	27

**Results: Quasi Peak Detector Measurements**

Frequency (MHz)	Line	Quasi Peak Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.181500	Live	43.8	64.4	20.6	Complied
0.388500	Live	37.8	58.1	20.3	Complied
0.681000	Live	35.5	56.0	20.5	Complied
1.266000	Live	36.1	56.0	19.9	Complied
1.639500	Live	40.1	56.0	15.9	Complied
2.638500	Neutral	38.2	56.0	17.8	Complied

**Results: Average Detector Measurements**

Frequency (MHz)	Line	Average Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Result
0.190500	Live	30.1	54.0	23.9	Complied
0.384000	Live	29.3	48.2	18.9	Complied
0.676500	Live	24.4	46.0	21.6	Complied
1.356000	Live	21.2	46.0	24.8	Complied
1.549500	Live	24.6	46.0	21.4	Complied
2.710500	Neutral	23.8	46.0	22.2	Complied

**Transmitter AC Conducted Spurious Emissions (continued)**

*Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.*



**5.2.4. Transmitter Effective Isotropic Radiated Power (EIRP)****Test Summary:**

<b>FCC Part:</b>	24.232
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.17.2

**Environmental Conditions:**

<b>Temperature (°C):</b>	26
<b>Relative Humidity (%):</b>	29

**Results: GSM**

Channel	Frequency (MHz)	Antenna Polarity	EIRP (dBm)	Limit (dBm)	Margin (dBm)	Result
Bottom	1850.2	Horizontal	29.4	33.0	3.6	Complied
Middle	1879.8	Horizontal	30.3	33.0	2.7	Complied
Top	1909.8	Horizontal	32.3	33.0	0.7	Complied

**Results: GPRS**

Channel	Frequency (MHz)	Antenna Polarity	EIRP (dBm)	Limit (dBm)	Margin (dBm)	Result
Bottom	1850.2	Horizontal	27.8	33.0	5.2	Complied
Middle	1879.8	Horizontal	28.6	33.0	4.4	Complied
Top	1909.8	Horizontal	30.0	33.0	3.0	Complied

**Note(s):**

1. The retractable antenna was in an extended position, as this was found to give the highest EIRP.

**5.2.5. Transmitter Frequency Stability (Temperature)****Test Summary:**

<b>FCC Part:</b>	24.235
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.2 referencing FCC CFR Part 2.1055

**Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	27

**Results: Bottom Channel (1850.2 MHz)**

Temperature (°C)	Frequency Error (Hz)	Measured Frequency (MHz)	Lower Band Edge Limit (MHz)	Margin (MHz)	Result
-30	18	1850.200018	1850.0	0.200018	Complied
-20	26	1850.200026	1850.0	0.200026	Complied
-10	21	1850.200021	1850.0	0.200021	Complied
0	19	1850.200019	1850.0	0.200019	Complied
10	29	1850.200029	1850.0	0.200029	Complied
20	28	1850.200028	1850.0	0.200028	Complied
30	38	1850.200038	1850.0	0.200038	Complied
40	40	1850.200040	1850.0	0.200040	Complied
50	35	1850.200035	1850.0	0.200035	Complied

**Results: Top Channel (1909.8 MHz)**

Temperature (°C)	Frequency Error (Hz)	Measured Frequency (MHz)	Upper Band Edge Limit (MHz)	Margin (MHz)	Result
-30	33	1909.800033	1910.0	0.199967	Complied
-20	15	1909.800015	1910.0	0.199985	Complied
-10	25	1909.800025	1910.0	0.199975	Complied
0	23	1909.800023	1910.0	0.199977	Complied
10	26	1909.800026	1910.0	0.199974	Complied
20	32	1909.800032	1910.0	0.199968	Complied
30	39	1909.800039	1910.0	0.199961	Complied
40	37	1909.800037	1910.0	0.199963	Complied
50	36	1909.800036	1910.0	0.199964	Complied

**5.2.6. Transmitter Frequency Stability (Voltage Variation)****Test Summary:**

<b>FCC Part:</b>	24.235
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.2 referencing FCC CFR Part 2.1055

**Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	29

**Results: Bottom Channel (1850.2 MHz)**

Supply Voltage (V)	Frequency Error (Hz)	Measured Frequency (MHz)	Lower Band Edge Limit (MHz)	Margin (MHz)	Result
3.145	-29	1850.199971	1850.0	0.199971	Complied
4.255	-23	1850.199977	1850.0	0.199977	Complied

**Results: Top Channel (1909.8 MHz)**

Supply Voltage (V)	Frequency Error (Hz)	Measured Frequency (MHz)	Upper Band Edge Limit (MHz)	Margin (MHz)	Result
3.145	-34	1909.799966	1910.0	0.200034	Complied
4.255	-31	1909.799969	1910.0	0.200031	Complied

**5.2.7. Transmitter Occupied Bandwidth****Test Summary:**

<b>FCC Part:</b>	24.238
<b>Test Method Used:</b>	As detailed in ANSI C63.4 Section 13.1.7 and relevant annexes referencing FCC CFR Part 2.1049 (see note below)
<b>Modulation:</b>	GSM Circuit Switched

**Environmental Conditions:**


<b>Temperature (°C):</b>	28
<b>Relative Humidity (%):</b>	29

**Results:**

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	1879.8	238.076

**Note(s):**

- In lieu of the test method detailed in ANSI C63.4 Section 13.1.7 the 99% occupied bandwidth was measured using the Occupied Bandwidth function of the spectrum analyser.



**Transmitter Occupied Bandwidth (continued)****Test Summary:**

<b>FCC Part:</b>	24.238
<b>Test Method Used:</b>	As detailed in ANSI C63.4 Section 13.1.7 and relevant annexes referencing FCC CFR Part 2.1049 (see note below)
<b>Modulation:</b>	GPRS

**Environmental Conditions:**


<b>Temperature (°C):</b>	28
<b>Relative Humidity (%):</b>	29

**Results:**

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	1879.8	240.481

**Note(s):**

- In lieu of the test method detailed in ANSI C63.4 Section 13.1.7 the 99% occupied bandwidth was measured using the Occupied Bandwidth function of the spectrum analyser.



**5.2.8. Transmitter Out of Band Radiated Emissions****Test Summary:**

<b>FCC Part:</b>	2.1053 & 24.238
<b>Frequency Range:</b>	30 MHz to 20 GHz
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.12 referencing FCC CFR Parts 2.1053 and 24.238

**Environmental Conditions:**

<b>Temperature (°C):</b>	27
<b>Relative Humidity (%):</b>	36

**Results: Bottom Channel**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
3700.410	-38.4	-13.0	25.4	Complied
5550.327	-38.6	-13.0	25.6	Complied
7400.798	-24.6	-13.0	11.6	Complied
9250.759	-26.9	-13.0	13.9	Complied

**Results: Middle Channel**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
3759.434	-37.2	-13.0	24.2	Complied
5639.173	-33.5	-13.0	20.5	Complied
7519.352	-24.0	-13.0	11.0	Complied
9399.195	-25.2	-13.0	12.2	Complied





**Results: Top Channel**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
3819.618	-36.8	-13.0	23.8	Complied
5729.619	-34.9	-13.0	21.9	Complied
7638.828	-26.1	-13.0	13.1	Complied
9548.767	-24.4	-13.0	11.4	Complied



**Note(s):**

1. The transmitter fundamental is shown on the 1 GHz to 4 GHz pre-scan plot at approximately 1908 MHz.
2. The test antenna was rotated in the horizontal and vertical planes. The highest levels were recorded in the above table.
3. The high level of the 2nd harmonic (at 3.8256 GHz on the 1 GHz to 4 GHz plot) is caused by distortion in the preamplifier used during pre-scans. The final measurement of this harmonic emission was measured using an appropriate filter.

Transmitter Out of Band Radiated Emissions (continued)



Transmitter Out of Band Radiated Emissions (continued)



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.



**5.2.9. Transmitter Radiated Emissions at Band Edges****Test Summary:**

<b>FCC Part:</b>	2.1053 & 24.238
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.12 referencing FCC CFR Parts 2.1053 and 24.238
<b>Modulation:</b>	GSM

**Environmental Conditions:**



<b>Temperature (°C):</b>	26
<b>Relative Humidity (%):</b>	32

**Results: Bottom Band Edge**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
1850.0	-25.4	-13.0	12.4	Complied

**Results: Top Band Edge**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
1910.0	-23.0	-13.0	10.0	Complied



**Transmitter Radiated Emissions at Band Edges (continued)****Test Summary:**

<b>FCC Part:</b>	2.1053 & 24.238
<b>Test Method Used:</b>	As detailed in ANSI TIA-603-C-2004 Section 2.2.12 referencing FCC CFR Parts 2.1053 and 24.238
<b>Modulation:</b>	GPRS

**Environmental Conditions:**



<b>Temperature (°C):</b>	26
<b>Relative Humidity (%):</b>	33

**Results: Bottom Band Edge**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
1850	-18.7	-13.0	5.7	Complied

**Results: Top Band Edge**

Frequency (MHz)	Peak Emission Level (dBm)	Limit (dBm)	Margin (dBm)	Result
1910	-23.0	-13.0	10.0	Complied



## 6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document “approximately” is interpreted as meaning “effectively” or “for most practical purposes”.

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±3.72 dB
Effective Isotropic Radiated Power (EIRP)	Not applicable	95%	±2.94 dB
Frequency Stability	Not applicable	95%	±0.92 ppm
Occupied Bandwidth	Not applicable	95%	±0.92 ppm
Radiated Spurious Emissions	30 MHz to 26 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

## **Appendix 1. Test Equipment Used**

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Last Calibrated	Cal. Interval (Months)
A1141	Directional Coupler	Hewlett Packard	11691D	1212A02494	Calibrated before use	-
A1391	Attenuator	Huber + Suhner	757987	6810.17.B	Calibrated before use	-
A1392	Attenuator	Huber + Suhner	757456	6820.17.B	Calibrated before use	-
A1394	Attenuator	Huber + Suhner	753459	6806.17.B	Calibrated before use	-
A1534	Pre Amplifier	Hewlett Packard	8449B OPT H02	3008A00405	Calibrated before use	-
A1818	Antenna	EMCO	3115	00075692	25 Oct 2008	12
A1830	Pulse Limiter	Rhode & Schwarz	ESH3-Z2	100668	05 Jan 2009	12
A1931	High Pass Filter	AtlanTecRF	AFH-02000	20r-JFBD04-001	Calibrated before use	-
A1975	High Pass Filter	AtlanTecRF	AFH-03000	090424010	Calibrated before use	-
A288	Antenna	Chase	CBL6111A	1589	13 Mar 2009	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	19 Mar 2009	12
E013	Environmental Chamber	Sanyo	ATMOS chamber	None	Calibrated before use	-
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 Sep 2009	12
L0990	CMU 200	R&S	CMU 200	S220447	18 Feb 2009	12
M1124	Spectrum Analyser	Rohde & Schwarz	ESIB26	100046K	09 Mar 2009	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	22 Apr 2009	12
M1269	Multimeter	Fluke	179	90250210	23 Jun 2009	12
M1379	Test Receiver	Rohde & Schwarz	ESIB7	100330	20 Aug 2009	12
M208	Thermometer	RS Components	RS212-124	N/A	30 Apr 2009	12
S021	DC Power Supply	Thurlby Thandar	CPX200	061034	Calibrated before use	-

**NB** In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.