

Report No.: KSCR221000193904

Page: 1 of 15

1 Cover Page

RF Exposure Evaluation Report

Application No.:	KSCR2210001939AT
FCC ID:	UCZ-F462AQ-Z
IC :	8575A-F462AQZ
Applicant:	Lorex Technology Inc.
Address of Applicant:	250 Royal crest Court Markham, L3R 3S1 Ontario, Canada.
Manufacturer:	Lorex Technology Inc.
Address of Manufacturer:	250 Royal crest Court Markham, L3R 3S1 Ontario, Canada.
Equipment Under Test (EUT):	
EUT Name:	2K Wire Free Outdoor PT Camera
Model No.:	F462AQ-Z, F462AQD-E, F462AQD-F
For IC Model No.:	F462AQD-E
Standard(s) :	FCC Rules 47 CFR §2.1091 KDB 447498 D04 interim General RF Exposure Guidance v01 RSS-102 Issue 5 Amendment 1 (February 2, 2021)
Date of Receipt:	2022-10-14
Date of Test:	2022-10-18 to 2022-10-20
Date of Issue:	2022-10-24
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.

Ena fri

Eric Lin Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@csc.com

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: KSCR221000193904

Page: 2 of 15

Revision Record					
Version	Date	Remark			
00	Original	2022-10-24	/		

Authorized for issue by:		
	Paun. Lin	
	Pawn.Liu/Project Engineer	
	En fri	
	Eric Lin/Reviewer	-



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, attention is drawn to the limitation of liability. Indemnification and juriadiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unawful and offenders may be prosecuted to the fullest extent of the automatic to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing "inspection report & certificate, piese contact us at telephone; (86-512)5735088 [(86-512)57370818 www.sgsgroup.com.cn to mail: CN_Doccheck@sgs.com (86-512)573755888 [(86-512)5737888 § gs.china@sgs.com

Test Report Form Version: Rev01



Report No.: KSCR221000193904 Page: 3 of 15

2 Contents

			Page
1	COV	/ER PAGE	1
2	CON	ITENTS	3
3	GEN	IERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T.	4
	3.3	TEST LOCATION	6
	3.4	TEST FACILITY	6
4	FCC	RADIOFREQUENCY RADIATION EXPOSURE LIMITS	7
	4.1	BLANKET 1 MW BLANKET EXEMPTION	7
	4.2	MPE-BASED EXEMPTION	7
	4.3	SAR-BASED EXEMPTION	8
5	IC R	ADIOFREQUENCY RADIATION EXPOSURE LIMITS	11
6	MEA	ASUREMENT AND CALCULATION	12
	6.1	MAXIMUM TRANSMIT POWER	12
	6.2	RF Exposure Calculation	14



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.format-Ocomditions.format-Ocomditions.format-Ocomditions</u> and juriadiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification on the content or appearance of this document is under the transaction document is unaversated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing "inspection report & certificate, piese contact us at telephone; (86-512)5735088 [(86-512)57370818 www.sgsgroup.com.cn to mail: CN_Doccheck@sgs.com] (86-512)573755888 [(86-512)5737888 sgs.china@sgs.com]



Report No.: KSCR221000193904

Page: 4 of 15

3 **General Information**

3.1 General Description of E.U.T.

Power supply:	DC 12V 1.5A DC 3.6V by Battery
	Battery model:L018-3618650/10Ah/36Wh/1S4P Rated Voltage:3.6V
	Charging Limited Voltage:4.2V

3.2 Details of E.U.T.

2.4G

Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz		
Markelation Truck	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM,		
Modulation Type:	16QAM, QPSK, BPSK)		
Number of Channels:	802.11b/g/n(HT20):11		
Channel Spacing:	5MHz		
Antenna Type:	Antenna1: Dipole Antenna, Antenna2: Dipole Antenna		
	Antenna1: 4.02dBi (Provided by the manufacturer)		
Antenna Gain:	Antenna2: 4.02dBi (Provided by the manufacturer)		
	Two antennas can't transmit simultaneously and they are uncorrelated.		

- -

Operation Frequency	U-NII-1: 5180-5240MHz; U-NII-2A: 5260-5320MHz; U-NII-2C: 5500-
(20MHz):	5700MHz; U-NII-3: 5745-5825MHz
Operation Frequency	U-NII-1: 5190-5230MHz; U-NII-2A: 5270-5310MHz; U-NII-2C: 5510-
(40MHz):	5670MHz; U-NII-3: 5755-5795MHz
Operation Frequency	U-NII-1: 5210MHz; U-NII-2A: 5290MHz; U-NII-2C: 5530-5610MHz; U-NII-
(80MHz):	5775MHz
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11n: OFDM (BPS
	QPSK, 16QAM, 64QAM)
Channel Spacing:	802.11a/n(HT20)
DFS Function:	Slave without Radar detection



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are relained for 30 days only. Attention: To check the authenticity of testing linspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or earnil: C. Doccheck desps.com t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 f(86-512)57370818 sgs.china@sgs.com 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888

Test Report Form Version: Rev01



Report No.: KSCR221000193904

Page: 5 of 15

TPC Function:	Without TPC function		
Antenna Type:	Antenna1: Dipole Antenna, Antenna2: Dipole Antenna		
	Antenna1: 2.04dBi (Provided by the manufacturer)		
Antenna Gain:	Antenna2: 2.04dBi (Provided by the manufacturer)		
	Two antennas can't transmit simultaneously and they are uncorrelated.		
SN:	ND102408031024		
Software Version:	V2.800.0000000.0.R		

Remark: For frequencies falling between 5150-5250 and 5600-5650MHz will not be used in Canada.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.format-Ocomditions.format-Ocomditions.format-Ocomditions</u> and juriadiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification on the content or appearance of this document is under the transaction document is unaversated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing "inspection report & certificate, piese contact us at telephone; (86-512)5735088 [(86-512)57370818 www.sgsgroup.com.cn to mail: CN_Doccheck@sgs.com] (86-512)573755888 [(86-512)5737888 sgs.china@sgs.com]

Test Report Form Version: Rev01



Report No.: KSCR221000193904 Page: 6 of 15

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China. Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc.) is provided by the applicant. (if applicable).
 SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

Designation Number: CN1172.

• ISED

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

• VCCI

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.





 Report No.:
 KSCR221000193904

 Page:
 7 of 15

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

	RF Source Frequency			Minimum Distance			Threshold ERP	
f _L MHz f _H MHz		λ _L / 2π		λ _H / 2π	W			
	0.3 – 1.34		1.34	159 m	_	35.6 m	1,920 R ²	
	1.34 – 30			35.6 m	_	1.6 m	3,450 R²/f ²	
	30 – 300			1.6 m	_	159 mm	3.83 R ²	
	300	—	1,500	159 mm	_	31.8 mm	0.0128 R ² f	
1,500 – 100,000 31.8 mm – 0.5 mm 19.2R ³							19.2R ²	
	Subscripts L and H are low and high; λ is wavelength.							
	From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.							

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are





 Report No.: KSCR221000193904

 Page:
 8 of 15

based on the general population MPE limits with a single perfect reflection, outside of the reactive nearfield, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of \$1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in \$1.1310 is necessary if the ERP of the device is greater than *ERP*_{20cm} in Formula (B.1) [repeated from \$2.1091(c)(1); also in \$1.1307(b)(1)(i)(B)].

$$P_{\rm th} (\rm mW) = ERP_{20 \,\rm cm} (\rm mW) = \begin{cases} 2040f & 0.3 \,\rm GHz \le f < 1.5 \,\rm GHz \\ 3060 & 1.5 \,\rm GHz \le f \le 6 \,\rm GHz \end{cases}$$
(B.1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation					
Frequency range Frequency (MHz) $R(\lambda 2\pi)(m)$ Threshold ERP(W)					
300~1500MHz 915		0.0522	0.032		
1500~100000MHz	2462	0.0194	0.007		

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued overleaf, available on request or accessible at <u>http://www.sgs</u> subject to Terms and Conditions for Electronic Documents as	at http://www.sgs.com/en/	ditions.aspx and /Terms-and-Co	d, for electronic f nditions/Terms-e	ormat documents, a-Document.aspx.
Attention is drawn to the limitation of liability, indemnification advised that information contained hereon reflects the Comp				
Client's instructions, if any. The Company's sole responsibility				
transaction from exercising all their rights and obligations u	under the transaction doe	cuments. This	document cann	ot be reproduced
except in full, without prior written approval of the Company				
appearance of this document is unlawful and offenders may b	be prosecuted to the fulle	est extent of the	a law. Unless oth	nerwise stated the
results shown in this test report refer only to the sample(s) test Attention: To check the authenticity of testing /inspection i	ted and such sample(s) ar	re retained for 3	30 days only.	C 755) 0207 4442
or email: CN.Doccheck@sgs.com	report & certificate, plea	ase contact us	at telephone. (50-755/0307 1445,
No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215	5300 t/86-5	512)57355888 f(8	6-512)57370818 w	ww.sgsgroup.com.cn
		· ·		
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215	5300 t(86-5	512)57355888 f(8	6-512)57370818 S	gs.china@sgs.com



 Report No.:
 KSCR221000193904

 Page:
 9 of 15

The SAR-based exemption formula of \$1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\rm th} (\rm mW) = \begin{cases} ERP_{20 \,\rm cm} (d/20 \,\rm cm)^x & d \le 20 \,\rm cm \\ \\ ERP_{20 \,\rm cm} & 20 \,\rm cm < d \le 40 \,\rm cm \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and *f* is in GHz, d is the separation distance (cm), and *ERP*_{20cm} is per Formula (B.1).





Report No.: KSCR221000193904

Page: 10 of 15

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)										
Frequency	Distance(mm)									
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

For 2.4G WiFi

Limit calculation						
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)		
1.5~6	2.462	1.903	20	3060.000		

For 5G WiFi

Limit calculation						
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)		
1.5~6	5.825	2.090	20	3060.000		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forger yor falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) testing / days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)8307 1443, testematication and the sample) testing / inspection report & certificate, please contact us at telephone: (86-755)8307 1443, testematication and the sample) is the sample of the t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

Test Report Form Version: Rev01



Report No.: KSCR221000193904 Page: 11 of 15

5 IC Radiofrequency radiation exposure limits

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

• at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where *f* is in MHz;

• at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

• at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where *f* is in MHz;

• at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68W

For 5G device, the limit of worse case is 4.53W



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.apx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unaveruent to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & central central test contact as telephone; (86-512)57355888 [(86-512)57355888 [(86-512)57355888 [(86-512)57375688] (86-512)57375688 [(86-512)57375688] sys.china@sgs.com



Report No.: KSCR221000193904

Page: 12 of 15

6 Measurement and Calculation

6.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR221000193901, KSCR221000193902

2.4G WiFi

Test Mode	Test Frequency (MHz)	Antenna 1 Power (dBm)	Antenna 2 Power (dBm)	Antenna 1 Power (mW)	Antenna 2 Power (mW)
	2412	9.63	9.67	9.18	9.27
11B	2437	9.35	9.31	8.61	8.53
110	2462	9.55	9.73	9.02	9.40
	2412	11.82	11.73	15.21	14.89
11G	2437	11.24	11.28	13.30	13.43
	2462	9.93	9.97	9.84	9.93
	2412	10.19	10.19	10.45	10.45
11N20 SISO	2437	11.18	11.19	13.12	13.15
	2462	9.01	8.96	7.96	7.87



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format document, subject to Terms and Conditions of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document connorate paties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results how in this test report refer only to the sample(s) lested and such sample(s) are relatined for 30 days only. Altertion: To check the authenticity of testing /inspection report accriticate, please contact us at telephone: (86-575)8307 1443, or email: CN.Doccheck@ags.com (186-512)57355888 [186-512)57376818 www.sgsgroup.com.cn

中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



5C WIEI

Compliance Certification Services (Kunshan) Inc.

Report No.: KSCR221000193904

Page: 13 of 15

Test Mode	Test Frequency (MHz)	Antenna 1 Power (dBm)	Antenna 2 Power (dBm)	Antenna 1 Power (mW)	Antenna 2 Power (mW)
	5180	11.50	11.36	14.13	13.68
	5200	11.77	11.63	15.03	14.55
	5240	11.47	10.86	14.03	12.19
	5260	11.58	10.83	14.39	12.11
	5300	12.27	11.82	16.87	15.21
110	5320	12.48	12.25	17.70	16.79
11A —	5500	8.73	11.03	7.46	12.68
	5580	7.58	9.48	5.73	8.87
	5700	8.45	8.36	7.00	6.85
	5745	7.67	7.65	5.85	5.82
	5785	8.25	7.94	6.68	6.22
	5825	8.83	8.20	7.64	6.61
	5180	11.21	11.87	13.21	15.38
	5200	11.63	11.99	14.55	15.81
	5240	11.29	11.54	13.46	14.26
	5260	11.30	11.44	13.49	13.93
	5300	12.13	12.28	16.33	16.90
802.11n	5320	12.31	12.85	17.02	19.28
(HT20)	5500	8.69	10.83	7.40	12.11
	5580	7.29	9.68	5.36	9.29
Γ	5700	7.67	9.10	5.85	8.13
	5745	7.06	8.41	5.08	6.93
	5785	7.79	8.68	6.01	7.38
	5825	8.59	9.14	7.23	8.20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document connot be reproduced except in full, without er teopt refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 (86-512)5735888 fi86-512)57370818 www.sgsgroup.com.cn

中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

Test Report Form Version: Rev01

Member of the SGS Group (SGS SA)

t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: KSCR221000193904

Page: 14 of 15

6.2 RF Exposure Calculation

2.4G WiFi

The Max Conducted Peak Output Power is 15.21 mW for antenna1,. 14.89 mW for antenna2.

The best case gain of the antenna is 4.02dBi for antenna1 ,4.02dBi for antenna2.

4.02dBi logarithmic terms convert to numeric result is nearly 2.52

4.02dBi logarithmic terms convert to numeric result is nearly 2.52

According to the formula. calculate the EIRP test result:

Antenna1: EIRP= P x G = 15.21 mW x 2.52= 38.33mW

Antenna2: EIRP= P x G = 24.89 mW x 2.52= 67.72mW

5G WiFi

The Max Conducted Peak Output Power is 17.70 mW for antenna1,. 19.28 mW for antenna2.

The best case gain of the antenna is 2.04dBi for antenna1 ,2.04dBi for antenna2.

2.04dBi logarithmic terms convert to numeric result is nearly 1.60

2.04dBi logarithmic terms convert to numeric result is nearly 1.60

According to the formula. calculate the EIRP test result:

Antenna1: EIRP= P x G = 17.70 mW x 1.60 = 28.32mW

Antenna2: EIRP= P x G = 19.28 mW x 1.60 = 30.85mW

The 2.4GHz WiFi and 5GHz WiFi can transmit simultaneously, but the maximum rate of MPE is 67.72/3060+30.85/3060=0.0299≤1.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP) (2.4GHz Band)	N/A
\boxtimes	SAR-based Exemption(<i>P</i> th)	3060mW(ERP) (1.5GHz~6GHz)	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report





Report No.: KSCR221000193904

Page: 15 of 15

For IC: 2.4G WiFi The Max Conducted Peak Output Power is 15.21 mW for antenna1.. 14.89 mW for antenna2.

The best case gain of the antenna is 4.02dBi for antenna1 ,4.02dBi for antenna2. 4.02dBi logarithmic terms convert to numeric result is nearly 2.52 4.02dBi logarithmic terms convert to numeric result is nearly 2.52 According to the formula. calculate the EIRP test result: Antenna1: EIRP= P x G = 0.01521W x 2.52= 0.0383W < 2.68W Antenna2: EIRP= P x G = 0.02489W x 2.52= 0.0627W < 2.68W

5G WiFi

The Max Conducted Peak Output Power is 17.70 mW for antenna1, 19.28 mW for antenna2. The best case gain of the antenna is 2.04dBi for antenna1 ,2.04dBi for antenna2. 2.04dBi logarithmic terms convert to numeric result is nearly 1.60 2.04dBi logarithmic terms convert to numeric result is nearly 1.60 According to the formula. calculate the EIRP test result: Antenna1: EIRP= P x G = 0.01770W x 1.60 = 0.0283W <4.53W Antenna2: EIRP= P x G = 0.01928W x 1.60 = 0.0308W <4.53W

The 2.4GHz WiFi and 5GHz WiFi can transmit simultaneously, but the maximum rate of MPE is 0.0627/2.68+0.0308/4.53=0.0302≤1.

So the device is exclusion from SAR test.

--End of the Report--

