



1 Cover Page

RF MPE REPORT

Application No.: SHEM2007006345CR
FCC ID: UCZ-H871T6-Z
IC : 8575A-H871T6Z
Applicant: LOREX Technology Inc.
Address of Applicant: 250 Royal Crest Court, Markham, ON L3R 3S1 Canada
Manufacturer: Lorex Technology Inc.
Address of Manufacturer: 250 Royal crest Court, Markham, L3R 3S1 Canada
Equipment Under Test (EUT):
EUT Name: HUB
Model No.: H871T6-Z
Trade mark: LOREX
Standard(s) : FCC Rules 47 CFR §2.1091
 KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2020-07-30
Date of Test: 2020-08-13 to 2020-08-14
Date of Issue: 2020-08-15

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Parlam Zhan

Parlam Zhan
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 t(86-21) 61915666 f(86-21)61915678 www.sgsgroup.com.cn
 中国·上海·松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21)61915678 e sgs.china@sgs.com



Revision Record			
Version	Description	Date	Remark
00	Original	2020-08-15	/

Authorized for issue by:			
			
		<hr/>	
		Micheal Niu / Project Engineer	
			
		<hr/>	
		Parlam Zhan / Reviewer	



2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 GENERAL DESCRIPTION OF E.U.T.	4
3.2 TECHNICAL SPECIFICATIONS	4
3.3 TEST LOCATION	6
3.4 TEST FACILITY.....	6
4 TEST STANDARDS AND LIMITS	7
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	7
5 MEASUREMENT AND CALCULATION	8
5.1 MAXIMUM TRANSMIT POWER	8
5.2 MPE CALCULATION	11

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 5V by adapter Adapter Model:NBS10B050200VUU INPUT:100-240V,50/60Hz,0.3A OUTPUT:5V,2A
Serial Number:	ND012008087585
Firmware Version:	V1.000.0000002.2.R.200904

3.2 Technical Specifications

2.4GHz

Antenna Gain:	Ant 1:2.03dBi, Ant 2:2.03dBi Directional gain:5.04dBi
Antenna Type:	Antenna 1: PIFA Antenna Antenna 2: PIFA Antenna
Channel Spacing:	5MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

BLE

Antenna Gain:	2.03dBi
Antenna Type:	PIFA Antenna
Bluetooth Version:	V5.0 BLE
Channel Spacing:	2MHz
Modulation Type:	GFSK
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz



5G

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	Band 1	802.11a/n(HT20)/ac(VHT20)	5180-5240	4
		802.11n(HT40)/ac(VHT40)	5190-5230	2
		802.11ac(VHT80)	5210	1
	Band 4	802.11a/n(HT20)/ac(VHT20)	5745-5825	5
		802.11n(HT40)/ac(VHT40)	5755-5795	2
		802.11ac(VHT80)	5775	1
		802.11a/n(HT20)/ac(VHT20)	5180-5240	4
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)			
Channel Spacing:	802.11a/n(HT20)/ac(VHT20): 20MHz 802.11n(HT40)/ac(VHT40): 40MHz 802.11ac(VHT80): 80MHz			
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-7 802.11ac: MCS0-9			
Antenna Gain:	Antenna 1: 3.15dBi; Antenna 2: 3.15dBi Directional gain: 6.16dBi			
Antenna Type:	Antenna 1: PIFA Antenna Antenna 2: PIFA Antenna			

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

• **ISED (CAB identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.

• **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

4.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W

For 5G device, the limit of worse case is 4.53 W

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200700634501-2.4GHz

Test Mode	Channel	Antenna 1 Power[dBm]	Antenna 2 Power[dBm]	MIMO Power[dBm]	Antenna 1 Power[mW]	Antenna 2 Power[mW]	MIMO Power[mW]
11B	2412	17.20	18.31	NA	52.48	67.76	N/A
11B	2437	18.74	19.40	NA	74.82	87.10	N/A
11B	2462	19.71	19.95	NA	93.54	98.86	N/A
11G	2412	19.06	20.53	NA	80.54	112.98	N/A
11G	2437	20.37	21.14	NA	108.89	130.02	N/A
11G	2462	21.24	21.77	NA	133.05	150.31	N/A
11N20MIMO	2412	18.74	19.81	22.32	74.82	95.72	170.61
11N20MIMO	2437	20.21	20.96	23.61	104.95	124.74	229.61
11N20MIMO	2462	21.13	21.40	24.28	129.72	138.04	267.92
11N40MIMO	2422	20.53	21.48	24.04	112.98	140.60	253.51
11N40MIMO	2437	21.21	21.94	24.60	132.13	156.31	288.40
11N40MIMO	2452	21.83	22.29	25.08	152.41	169.43	322.11

The Power Data is based on the RF Test Report SHEM200634502-BLE

Test Mode	Channel	Antenna 1 Power[dBm]	Antenna 1 Power[mW]
1M	2402	6.40	4.37
1M	2440	6.89	4.89
1M	2480	5.39	3.46



5GHz for FCC:

The Power Data is based on the RF Test Report SHEM200700634503-5GHz

Test Mode	Test Channel	Antenna 1 Power[dBm]	Antenna 2 Power[dBm]	MIMO Power[dBm]	Antenna 1 Power[mW]	Antenna 2 Power[mW]	MIMO Power[mW]
11A	5180	12.93	12.91	NA	19.63	19.54	NA
11A	5200	13.13	13.18	NA	20.56	20.80	NA
11A	5240	14.09	13.19	NA	25.64	20.84	NA
11A	5745	20.90	20.88	NA	123.03	122.46	NA
11A	5785	20.34	20.38	NA	108.14	109.14	NA
11A	5825	19.47	20.03	NA	88.51	100.69	NA
11N20	5180	9.05	9.28	12.18	8.04	8.47	16.52
11N20	5200	8.46	8.20	11.34	7.01	6.61	13.61
11N20	5240	9.30	8.37	11.87	8.51	6.87	15.38
11N20	5745	20.85	21.08	23.98	121.62	128.23	250.03
11N20	5785	20.47	20.28	23.39	111.43	106.66	218.27
11N20	5825	19.63	20.06	22.86	91.83	101.39	193.20
11N40	5190	8.81	8.46	11.65	7.60	7.01	14.62
11N40	5230	9.50	8.83	12.19	8.91	7.64	16.56
11N40	5755	19.39	19.47	22.44	86.90	88.51	175.39
11N40	5795	20.22	20.21	23.23	105.20	104.95	210.38
11AC20	5180	8.77	8.68	11.74	7.53	7.38	14.93
11AC20	5200	9.50	9.21	12.37	8.91	8.34	17.26
11AC20	5240	9.79	9.18	12.51	9.53	8.28	17.82
11AC20	5745	20.61	20.79	23.71	115.08	119.95	234.96
11AC20	5785	20.37	20.32	23.36	108.89	107.65	216.77
11AC20	5825	19.64	20.03	22.85	92.04	100.69	192.75
11AC40	5190	9.02	8.75	11.90	7.98	7.50	15.49
11AC40	5230	9.52	8.86	12.21	8.95	7.69	16.63
11AC40	5755	19.79	19.53	22.67	95.28	89.74	184.93
11AC40	5795	20.21	20.35	23.29	104.95	108.39	213.30
11AC80	5210	9.54	9.43	12.50	8.99	8.77	17.78
11AC80	5775	19.27	18.59	21.95	84.53	72.28	156.68



5GHz EIPR for IC:

Test Mode	Frequency (MHz)	Tx Type	Measured Output Power (dBm)			EIRP (dBm)			EIRP (mw)		
			Ant 1	Ant 2	Total	Ant 1	Ant 2	Total	Ant 1	Ant 2	Total
802.11a	5180	SISO	12.93	12.91	/	16.08	16.06	/	40.55	40.36	/
	5200	SISO	13.13	13.18	/	16.28	16.33	/	42.46	42.95	/
	5240	SISO	14.09	13.19	/	17.24	16.34	/	52.97	43.05	/
	5745	SISO	20.90	20.88	/	/	/	/	/	/	/
	5785	SISO	20.34	20.38	/	/	/	/	/	/	/
	5825	SISO	19.47	20.03	/	/	/	/	/	/	/
802.11n (HT20)	5180	MIMO	9.05	9.28	12.18	15.21	15.44	18.34	33.19	34.99	68.23
	5200	MIMO	8.46	8.20	11.34	14.62	14.36	17.50	28.97	27.29	56.23
	5240	MIMO	9.30	8.37	11.87	15.46	14.53	18.03	35.16	28.38	63.53
	5745	MIMO	20.85	21.08	23.98	/	/	/	/	/	/
	5785	MIMO	20.47	20.28	23.39	/	/	/	/	/	/
	5825	MIMO	19.63	20.06	22.86	/	/	/	/	/	/
802.11n (HT40)	5190	MIMO	8.81	8.46	11.65	14.97	14.62	17.81	31.41	28.97	60.39
	5230	MIMO	9.50	8.83	12.19	15.66	14.99	18.35	36.81	31.55	68.39
	5755	MIMO	19.39	19.47	22.44	/	/	/	/	/	/
	5795	MIMO	20.22	20.21	23.23	/	/	/	/	/	/
802.11ac (VHT20)	5180	MIMO	8.77	8.68	11.74	14.93	14.84	17.90	31.12	30.48	61.66
	5200	MIMO	9.50	9.21	12.37	15.66	15.37	18.53	36.81	34.43	71.29
	5240	MIMO	9.79	9.18	12.51	15.95	15.34	18.67	39.36	34.20	73.62
	5745	MIMO	20.61	20.79	23.71	/	/	/	/	/	/
	5785	MIMO	20.37	20.32	23.36	/	/	/	/	/	/
	5825	MIMO	19.64	20.03	22.85	/	/	/	/	/	/
802.11ac (VHT40)	5190	MIMO	9.02	8.75	11.90	15.18	14.91	18.06	32.96	30.97	63.97
	5230	MIMO	9.52	8.86	12.21	15.68	15.02	18.37	36.98	31.77	68.71
	5755	MIMO	19.79	19.53	22.67	/	/	/	/	/	/
	5795	MIMO	20.21	20.35	23.29	/	/	/	/	/	/
802.11ac (VHT80)	5210	MIMO	9.54	9.43	12.50	15.7	15.59	18.66	37.15	36.22	73.45
	5775	MIMO	19.27	18.59	21.95	/	/	/	/	/	/

5.2 MPE Calculation

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

For 2.4G WiFi –Antenna1:

The max. antenna gain is 2.03 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
152.41	1.596	20	0.04839	1	Pass

For 2.4G WiFi –Antenna2:

The max. antenna gain is 2.03 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
169.43	1.596	20	0.05379	1	Pass

In MIMO mode:

The max. antenna gain is 5.04 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
322.11	3.192	20	0.20452	1	Pass

For BLE:

The max. antenna gain is 2.03 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
4.89	1.596	20	0.00155	1	Pass

For 5G WiFi–Antenna1:

The max. antenna gain is 3.15 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
123.03	2.065	20	0.05055	1	Pass

For 5G WiFi–Antenna2:

The max. antenna gain is 3.15 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
128.23	2.065	20	0.05269	1	Pass

In MIMO mode:

The max. antenna gain is 6.16 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
250.03	4.130	20	0.20546	1	Pass

2.4G WiFi & BLE and 5G WiFi modules can simultaneous transmitting, so the maximum rate of MPE is $0.20452/1.0+0.00155/1.0+0.20546/1.0=0.411\leq 1.0$. according to the KDB447498 section 7.2 determine the device is exclusion from SAR test

For IC:

For BLE

$$E.I.R.P.= P*G= 0.00489\times 1.596=0.0078W<2.68W$$

For 2.4GHz WiFi SISO mode:

$$\text{Antenna 1: } E.I.R.P.= P*G= 0.15241\times 1.596=0.243W<2.68W$$

$$\text{Antenna 2: } E.I.R.P.= P*G= 0.16943\times 1.596=0.270W<2.68W$$

$$\text{For 2.4GHz WiFi MIMO mode: } E.I.R.P.= 0.32211\times 3.192= 1.028<2.68W$$

For 5GHz WiFi SISO mode:

$$\text{Antenna 1: } E.I.R.P.= P*G= 0.12303\times 2.065=0.254W<4.53W$$

$$\text{Antenna 2: } E.I.R.P.= P*G= 0.12823\times 2.065=0.265W<4.53W$$

$$\text{For 5GHz WiFi MIMO mode: } E.I.R.P.= P*G= 0.25003\times 4.130=1.033W<4.53W$$

2.4G WiFi, BLE and 5G WIFI can simultaneous transmitting. But the maximum rate of MPE is $0.0078/2.68+1.028/2.68+1.033/4.53=0.615\leq 1.0$. the device is exclusion from SAR test.

--End of the Report--