

<b>EMC TEST REPORT</b> <b>FCC 47 CFR Part 15B</b> <b>Industry Canada ICES-003</b> <b>Electromagnetic compatibility - Unintentional radiators</b>	
<b>Report Reference No.</b> .....	G0M-1507-4913-EF0115B-V01
<b>Testing Laboratory</b> .....	Eurofins Product Service GmbH
Address .....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation .....	<div style="text-align: center;">   </div> <p>A2LA Accredited Testing Laboratory, Certificate No.: 1983.01                      FCC Filed Test Laboratory, Reg.-No.: 96970                      IC OATS Filing assigned code: 3470A</p>
<b>Applicant's name</b> .....	Quail Digital UK
Address .....	92 Lots Road SW10 0QD London UNITED KINGDOM
<b>Test specification:</b>	
Standard.....	47 CFR Part 15 Subpart B ICES-003, Issue 6:2016 ANSI C63.4:2014
<b>Equipment under test (EUT):</b>	
Product description	DECT Wireless headset for intercommunication use
Model No.	Q-P7HS
Additional Models	None
Hardware version	Rev B
Firmware / Software version	Version 1.0.0
	FCC-ID: UDDQP7HS                      IC: 6402A-QP7HS
<b>Test result</b>	<b>Passed</b>

**Possible test case verdicts:**

- not applicable to test object .....: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

**Testing:**

Date of receipt of test item .....: 2015-08-07

Date (s) of performance of tests .....: 2016-09-08


Compiled by .....: Matthias Laurisch

 Tested by (+ signature).....: Andreas Pflug /  
Matthias Laurisch

 Approved by (+ signature) .....: Jens Marquardt  
Deputy Head of Lab

Date of issue .....: 2016-09-14

Total number of pages .....: 30


**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

---

## Version History

Version	Issue Date	Remarks	Revised by
V01	2016-09-14	Initial Release	

---

## REPORT INDEX

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION</b>	<b>5</b>
1.1	Photos – Equipment external	6
1.2	Photos – Equipment internal	8
1.3	Photos – Test setup	10
1.4	Supporting Equipment Used During Testing	12
1.5	Input / Output Ports	12
1.6	Operating Modes and Configurations	13
1.7	Test Equipment Used During Testing	14
1.8	Sample emission level calculation	15
<b>2</b>	<b>RESULT SUMMARY</b>	<b>16</b>
<b>3</b>	<b>TEST CONDITIONS AND RESULTS</b>	<b>17</b>
3.1	Test Conditions and Results – Radiated emissions	17
3.2	Test Conditions and Results – AC power line conducted emissions	27

## 1 Equipment (Test item) Description

<b>Description</b>	DECT Wireless headset for intercommunication use
<b>Model</b>	Q-P7HS
<b>Additional Models</b>	None
<b>Serial number</b>	None
<b>Hardware version</b>	Rev B
<b>Software / Firmware version</b>	Version 1.0.0
<b>FCC-ID</b>	UDDQP7HS
<b>IC</b>	6402A-QP7HS
<b>Power supply</b>	3.7 VDC (rechargeable battery)
<b>AC/DC-Adaptor</b>	None
<b>Manufacturer</b>	Quail Digital UK 92 Lots Road SW10 0QD London UNITED KINGDOM
<b>Highest emission frequency</b>	1900 MHz
<b>Device classification</b>	Class B
<b>Equipment type</b>	Tabletop
<b>Number of tested samples</b>	1

#### 1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments (e.g. serial no.)
AE	Charger	Quail Digital	Q-RCH	
AE	Base Station	Quail Digital	Q-P7BS	
AE	Battery	GN Netcom	14151-02	
None				
<p><b>*Note:</b> Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

#### 1.5 Input / Output Ports

Port #	Name	Type*	Max. Cable Length	Cable Shielded	Comments (e.g. Cat. of Cable)
1	DC Main	DC	0m	N/A	direct connection via plug
<p><b>*Note:</b> Use the following abbreviations:</p> <p>AC : AC power port</p> <p>DC : DC power port</p> <p>N/E : Non electrical</p> <p>I/O : Signal input or output port</p> <p>TP : Telecommunication port</p>					

**1.6 Operating Modes and Configurations**

<b>Mode #</b>	<b>Description</b>
1	Active DECT connection
2	Charging mode

<b>Configuration #</b>	<b>EUT Configuration</b>
1	EUT fully assembled incl. battery
2	EUT fully assembled connected to charger

**1.7 Test Equipment Used During Testing**

<b>Measurement Software</b>			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2015.1.12

<b>Radiated emissions – 3m Chamber</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Biconical Antenna	R&S	HK 116	EF00012	2016-05	2019-05
LPD-Antenne	R&S	HL 223	EF00187	2016-05	2019-05
Horn antenna	Schwarzbeck	BBHA 9120D	EF00018	2013-09	2016-09
EMI Test Receiver	R&S	ESU26	EF00887	2016-01	2017-01

<b>Radiated emissions 10m Chamber</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
TRILOG Broadband Antenna	Schwarzbeck	VULB 9162	EF00978	2015-10	2016-10
Double-Ridged Guide Antenna	ETS-Lindgren	3117	EF00976	2016-03	2017-03
EMI Test Receiver	R&S	ESU26	EF00887	2016-01	2017-01

<b>Conducted emissions</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH3-Z5	EF00036	2014-12	2016-12
AMN	Schwarzbeck	NSLK 8128	EF00975	2015-12	2016-12
EMI Test Receiver	R&S	ESR7	EF00943	2015-09	2016-09
Cable	-	RG58/U	-	System Cal.	System Cal.

## 1.8 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB $\mu$ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB $\mu$ V/m). The FCC limits are given in units of  $\mu$ V/m. The following formula is used to convert the units of  $\mu$ V/m to dB $\mu$ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

## 2 Result Summary

FCC 47 CFR Part 15B, Industry Canada ICES-003				
Product Specific Standard	Requirement – Test	Reference Method	Result	Remarks
47 CFR 15.109 ICES-003 Item 6.2	Radiated emissions	ANSI C 63.4	PASS	
47 CFR 15.107 ICES-003 Item 6.1	AC power line conducted emissions	ANSI C63.4	PASS	
<b>Remarks:</b>				

### 3 Test Conditions and Results

#### 3.1 Test Conditions and Results – Radiated emissions

Radiated emissions acc. FCC 47 CFR 15.109 / ICES-003				Verdict: PASS		
Laboratory Parameters:		Required prior to the test		During the test		
Ambient Temperature		15 to 35 °C		25°C		
Relative Humidity		30 to 60 %		45%		
Test according referenced standards		Reference Method				
		ANSI C63.4				
Sample is tested with respect to the requirements of the equipment class		Equipment class				
		Class B				
Test frequency range determined from highest emission frequency		Highest emission frequency				
		Fmax [MHz] = 1.9 GHz				
Fully configured sample scanned over the following frequency range		Frequency range				
		30 MHz to 10 GHz				
Operating mode		1, 2				
Configuration		1, 2				
Limits and results Class B						
Frequency [MHz]	Quasi-Peak [dBµV/m]	Result	Average [dBµV/m]	Result	Peak [dBµV/m]	Result
30 – 88	40	PASS	-		-	-
88 – 216	43.5	PASS	-		-	-
216 – 960	46	PASS	-		-	-
960 – 1000	54	PASS	-		-	-
> 1000	-	-	54	PASS	74	PASS
Comments:						

**Test Procedure:**

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.  
The measurement procedure is as follows:

## Exploratory measurement:

- The EUT was placed on a non-conductive table at a height of 0.8m.
- The EUT and support equipment, if needed, were set up to simulate typical usage.
- Cables, of type and length specified by the manufacturer, were connected to at least one port of each type and were terminated by a device or simulating load of actual usage.
- The antenna was placed at a distance of 3 or 10 m.
- The received signal was monitored at the measurement receiver.
  - Cables not bundled were manipulated within the range of likely arrangements to produce the highest emission amplitude
  - To maximize the suspected emissions the EUT is rotated 360 degrees. If the signal exceeds the previous amplitude, go back to the corresponding azimuth and manipulate the cables again for maximizing the emissions if possible.
  - Move the antenna from 1 to 4m to maximize the suspected highest amplitude signal.
- This procedure has to be performed in both antenna polarizations, horizontal and vertical.
- The arrangement of the equipment with the maximum emission level is shown on the setup picture at item 1.3.

## Final measurement:


- The EUT was placed on a 0.8 m non-conductive table at a 3 m distance from the receive antenna. The antenna output was connected to the measurement receiver
- A biconical antenna was used for the frequency range 30 – 200 MHz, a logarithmic periodical antenna was used for the frequency range from 200 – 1000 MHz. Above one 1 GHz a Double Ridged Broadband Horn antenna was used. The antenna was placed on an adjustable height antenna mast
- The EUT and cable arrangement were based on the exploratory measurement results
- Emissions were maximized at each frequency by rotating the EUT and adjusting the receive antenna height and polarization. The maximum values were recorded.
- The test data of the worst-case conditions were recorded and shown on the next pages.

**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 3.7 VDC
Antenna:	Schwarzbeck VULB 9162, Horizontal
Measurement distance:	3 m
Mode:	1
Test Date:	2016-08-09
Note:	

Index 8




**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 3.7VDC
Antenna:	Schwarzbeck VULB 9162, Vertical
Measurement distance:	3 m
Mode:	1
Test Date:	2016-08-09
Note:	

Index 7




**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 3.7 VDC
Antenna:	ETS-Lindgren 3117, Horizontal
Measurement distance:	3 m
Mode:	1
Test Date:	2016-08-09
Note:	

Index 2




**Spurious emissions under normal conditions according to FCC part 15B |**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 3.7 VDC
Antenna:	ETS-Lindgren 3117, Vertical
Measurement distance:	3 m
Mode:	1
Test Date:	2016-08-09
Note:	

Index 1




**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 120VAC
Antenna:	Schwarzbeck VULB 9162, Horizontal
Measurement distance:	3 m
Mode:	2
Test Date:	2016-08-09
Note:	

Index 5




**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant: Quail Digital UK  
 EUT Name: DECT 6.0 headset  
 Model: Pro7  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Laurisch  
 Test Conditions: Tnom: 25°C, Unom: 120 VAC  
 Antenna: Schwarzbeck VULB 9162, Vertical  
 Measurement distance: 3 m  
 Mode: 2  
 Test Date: 2016-08-09  
 Note:

Index 6




Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
1	31.2 MHz	28.2 dBµV/m	40 dBµV/m	-11.8 dB	Pass	-180 Degree	1 m
2	35.1 MHz	29.6 dBµV/m	40 dBµV/m	-10.4 dB	Pass	-180 Degree	1 m

**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 25°C, Unom: 120 VAC
Antenna:	ETS-Lindgren 3117, Horizontal
Measurement distance:	3 m
Mode:	2
Test Date:	2016-08-09
Note:	Pass

Index 3




**Spurious emissions under normal conditions according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT 6.0 headset
Model:	Pro7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Laurisch
Test Conditions:	Tnom: 24°C, Unom: 120 VAC
Antenna:	ETS-Lindgren 3117, Vertical
Measurement distance:	3 m
Mode:	2
Test Date:	2016-08-09
Note:	

Index 4



**3.2 Test Conditions and Results – AC power line conducted emissions**

<b>Conducted emissions acc. FCC 47 CFR 15.107 / ICES-003</b>			<b>Verdict: PASS</b>	
Laboratory Parameters:	Required prior to the test		During the test	
Ambient Temperature	15 to 35 °C		25 °C	
Relative Humidity	30 to 60 %		45 %	
Test according referenced standards	Reference Method			
	ANSI C63.4			
Fully configured sample scanned over the following frequency range	Frequency range			
	0.15 MHz to 30 MHz			
Sample is tested with respect to the requirements of the equipment class	Equipment class			
	Class B			
Points of Application	Application Interface			
AC Mains	LISN			
Operating mode	2			
Configuration	2			
<b>Limits and results Class B</b>				
Frequency [MHz]	Quasi-Peak [dB $\mu$ V]	Result	Average [dB $\mu$ V]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Comments:				
* Limit decreases linearly with the logarithm of the frequency.				

**Test Procedure:**

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.  
The measurement procedure is as follows:

## Exploratory measurement:

- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2014 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- I/O cables were bundled not longer than 0.4 m
- Measurement was performed in the frequency range 0.15 – 30MHz on each current-carrying conductor
- To maximize the emissions the cable positions were manipulated
- The worst configuration of EUT and cables is shown on a test setup picture at item 1.3

**Test Procedure:**

## Final measurement:


- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2014 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- The EUT and cable arrangement were based on the exploratory measurement results
- The test data of the worst-case conditions were recorded and shown on the next pages.

**EMI voltage test in the ac-mains according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT wireless headset for intercommunication use
Model:	Q-P7HS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pflug
Test Conditions:	Tnom: 23°C, Unom: 120VAC(AC/DC-adapter)
LISN:	ESH2-Z5 N
Mode:	2
Test Date:	2015-08-04
Note:	

Index 1



**EMI voltage test in the ac-mains according to FCC part 15B**

Project number: G0M-1507-4913

Applicant:	Quail Digital UK
EUT Name:	DECT wireless headset for intercommunication use
Model:	Q-P7HS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pflug
Test Conditions:	Tnom: 23°C, Unom: 120VAC(AC/DC-adapter)
LISN:	ESH2-Z5 L
Mode:	2
Test Date:	2015-08-04
Note:	

Index 3

