

# HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.



PRODUCT COMPLIANCE DIVISION  
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA  
TEL : +82 31 639 8518 FAX : +82 31 639 8525 [www.hct.co.kr](http://www.hct.co.kr)

## CERTIFICATE OF COMPLIANCE FCC PART 15.247 Certification

**Applicant Name:**  
Uriver Inc

3<sup>rd</sup>., Fl., Bogwang Bldg., Poi-dong, 238-7  
Gangnam-gu, Seoul, Korea

**Date of Testing:**  
May 10, 2007

**Test Site/Location:**

HCT, San 136-1 Ami-ri, Bubal-eup, Icheon-si,  
Kyungki-do, Korea

**Test Report No.:** HCT-R07-010

**FCC ID: UDTSP500**

**APPLICANT: Uriver Inc**

EUT Type:	Tri-Band GSM Phone with Bluetooth
Frequency range:	2402 - 2480 MHz (Bluetooth)
Max. RF Output Power:	0 dBm
Trade Name/Model(s):	Uriver Inc. / SP500
FCC Classification:	FCC Part 15 Frequency Hopping Spread Spectrum Transceiver
Application Type:	Certification
FCC Rule Part(s):	Part 15 subpart C 15.247
Antenna Specifications:	Manufacturer: AMOTECH.Co.Ltd PART NUMBER: ALA621C4 / Chip Antenna

Engineering Statement:

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT Co., Ltd. certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti- Drug Abuse Act of 1998, 21 U.S. C. 853(a)

**Report prepared by**

**: Youn Seok Jung**

**Test engineer of RF Part**

**Approved by**

**: Sang Jun Lee**

**Manager of RF Part**

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R07-010	Test Dates: May 10, 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP500	Page 1 of 42

# Table of Contents

<b>1. GENERAL INFORMATION .....</b>	<b>3</b>
1.1 EUT DESCRIPTION .....	3
<b>2. TEST METHODOLOGY .....</b>	<b>4</b>
2.1 EUT CONFIGURATION.....	4
2.2 EUT EXERCISE.....	4
2.3 GENERAL TEST PROCEDURES.....	4
2.4 DESCRIPTION OF TEST MODES .....	4
<b>3. INSTRUMENT CALIBRATION.....</b>	<b>5</b>
<b>4. FACILITIES AND ACCREDITATIONS .....</b>	<b>6</b>
4.1 FACILITIES.....	6
4.2 EQUIPMENT .....	6
<b>5. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>6</b>
5.1 SETUP CONFIGURATION OF EUT .....	6
<b>6. TEST RESULT .....</b>	<b>7</b>
6.1 SUMMARY.....	8
6.2 PEAK POWER.....	8
6.3 BAND EDGES MEASUREMENT .....	1 8
6.3.1 BAND EDGES RADIATED MEASUREMENT .....	1 8
6.4 FREQUENCY SEPARATION .....	1 8
6.5 NUMBER OF HOPPING FREQUENCY .....	2 1
6.6 TIME OF OCCUPANCY (DWELL TIME) .....	2 3
6.7 SPURIOUS EMISSIONS .....	2 6
6.7.1 Conducted Spurious Emissions .....	2 6
6.7 .2 Radiated Spurious Emissions.....	2 6
6.8 POWERLINE CONDUCTED EMISSIONS .....	3 7
<b>7. LIST OF TEST EQUIPMENT.....</b>	<b>4 2</b>

# 1. GENERAL INFORMATION

<b>Company Name:</b>	<b>Uriver Inc.</b>
<b>Address:</b>	<b>3rd., Fl., Bogwang Bldg., Poi-dong, 238-7 Gangnam-gu, Seoul, Korea</b>
<b>Attention:</b>	<b>TS JEONG - Managing Director</b>
<b>Tel. / Fax :</b>	<b>82-2-3497-8432 / 82-2-579-6624</b>
<b>E-Mail :</b>	<b>tsjeong@uriver.co.kr</b>

## 1.1 EUT DESCRIPTION

- FCC ID: UDTSP500
- EUT Type: Tri -Band GSM Phone with Bluetooth (GSM850/ DCS1800/ PCS1900). Prototype
- Trade Name: Uriver Inc.
- Model(s): SP500
- Frequency range: 2402 – 2480 MHz (Bluetooth)
- Transmit power: 0 dBm
- Modulation(s): GFSK
- Antenna Specification: Manufacturer: AMOTECH.Co.Ltd  
Part Number: ALA621C4 / Chip Antenna  
Gain (Peak / Avg) [dBi] -3.5 / -1.0
- Frequency range: 2402 – 2480 MHz (Bluetooth)
- Application Type: Certification
- FCC Classification: FCC Part 15 Frequency Hopping Spread Spectrum Transceiver
- FCC Rule Part(s): Part 15 subpart C 15.247
- Date(s) of Tests: May 10, 2007
- Report Serial No.: HCT-R07-010

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4.  
(Version :2003) Radiated testing was performed at an antenna to EUT distance 3 meters.

### 2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3 GENERAL TEST PROCEDURES

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

### 2.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP500	Page 4 of 42

### 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP500	Page 5 of 42

## 4. FACILITIES AND ACCREDITATIONS

### 4.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

### 4.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 5. SETUP OF EQUIPMENT UNDER TEST

### 5.1 SETUP CONFIGURATION OF EUT

See test photographs for the actual connections between EUT and support equipment.

## 6. TEST RESULT

### 6.1 SUMMARY

Company Name: Uriver Inc.

FCC ID: UDTSP500

Method/System: Frequency Hopping Spread Spectrum (FHSS)

Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (Tx)</b>					
15.247(b)(1)	PEAK POWER	< 1 Watt if > 75 non-overlapping channels used	CONDUCTED	PASS	Section 6.2
15.247(d)	BAND EDGES MEASUREMENT	Conducted < 20dBc		PASS	Section 6.3
15.247(a)(1)	FREQUENCY SEPARATION / 20 dB BANDWIDTH	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 6.4
15.247(a)(1)(iii)	NUMBER OF CHANNELS	> 15 Channels		PASS	Section 6.5
15.247(a)(1)(iii)	TIME OF OCCUPANCY	< 0.4 sec in 31.6 sec period		PASS	Section 6.6
15.247(d)	Conducted Spurious Emissions	Conducted < 20dBc		PASS	Section 6.7.1
15.205 15.209	Radiated Spurious Emissions	Radiated < 20dBc Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)	RADIATED	PASS	Section 6.7.2
15.207	AC CONDUCTED EMISSIONS 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.8


## 6.2 PEAK POWER

### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Test Configuration



### TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. The RBW is set to 1MHz. The VBW is set to 3MHz.

### TEST RESULTS

*No non-compliance noted*


### Test Data

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	0.03	0.001006	1	PASS
Mid	2440	-0.31	0.000931		PASS
High	2480	-1.59	0.000693		PASS




## Test Plots


### Peak Power ( Low CH )



### Peak Power ( Mid CH )



## Peak Power ( High CH )




## 6.3 BAND EDGES MEASUREMENT

### LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 8 MHz
2. RBW = 100 KHz
3. VBW = 300 KHz
4. Sweep = auto

### TEST RESULTS


See attached.

## Test Data

### Band Edges (CH-Low)



### Band Edges (CH-Low)




### 6.3.1 BAND EDGES RADIATED MEASUREMENT

#### LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

#### Test Configuration



#### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW = VBW = 1 MHz / Sweep = AUTO
  - (b) AVERAGE: RBW = 1 MHz / VBW = 10 Hz / Sweep = AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

#### TEST RESULTS

Refer to attach spectrum analyzer data chart.


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP500	Page 13 of 42

## Test Data


Band Edges (Low- CH)

Polarity: Vertical

Detector mode: Peak




Detector mode: Average




## Band Edges (Low- CH)

Polarity: Horizontal

### Detector mode: Peak




### Detector mode: Average




## Band Edges (High- CH)

Polarity: Vertical

Detector mode: Peak



Detector mode: Average







## Band Edges (High- CH)

Polarity: Horizontal

Detector mode: Peak



Detector mode: Average




## 6.4 FREQUENCY SEPARATION

### LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### Test Configuration



### TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 30 KHz
3. VBW = 100 KHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

### TEST RESULTS


*No non-compliance noted*

#### Test Data

Channel Separation (MHz)	20dB Bandwidth (KHz)		Limit (KHz)	Result
1.005	Low CH	750	>25	Pass
	Middle CH	771		
	High CH	759		

## Test Plot


### Measurement of Channel Separation



## Test Plot

### 20 dB bandwidth

### (Low CH)



(Mid CH)



(High CH)




## 6.5 NUMBER OF HOPPING FREQUENCY

### LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

### Test Configuration



### TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation ( Start = 2400 MHz, Stop = 2483.5 MHz )
2. RBW = 300 KHz
3. VBW = 1 MHz
4. Sweep = auto

The trace was allowed to stabilize.

### TEST RESULTS

*No non-compliance noted*


### Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>75	Pass

## Test Plot

Channel Number

2.4 GHz – 2.4835 GHz




## 6.6 TIME OF OCCUPANCY (DWELL TIME)

### LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### TEST PROCEDURE

EUT was set to transmit the longest packet type (DH5)

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 3 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

### TEST RESULTS

See the table.

#### DH 5

CH Low:  $2.914 * (1600/6)/79 * 31.6 = 310.8$  (ms)

CH Mid:  $2.914 * (1600/6)/79 * 31.6 = 310.8$  (ms)


CH High:  $2.904 * (1600/6)/79 * 31.6 = 309.8$  (ms)

Channel	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.914	310.8	31.6	400	PASS
Mid	2.914	310.8	31.6		PASS
High	2.904	309.8	31.6		PASS


## Test Plots

DH 5

( Low CH )




( Mid CH )





(CH High)




## 6.7 SPURIOUS EMISSIONS

### 6.7.1 Conducted Spurious Emissions

#### LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.


Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.

#### TEST RESULTS


*No non-compliance noted*

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP500	Page 26 of 42


## Test Plots ( Low CH )



## (Mid CH )



( High CH )



## 6.7.2 Radiated Spurious Emissions


### LIMIT

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed


Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

## Test Configuration


### Below 30 MHz



### 30 MHz - 1 GHz



## Above 1 GHz



## TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

## TEST RESULTS

**9 kHz – 30MHz**

**Operation Mode:** Normal Link

### **Notes:**

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor



## TEST RESULTS

### Below 1 GHz

**Operation Mode:** Normal Link

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
37.50	11.81	12.55	1.54	V	25.90	40	14.10
54.20	15.52	10.12	1.90	V	27.54	40	12.46
136.5	13.37	12.56	3.05	V	28.98	43.5	14.52
166.0	8.50	12.66	4.21	V	25.37	43.5	20.63

### Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Quasi peak detector mode.

## Above 1 GHz

**Operation Mode:** CH Low

Frequency [MHz]	Level [dBuV]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804.00	-105.7	36.7	V	35.40	54	18.60	AV
4804.00	-118.5	36.7	V	48.22	74	25.78	Peak

### Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

**Operation Mode:** CH Mid

Frequency [MHz]	Level [dBuV]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4882.00	-104.3	36.9	V	34.17	54	19.83	AV
4882.00	-117.0	36.9	V	46.90	74	27.10	Peak

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

**Operation Mode:** CH High

Frequency [MHz]	Level [dBuV]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960.00	-102.6	37.1	V	32.75	54	21.25	AV
4960.00	-115.6	37.1	V	45.70	74	28.30	Peak

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MH.
  - b. AV Setting 1 GH z- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

## 6.8 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference groundplane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

## Test Plot

### Conducted emissions (Line 1)


HCT

EMC TEST LAB.

EUT: SP500  
 Manufacturer: Uriver Inc  
 Operating Condition: BLUETOOTH MODE  
 Test Site: SHIELD ROOM  
 Operator: YS-JUNG  
 Test Specification: CISPR 22 CLASS B  
 Comment: N

#### SCAN TABLE: "CISPR 22 Voltage"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	5.0 kHz	Average	10.0 ms	9 kHz	None
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



#### MEASUREMENT RESULT: "MOBILE PHONE\_fin QP"

5/2/2007 11:43AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Line	PE
0.237600	39.60	10.0	62	22.6	---	---
0.452600	30.40	10.1	57	26.5	---	---
0.467600	40.00	10.1	57	16.3	---	---
0.705000	28.10	10.1	56	27.9	---	---
0.945000	28.70	10.1	56	27.3	---	---
1.650000	29.80	10.2	56	26.2	---	---
6.345000	19.10	10.8	60	40.9	---	---
8.785000	22.20	11.0	60	37.8	---	---
9.835000	16.60	11.1	60	43.4	---	---

MEASUREMENT RESULT: "MOBILE PHONE\_fin AV"

5/2/2007 11:43AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.235100	31.80	10.0	52	20.5	---	---
0.452600	15.80	10.1	47	31.1	---	---
0.467600	31.60	10.1	47	14.9	---	---
0.705000	21.60	10.1	46	24.4	---	---
0.940000	21.70	10.1	46	24.3	---	---
1.645000	19.20	10.2	46	26.8	---	---
5.680000	14.20	10.7	50	35.8	---	---
6.815000	12.10	10.9	50	37.9	---	---
8.690000	12.10	11.0	50	37.9	---	---

## Conducted emissions (Line 2)


HCT

EMC TEST LAB.

EUT: SP500  
 Manufacturer: Uriver Inc.  
 Operating Condition: BLUETOOTH MODE  
 Test Site: SHIELD ROOM  
 Operator: YS-JUNG  
 Test Specification: CISPR 22 CLASS B  
 Comment: H

### SCAN TABLE: "CISPR 22 Voltage"

Short Description:		CISPR 22 Voltage					
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency	Frequency	Width					
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	5 kHz	None	
			Average				
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



### MEASUREMENT RESULT: "MOBILE PHONE\_fin QP"

5/2/2007 11:40AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.220100	31.80	10.0	63	31.0	---	---
0.230100	43.30	10.0	62	19.1	---	---
0.460100	44.40	10.1	57	12.3	---	---
0.695000	34.20	10.1	56	21.8	---	---
0.925000	30.30	10.1	56	25.7	---	---
1.615000	19.40	10.2	56	36.6	---	---
5.550000	23.40	10.7	60	36.6	---	---
6.715000	23.00	10.8	60	37.0	---	---
9.465000	20.60	11.1	60	39.4	---	---



MEASUREMENT RESULT: "MOBILE PHONE\_fin AV"

5/2/2007 11:40AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	FE
0.222600	20.20	10.0	53	32.6	---	---
0.230100	35.70	10.0	52	16.7	---	---
0.460100	36.50	10.1	47	10.2	---	---
0.695000	18.70	10.1	46	27.3	---	---
0.925000	22.40	10.1	46	23.6	---	---
1.615000	24.70	10.2	46	21.3	---	---
5.535000	12.20	10.7	50	37.8	---	---
6.270000	16.60	10.8	50	33.4	---	---
6.710000	13.20	10.8	50	36.8	---	---

## 8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESI40/ EMI Test Receiver	11/06/2006	Annual	11/06/2007	831564103
Rohde & Schwarz	ESCI/ EMI Test Receiver	08/24/ 2006	Annual	08/24/ 2007	100033
Rohde & Schwarz	ESH2-Z5/ LISN	04/20/2007	Annual	04/20/2008	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	04/11/2007	Annual	03/16/2008	837950/023
Schwarzbeck	VULB 9160/ TRILOG Antenna	04/20/2007	Annual	04/20/2008	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	03/16/2007	Annual	03/16/2008	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P	01/24/2007	Annual	01/24/2008	1200937
MITEQ	AMF-6D-01180-35-20P	02/24/2007	Annual	02/24/2008	990893
Schwarzbeck	BBHA 9120D/ Horn Antenna	03/30/2007	Annual	03/30/2008	147
Schwarzbeck	BBHA9170/ SHF-EHF Horn Antenna	03/20/2007	Annual	03/20/2008	BBHA9170342
Rohde & Schwarz	HFH2-Z2/Loop Antenna	05/11/2007	Annual	01/10/2008	881056/070
ADVANTEST	R3273/Spectrum Analyzer	05/02/2007	Annual	05/02/2008	J004821
Agilent	E4416A /Power Meter	01/22/2007	Annual	01/22/2008	GB41291412
Agilent	E7405A	10/02/2006	Annual	10/02/2007	US40240209
Weinschel	2/Attenuator	01/24/2007	Annual	01/24/2008	BR0554
Wainwright Instrument	WHF.3.3/18G-10EF / High Pass Filter	06/28/2006	Annual	06/28/2007	1