



RF Exposure Evaluation Report

APPLICANT : SIMCom

Building A, SIM Technology Building, No. 633, Jinzhong Road, Changning District, Shanghai P.R. China 200335

EQUIPMENT : WCDMA/HSDPA/HSUPA (2100MHz+1900MHz+900MHz)
/EDGE/GPRS/GSM (850MHz+900MHz+1800MHz+1900MHz)
GPS Module

BRAND NAME : SIMCom

MODEL NAME : SIM5218E

FCC ID : UDV-0200901181058

FILING TYPE : Certification

STANDARD : OET Bulletin 65 Supplement C (Edition 01-01)

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with FCC OET Bulletin 65 Supplement C (Edition 01-01).

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Revision History



1. Introduction

The report has been prepared on behalf of SIMCom WCDMA/HSDPA/HSUPA (2100MHz+1900MHz+900MHz) /EDGE/GPRS/GSM (850MHz+900MHz+1800MHz+1900MHz) GPS Module to show compliance with the RF Exposure.

Requirements

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile and portable and are defined as follows:

▪ Fixed installation:

Fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

▪ Mobile Devices:

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR 2.1091.

▪ Portable Devices:

A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR 2.1093)

For this test report the SIMCom SIM5218E is being done as a mobile device and the MPE is evaluated at the 20cm test distance.

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

**▪ Occupational/controlled Exposure:**

In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.

▪ General Population/Uncontrolled Exposure:

The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category and the general population/uncontrolled exposure limits apply to these devices.

Since there are no warnings or training associated with this unit and it can be used by anyone, WCDMA/HSDPA/HSUPA (2100MHz+1900MHz+900MHz) /EDGE/GPRS/GSM (850MHz+900MHz+1800MHz+1900MHz) GPS Module is evaluated to the General Population / Uncontrolled Exposure limits.



2. Radio Frequency Radiation Exposure Evaluation

According to 1.1310 of the FCC rules, the power density limit for General Population/Uncontrolled Exposure is $f/1500 \text{ mW/cm}^2$ for Cellular band and 1.0 mW/cm^2 for PCS band. As this is a mobile application the MPE shall be calculated at 20cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

For this device, the calculation is as follows:

<GPRS Multi-slot Class 8>

Function	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Cellular Band	2.00	1.58	32.43	1749.85	346.67	0.07	0.57
PCS Band	2.00	1.58	30.41	1099.01	217.73	0.04	1.00

<GPRS Multi-slot Class 10>

Function	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Cellular Band	2.00	1.58	30.81	1205.04	477.46	0.10	0.57
PCS Band	2.00	1.58	29.96	990.83	392.59	0.08	1.00

<GPRS Multi-slot Class 12>

Function	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Cellular Band	2.00	1.58	27.58	572.80	453.91	0.09	0.57
PCS Band	2.00	1.58	28.39	690.24	546.98	0.11	1.00

**<WCDMA>**

Function	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated RF Exposure at d = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Band II	2.00	1.58	22.64	183.65	0.06	1.00

Based on the above calculation at 20 cm the WCDMA/HSDPA/HSUPA (2100MHz+1900MHz+900MHz) /EDGE/GPRS/GSM (850MHz+900MHz+1800MHz+1900MHz) GPS Module is below the Power Density limit.