



A D T

EXPOSURE REPORT

REPORT NO.: SA140820C01A

MODEL NO.: MR32-HW

FCC ID: UDX-60031010

RECEIVED: Aug. 04, 2014

TESTED: Aug. 04 ~ Oct. 09, 2014

ISSUED: Nov. 18, 2014

APPLICANT: Cisco Systems, Inc.

ADDRESS: 170 West Tasman Drive, San Jose, CA 95134

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	5
2.2 MPE CALCULATION FORMULA.....	5
2.3 CLASSIFICATION.....	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140820C01A	Original release	Nov. 18, 2014



1. CERTIFICATION

PRODUCT: Wireless 802.11 abgn/ac AP
MODEL NO.: MR32-HW
BRAND: Cisco
APPLICANT: Cisco Systems, Inc.
TESTED: Aug. 04 ~ Oct. 09, 2014
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1091)**
KDB 447498 D03
IEEE C95.1

The above equipment (model: MR32-HW) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou , **DATE** : Nov. 18, 2014
Celine Chou / Specialist

APPROVED BY : Ken Liu , **DATE** : Nov. 18, 2014
Ken Liu / Senior Manager

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 29cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

RADIO	TX	FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
1	1TX	2412-2462	26.26	5.05	29	0.1279	1
	2TX	2412-2462	29.35	7.79	29	0.4898	1
2	1TX	5180-5240	25.25	5.31	29	0.1076	1
	1TX	5260-5320	23.91	4.40	29	0.0641	1
	1TX	5500-5700	23.98	5.01	29	0.0750	1
	1TX	5745-5825	22.35	5.60	29	0.0590	1
	2TX	5180-5240	28.22	8.20	29	0.4149	1
	2TX	5260-5320	23.44	7.24	29	0.1107	1
	2TX	5500-5700	23.81	8.60	29	0.1648	1
	2TX	5745-5825	25.26	8.37	29	0.2183	1
3	1TX	2412-2462	21.26	2.38	29	0.0219	1
	1TX	5180-5240	17.21	4.22	29	0.0132	1
	1TX	5260-5320	17.94	4.36	29	0.0161	1
	1TX	5500-5700	21.24	3.99	29	0.0315	1
	1TX	5745-5825	20.92	3.22	29	0.0245	1
4	-	2402-2480	3.43	0.67	29	0.0002	1

NOTE:

- 2TX (Radio 1): Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}] = 7.79\text{dBi}$
- 2TX (Radio 2): 5180-5240MHz: Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}] = 8.20\text{dBi}$
5260-5320MHz: Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}] = 7.24\text{dBi}$
5500-5700MHz: Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}] = 8.40\text{dBi}$
5745-5825MHz: Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}] = 8.37\text{dBi}$



A D T

FREQUENCY BAND	MAX POWER (dBm)				TOTAL POWER (dBm)	POWER LIMIT (dBm)
	RADIO 1	RADIO 2	RADIO 3	RADIO 4		
2.4GHz	29.35	-	21.26	3.43	29.99	30
5180-5240MHz	-	28.22	17.21	-	28.55	30
5260-5320MHz	-	23.91	17.94	-	24.89	30
5500-5700MHz	-	23.98	21.24	-	25.83	30
5745-5825MHz	-	25.26	20.92	-	26.62	30

CONCLUSION:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$\text{Radio 1} + \text{Radio 2} + \text{Radio 3 (2.4G)} + \text{Radio 3 (5GHz)} + \text{Radio 4} = 0.4898 + 0.4149 + 0.0219 + 0.0315 + 0.0002 = 0.9583$$

Therefore the maximum calculations of above situations are less than the "1" limit.