



RADIO EXPOSURE TEST REPORT

FCC ID : UDX-60093011
Equipment : 4x4 Wi-Fi 6 Access Point with External Antennas
Brand Name : Cisco
Model Name : MR46E-HW
Applicant : Cisco Systems, Inc.
170 West Tasman Drive, San Jose, CA 95134 USA
Manufacturer : Cisco Systems, Inc.
170 West Tasman Drive, San Jose, CA 95134 USA
Standard : 47 CFR Part 2.1091

The product was received on Jun. 20, 2019, and testing was started from Jul. 03, 2019 and completed on Aug. 03, 2023. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3
Summary of Test Result.....4
1 General Description5
1.1 EUT General Information5
1.2 Antenna Information6
1.3 Table for DDR information.....9
1.4 Accessories10
1.5 Applicable Standards10
1.6 Testing Location10
2 Maximum Permissible Exposure11
2.1 Limit of Maximum Permissible Exposure11
2.2 MPE Calculation Method11
2.3 MPE Exemption12
2.4 Calculated Result and Limit.....13

Photographs of EUT v01



History of this test report

| Report No. | Version | Description | Issued Date |
|-------------|---------|-------------------------|---------------|
| FA960317-14 | 01 | Initial issue of report | Oct. 06, 2023 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2 | - | Exposure evaluation | PASS | - |

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Viola Huang



1 General Description

1.1 EUT General Information

| RF General Information | | | |
|------------------------|--|--|--|
| Evaluation Mode | Frequency Range (MHz) | Operating Frequency (MHz) | Modulation Type |
| 2.4GHz WLAN | 2400-2483.5 | 2412-2462 | 802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) |
| 5GHz WLAN | 5150-5250 5250-5350 5470-5725 5725-5850 | 5180-5240 5260-5320 5500-5720 5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) |
| Bluetooth | 2400-2483.5 | 2402-2480 | LE: GFSK |



1.2 Antenna Information

| Set | Brand | Official Model Number | Antenna Type | Connector | Gain (dBi) |
|-----|-------|-----------------------|----------------------|-----------|------------|
| 1 | Cisco | MA-ANT-3-A6 | Dipole antenna | RP-TNC | Note 1 |
| 2 | Cisco | MA-ANT-3-B6 | Dipole antenna | RP-TNC | |
| 3 | Cisco | MA-ANT-3-C6 | Panel antenna | RP-TNC | |
| 4 | Cisco | MA-ANT-3-D6 | Panel antenna | RP-TNC | |
| 5 | Cisco | MA-ANT-3-E6 | Wide patch antenna | RP-TNC | |
| 6 | Cisco | MA-ANT-3-F6 | Narrow patch antenna | RP-TNC | |

Note1:

| Radio 1 (2.4GHz) | | | | | | | | | | | | |
|------------------|--------------------|--------|--------|--------|-----------------|--------|--------|--------|-----------------|--------|--------|--------|
| Set | Antenna Gain (dBi) | | | | Cable Loss (dB) | | | | True Gain (dBi) | | | |
| | Port 1 | Port 2 | Port 3 | Port 4 | Port 1 | Port 2 | Port 3 | Port 4 | Port 1 | Port 2 | Port 3 | Port 4 |
| 1 | 3.80 | 3.80 | 3.80 | 3.80 | 1.01 | 0.41 | 0.41 | 1.00 | 2.79 | 3.39 | 3.39 | 2.80 |
| 2 | 3.00 | 3.00 | 3.00 | 3.00 | 1.01 | 0.41 | 0.41 | 1.00 | 1.99 | 2.59 | 2.59 | 2.00 |
| 3 | 4.90 | 4.90 | 4.90 | 4.90 | 1.01 | 0.41 | 0.41 | 1.00 | 3.89 | 4.49 | 4.49 | 3.90 |
| 4 | 2.90 | 2.90 | 2.90 | 2.90 | 1.01 | 0.41 | 0.41 | 1.00 | 1.89 | 2.49 | 2.49 | 1.90 |
| 5 | 7.00 | 7.00 | 7.00 | 7.00 | 1.01 | 0.41 | 0.41 | 1.00 | 5.99 | 6.59 | 6.59 | 6.00 |
| 6 | 11.20 | 11.20 | 11.20 | 11.20 | 1.01 | 0.41 | 0.41 | 1.00 | 10.19 | 10.79 | 10.79 | 10.20 |

| Radio 2 (5GHz) | | | | | | | | | | | | |
|----------------|--------------------|--------|--------|--------|-----------------|--------|--------|--------|-----------------|--------|--------|--------|
| Set | Antenna Gain (dBi) | | | | Cable Loss (dB) | | | | True Gain (dBi) | | | |
| | Port 1 | Port 2 | Port 3 | Port 4 | Port 1 | Port 2 | Port 3 | Port 4 | Port 1 | Port 2 | Port 3 | Port 4 |
| 1 | 5.5 | 5.5 | 5.5 | 5.5 | 1.53 | 0.66 | 0.61 | 1.54 | 3.97 | 4.84 | 4.89 | 3.96 |
| 2 | 5.7 | 5.7 | 5.7 | 5.7 | 1.53 | 0.66 | 0.61 | 1.54 | 4.17 | 5.04 | 5.09 | 4.16 |
| 3 | 4.9 | 4.9 | 4.9 | 4.9 | 1.53 | 0.66 | 0.61 | 1.54 | 3.37 | 4.24 | 4.29 | 3.36 |
| 4 | 3.7 | 3.7 | 3.7 | 3.7 | 1.53 | 0.66 | 0.61 | 1.54 | 2.17 | 3.04 | 3.09 | 2.16 |
| 5 | 6.3 | 6.3 | 6.3 | 6.3 | 1.53 | 0.66 | 0.61 | 1.54 | 4.77 | 5.64 | 5.69 | 4.76 |
| 6 | 10.8 | 10.8 | 10.8 | 10.8 | 1.53 | 0.66 | 0.61 | 1.54 | 9.27 | 10.14 | 10.19 | 9.26 |



| Radio 3 (2.4GHz + 5GHz) | | | | | | |
|-------------------------|--------------------|-------|-----------------|------|-----------------|------|
| Set | Antenna Gain (dBi) | | Cable Loss (dB) | | True Gain (dBi) | |
| | Port 1 | | Port 1 | | Port 1 | |
| | 2.4GHz | 5GHz | 2.4GHz | 5GHz | 2.4GHz | 5GHz |
| 1 | 3.80 | 5.50 | 0.68 | 1.09 | 3.12 | 4.41 |
| 2 | 3.00 | 5.70 | 0.68 | 1.09 | 2.32 | 4.61 |
| 3 | 4.90 | 4.90 | 0.68 | 1.09 | 4.22 | 3.81 |
| 4 | 2.90 | 3.70 | 0.68 | 1.09 | 2.22 | 2.61 |
| 5 | 7.00 | 6.30 | 0.68 | 1.09 | 6.32 | 5.21 |
| 6 | 11.20 | 10.80 | 0.68 | 1.09 | 10.52 | 9.71 |

| Radio 4 (Bluetooth) | | | |
|---------------------|--------------------|-----------------|-----------------|
| Set | Antenna Gain (dBi) | Cable Loss (dB) | True Gain (dBi) |
| | Port 1 | Port 1 | Port 1 |
| 1 | 3.80 | 0.56 | 3.24 |
| 2 | 3.00 | 0.56 | 2.44 |
| 3 | 4.90 | 0.56 | 4.34 |
| 4 | 2.90 | 0.56 | 2.34 |
| 5 | 7.00 | 0.56 | 6.44 |
| 6 | 11.20 | 0.56 | 10.64 |

Note2: The above information was declared by manufacturer.

Note3: The EUT has six set antennas.

The EUT has four radios, Radio 1 supports WLAN 2.4GHz (802.11b/g/n/ax mode), Radio 2 supports WLAN 5GHz (802.11a/n/ac/ax mode), Radio 3 supports WLAN 2.4GHz + 5GHz (scanning radio) and Radio 4 supports Bluetooth function.

Set 1 and Set 2 antennas are the same type antennas, only the highest gain antennas Set 1 for 2.4GHz, Set 2 for 5GHz were tested.



Note 4: Directional gain information

| Type | Maximum Output Power | Power Spectral Density |
|--------|---|---|
| Non-BF | Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4 | $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$ |
| BF | $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$ | $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$ |

Ex.

Directional Gain (NSS1) formula :

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$$

$$NSS1(g1,1) = 10^{G1/20} ; NSS1(g1,2) = 10^{G2/20} ; NSS1(g1,2) = 10^{G3/20} ; NSS1(g1,2) = 10^{G4/20}$$

$$g_{j,k} = (NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2$$

$$DG = 10 \log \left[\frac{(NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2}{N_{ANT}} \right] \Rightarrow 10 \log \left[\frac{(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2}{N_{ANT}} \right]$$

Where ;

Antenna Set 1

2.4G G1= 2.79 dBi ; G2= 3.39 dBi ; G3= 3.39 dBi ; G4= 2.8 dBi ;
4TX DG= 9.12dBi ; 2TX DG= 6.11dBi

Antenna Set 2

5G G1= 4.17 dBi ; G2= 5.04 dBi ; G3= 5.09 dBi ; G4= 4.16 dBi ;
4TX DG= 10.65dBi ; 2TX DG= 7.63dBi

Antenna Set 3

2.4G G1= 3.89 dBi ; G2= 4.49 dBi ; G3= 4.49 dBi ; G4= 3.9 dBi ;
4TX DG= 10.22dBi ; 2TX DG= 7.21dBi
5G G1= 3.37 dBi ; G2= 4.24 dBi ; G3= 4.29 dBi ; G4= 3.36 dBi ;
4TX DG= 9.85dBi ; 2TX DG= 6.83dBi

Antenna Set 4

2.4G G1= 1.89 dBi ; G2= 2.49 dBi ; G3= 2.49 dBi ; G4= 1.9 dBi ;
4TX DG= 8.22dBi ; 2TX DG= 5.21dBi
5G G1= 2.17 dBi ; G2= 3.04 dBi ; G3= 3.09 dBi ; G4= 2.16 dBi ;
4TX DG= 8.65dBi ; 2TX DG= 5.63dBi



Antenna Set 5

2.4G G1= 5.99 dBi ; G2= 6.59 dBi ; G3= 6.59 dBi ; G4= 6 dBi ;

4TX DG= 12.32dBi ; 2TX DG= 9.31dBi

5G G1= 4.77 dBi ; G2= 5.64 dBi ; G3= 5.69 dBi ; G4= 4.76 dBi ;

4TX DG= 11.25dBi ; 2TX DG= 8.23dBi

Antenna Set 6

2.4G G1= 10.19 dBi ; G2= 10.79 dBi ; G3= 10.79 dBi ; G4= 10.2 dBi ;

4TX DG= 16.52dB i ; 2TX DG= 13.51dBi

5G G1= 9.27 dBi ; G2= 10.14 dBi ; G3= 10.19 dBi ; G4= 9.26 dBi ;

4TX DG= 15.75dBi ; 2TX DG= 12.73dBi

<For Radio 1 (2.4GHz Functions) and Radio 2 (5GHz Functions)>

For 1TX/4RX:

Only Port 1 can be use as transmitting antenna

Port 1, Port 2, Port 3 and Port 4 can be used as receiving antennas.

Port 1, Port 2, Port 3 and Port 4 could receive simultaneously.

For 2TX/4RX:

Only Port 1 and Port 2 can be use as transmitting antenna

Port 1, Port 2, Port 3 and Port 4 can be used as receiving antennas.

Port 1, Port 2, Port 3 and Port 4 could receive simultaneously.

For 4TX/4RX:

Port 1, Port 2, Port 3 and Port 4 can be use as transmitting/receiving antenna

Port 1, Port 2, Port 3 and Port 4 could receive simultaneously.

<For Radio 3 / 2.4GHz + 5GHz Functions>

Only Port 1 can be used as receiving antennas.

<For Radio 4 / Bluetooth Functions>

Only Port 1 can be use as transmitting/receiving antenna.



1.3 Accessories

| Accessories | | | | |
|---------------------|------------|------------------|-------------|--|
| Equipment Name | Brand Name | Model Name | P/N | Rating |
| Adapter 1 | CISCO | KSAS0361200250HU | - | Input: 100-240V, 50/60Hz, 1.0A Output: 12V, 2.5A |
| Adapter 2 | CISCO | MA-PWR-30W-US | 640-39010-A | Input: 100-240V, 50-60Hz, 0.8A Max. Output: 12V, 2.5A 30W |
| Other | | | | |
| Wall-mounted rack*1 | | | | |

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
 - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
 - ♦ 47 CFR Part 1.1310

1.5 Testing Location

| Testing Location Information | |
|---|--|
| Test Lab. : Sporton International Inc. Hsinchu Laboratory | |
| Hsinchu | ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) |
| (TAF: 3787) | TEL: 886-3-656-9065 FAX: 886-3-656-9085 |
| | Test site Designation No. TW3787 with FCC. |
| | Conformity Assessment Body Identifier (CABID) TW3787 with ISED. |

Note: The tested sample of the power test item was received on Sep. 22, 2022.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | *(100) | <6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | <6 |
| 30-300 | 61.4 | 0.163 | 1.0 | <6 |
| 300-1500 | - | - | f/300 | <6 |
| 1500-100,000 | - | - | 5 | <6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | *(100) | <30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | <30 |
| 30-300 | 27.5 | 0.073 | 0.2 | <30 |
| 300-1500 | - | - | f/1500 | <30 |
| 1500-100,000 | - | - | 1.0 | <30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 54 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

| Single RF Sources Subject to Routine Environmental Evaluation | |
|---|--|
| RF Source frequency (MHz) | Threshold ERP (watts) |
| 0.3-1.34 | 1,920 R ² . |
| 1.34-30 | 3,450 R ² /f ² . |
| 30-300 | 3.83 R ² . |
| 300-1,500 | 0.0128 R ² f. |
| 1,500-100,000 | 19.2R ² . |

Note: R is in meters, f is in MHz.



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

MPE / Antenna / Set 1 and Set 2

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|----------------------|----------|-------------|------------|----------------|--------------------|---------------|-------------------------|-------------------------------|
| 2.4G;D1D (Radio 1) | 3.39 | 28.51 | 31.90 | 0.50 | 32.40 | 54 | 0.04742 | 1 |
| 5.2G;D1D (Radio 2) | 10.65 | 24.29 | 34.94 | 0.50 | 35.44 | 54 | 0.09550 | 1 |
| 5.3G;D1D (Radio 2) | 7.63 | 21.91 | 29.54 | 0.45 | 29.99 | 54 | 0.02723 | 1 |
| 5.6G;D1D (Radio 2) | 7.63 | 21.92 | 29.55 | 0.44 | 29.99 | 54 | 0.02723 | 1 |
| 5.8G;D1D (Radio 2) | 10.65 | 24.71 | 35.36 | 0.17 | 35.53 | 54 | 0.09750 | 1 |
| 2.4G;BT-LE (Radio 4) | 3.24 | 19.01 | 22.25 | 0.50 | 22.75 | 54 | 0.00527 | 1 |

MPE / Antenna / Set 3

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|----------------------|----------|-------------|------------|----------------|--------------------|---------------|-------------------------|-------------------------------|
| 2.4G;D1D (Radio 1) | 4.49 | 29.92 | 34.41 | 0.50 | 34.91 | 54 | 0.08453 | 1 |
| 5.2G;D1D (Radio 2) | 9.85 | 26.10 | 35.95 | 0.04 | 35.99 | 54 | 0.10839 | 1 |
| 5.3G;D1D (Radio 2) | 9.85 | 20.06 | 29.91 | 0.08 | 29.99 | 54 | 0.02723 | 1 |
| 5.6G;D1D (Radio 2) | 9.85 | 19.68 | 29.53 | 0.46 | 29.99 | 54 | 0.02723 | 1 |
| 5.8G;D1D (Radio 2) | 9.85 | 25.56 | 35.41 | 0.50 | 35.91 | 54 | 0.10641 | 1 |
| 2.4G;BT-LE (Radio 4) | 4.34 | 19.12 | 23.46 | 0.50 | 23.96 | 54 | 0.00679 | 1 |

**MPE / Antenna / Set 4**

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|----------------------|----------|-------------|------------|----------------|--------------------|---------------|-------------------------|-------------------------------|
| 2.4G;D1D (Radio 1) | 2.49 | 29.92 | 32.41 | 0.50 | 32.91 | 54 | 0.05333 | 1 |
| 5.2G;D1D (Radio 2) | 8.65 | 27.26 | 35.91 | 0.08 | 35.99 | 54 | 0.10839 | 1 |
| 5.3G;D1D (Radio 2) | 8.65 | 21.31 | 29.96 | 0.03 | 29.99 | 54 | 0.02723 | 1 |
| 5.6G;D1D (Radio 2) | 8.65 | 21.31 | 29.96 | 0.03 | 29.99 | 54 | 0.02723 | 1 |
| 5.8G;D1D (Radio 2) | 8.65 | 27.33 | 35.98 | 0.01 | 35.99 | 54 | 0.10839 | 1 |
| 2.4G;BT-LE (Radio 4) | 2.34 | 19.01 | 29.65 | 0.50 | 30.15 | 54 | 0.02825 | 1 |

MPE / Antenna / Set 5

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|----------------------|----------|-------------|------------|----------------|--------------------|---------------|-------------------------|-------------------------------|
| 2.4G;D1D (Radio 1) | 6.59 | 28.42 | 35.01 | 0.50 | 35.51 | 54 | 0.09705 | 1 |
| 5.2G;D1D (Radio 2) | 11.25 | 24.29 | 35.54 | 0.45 | 35.99 | 54 | 0.10839 | 1 |
| 5.3G;D1D (Radio 2) | 5.69 | 23.91 | 29.60 | 0.39 | 29.99 | 54 | 0.02723 | 1 |
| 5.6G;D1D (Radio 2) | 5.69 | 23.97 | 29.66 | 0.33 | 29.99 | 54 | 0.02723 | 1 |
| 5.8G;D1D (Radio 2) | 5.69 | 29.98 | 35.67 | 0.32 | 35.99 | 54 | 0.10839 | 1 |
| 2.4G;BT-LE (Radio 4) | 6.44 | 19.01 | 25.45 | 0.50 | 25.95 | 54 | 0.01074 | 1 |



MPE / Antenna / Set 6

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|----------------------|----------|-------------|------------|----------------|--------------------|---------------|-------------------------|-------------------------------|
| 2.4G;D1D (Radio 1) | 10.79 | 24.93 | 35.72 | 0.27 | 35.99 | 54 | 0.10839 | 1 |
| 5.2G;D1D (Radio 2) | 9.27 | 26.70 | 35.97 | 0.02 | 35.99 | 54 | 0.10839 | 1 |
| 5.3G;D1D (Radio 2) | 9.27 | 20.69 | 29.96 | 0.50 | 30.46 | 54 | 0.03034 | 1 |
| 5.6G;D1D (Radio 2) | 9.27 | 20.69 | 29.96 | 0.50 | 30.46 | 54 | 0.03034 | 1 |
| 5.8G;D1D (Radio 2) | 9.27 | 26.36 | 35.63 | 0.36 | 35.99 | 54 | 0.10839 | 1 |
| 2.4G;BT-LE (Radio 4) | 10.64 | 19.01 | 29.65 | 0.50 | 30.15 | 54 | 0.02825 | 1 |

| MPE Exemption Option C | | | | | | | |
|------------------------|--------------------|-------|--------------------|-------------------|-----------------|-------------------|---------------|
| Frequency (MHz) | $\lambda/2\pi$ (m) | R (m) | Tune-up EIRP (dBm) | Tune-up ERP (dBm) | Tune-up ERP (W) | ERP Threshold (W) | MPE Exemption |
| 2402 | 0.0199 | 0.54 | 30.15 | 28.00 | 0.631 | 5.599 | Complies |
| 2462 | 0.0194 | | 35.99 | 33.84 | 2.421 | 5.599 | Complies |
| 5745 | 0.0083 | | 35.99 | 33.84 | 2.421 | 5.599 | Complies |

Simultaneous Transmission Analysis Mode:

Radio 1 (2.4GHz) + Radio 2 (5GHz) + Radio 4 (BT4.0)

| Simultaneous Transmissions Option C | | | | | | | |
|-------------------------------------|-------|--------------------|-------------------|-----------------|-------------------|----------------------------|----------------------------------|
| Frequency (MHz) | R (m) | Tune-up EIRP (dBm) | Tune-up ERP (dBm) | Tune-up ERP (W) | ERP Threshold (W) | Simultaneous Transmissions | Simultaneous Transmissions Limit |
| 2402 | 0.54 | 30.15 | 28.00 | 0.631 | 5.599 | 0.98 | <= 1 |
| 2462 | | 35.99 | 33.84 | 2.421 | 5.599 | | |
| 5745 | | 35.99 | 33.84 | 2.421 | 5.599 | | |

Note: The above antenna gain was declared by manufacturer.

—————THE END—————