

Request for Modular/Limited Modular Approval

Date: March 25, 2020					
Subject: Manufacturer's Declaration for		 Split Modula Limited Spli 		pproval	
Confidentiality Request for: <u>UE38</u>	X243				
8 B	asic Requirements – FCC Part 15.212(a)(1)			
	Limited Module Description Must be l	Filled Out on the Fo			
	pproval Requirement		Require	ment Met	
 The modular transmitter must have its own does not have to rely upon the shielding pr all modular transmitter emissions to compl between the RF circuitry of the module and is installed. Such coupling may result in no capacitors may be located external to the s 	ovided by the device into which it is inst by with FCC limits. It is also intended to a any wires or circuits in the device into on-compliant operation. The physical cry	alled in order for prevent coupling which the module	🖾 - YES	🗌 - NO(*)	
	Details: The module contains a metal shield which covers all RF components and circuitry of the module. The shield is located on the module sub-PCB board that is surface mounted to the host board.				
 The modular transmitter must have buffered ensure that the module will comply with F or over-modulation. 15.212(a)(1)(ii) 			🖾 - YES	🗌 - NO(*)	
Details: The SX1281 single chip radio tro of the carrier. Maximum data rate is har		gisters and does not	permit direct	modulation	
 The modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into which 	FCC requirements regardless of the desi	ign of the power	🗆 - YES	🖾 - NO(*)	
host boards are only manufactured for an	Details: The host board contains its own voltage regulator. Host boards will always contain the same voltage regulator as the host boards are only manufactured for and by Banner Engineering. Please refer to schematics filed with this application.				
 The modular transmitter must comply with 15.203, 15.204(b), 15.204(c), 15.212(a), ar attached or employ a "unique" antenna co antenna, including the cable). The "profess to modules but can apply to limited modular 	nd 2.929(b). The antenna must either be p upler (at all connections between the mo sional installation" provision of § 15.203	bermanently dule and the 3 is not applicable	🗆 - YES	🖾 - NO(*)	
Details: The host board contains a non-s standard connectors as all host boards ar approved with this device may be found in	e only manufactured for and by Banner	r Engineering. A lis			
5. The modular transmitter must be tested in a inside another device during testing. This is complying with Part 15 emission limits regulates the transmitter module will be batter requirements found in Section 15.207. AC the module must not contain ferrites, unless 15.27(a)). The length of these lines shall be at least 10 centimeters to insure that there i supporting equipment. Any accessories, peduring testing shall be unmodified or common.	s intended to demonstrate that the module ardless of the device into which it is even ry powered, it must comply with the AC or DC power lines and data input/output s they will be marketed with the module e length typical of actual use or, if that len s no coupling between the case of the mo- ripherals, or support equipment connecten nercially available (see Section 15.31(i)).	e is capable of ntually installed. line conducted lines connected to (see Section ngth is unknown, odule and d to the module . 15.212(a)(1)(v)	🗆 - YES	⊠ - NO(*)	
Details: The SX243 Radio Module was tested using a typical host necessary for limited modular approval as shown in test setup photographs filed with this application. The module installed onto typical host was found to be compliant with Part 15 regulations.					

Banner Engineering Corporation

9714 Tenth Avenue North • Minneapolis, MN 55441 • Phone 763.544.3164 • Fax 763.544.3213 • www.bannerengineering.com



	Modular Approval Requirement	Requir	ement Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC ciffied transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application in the application. 15.212(a)(1)(vi)	⊠ - YES	- NO(*)
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(c), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	🛛 - YES	🗆 - NO(*)
	Details: The module installed on host complies with FCC Part 15C requirements as tested.		
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	🖾 - YES	🗆 - NO(*)

Details: The module installed on host complies with all RF exposure requirements as tested.



Limited Module Description - When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: The SX243 Radio Module is mounted onto the host board. The SX243 Radio Module is a complete module except for the antenna connector and voltage regulator; these components are located on the host board The SX243 Radio Module was tested using a typical host necessary for limited modular approval as shown in test setup photographs filed with this application. The module installed onto typical host was found to be compliant with Part 15 regulations.

It is desired to have the SX243 Radio Module as a Limited Modular Approval for use with the host board. In the future, any changes to the host board, or change in non-radio functionality, could be updated via a Class I permissive change by adding model numbers of changed or new host boards.

Host boards will always contain the same voltage regulator and non-standard antenna connections as the host boards are only manufactured for and by Banner Engineering. Banner Engineering will retain complete control of the use and installation of

this product such that full compliance of all end products is assured. The SX243 Radio Module is not for sale to third parties and all integration documentation remains proprietary.

	Software Considerations - KDB 594280 / KDB 442812 (One of the follow	ing 2 items must be applied)	
	Requirement	Requirement Met	
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	 Provided in Separate Cover Letter 	🗆 - N/A
	Details: The firmware of the device cannot be modified or adjusted by the end user a with this application.	as described in a separate cove	r letter filed
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	Cover Letter	🖾 - N/A
	Details: N/A		

Split Modular Requirements Requirement	Provided in Manual	
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	Provided in Separate Cover Letter	🖾 - N/A
Details: N/A		

Banner Engineering Corporation

9714 Tenth Avenue North • Minneapolis, MN 55441 • Phone 763.544.3164 • Fax 763.544.3213 • www.baunerengineering.com



OEM Integration Manual Guidance – KDB 996369 D03 Section 2				
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures				
for third-parties to use and/or integrate the module into a host device.				
Requirement				
		⊠ - No,	11 1	
		If No, and LMA applies, the applicant can optionally choose to not		
		make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the		
Is this module intended for sale to third parties?	🗆 - YES	information below must still be incl		
sale to ante parties?		description. If the applicant wishes to		
		this will require a separate statement of		
		module is not for sale to third parti		
		instructions are internal confid	lential documents.	
		ual – See KDB 996369 D03, Section 2 formation to be in the installation manua	Madulan transmittar	
applicants should include inform:	ation in their instructions f	for all these items indicating clearly when	they are not applicable	
		ate "Not Applicable". Also if a module is		
		e user instructions may not need to be det		
		n, but this should include a cover letter a	s cited above.	
1. List of applicable FCC rules. Kl		2		
	ated to the transmitter.			
	the specific operational use conditions. KDB 996369 D03, Section 2.3 Conditions such as limits on antennas, cable loss, reduction of power for point to point			
	is fimits on antennas, cable f	oss, reduction of power for point to point		
3. Limited Module Procedures. KD				
		ses to verify the host meets the necessary		
limiting conditior			🗆 - All Items shown to	
b. When RF exposu	re evaluation is necessary, st	tate how control will be maintained such	the left are provided in	
	s ensured, such as Class II fo	or new hosts, etc.	the Modular Integration	
	4. Trace antenna designs. KDB 990309 D05, Section 2.5			
		dures for ensuring compliance. If	Modular Approval (MA)	
		ntial must be identified and information	or LMA.	
	perational description.			
5. RF exposure considerations. KD	B 996369 D03, Section 2.6		An LMA applies	
		ow host manufacturers to use the module.	and is approved ONLY for use by the grantee in	
		to the host manufacturer to define	their own products, and	
	e, portable – xx cm from boo e end user in the host produc	dy) and second additional text needed to	not intended for sale to	
6. Antennas. KDB 996369 D03, Se		· Indindio.	3 rd parties as provided in	
		d all applicable professional installer	a separate cover letter,	
instructions when	applicable. The antenna list	shall also identify the antenna types	Therefore the	
(monopole, PIFA,	dipole, etc - note that "omr	ni-directional" is not considered a type)	information shown to	
7. Label and compliance information. KDB 996369 D03, Section 2.8 the left is found in the theory of operation.				
	egrators that they need to pro- be the set of the set o	ovide a physical or e-label stating	www.j v. upvillion	
8. Information on test modes and ac				
a. Test modes that sl	nould be taken into consider	ation by host integrators including		
clarifications nece	ssary for stand-alone and sin	multaneous configurations.		
	on on how to configure test			
9. Additional testing, Part 15 Subpa	rt B disclaimer. KDB 99636	59 D03, Section 2.10		
			george for black galacite and a 194 D.C.	

Sincerely,

12

By:

John McMahon Senior Manager of Regulatory Compliance

Banner Engineering Corporation

9714 Tenth Avenue North • Minncapolis, MN 55441 • Phone 763.544.3164 • Fax 763.544.3213 • www.bannerengineering.com