

Report No. : AG030175-001 Date : 2006 November 28

Application No. : LG223517(9)

Client : iRobot Corporation

63 South Ave

Burlington, MA 01803

**United States** 

Sample Description : One(1) submitted sample(s) stated to be <u>iRobot Command Module</u>

of Model No. 4812

Rating : AC 100-240V to DC 22V adaptor

12 x 1.5V AA size batteries

DC 14.4V NiMH Rechargeable Battery

No. of submitted sample: Two(2) set(s) \*\*\*

Date Received : 2006 November 13

Test Period : 2006 November 13 – 2006 November 28

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)

ANSI C63.4 - 2003

Test Result : See attached sheet(s) from page 2 to 13.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart B.

For and on behalf of

CMA Industrial Development Foundation Limited

Authorized Signature :

Danny Chui Deputy Manager - EL. Division

Page 1 of 13

FCC ID: UFE4812



Report No. : AG030175-001 Date : 2006 November 28

## **Table of Contents**

1	Gen	eral Information	3
		General Description	
	1.2	Location of the test site	
	1.3	List of measuring equipment	
	1.4	List of support equipment	
2	Des	cription of the radiated emission test	
	2.1	Test Procedure	
	2.2	Test Result	7
	2.3	Radiated Emission Measurement Data	8
3	Des	cription of the Line-conducted Test	10
	3.1	Test Procedure	
	3.2	Test Result	10
	3.3	Graph and Table of Conducted Emission Measurement Data	10
4	Pho	tograph	11
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	11
	4.2	Photographs of the External and Internal Configurations of the EUT	11
5	Sup	plementary document	
	5.1	Bandwidth	12
	5.2	Duty cycle	12
	5.3	Transmission time	
6	App	endices	13



Report No. : AG030175-001 Date : 2006 November 28

#### 1 General Information

#### 1.1 General Description

The EUT is a Microprocessor based product powered by DC 5V iRobot external power source. The Main unit is controlled by an Atmel ATMEGA168-20AU microprocessor that utilizes an 18.432 MHz crystal for timing and control. A USB interface controller FDTI FT232RL is used for serial PC interface.

The EUT has the following features:

- As a programmable device that is able to accept user commands via a USB/COM interface.
- As a stand alone device able to read external sensors and control actuators.

The brief circuit description is saved with filename: OpDes.pdf



Report No. : AG030175-001 Date : 2006 November 28

#### 1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AG030175-001 Date : 2006 November 28

## 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCS30	100001
EMI Test Receiver	R&S	ESCI	100152
Broadband Antenna	Schaffner	CBL6112B	2718
LISN	R&S	ESH3-Z5	100038
LISN	R&S	ESH3-Z5	100010



Report No. : AG030175-001 Date : 2006 November 28

#### 1.4 List of support equipment

1. Intel CPU P4 2.8GHz / 512k cache / 533MHz bus

Model: 9426A657

2. Intel Mother Board

Model: Intel Type: D845EPI/D845GVSR

3. Seagate Hard-disk

Model: ST340014A, 40GB

4. Proview LCD Monitor

Model: 568

5. Logitech Mouse Model: M-S34

6. Hewlett Packard Keyboard Model: SK-2502C

7. Hewlett Packard LaserJet 2100TN

Model: C4172A

8. PenPower Handwriting System

Model: PP403N

9. RS232 cable 1 meter x 4 pieces (330Ω terminated)

10. USB Cable

(Provided by Applicant)

11. iRobot Command Module (with USB Port)

Model: 3812 (Provided by Applicant)

12. AC 120V 60Hz to DC 22V adaptor

Model: 10558 (Provided by Applicant)

13. 12 x 1.5V AA size batteries Box

(Provided by Applicant)

14. DC 14.4V NiMH Rechargeable Battery

(Provided by Applicant)



Report No. : AG030175-001 Date : 2006 November 28

#### 2 Description of the radiated emission test

#### 2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

#### 2.2 Test Result

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



Report No. : AG030175-001 Date : 2006 November 28

## 2.3 Radiated Emission Measurement Data

#### **Radiated emission**

#### pursuant to

## the requirement of FCC Part 15 subpart B

Operation Mode: PC Connection

Frequency	Polarity	Reading at	Antenna and	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Strength	$(dB\mu V/m)$	(dB)
		(dBµV/m)	(dB)	$(dB\mu V/m)$		
85.389	Н	19.0	7.3	26.3	40.0	-13.7
100.010	Н	15.2	11.1	26.3	43.5	-17.2
144.186	Н	19.5	12.0	31.5	43.5	-12.0
216.355	Н	18.1	9.8	27.9	46.0	-18.1
192.099	Н	20.1	9.5	29.6	46.0	-16.4
668.355	Н	12.1	21.2	33.3	46.0	-12.7
768.235	Н	12.1	21.8	33.9	46.0	-12.1



Report No. : AG030175-001 Date : 2006 November 28

#### **Radiated emission**

## pursuant to

## the requirement of FCC Part 15 subpart B

Operation Mode: Stand Alone

Frequency	Polarity	Reading at	Antenna and	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Strength	$(dB\mu V/m)$	(dB)
		(dBµV/m)	(dB)	$(dB\mu V/m)$		
85.385	Н	13.4	7.3	20.7	40.0	-19.3
100.004	Н	10.0	11.1	21.1	43.5	-22.4
144.185	Н	11.5	12.0	23.5	43.5	-20.0
216.543	Н	12.8	9.8	22.6	46.0	-23.4
192.090	Н	11.8	9.5	21.3	46.0	-24.7
668.346	Н	1.3	21.2	22.5	46.0	-23.5
768.212	Н	0.4	20.8	21.4	46.0	-24.6



Report No. : AG030175-001 Date : 2006 November 28

## 3 Description of the Line-conducted Test

#### 3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### 3.2 Test Result

The PC connected mode has been tested. The EUT connecting with USB Cable to measurement. Data was indicated in Appendix. The result showed that the EUT met the FCC requirement.

#### 3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the documents are saved with filename TestRpt2.pdf



Report No. : AG030175-001 Date : 2006 November 28

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



Report No. : AG030175-001 Date : 2006 November 28

## 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan1.pdf - UserMan2.pdf
Operational Description	OpDes.pdf

#### 5.1 Bandwidth

N/A

#### 5.2 Duty cycle

N/A

## **5.3** Transmission time

N/A



Report No. : AG030175-001 Date : 2006 November 28

## 6 Appendices

A1	Photos of the set-up of Radiated Emissions	1	page
A2	Photos of the set-up of Conducted Emissions	2	pages
A3	Photos of External Configurations	1	page
A4	Photos of Internal Configurations	1	page
A5	ID Label/Location	1	page
A6	Conducted Emission Measurement Data	4	pages
A7	Block Diagram	1	page
A8	Schematics Diagram	6	pages
A9	User Manual	3	pages
A10	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*