

FCC PART 15.249

TEST REPORT

For

Gajah International (HK) Co., Ltd.

18/F, Bel Trade Commercial Building, 1-3, Burrows Street, Wan Chai, Hong Kong

FCC ID: UFKRC030000

Report Type: Original Report	Product Type: motion remote control
Test Engineer:	Tiger Ye <i>Tiger Ye</i>
Report Number:	RSZ130307004-00
Report Date:	2013-03-19
Reviewed By:	Alvin Huang <i>Alvin Huang</i> RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EQUIPMENT MODIFICATIONS	5
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC §15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY.....	8
TEST EQUIPMENT SETUP	8
EUT SETUP	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC §15.249(D) - OUT OF BAND EMISSION.....	13
APPLICABLE STANDARD	13
TEST PROCEDURE	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST DATA	13

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Gajah International (J M) Co., Ltd.* 's product, model number: *RC03 (FCC ID: UFKRC030000)* or the "EUT" in this report is a *motion remote control*, named as Wireless Presenter by applicant, which was measured approximately: 16.8 cm (L) × 4.8 cm (W) × 1.5 cm (H), rated input voltage: DC 2*1.5V battery.

All measurement and test data in this report was gathered from production sample serial number: 1303008 (Assigned by BACL, Shenzhen). The EUT was received on 2013-03-07.

Objective

This type approval report is prepared on behalf of *Gajah International (J M) Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No related submittal(s)

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The system was configured in a testing mode which provided by manufacturer.


Equipment Modifications

No modifications were made to the unit tested.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	N/A*
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.249(d)	Outside of Band Emission	Compliance

Note: EUT is powered by battery only.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna arrangement, the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliant.

FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS**Applicable Standard**

As per FCC"§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC"§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. (k=2, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

Test Equipment Setup

The spectrum analyzer or receiver is set as:


Below 1000MHz:

RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto

Above 1000MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto

EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2012-11-24	2013-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2013-03-17	2014-03-16
Mini-Circuits	Amplifier	ZVA-213+	N/A	2012-11-24	2013-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2012-12-01	2013-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
Electro-Mechanics	Horn antenna	3116	9510-2270	2012-10-14	2013-10-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.205 & 15.249, with the worst margin reading of:

4.05 dB at 2401.9 MHz in the Vertical polarization

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa

The testing was performed by Tiger Ye on 2013-03-17.

Test Mode: Transmitting

30 MHz to 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.249/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H /V)			Limit (dBμV/m)	Margin (dB)
Low channel (2402 MHz)									
2402	83.82	Ave.	36	1.40	V	6.13	89.95	94.00	4.05
2402	83.60	Ave.	48	1.60	H	6.13	89.73	94.00	4.27
9608	23.33	Ave.	105	1.40	V	19.28	42.61	54.00	11.39
7206	23.24	Ave.	347	1.50	V	17.06	40.30	54.00	13.70
4804	23.33	Ave.	174	1.60	V	12.4	35.73	54.00	18.27
9608	35.11	PK	105	1.40	V	19.28	54.39	74.00	19.61
327.1	39.56	QP	234	1.50	V	-13.50	26.06	46.00	19.94
7206	33.84	PK	347	1.50	V	17.06	50.90	74.00	23.10
2402	84.01	PK	36	1.40	V	6.13	90.14	114.00	23.86
2402	83.78	PK	48	1.60	H	6.13	89.91	114.00	24.09
2488.5	22.25	Ave.	290	1.70	H	7.21	29.46	54.00	24.54
2398.6	21.30	Ave.	193	1.50	V	6.13	27.43	54.00	26.57
2324.7	21.28	Ave.	249	1.80	V	5.48	26.76	54.00	27.24
4804	34.15	PK	174	1.60	V	12.4	46.55	74.00	27.45
2488.5	34.70	PK	290	1.70	H	7.21	41.91	74.00	32.09
2324.7	34.99	PK	249	1.80	V	5.48	40.47	74.00	33.53
2398.6	34.19	PK	193	1.50	V	6.13	40.32	74.00	33.68
Middle channel (2441 MHz)									
2441	83.76	Ave.	230	1.80	V	6.13	89.89	94.00	4.11
2441	83.49	Ave.	326	1.40	H	6.13	89.62	94.00	4.38
9764	23.18	Ave.	298	1.00	V	19.40	42.58	54.00	11.42
7323	23.03	Ave.	165	1.50	V	16.49	39.52	54.00	14.48
4882	23.08	Ave.	321	1.10	V	12.46	35.54	54.00	18.46
9764	35.03	PK	298	1.00	V	19.40	54.43	74.00	19.57
327.1	39.06	QP	280	1.90	V	-13.50	25.56	46.00	20.44
2441	83.87	PK	230	1.80	V	6.13	90.00	114.00	24.00
7323	33.43	PK	165	1.50	V	16.49	49.92	74.00	24.08
2441	83.66	PK	326	1.40	H	6.13	89.79	114.00	24.21
2486.7	21.83	Ave.	44	1.90	H	7.21	29.04	54.00	24.96
2396.4	21.13	Ave.	128	1.00	V	6.13	27.26	54.00	26.74
2323.5	21.03	Ave.	214	1.80	V	5.48	26.51	54.00	27.49
4882	33.93	PK	321	1.10	V	12.46	46.39	74.00	27.61
2486.7	34.36	PK	44	1.90	H	7.21	41.57	74.00	32.43
2396.4	34.07	PK	128	1.00	V	6.13	40.20	74.00	33.80
2323.5	34.49	PK	214	1.80	V	5.48	39.97	74.00	34.03
High channel (2475 MHz)									
2475	83.58	Ave.	40	1.30	V	6.13	89.71	94.00	4.29
2475	82.43	Ave.	354	1.20	H	6.13	88.56	94.00	5.44
9900	23.15	Ave.	293	1.80	V	19.38	42.53	54.00	11.47
7425	23.03	Ave.	233	1.80	V	15.90	38.93	54.00	15.07
4950	23.33	Ave.	255	1.50	V	12.50	35.83	54.00	18.17
9900	34.85	PK	293	1.80	V	19.38	54.23	74.00	19.77
327.1	39.14	QP	203	1.50	V	-13.50	25.64	46.00	20.36
7425	33.43	PK	233	1.80	V	15.90	49.33	74.00	24.67
2487.4	21.93	Ave.	99	1.30	H	7.21	29.14	54.00	24.86

2475	83.74	PK	40	1.30	V	6.13	89.87	114.00	24.13
2475	82.61	PK	354	1.20	H	6.13	88.74	114.00	25.26
2394.3	20.84	Ave.	354	1.50	V	6.13	26.97	54.00	27.03
2324.1	21.22	Ave.	229	1.80	V	5.48	26.70	54.00	27.30
4950	33.66	PK	255	1.50	V	12.50	46.16	74.00	27.84
2487.4	34.22	PK	99	1.30	H	7.21	41.43	74.00	32.57
2324.1	34.93	PK	229	1.80	V	5.48	40.41	74.00	33.59
2394.3	33.77	PK	354	1.50	V	6.13	39.90	74.00	34.10

FCC §15.249 (d) - OUT OF BAND EMISSIONS

Applicable Standard

As per FCC"§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC"§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. (k=2, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

Test Equipment Setup

The spectrum analyzer or receiver is set as:


Below 1000 MHz:

RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto


Above 1000 MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto

Band Edge: Left Side



Band Edge: Right Side



***** END OF REPORT *****