

1.1. Test Result of RF Exposure Evaluation

- . Product: Wireless Bar Code Scanner
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 2.1 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Modulation Standard: Bluetooth

Test Date: Sep. 13, 2006

Temperature: 27°C

Humidity: 60%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
00	2402	-3.17	0.000156
39	2441	-4.39	0.000117
78	2480	-5.07	0.000100

The MPE is calculated as $0.000156 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

For 2400~2483.5 MHz, the EUT will only be used with a separation of 2.5cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.