



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>



Dates of Tests: July 12 ~ 20, 2006  
Test Report S/N: LR500110608D  
Test Site : LTA CO., LTD.

## CERTIFICATIO OF COMPLIANCE

FCC ID.	<b>UG9UBHS-NC1</b>
APPLICANT	<b>Ubixon Co., Ltd.</b>

<b>FCC Classification</b>	:	<b>FHSS Sequence Spread Spectrum (FHSS)</b>
<b>Manufacturing Description</b>	:	<b>Bluetooth Headset</b>
<b>Manufacturer</b>	:	<b>Ubixon Co., Ltd.</b>
<b>Model name</b>	:	<b>UBHS-NC1</b>
<b>Test Device Serial No.:</b>	:	<b>Identification</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	:	<b>2402 ~ 2480MHz</b>
<b>RF power</b>	:	<b>0.76dBm - Conducted</b>
<b>Data of issue</b>	:	<b>July 24, 2006</b>

This test report is issued under the authority of:

The test was supervised by:

Dong -Min JUNG, Technical Manager

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

---

## TABLE OF CONTENTS

1. GENERAL INFORMATION'S .....	3
2. INFORMATION'S ABOUT TEST ITEM .....	4
3. TEST REPORT .....	5
3.1 SUMMARY OF TESTS .....	5
3.2 TECHNICAL CHARACTERISTICS TEST .....	6
3.2.1 CARRIER FREQUENCY SEPARATION .....	6
3.2.2 NUMBER OF HOPPING FREQUENCIES .....	8
3.2.3 20 dB BANDWIDTH .....	11
3.2.4 TIME OF OCCUPANCY (Dwell Time) .....	13
3.2.5 TRANSMITTER OUTPUT POWER .....	15
3.2.6 BAND - EDGE .....	17
3.2.7 FIELD STRENGTH OF HARMONICS .....	26
3.2.9 AC CONDUCTED EMISSIONS .....	27
<b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS .....	31

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2006-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2007-07-13	EMC accredited Lab.
FCC	U.S.A	610755	2008-03-28	FCC filing
VCCI	JAPAN	R2133, C2307	2008-06-22	VCCI registration
IC	CANADA	IC5799	2008-04-23	IC filing

## 2. Information's about test item

### 2-1 Client & Manufacturer

Company name : Ubixon Co., Ltd.  
 Address : 2F Jung-dong Bldg. 1344-29, Seocho-dong, Seocho-gu,  
 Seoul, 137-070, Korea  
 TEL / FAX : +82-2-582-1115/ +82-2-582-0115

### 2-2 Equipment Under Test (EUT)

Trade name : Bluetooth Headset  
 FCC ID : UG9UBHS-NC1  
 Model name : UBHS-NC1  
 Serial number : Identification  
 Date of receipt : July 05, 2006  
 EUT condition : Pre-production, not damaged  
 Antenna type : PIFA antenna Gain 0.7dBi  
 Frequency Range : 2402 ~ 2480MHz  
 RF output power Range : -6dBm~+4dBm (Class 2)  
 Number of channels : 79  
 Channel spacing : 1MHz  
 Channel Access Protocol : Frequency Hopping  
 Type of Modulation : GFSK  
 Power Source : 3.7V (Li-ion Rechargeable)

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

### 2-5 Ancillary Equipment – Bluetooth mode

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

### 2-6 Ancillary Equipment – Charging mode

Equipment	Model No.	Serial No.	Manufacturer
Mouse	MO56UO	510022473	DELL
Notebook	Latitude D505	8N29F1S	DELL
-	-	-	-

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 75 hops		C
15.247(a)	20 dB Bandwidth	< 1 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

*Note 1:* C=Complies    NC=Not Complies    NT=Not Tested    NA=Not Applicable

*Note 2:* The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

### 3.2 Transmitter requirements

#### 3.2.1 Carrier Frequency Separation

**Procedure:**

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz (1% of the span or more)      Sweep = auto

VBW = 30 kHz      Detector function = peak

Trace = max hold

**Measurement Data:**

Test Results	
Carrier Frequency Separation (MHz)	Result
0.982	Complies

- See next pages for actual measured spectrum plots.

**Minimum Standard:**

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

**Measurement Setup**





Figure 1: Measurement setup for the carrier frequency separation

### Carrier Frequency Separation



### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

#### The spectrum analyzer is set to:

Frequency range    1: Start = 2389.5MHz,    Stop = 2414.5 MHz

                          2: Start = 2414.5MHz,    Stop = 2439.5 MHz

                          3: Start = 2439.5MHz,    Stop = 2464.5 MHz

                          4: Start = 2464.5MHz,    Stop = 2489.5 MHz

RBW = 300 kHz (1% of the span or more)      Sweep = auto

VBW = 300 kHz (VBW  $\geq$  RBW)              Detector function = peak

Trace = max hold                                  Span = 25MHz

#### Measurement Data: Complies

<b>Total number of Hopping Channels</b>	79
---	----

- See next pages for actual measured spectrum plots.

#### Minimum Standard:



At least 75 hops

#### Measurement Setup



Same as the Chapter 3.2.1 (Figure 1)



### Number of Hopping Frequencies



### Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (MHz)	Result
2441	39	0.920	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

The transmitter shall have a maximum 20dB bandwidth of 1 MHz.

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

### 20 dB Bandwidth



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Channel Number	Channel Frequency (MHz)	Packet Type	Test Results	
			Dwell Time (ms)	Result
39	2441	DH 1	135.21	Complies
		DH 3	272.30	Complies
		DH 5	310.78	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

0.4 seconds within a 30 second period per any frequency


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


**DH 1**



**DH 3**



**DH 5**



### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>0.51</b>	<b>1.125</b>	Complies
2441	39	<b>0.76</b>	<b>1.191</b>	Complies
2480	78	<b>0.62</b>	<b>1.153</b>	Complies


- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	< 1W
--------------------------	------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


### Peak Output Power



RL



RL



CLEAR  
WRITE A

MAX  
HOLD A

VIEW A

BLANK A

Trace  
A B C

More  
1 of 3

RL



### 3.2.6 Band - edge

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies


- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

**Band - edge (with Hopping)**





RL



RL


**Band - edge (without Hopping)**





**Band - edge (at 20 dB blow) – Low channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonics.**



- Continues








**Band - edge (at 20 dB blow) – High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**





**Band - edge (at 20 dB blow) – High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonics.**

- Continues



### 3.2.7 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV)	Frequency (MHz)	Level (dBuV)	Frequency (MHz)	Level (dBuV)
4804	50.2	4882	48.3	4960	44.3
7206	40.6	9764	46.2	9920	44.8
9608	43.4	-	-	-	-
No other emissions were detected at a level greater than 10dB below limit.					
-	-	-	-	-	-
Measurement uncertainty		$\pm$ 6 dB			

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

### 3.2.8 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency


AC Conducted Emissions –Line



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : UBHS-NC1 Phase : LINE  
 Test Mode : Charging mode Test Power : 120 / 60  
 Temp./Humi. : 26 / 70 Test Engineer : K. T. LEE

Data: 354 File: E:\00\_e3 EMI DATA\LTA\_Conduction\_0607-1.EMI (380) Date: 2006-07-12



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.199	46.20	31.00	0.19	46.39	31.19	63.65	53.65	17.26	22.46
0.237	43.70	30.07	0.22	43.92	30.29	62.22	52.22	18.30	21.93

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


### AC Conducted Emissions -Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-323-6008  
Fax:+82-31-323-6010

EUT / Model No. : UBHS-NC1	Phase : NEUTRAL
Test Mode : Charging mode	Test Power : 120 / 60
Temp./Humi. : 26 / 70	Test Engineer : K. T. LEE

Data: 356 File: E:\00\_e3 EMI DATA\LTA\_Conduction\_0607-1.EMI (380) Date: 2006-07-12



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.202	46.00	29.24	0.18	46.18	29.42	63.54	53.54	17.35	24.11
1.396	30.80	24.44	0.34	31.14	24.78	56.00	46.00	24.86	21.22

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Dec-06
2	Signal Generator	8657A	3430U02049	HP	Dec-06
3	Attenuator (3dB)	8491A	37822	HP	Dec-06
4	Attenuator (3dB)	8491A	28881	HP	Dec-06
5	EMI Test Receiver	ESVD	843748/001	R&S	Dec-06
6	Spectrum Analyzer	8591E	3649A05888	HP	Jan-07
7	Spectrum Analyzer	8563E	3425A02505	HP	Jan-07
8	RF Amplifier	8447D	2949A02670	HP	Jan-07
9	RF Amplifier	8447D	2439A09058	HP	Jan-07
10	RF Amplifier	8449B	3008A02126	HP	Jun-07
11	TRILOG Antenna	VULB 9160	9160-3172	SCHWARZBECK	Feb-07
12	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Feb-07
13	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Feb-07
14	Horn Antenna	3115	00055005	ETS LINDGREN	Jun-07
15	Horn Antenna	BBHA 9120D	0499	Schwarzbeck	Jun-07
16	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Feb-07
17	Splitter (BNC)	ZFM-150	15542	Mini-Circuits	-
18	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
19	Power Divider	11636A	6243	HP	Apr-07
20	DC Power Supply	6622A	3448A03079	HP	Apr-07
21	Attenuator (30dB)	8498A	1801A06689	HP	Apr-07
22	Attenuator (10dB)	8491A	63196	HP	Apr-07
23	Power Meter	EPM-441A	GB32481702	HP	Apr-07
24	Power Sensor	8481A	2702A64048	HP	Apr-07
25	Audio Analyzer	8903B	3729A18901	HP	May-07
26	Modulation Analyzer	8901B	3749A05878	HP	May-07
27	Dipole Antenna	VHA9103	2116	Schwarzbeck	Oct-06
28	Dipole Antenna	VHA9103	2117	Schwarzbeck	Oct-06
29	Dipole Antenna	UHA9105	2261	Schwarzbeck	Oct-06
30	Dipole Antenna	UHA9105	2262	Schwarzbeck	Oct-06
31	Digital Multimeter	34401A	US36062141	HP	Apr-07
32	LISN	KNW-407	8-1430-1	Kyoritsu	Jan-07
33	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Jan-07
34	Test Receiver	ESHS10	828404009	R&S	Jan-07
35	TEMP & HUMIDITY Chamber	YJ-500	L05022	JinYoung Tech	-